





REV.	ECN. NO.	APPD.
A	BC07700781	C.C. Huang




ACCEPT 1.57±0.20mm
THICKNESS P.C.B.




SECTION Y-Y



Recommended PCB. Layout



Recommended Gold Finger



DETAIL C
SCALE 2 : 1

NOTES:

- GENERAL CHARACTERISTICS:
 - 1-1 CURRENT RATING: 3 AMPS AC.
 - 1-2 VOLTAGE RATING: AC 250V RMS.
 - 1-3 OPERATING TEMPERATURE: -55°C TO +85°C
- MECHANICAL CHARACTERISTICS:
 - 2-1 CONTACT MATING FORCE: 340gf MAX.
PER PAIR CONTACT USE 1.58mm THICK GAUGE.
 - 2-2 CONTACT UNMATING FORCE: 15gf MIN.
PER PAIR CONTACT USE 1.37mm THICK GAUGE.
 - 2-3 CONTACT RETENTION FORCE: 1.0KgF MIN.
 - 2-4 DURABILITY: 50 CYCLES.
- ELECTRICAL CHARACTERISTICS:
 - 3-1 INSULATION RESISTANCE: 5000 MEGAOHMS MIN.
 - 3-2 CONTACT RESISTANCE: 15 MILLIOHMS MAX. INITIAL.
25 MILLIOHMS MAX. AFTER TEST.
 - 3-3 DIELECTRIC WITHSTANDING VOLTAGE: AC 1000V RMS.
AT SEA LEVEL.
- POSITION OF CLINCH LEADS AT 3-6,47-50,55-58,93-96.

PRUDUCT NO: E S O 49 0 * - DF

SERIES PREFIX :

2.54 PICTH

EDGE CARD CONN.

TERMINATION TYPE

0: STRAIGHT TYPE.

NO. OF POS.:

49: 98 POS.

TAIL LENGTH TYPE:

0: 3.18

PLATING TYPE
DF: LEAD FREE

CONTACT AREA PLATING
1: GOLD FLASH.
3: 30u" GOLD.
6: 10u" GOLD.
7: 15u" GOLD.

2	HOUSING	1	THERMOPLASTIC UL 94V-0	MOLDED BLACK
1	CONTACT	98	COPPER ALLOY	GOLD PLATING AT CONTACT AREA; TIN OR TIN/LEAD ON TAIL OVER NICKEL OVERALL.
ITEM	DESC.	Q'TY	MATERIAL	TREATMENT
X.±	X'± 2"	UNITS	mm	NAME(INTENDED USE) 2.54mm PITCH ISA. CONN.
.X± 0.38	.X'± 1"	MAT'L		FOXCONN HON HAI PRECISION IND. CO.,LTD. TAIPEI, TAIWAN, R.O.C.
.XX± 0.25	.XX'±	SEE BOM		PART NO.(INTENDED USE) ES0490*-**
.XXX±	.XXX'±	FINISH	N/A	TITLE: CUSTOMER
			Q'TY	N/A
			APPD:	C.C. Huang 1/8'07
			CHKD:	Tin-Suen Liu 1/8'07
			DR:	K.P.Dong 1/8'07
				DWG NO.: 303-0000-1459
				SCALE SHEET REV. 1:1 1/1 A

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF HON HAI PRECISION IND. CO., LTD. AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF HON HAI PRECISION IND. CO., LTD.