

EDN[®]

Designer's guide to
dynamic RAMs—Part 2

Graphing software plots
sophisticated numerical data

Use dual-port static RAMs
for tricky interface problems

NuBus interface options

ELECTRONIC TECHNOLOGY FOR ENGINEERS AND ENGINEERING MANAGERS

IEEE-488 software lets you automatically generate instrument programming code



supports your choice.

It's no secret that the faster you can design your ASICs, the faster you can get your products to market. Which is why Fujitsu lets you decide which design tools to use. Then we provide you with all the on-site support you need to breeze through not only product development but also product verification.

As your ASIC partner, we've got what it takes to help you turn a good idea into a great new product.

If you choose a popular engineering workstation, for example, we'll support you all the way. With libraries, convertors, test vector editor and a powerful, menu-driven file-management program called FAME (Fujitsu ASIC Management Environment) that boosts productivity by 300%.

If, on the other hand, you're using computers running third-party software, we'll support you there too. Our support goes even further with ViewCAD™. A complete set of easy-to-use tools that gives you a choice. Use ViewCAD for on-site verification or as a complete, stand-alone ASIC engineering workstation.

ViewCAD supports your entire design cycle. From schematic capture and logic design rule checking to test data entry, simulation, analysis and data conversion. All running on your favorite industry-standard UNIX®-based platforms. And all from Fujitsu.

ViewCAD puts years of ASIC experience under your belt. Experience that has led to more than 10,000 successful designs. And made Fujitsu the world's leading ASIC supplier.

ViewCAD's design methodology helps you shorten your product development cycle. Because it catches more design errors earlier in the process. Its powerful design capabilities and X Windows™ software lets you easily handle the overwhelming complexities of high-density ICs. Even our 100,000 gates and beyond.

With ViewCAD, you get the benefit of a powerful simulator that provides you with virtual mainframe compatibility. Including a simulation-to-silicon correlation of over 99.9%.

What's more, you can integrate ViewCAD with third-party tools for interactive design verification.

Which ensures the integrity of your design and reduces design verification and modification time. So your circuit is closer to silicon than ever before. And you're closer to market.

But supporting your design tool decision is only part of the story. As your ASIC partner, we expand your design team, providing you with fully staffed and equipped technical resource centers, coast to coast.

Each able to train your engineers and provide twenty-four hour design suites, so you can work whenever inspiration strikes. You also get ASIC sales and marketing support to help you smooth out all the administrative wrinkles.

So no matter what your decision, you can count on Fujitsu to support it. Which, after all, is everything an ASIC partner should be.



FUJITSU

FUJITSU MICROELECTRONICS, INC.

Integrated Circuits Division

3545 North First St., San Jose, CA 95134-1804. (800) 642-7616

Everything an ASIC partner should be.

UNIX is a registered trademark of Bell Laboratories. X Windows is a trademark of the Massachusetts Institute of Technology. ViewCAD is a trademark of Fujitsu Microelectronics, Inc.

CIRCLE NO 62

An ASIC partner who



**When it comes
to design tools,
there's only one thing
you need.**

NOT JUST ANOTHER UGLY WORKSTATION



More than a workstation, Ziatech's new ZT 1000 provides an innovative solution for many levels of factory automation.

Multi-Talented

The ZT 1000 can operate as a cell controller, a low cost PLC, and as a stand-alone controller. It can perform these tasks simultaneously with add-in intelligent control processor cards.

Trustworthy

The ZT 1000 is based on the STD Bus, designed for reliability under harsh industrial conditions.

Compatible

The ZT 1000 runs IBM PC software on Ziatech's PC-compatible single board computers, which feature IBM PC DOS and Ziatech's industrial BIOS in EPROM.

Well-Connected

The ZT 1000 comes with industrial networking options fully supported by Ziatech.

Ruggedly Handsome


The ZT 1000 is tough enough for the factory floor. Its ½" anodized front panel meets NEMA 4/12 standards for protection from water, dirt, dust and non-corrosive liquids.

Friendly

The ZT 1000 is designed for easy operation by non-technical personnel.

In Good Company

Ziatech also offers integrated systems for rack-mounting as well as a wide selection of STD and GPIB board-level products.



Easy to Get to Know

For a free ZT 1000 brochure, including specifications, configuration guide and price list, call Ziatech today.

805-541-0488



Corporate Headquarters
3433 Roberto Court
San Luis Obispo, California 93401 USA
ITT Telex 4992316 • FAX (805) 541-5088
Telephone (805) 541-0488



The idea behind our GPIB software was discovered by a 3-year-old.



With WaveTest® you can build the most complex GPIB test programs, using the simplest of methods. Because WaveTest writes all the programming code for you.

It even prepares the documentation, complete with flow charts.

You simply stack one block on top of another.

A block could be a data gathering operation, a FOR...NEXT loop or branching decision.

In other words, each block is the equivalent of many lines of code. Only you don't have to write it!

A block can also represent one of your instruments at a certain output, or taking a measurement. More than 100 makes and models of instruments are provided, and you can always add more.

WaveTest runs under Microsoft® Windows, so rearranging a test or adding steps is child's play. Just use the mouse to point at the blocks, pick them up and put them where you want. The code is automatically rewritten.

Since you won't have to spend months figuring out GPIB command strings and writing code, you'll be able to spend your time developing better tests—or better products!

There are other software programs out there to control instruments, but when it comes to writing a test program, they just don't stack up to WaveTest.

Call us today at (619) 279-2200 and we'll prove it to you.

DC/DC Converter Solution for ISDN Designers



Siliconix' new 5mW Switchmode Regulator. The only monolithic IC that meets CCITT power-down standards.

Get efficient power conversion for ISDN emergency operation in the power-down state!

The Si9105 high-voltage switchmode regulator's low (0.5 mA max.) supply current reduces power consumption. And its wide input voltage range (10-120 V) means you can design with fewer SMPS components.

Convert 40V down to 5V with 60% efficiency in the light load condition to meet the CCITT 25mW maximum limit. And still get 85% efficiency at full load.

1.430

Restricted Conditions

TE drawing power from PS 1 Designated TE

Active State	380 mW max.
Deactive State	25 mW max.

The Si9105 Switchmode Regulator consumes only 5mW of your CCITT 1.430 power budget—leaving another 5mW for other SMPS components and delivering 15mW to output for line activity detection and retention of the terminal endpoint identifier (TEI).


For ISDN designs that meet the CCITT standard dial our toll-free hot line now! Call 1-800-554-5565, Ext. 944 for your Si9105 Design Kit including free sample.



Siliconix
incorporated

2201 Laurelwood Road, Santa Clara, CA 95054

© 1989 Siliconix inc.



On the cover: IEEE software packages featuring instrument function panels let you use simple English commands to set or change instrument controls. The software then automatically generates IEEE-488 control programs. See pg 142. (Photo courtesy Wavetek Corp)

SPECIAL REPORT

IEEE-488 test and measurement software

142

Instrument function panels and automatic code generation are making it easy for the new or infrequent user to write IEEE-488 control programs.—*Doug Conner, Regional Editor*

DESIGN FEATURES

Designer's guide to dynamic RAMs—Part 2

157

To tap the full potential of a dynamic RAM (DRAM), you must tailor your memory-system architecture for the DRAM you've chosen. This article examines your architectural options in designing a memory system.—*Ronald Wawrzynek, Texas Instruments*

Following simple rules lets embedded systems work with μ P emulators

171

You can get a lot of mileage from a μ P emulator, but finding that your system crashes when you connect the emulator is frustrating. Observe some simple rules at the outset of a new design to forestall crashes and speed debugging.—*Arnold S Berger, Hewlett-Packard*

Stimulus-response tests are easy with an 8-bit μ P

181

Despite its association with large and costly test systems, stimulus-response testing is actually simple and straightforward. You can build a low-cost stimulus-response tester around an 8-bit μ P and easily adapt it to a remarkably wide variety of tasks.—*Paul D Gracie, Microdoctors Inc*

Use a logic analyzer to debug real-time software

193

Cleaning up real-time operating bugs requires real-time monitoring and analysis, for which the best tool is still the logic analyzer. However, to use a logic analyzer effectively, you need to understand the special triggering requirements that multiprocessing presents.—*Ken Marti, Tektronix Inc*

Continued on page 7

EDN®(ISSN 0012-7515) is published 49 times a year (biweekly with 2 additional issues a month, except for February, which has 3 additional issues and July and December which have 1 additional issue) by Cahners Publishing Company, A Division of Reed Publishing USA, 275 Washington Street, Newton, MA 02158-1630. Terrence M McDermott, President; Frank Sibley, Electronics/ Computer Group Vice President; Jerry D Neth, Vice President/Publishing Operations; J J Walsh, Financial Vice President/Magazine Division; Thomas J Dellamaria, Vice President/Production and Manufacturing. Circulation records are maintained at Cahners Publishing Company, 44 Cook Street, Denver, CO 80206-5800. Telephone: (303) 388-4511. Second-class postage paid at Denver, CO 80206-5800 and additional mailing offices. POSTMASTER: Send address corrections to EDN® at the Denver address. EDN® copyright 1989 by Reed Publishing USA; Saul Goldweitz, Chairman; Ronald G Segel, President and Chief Executive Officer; Robert L Krakoff, Executive Vice President; William M Platt, Senior Vice President. Annual subscription rates for nonqualified people: USA, \$105/year; Canada/Mexico, \$125/year; Europe air mail, \$150/year; all other nations, \$150/year for surface mail and \$230/year for air mail. Single copies are available for \$10. Please address all subscription mail to Eric Schmierer, 44 Cook Street, Denver, CO 80206-5800.



PHILIPS



Finally! The one thing you've always wanted in a low-cost logic analyzer: No restraint.

The Philips PM 3655. It's the first true 100 MHz logic analyzer for under \$10,000! That means it comes with a feature no other low-cost analyzer in the world can offer you: Freedom to use 100% of its capability 100% of the time.

UNRESTRAINED PERFORMANCE

- *High-speed timing and state analysis:* Get full 100 MHz synchronous and asynchronous sampling on up to 96 channels. And never again sacrifice width for speed.
- *Deep memory:* 2K memory depth per channel lets you measure complex data flows—with no loss of width, speed or glitch capturing potential.
- *GLITCH mode:* 5 ns glitch capture at 100 MHz on all channels. Again, without forfeiting speed, width or depth.

- *Flexible triggering plus Trace:* Powerful, multi-level triggerword sequence, range recognition and four clock qualifiers help you find and display exactly the data you're looking for.

- *Expandability:* Add 24-channel modules any time for 24, 48, 72 or 96 channel configurations.

- *Broad support:* Choose from a wide range of disassemblers and dedicated personality modules.

SIMPLE OPERATION PLUS PC

- *Immediate familiarity:* All this capability and so easy to use—menu-driven operation; extensive user-defined labeling; and standard PC-style keyboard interface.

- *Plus full MS-DOS-based PC:* Adds versatility and value without compromising logic analysis. On-line disk storage for measurement data and instrument set-ups.

Expansion slots for extra memory, modem or other PC options.

UNRESTRAINED SUPPORT

Count on a one-year warranty and all the application and service assistance you'll ever need. From Fluke—the people who believe that extraordinary technology deserves extraordinary support.

TEST THE DIFFERENCE

Call Fluke today at **800-44-FLUKE ext. 77**. And look into a logic analyzer that unleashes your potential instead of tying your hands.

John Fluke Mfg. Co., Inc., P.O. Box C9090, M/S 250C, Everett, WA 98206
U.S.: 206-356-5400 CANADA: 416-890-7600
OTHER COUNTRIES: 206-356-5500

© Copyright 1988 John Fluke Mfg. Co., Inc. All rights reserved. Ad No. 0581-P3655



PM 3655 - 100 MHz - LOGIC ANALYZER





Graphing software packages enable today's small computers to plot almost any numerical information (pg 53).

EDN magazine
now offers
Express Request,
a convenient way
to retrieve product
information by
phone. See the
Reader Service
Card in the front
for details on how
to use this free
service.



TECHNOLOGY UPDATE

Graphing-software packages: 53 Draw your graphs on printers and plotters

Today's small computers, when combined with a pen plotter, an ink-jet printer, or even a dot-matrix printer, let you plot almost any numerical information.—*Jon Titus, Editor*

Dual-port static RAMs: 83 Specialized memories ease communications

Although they make up only a small fraction of the hundreds of millions of RAMs produced each year, dual-port static RAMs (SRAMs) are becoming increasingly important for solving difficult interface problems.—*Dave Pryce, Associate Editor*

Design choices let you 101 optimize Nubus access

To take full advantage of the Nubus's features—which include a 32-bit backplane with multiprocessing capability, multiplexed address and data lines, and a 10-MHz clock—you can either design your own boards, adapt existing boards to the Nubus backplane, or purchase one of the many Nubus-compatible boards currently available.—*J D Mosley, Regional Editor*

PRODUCT UPDATE

VXI Bus enhancement	119
32-bit Ethernet controller chip	123
Software-development tool	126
Software-modeling simulator	128
Color LCD panel	130
Prototyping board kits	132

DESIGN IDEAS

NPN replaces PNP pass transistor	209
Variable slew-rate filter tames noise	210
386SX interfaces with IBM PC/AT chip set	212
C string comparer handles abbreviations	214
500-kHz switcher produces -5V	216

Continued on page 9

Cahners Publishing Company, A Division of Reed Publishing USA Specialized Business Magazines for Building & Construction Manufacturing Foodservice & Lodging Electronics & Computers Interior Design Printing Publishing Industrial Research & Technology Health Care and Entertainment. Specialized Consumer Magazines: American Baby and Modern Bride.

LSI LOGIC ACROSS THE BOARD.SM

When historians write the history of computing, the above five words may well deserve a chapter of their own.

With them, LSI Logic becomes the first company to provide an integrated design methodology for combining ASIC and RISC technologies.

Using our new approach, manufacturers can produce systems that are smaller. More powerful. More flexible. More reliable. And less expensive. Than ever before.

Computers that can be personalized to perform specific functions. And that can be changed as quickly as markets change.

LSI Logic Across The Board.

It's more than just a clever title. It's the beginning of a whole new chapter.



VP/Publisher
Peter D Coley

Editor/Editorial Director
Jonathan Titus

Managing Editor
John S Haystead

Assistant Managing Editor
Joan Morrow

Special Projects
Gary Legg

Home Office Editorial Staff
275 Washington St, Newton, MA 02158
(617) 964-3030

Tom Ormond, *Senior Editor*
Joanne De Oliveira, *Associate Editor*
John A Gallant, *Associate Editor*
Michael C Markowitz, *Associate Editor*
Christine McElvenny, *Associate Editor*
Dave Pryce, *Associate Editor*
Cynthia B Rettig, *Associate Editor*
Julie Anne Schofield, *Associate Editor*
Charles Small, *Associate Editor*
Dan Strassberg, *Associate Editor*
Anne Watson Swager, *Associate Editor*
Chris Terry, *Associate Editor*
Helen McElwee, *Senior Copy Editor*
James P Scanlan, *Staff Editor*
Kathleen M Vejvoda, *Staff Editor*
Steven Paul, *Senior Production Editor*
Flo E Evans, *Production Editor*

Editorial Field Offices

Margery S Conner, *Regional Editor*
Los Osos, CA: (805) 528-0833

Doug Conner, *Regional Editor*
Los Osos, CA: (805) 528-0865

Steven H Leibson, *Regional Editor*
Boulder, CO: (303) 494-2233

J D Mosley, *Regional Editor*
Arlington, TX: (817) 465-4961

Richard A Quinnell, *Regional Editor*
San Jose, CA: (408) 296-0868

David Shear, *Regional Editor*
San Jose, CA: (408) 997-5452

Maury Wright, *Regional Editor*
San Diego, CA: (619) 748-6785

Peter Harold, *European Editor*
0603-630782
(St Francis House, Queens Rd,
Norwich, Norfolk NR1 3PN, UK)

Contributing Editors
Robert Pease, Bob Peterson,
Don Powers, Bill Travis

Editorial Services
Kathy Leonard, *Office Manager*
Nancy Weiland, Helen Benedict

Art Staff
Ken Racicot, *Senior Art Director*
Chinsoo Chung, *Associate Art Director*
Cathy Filipski, *Staff Artist*
Martha Crowell, *Staff Artist*

Production/Manufacturing Staff
William Tomaselli, *Production Supervisor*
Danielle M Biviano, *Production Assistant*
Deborah Hodin, *Production Assistant*
Diane Malone, *Composition*

Director of Art Department
Joan Kelly
Norman Graf, *Associate*

VP/Production/Manufacturing
Wayne Hulitzky

Director of Production/Manufacturing
John R Sanders

Business Director
Deborah Virtue

Marketing Communications
Anne Foley, *Promotion Manager*
Sara Morris, *Marketing Services Administrator*
Gordon Keegan, *Promotion Specialist*

EDITORIAL

47

A look at the video-game market shows what can happen when a manufacturer uses electronics to stifle a market instead of letting it expand.

NEW PRODUCTS

Components & Power Supplies	223
Computers & Peripherals	239
Integrated Circuits	246
CAE & Software Development Tools	256
Test & Measurement Instruments	262

PROFESSIONAL ISSUES

283

Improving working conditions for engineers: Should the IEEE do more?—*Paul Kinnucan*

LOOKING AHEAD


299

Consumers are unaware of fax for personal computers . . . NASA information-systems budget to increase to \$1.3B.

DEPARTMENTS

News Breaks	21
News Breaks International	24
Signals & Noise	33
Calendar	40
Readers' Choice	136
Literature	272
Career Opportunities	288
Business/Corporate Staff	296
Advertisers Index	298

Odds are 50-50
your perfect ASIC is a
perfect dud the first time
you plug it in.



That's why Mentor Graphics lets you combine ASIC and board circuitry in a single simulation.

Trouble in ASIC paradise.

The big day has arrived.

Your first gate array is back from the foundry. With high expectations, you plug it into your board and power up.

It doesn't work.

Don't feel alone. Over 50% of ASICs aren't operational when first installed in their target system. Even though 95% pass their foundry tests with flying colors.

An immediate solution.

Mentor Graphics shifts these even odds heavily in your favor with our QuickSim™ logic simulator, which lets you simulate both your ASIC and board circuitry in a single run.

With QuickSim, you not only track the internal operations of your ASIC circuitry, but also its transactions with the system at large. If there's a problem, you see precisely where it's located, either inside or outside your ASIC. All in a single, interactive simulation environment, where you can view and graphically "probe" the circuitry created by our NETED™ schematic editor.

Check out our libraries.

Library support is an ideal benchmark to gauge the true worth of an electronic design automation system. The more diverse and plenti-

ful the component modeling libraries, the greater the design capability. It's as simple as that.

By this simple, yet decisive measure, Mentor Graphics brings you unequaled design capability. While other EDA vendors scurry to produce their own ASIC libraries (with little guarantee of accuracy), more ASIC vendors put their libraries on Mentor Graphics workstations than any other. And in most cases, we're the first workstation supported, which means you have the first shot at exploiting new chip technologies.

With Mentor Graphics, you get a breadth of LSI and VLSI component models, both hardware and software based. All of which can be mixed with ASICs in a single simulation that cuts your run time to an absolute minimum.


To be continued.

So much for the present. We're already developing new EDA tools for systems design that will extend to every dimension of electronic product development. From high-level systems descriptions to CASE. It's what our customers expect. It's what we'll deliver.

It's all part of a vision unique to Mentor Graphics, the leader in electronic design automation. Let us show you where this vision can take you.


Call us toll-free for an overview brochure and the number of your nearest sales office.

Phone 1-800-547-7390
(in Oregon call 284-7357).



Mentor Graphics®

Your ideas. Our experience.



8x10⁶ ways what y

We have 8 CMOS PAL[®] chips. That totals up to 8 million different ways to program your logic. Quite enough of a choice to meet your most exacting low power logic needs. From universal PAL architectures to zero stand-by power PAL devices. You can have the system you want without compromise. And without costly delays.

Our all-purpose CMOS architectures give flexibility without draining precious power. The 24-pin industry standard

PALC22V10 uses just 90mA—even when it's running at 25ns.

If you liked us in bipolar, you should see us in CMOS.

We have five CMOS ZPAL[™] devices based on familiar bipolar architectures. You can use them in battery powered and low duty-cycle applications. And they use virtually no power when in stand-by. Two versions are electrically erasable. You can get the functions you're used to and you can change your design as fast as



to get exactly
what you want.

you change your mind.

What did you expect from the people who invented PAL devices?

The largest and most experienced Field Application Engineer force is as close as your phone all during your design-in process.

Our TestPro™ Centers give you access to superior testing and programming support. Just call your AMD sales office for the center nearest you.

And we've kept the classic PALASM®

software up to date with our parts and your needs.

Most important, you can get your hands on our parts. They're all in high volume supplies.

Call (800) 222-9323. It's hard enough to get what you want in life without passing up 8,000,000 more chances.

Advanced Micro Devices 
Monolithic Memories 

901 Thompson Place, P.O. Box 3453, Sunnyvale, CA 94088.

PAL and PALASM are registered trademarks. TestPro and ZPAL are trademarks of Advanced Micro Devices, Inc. © 1989 Advanced Micro Devices, Inc.

Over twice the speed,

NEC

If your design involves binary image processing, you can drive it straight to the winner's circle with NEC's Advanced Compression/Expansion Engine (ACEE).

Higher speed.

The CMOS ACEE gives you more than twice the speed of conventional devices: 0.34 sec for compression and 0.54 sec for expansion of 1,728 x 2,376 bits of binary data with MMR coding.

Greater functionality.

By integrating pipelined code/decode hardware, CPU and DMA controller all on a single chip, our high-performance engine streamlines your design while boosting performance. The CPU handles enlarge/shrink, bit boundary processing and multi-tasking routines such as simultaneous transmit/receive. And a sophisticated command structure assures easy interface with the host.

Put your image storage system, facsimile or PC-FAX on the fast-track to success with NEC's Advanced Compression/Expansion Engine. For full details, call NEC today.


For fast answers, call us at:

USA Tel:1-800-632-3531. TWX:910-379-6985.
W. Germany Tel:0211-650302. Telex:8589960.
The Netherlands Tel:040-445-845. Telex:51923.

Sweden Tel:08-753-6020. Telex:13839.
France Tel:1-3946-9617. Telex:699499.
Italy Tel:02-6709108. Telex:315355.

maximum functionality.


NEC's Advanced Compression/Expansion Engine.



ACEE features

- High speed: 0.34 sec (compression) and 0.54 sec (expansion) for 1,728 x 2,376 bits with MMR coding—A4-size CCITT standard test charts No. 1–8.
- 3 coding systems: MH, MR, MMR—compatible with G3 and G4 facsimiles.
- Max window size: 32K-pixel wide x 64K-pixel high.
- Bit boundary processing.
- Multi-tasking: time-division multiplex operations include code conversion between G3 (MH, MR) and G4 (MMR).
- Packages: 64-pin shrink DIP; 68-pin PLCC.





*size... 7 days**

Now, within just 7 working days, AUGAT will ship you a backplane or card cage in any size you need, from 3 through 21 slots. This isn't simply a promise — it's AUGAT's GUARANTEE*...

Or you pay 20% less!

Our no-nonsense 7-Day VME Program includes both J1 and J2 backplanes. It even includes our new high-performance monolithic backplanes, too. Only AUGAT has the production capability to guarantee 7-day shipment on such a broad selection of backplanes. Now you can plan on the arrival of your VME packaging hardware with no fear of delaying your critical development schedule.

In addition, AUGAT has greatly expanded its entire VME line to include more

standard products ... including new VME power chassis complete with backplane, fully harnessed power supply, cooling, card cage and optional enclosure. AUGAT also has the engineering talent and experience to handle your customized VME packaging needs.

Send for a copy of our new VME catalog today ... because when time is of the essence in locating quality VME products with full engineering support, your surest source is AUGAT!

*AUGAT GUARANTEES to ship backplanes and/or card cage kits in any size (from 3 through 21 slots) in 7 working days from date of approved credit — or you pay 20% less! (limit 3 pieces per part number)

For answers or orders

1-800-999-9VME



AUGAT INC., INTERCONNECTION PRODUCTS GROUP

**PLUS
An Expanded
VME
Product Line**

**NEW
Power Chassis**

**More
Power
Supplies**


**More
Extender
Boards**

**More
Wire-Wrap†
Panels**

**More
Cage Dividers**

**More
Support Data**

†Wire-Wrap is a registered trademark of Gardner-Denver



“We’re getting to market late because prototype revisions are killing us.”

“At HP we faced the same problem. So we developed electronic design automation tools that we use to get designs right before we build expensive prototypes.”

We haven't made prototype revisions a thing of the past...yet. But HP's Electronic Design Automation (EDA) tools can catch most problems while designs are still in their infancy. Where you can fix them faster. At less cost.

As part of DesignCenter, HP's EDA tools handle the spectrum of technology for systems design. From digital to analog and microwave. In designs with ASICs, hybrids and PCBs... even microprocessors. From design capture and simulation to layout and enclosure design. All the resources you need to make sure designs are right before you commit to prototypes.

Once you've built prototypes, HP supports you with the industry's finest test and measurement equipment. Along with the links to integrate design and prototype test.

But it's not just a question of choosing the right tools. It's also the right company. You want a company that's fully committed to support. When you need it. Where you need it. A partner you know you can trust in electronic design automation. That's HP.

Find out how HP EDA tools and support can put you on the competitive track. Call **1-800-752-0900**, Ext. C215, and ask for your FREE EDA "Tool Kit."


"Let's start a dialogue..."



CIRCLE NO 156



THE ANALOG IC SEARCH STARTS...



AND STOPS HERE

PMI's free **Precision Decisions selector guide disk** eliminates the search of your entire library for the analog or data conversion IC essential to your design.

All you need is the disk, an IBM®-compatible PC, and DOS. With PMI's unique program, input your IC design specs or current part number and the disk does the searching. **Once the optimum device has been identified for you,** (operational amplifier, data converter, matched transistor, voltage reference, voltage comparator, sample-and-hold amplifier, analog switch, or multiplexer) refer directly to the appropriate data sheet in PMI's 1300 page full line catalog for complete design curves and specifications on the part.

Precision Decisions also features pricing, Mil/Aero and SSM Audio product listings, new product guide, sales office listing, and part numbering system. **Free quarterly updates** ensure you have current information available.

PMI offers the latest design tools to make your job easier. Call us and find out the other ways we can help you.

To receive your free copy of Precision Decisions, call **800-843-1515** or complete and mail the coupon below. **Your next search for an analog IC will start and stop with PMI.**



Precision Monolithics, Inc.
A Bourns Company

1500 Space Park Drive
P.O. Box 58020
Santa Clara, California 95052-8020

Please send me a free copy of Precision Decisions

Name: _____

Title: _____

Company: _____

Address: _____

Phone Number: _____

Check boxes that apply:

I would like to receive free quarterly updates of Precision Decisions

Also send me PMI's full line catalog

EDN041389



ALTAMONTE SPRINGS: (407) 260-9780, ATLANTA: (404) 263-7995, BOSTON: (508) 794-0026, CHICAGO: (312) 250-0808, DALLAS: (214) 690-3495, DENVER: (303) 792-9595, DETROIT: (313) 227-2190, LOS ANGELES: (818) 886-6881, MILPITAS: (408) 942-8060, ORANGE COUNTY: (714) 637-9602, PHILADELPHIA: (215) 953-1070

NEWS BREAKS

EDITED BY JOANNE DE OLIVEIRA

LOW-COST FUNCTIONAL TESTER OFFERS MIXED-SIGNAL TESTING

To produce the Testar System 4000 desktop functional tester, Proteus Corp (Littleton, CO, (303) 795-5944) blended a Compaq personal computer, an 18-slot VME Bus rack, an assortment of standard test cards and power supplies, and a custom test head, then added a large amount of software to the PC. The test system employs guided-probe troubleshooting and shows the operator where to place the test probe by using the PC's graphics to paint a realistic picture of the circuit board under test. The tester employs Pascal for its test-programming language and includes several utility programs to help you generate, debug, and run functional tests. Yet another utility program allows you to create graphic images of the circuit boards. In operation, the tester verifies what it can from the circuit board's connectors. Next, it guides the operator to the suspect circuit nodes by superimposing a large arrow on the displayed image of the board; the arrow points to the device pin or lead in question. Because the system employs modular test cards, you can tailor the capabilities of the Testar System 4000 to your specific test needs. Prices start at \$50,000.—Steven H Leibson

VENDOR UNVEILS BOTH RISC- AND CISC-BASED WORKSTATIONS

Two months after a rival workstation vendor surprised almost everyone by making sweeping changes to its workstation product family, Sun Microsystems (Mountain View, CA, (415) 960-1300) parried the attack by making some changes of its own. In a move that could be interpreted either as hedging its bets or as serving both sides of the market, Sun announced both SPARC RISC-based workstations and 68030 CISC-based workstations. The SPARCstation 1 is a low-end workstation that provides 10 MIPS and 1.5M flops; it costs less than \$10,000. The higher-end SPARCstation 300 Series uses a 25-MHz SPARC CPU to perform 15 MIPS and 2.5M flops; it costs under \$30,000. Optional graphics upgrades let you use the workstations for 3-D modeling applications. The SPARCserver 330 is an entry-level server for a multiuser configuration. You can configure the 330 with as much as 1.3G bytes of disk memory and 40M bytes of main memory.

Sun offered some rays of hope for 68030 fans, too. The Sun-3/80 delivers 3 MIPS and 0.15M flops with 4M bytes of memory and as much as 200M bytes of internal disk space. Its price starts at less than \$7000. The 3/470 performs 7 MIPS and 0.8M flops and costs as little as \$35,000. Like their RISC-based cousins, the Sun-3 workstations offer optional graphics upgrades. Further, the Sun 3/480 servers support 14.3G bytes of disk storage and 128M bytes of main memory in a network system.

—Michael C Markowitz

TOUCHSCREEN SENSES FINGER PRESSURE AND POSITION

Conventional resistive, capacitive, and infrared touchscreens sense finger position only. Unlike those conventional models, the Z-Touch touchscreen from Transparent Devices Inc (Westlake Village, CA, (805) 497-8500) senses pressure as well. Finger pressure on a resistive touchscreen causes a film coated with transparent vertical conducting traces to touch a film directly behind it that is coated with transparent horizontal conducting traces. Scanning electronics convert the signals from the horizontal and vertical traces to an x-y position. The Z-Touch screen has a third film, and its electronics can sense when the pressure is strong enough to press the first two films into the third. (Surface-acoustic-wave (SAW) touchscreens can also detect

NEWS BREAKS

finger pressure, but when two fingers press the screen simultaneously, the screen electronics gives the x-y position as the average of the two positions.) To activate the third screen, the Z-Touch requires finger pressure that's about four times the pressure required for two screens. For example, if normal pressure on the screen is 25g, you need to apply 100g to activate the third layer. The manufacturer claims the screen's life is at least 6 million cycles. A 7-in. diagonal touchscreen costs \$130.—Margery Conner

SOFTWARE PERFORMS ELECTRICAL PARAMETER EXTRACTION

Valid Logic Systems' (San Jose, CA, (408) 432-9400) Allegro Release 3.0 lets you study the potential transmission-line effects that can affect your pc boards—before the boards go to manufacturing. The interactive electrical-parameter calculator obtains measurements of expected circuit behavior such as impedance, propagation delay, capacitance, inductance, and resistance. When you know these values, you can modify your design to achieve the signal behavior you need.

Additional enhancements to Allegro include two design-rule checks (DRCs), one by component height and one by net group. With these DRCs, you can specify a maximum component height to prevent potential interference that might result from the placement of large components, and you can create net classes for variably spaced line-to-line DRCs. The Allegro 3.0 runs on the Sun-3, the Sun-4, and DEC VAXstations and DECstations. The upgrade is available at no cost to current users who have maintenance contracts; otherwise, it costs between \$20,000 and \$50,000, depending on the configuration.—Michael C Markowitz

MULTIPLEXERS BOOST PERFORMANCE OF MULTIUSER SYSTEMS

System Corp (San Diego, CA, (619) 453-8970) now offers a second generation of its Unplug family of multiplexer products. The multiplexer family includes host adapters that occupy a single VME Bus or Multibus slot in the host computer. Eight- and 16-channel cluster controllers connect to the host via a single coaxial cable, and they can interface as many as 255 RS-232C devices to a system. (The first generation of products could serve 128 serial devices from a single host adapter.) The HPS-6200 Series host adapters range in price from \$1765 to \$2210 (100), and the HPS-7000 line of cluster controllers costs \$858 to \$1045 (100). The new family of products also includes the HPS-6236 and 6237 16-channel VME Bus multiplexer cards (the 6237 includes a parallel port). The bus-resident multiplexers cost \$1185 and \$1260 (100), respectively. The company achieved the new price/performance levels by designing and using a custom 8-channel UART IC called an Octart. The multiplexer family will be available in the second quarter.—Maury Wright

STD BUS CARD MONITORS EVENTS ON 24 LINES WITHOUT POLLING

The ZT8846 event-sense interface, an STD Bus card from Ziatech Corp (San Luis Obispo, CA, (805) 541-0488) lets you monitor events on 24 lines. The board takes advantage of the STD Bus's capability of supporting cascaded interrupt controllers, a feature that's not available on the IBM PC bus. Each of the 24 lines can generate a unique interrupt vector by using a single hardware-interrupt line. These interrupts quickly signal an STD Bus processor of events or changes in status without wasting processor time on polling. The board can generate interrupts on high transitions, low transitions, or both. You can individually enable or disable interrupts in software. The card costs \$495.—Doug Conner



TMC2310 Runs 1024-Point FFT in 0.5ms

Here's the FFT runner you need to win the race. It's the TMC2310 — the first single-chip FFT controller to be this fast and simple to use.

Imagine all of these capabilities on one chip: Arithmetic functions, FFT coefficients ("twiddle factors"), even built-in address generation. That's why the TMC2310 runs forward or inverse transformations, or multiple equal-length FFTs totalling 1024 points, in just 0.5ms. Or a complex radix-2 butterfly in only 100ns. The TMC2310 executes other functions just as quickly, including FIR filtering and vector operations. Even data windowing is included without impact on either performance or price.

Better still, no development system is required. The TMC2310 jumps into

action with just two 13-bit control words. It's so simple. No complex, bit-slice, microcode-intensive building blocks. No chip sets to contend with either.

You can qualify for a FREE sample. Just tell us about your application and we'll send you a TMC2310 to run in your system. You can build a complete spectrum analyzer with the TMC2310, our new 12-bit ADC (THC1200 Series), our TDC1012 DAC and external data and window memories. Be a winner. Try the TMC2310. Available now in 88-pin plastic pin grid array (PPGA) from TRW LSI Products or your nearest Hall-Mark or Hamilton/Avnet location.

TRW LSI Products — Bringing the worlds of Data Acquisition and DSP together.

TRW LSI Products Inc.
P.O. Box 2472, La Jolla, CA 92038
619.457.1000

In Europe, phone:
TRW LSI Products Inc.
Munich, 089.7103.115;
Guildford (U.K.), 0483.302364

In the Orient, phone:
Hong Kong, Tektron, 3.880629;
Tokyo, Dia Semicon, 3.487.0386,
Teksel, 3.461.5121;
Taipei, Sea Union, 2.751.2062;
Seoul, M.S., 2.553.0901;
Singapore, Seamax, 65.747.6155;
Australia, Email, 613.544.8244

TRW LSI Products Inc.

©TRW Inc., 1988 — 712A03688 TMC2310

NEWS BREAKS: INTERNATIONAL

MODEMS CONFORM TO LATEST CCITT ERROR-CORRECTION STANDARDS

The Sprint-24QB and -96QB asynchronous dial-up modems from Mayze Systems Ltd (Swindon, UK, FAX 0793-511683) comply with the V42 standard, which is the latest error-correction standard from the CCITT. V42 is expected to become the dominant form of error correction for modems. It also implements all the requirements of the V42-bis data-compression standard. The modems also include the MNP-5 error correction scheme, which makes them compatible with a wide range of equipment. The Sprint-24QB modem, which costs £595, has V21, V22, V22-bis, and V23 operating modes; it transmits and receives data at rates between 300 and 2400 bps. The Sprint-96QB, which sells for £1295, offers the same modes plus a V32, 9600-bps mode. Both modems feature automatic baud-rate detection, 12 prestored modem setups, five different dialing methods, and password-secured data protection. They are available as stand-alone units or as plug-in cards for the company's Network-16 distributed network-management system.—Peter Harold


5¼-IN., ERASABLE OPTICAL DISK DRIVE STORES 644M BYTES

Developed by Hitachi Ltd (Tokyo, Japan) in cooperation with NTT, the OD112-1 5¼-in., rewritable, optical disk drive employs magneto-optic recording to store 644M bytes on an ISO-compatible disk cartridge. The drive features a 75-msec average access time and can transfer data at a 925k-byte/sec rate in burst mode to its companion formatter/controller, the OD112S. The formatter/controller board communicates with a host system through its SCSI port, and it can transfer data to the host at a burst rate of 1.5M bytes/sec. Both the drive and the formatter/controller board are available in the US from Hitachi America Ltd (San Bruno, CA, (415) 872-1902); the pair costs \$5000 in sample quantities.—Steven H Leibson

SINGLE-EUROCARD PC SUITS INDUSTRIAL APPLICATIONS

The ECPC single-board computer from DSP Design (London, UK, FAX 01-482-1779) provides you with IBM PC compatibility on a single-Eurocard pc board. The ECPC is compatible with the IBM PC at both the BIOS and the hardware-register level. Based on the NEC V40 µP, the board includes a disk controller for 3½- or 5¼-in. floppy-disk drives; an RS-232C (serial) port; a Centronics (parallel) port; keyboard- and sound-output interfaces; and a graphics controller that provides CGA, monochrome, or Hercules-compatible graphics. As an alternative to booting MS-DOS from disk, you can configure the board to boot the operating system from an onboard 128k-byte ROM disk. The board can stand alone, or you can implement system expansion via its STE Bus interface. The computer is constructed from CMOS devices and operates from a single 5V supply. A version with an extended temperature range is available. The board costs from £450 to £1150, depending on its configuration.—Peter Harold

At last, an assistant that follows your directions



Wouldn't it be great to delegate your routing?

You can! We know your time is valuable. That's why Wintek pioneered comprehensive and affordable CAD packages for IBM personal computers. HiWIRE-Plus continued that tradition, integrating schematic-capture features and printed-circuit-artwork capabilities into one versatile package.

New autorouter.

The Autorouter for HiWIRE-Plus is powerful enough to handle the most demanding design problems, yet simple enough for a casual user. Just turn it loose on your design. It's hassle free because it works long hours, without supervision or errors.

100% autorouting.

The autorouter for HiWIRE-Plus rips-up, reroutes, and with appropriate design rules, racks up 100% completion.

- Forget gridded routers. This autorouter places vias and traces anywhere your design rules allow. With 1-mil resolution.
- Vary trace width and spacing for individual networks. Route 1, 2, 3, or more tracks between IC and connector pins.
- Set up boards from 1 to 250 layers, up to 60" x 60".
- Specify shape, size, and type of vias, layer-by-layer: through-hole, blind, buried, micro. Specify via types for individual networks.
- Use fewer vias and layers than comparably priced autorouters.
- For use on your IBM PC, XT, AT, PS/2, or compatible with 640K RAM.

Why pay more for a 100% autorouter?

Compare the features and performance to packages costing five times more. HiWIRE-Plus and the Autorouter for HiWIRE-Plus sell for \$895 each. Both have a no-nonsense, 30-day money-back guarantee. With unlimited, toll-free, no-charge technical support.

Let HiWIRE convince you that it makes a great assistant. Call us toll-free at (800) 742-6809 today and put HiWIRE-Plus and the Autorouter for HiWIRE-Plus to work for you tomorrow.



Wintek Corporation
1801 South Street
Lafayette, IN 47904-2993
Fax: (317) 448-4823
Phone: (317) 742-8428 or

(800) 742-6809



value-packed
filters from **\$11.45**

dc to 3GHz

- less than 1dB insertion loss over entire passband
- greater than 40dB stopband rejection
- 5 section, 30dB per octave roll-off
- VSWR less than 1.7 (typ)
- over 100 models, immediate delivery
- meets MIL-STD-202
- rugged hermetically sealed package (0.4 x 0.8 x 0.4 in.)
- BNC, Type N, SMA available

finding new ways...
 setting higher standards

Mini-Circuits

A Division of Scientific Components Corporation
 P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500
 Fax (718) 332-4661 Domestic and International Telexes: 6852844 or 620156

LOW PASS	Model	*LP-	10.7	21.4	30	50	70	100	150	200	300	450	550	600	750	850	1000
Min. Pass Band (MHz) DC to			10.7	22	32	48	60	98	140	190	270	400	520	580	700	780	900
Max, 20dB Stop Frequency (MHz)			19	32	47	70	90	147	210	290	410	580	750	840	1000	1100	1340


Prices (ea.): Qty. (1-9) P \$11.45, B \$32.95, N \$35.95, S \$34.95

HIGH PASS	Model	*HP-	50	100	150	200	250	300	400	500	600	700	800	900	1000
Pass Band (MHz)	start, max.		41	90	133	185	225	290	395	500	600	700	780	910	1000
	end, min.		200	400	600	800	1200	1200	1600	1600	1600	1800	2000	2100	2200
Min. 20dB Stop Frequency (MHz)			26	55	95	116	150	190	290	365	460	520	570	660	720

Prices (ea.): Qty. (1-9) P \$14.95, B \$36.95, N \$39.95, S \$38.95

*Prefix P for pins, B for BNC, N for Type N, S for SMA example: **PLP-10.7**

C105 REV. E



Amplifier Arsenal

50KHz—2000MHz, Low Noise 250mW output Gain Controlled from **\$69.95**

Our ZFL-2000 miniature wideband amplifier hit a bulls-eye when we introduced it last year. Now we've added more models to offer you a competitive edge in the continuing battle for systems improvement.

The ZFL-2000, flat from 10 to 2000MHz, delivers +17dBm output and is priced at only \$219.

Need more output? Our ZFL-1000H, flat from 10 to 1000MHz, delivers +20dBm output.

Is low noise a critical factor? Our ZFL-500LN and 1000LN boast a 2.9dB NF.

Variable gain important? Our ZFL-1000G, flat from 10 to 1000MHz, delivers +3dBm output with 30dB gain control while maintaining constant input/output impedance.

Searching for a high-quality, low-cost amplifier? Our ZFL-500 flat from 50KHz to 500MHz, delivers +10dBm output for the unbelievable low price of only \$69.95. Need to go higher in frequency? Consider the ZFL-750, from 0.2 to 750MHz, for only \$74.95. Or the \$79.95 ZFL-1000, spanning 0.1 to 1000 MHz.

One week delivery...one year guarantee.

SPECIFICATIONS

MODEL	FREQUENCY MHz	GAIN, dB (min.)	MAX. POWER OUTPUT dBm(typ)	NF dB(typ)	PRICE \$ Qty. (1-9) Ea.
ZFL-500	0.05-500	20	+9	5.3	69.95
ZFL-500LN	0.1-500	24	+5	2.9	79.95
ZFL-750	0.2-750	18	+9	6.0	74.95
ZFL-1000	0.1-1000	17	+9	6.0	79.95
ZFL-1000G*	10-1000	17	+3	12.0	199.00
ZFL-1000H	10-1000	28	+20	5.0	219.00
ZFL-500HLN	10-50	19	+16	3.8	99.95
ZFL-1000LN	0.1-1000	20	+3	2.9	89.95
ZFL-1000VH	10-1000	20	+25	4.5	229.00
ZFL-2000	10-2000	20	+17**	7.0	219.00

* 30dB gain control ** +15dBm below 1000MHz

finding new ways ...
setting higher standards

Mini-Circuits

A Division of Scientific Components Corporation
P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500
Fax (718) 332-4661 Domestic and International Telexes: 6852844 or 620156

C101 REV.F



WREN™

THE BEST 5¼" DISK DRIVES AVAILABLE.

Performance Second to None

The WREN family of 5¼" disk drives delivers the highest performance available today. For example, the WREN RUNNER™ has an average seek of only 10.7 ms. And all WREN products use a patented balanced straight-arm actuator. This reduced-mass design, unique to WREN, results in precision read/write head positioning and faster seek times.

A Lasting Quality

WREN drives feature a 40,000 hour MTBF, lower power consumption, special shock mounts, lifetime internal HDA environmental control, automatic actuator restraint and a dedicated head landing zone. It all adds up to years of trouble-free operation.

Introducing WREN VII

We've made the fastest, most reliable 5¼" disk drives better than ever. The new WREN VII has a capacity of 1200 Mbytes and is available with the SCSI interface. What's more, it uses IMPRIMIS ZBR™ variable track capacity recording. ZBR offers higher capacity, performance and reliability than standard recording techniques.

We've Made a Commitment to You

Our commitment to you is the same as our commitment to ourselves: To be the best. We're fulfilling it by building the most advanced, high performance, high quality, 5¼" rigid disk drives in the world. And we're backing them with top-notch service and support. It's a commitment to quality that goes into every WREN drive, from 50MB to 1200MB.

Get the High Performance Edge...
WREN disk drives from Imprimis



Performance to Match Your Needs

Model	Capacity (Mbytes) (UF)/(F)	Interface	Avg. Seek (ms)	Transfer Rate (MHz)
WREN VII	1200/1050	*SCSI	16.0	15-23
WREN VI	766/676	*SCSI	15.5	15
	766/676	ESDI	15.5	15
WREN VI H/H	383/338	*SCSI	15.0	18-20
	383/338	ESDI	16.0	15
	383/338	AT	16.0	15
	274/242	AT	16.0	15
	164/145	AT	16.0	15
WREN V	702/613	*SCSI	16.5	12-16
	385/339	*SCSI	10.7	15-16
	442/390	ESDI	16.0	10
	383/338	ESDI	14.5	10
WREN V H/H	209/183	*SCSI	18.0	9-15
WREN IV	376/330	*SCSI	17.5	10-15
	350/307	*SCSI	16.5	9-15
WREN III	182/160	*SCSI	16.5	10
	182/160	ESDI	16.5	10
WREN III H/H	106/94	*SCSI	18.0	10
	106/94	ESDI	18.0	10
WREN II	135/115	RLL	28.0	7.5
	96/80	ST506	28.0	5
	86/71	ST506	28.0	5
	85/71	ST506	28.0	5
	86/71	ESDI	28.0	5
WREN II H/H	81/74	AT	28.0	7.5
	74/65	AT	28.0	7.5
	77/65	RLL	28.0	7.5
	51/41	ST506	28.0	5


H/H = Half Height Models. (UF) = Unformatted Capacity. (F) = Formatted Capacity at 512 Bytes/Sector. All WREN Disk Drives have 40,000 hours MTBF. *Apple Mac compatible interface available.


For the authorized distributor nearest you call:

Arrow Electronics: 1-800-777-ARROW
Anthem Electronics:
 Northwest Region 1-800-395-3502
 Central Region 1-800-395-3517
 Eastern Region 1-800-395-3511
 Southwest Region 1-800-395-3501

IMPRIMIS

A Subsidiary of Control Data
CIRCLE NO 115





If you're testing complex boards,

You're facing one of test engineering's toughest challenges. VLSI boards like this one. But with a Teradyne L200 board tester on your side, complex test problems can be conquered quickly.



The L293 VLSI Module Test System.

Stay in front of VLSI/VHSIC advances.


Start with the most advanced hardware for analog and digital testing. An L200 fires functional test patterns at 40 MHz rates. At up to 1152 test channels. Top speed is 80 MHz. That's 4 to 8 times faster than any competitor can deliver.

And the L200 hits test signal timing precisely. With up to 32 timing sets for drive phases and test windows. Its 250 ps programming resolution with zero dead time puts signal edges right where you want them.

Divide and conquer.

VLSI/VHSIC boards demand large, complex test programs. But the L200's distributed computer architecture simplifies matters.

Testing is controlled by a VAX computer. It sends tasks to specialized processors for rapid deployment of analog, digital, and memory tests.



here's a simple plan of attack.

Programmers will appreciate clustered VAX workstations. Graphics, like waveforms and shmoo plots, make heavy debug and analysis light work.

Simulation and other tactics.

High-powered software tools tailor L200 test development to modern design techniques and test strategies. Precisely the caliber of tools you need to get tests up and running fast.

Test Channels	Maximum Pattern Rate	Channel Skew
L297	1152	80 MHz ± 1.5 ns
L293	576	80 MHz ± 1.5 ns
L280vx	1152	10 MHz ± 10 ns
L210vx	576	10 MHz ± 10 ns

L200 VLSI board test systems are the performance leaders.

Take our LASAR simulator. It works closely with the L200 for both cluster and board-level testing. LASAR accurately predicts VLSI circuit responses and reports test program fault coverage.

Significantly, LASAR simulates L200 charac-

teristics. So test programs automatically include when to test board responses. And what response is expected. The result is uncompromising go/no go tests as well as precise guided probe or fault dictionary diagnosis.


A powerful ally.

L200's have proven themselves under fire at hundreds of advanced manufacturing sites worldwide. So if you're about to take on a new VLSI/VHSIC project, find out how to launch a winning test strategy. Call Daryl Layzer at (617) 482-2700, Ext. 2808 without delay.



VAX is a trademark of Digital Equipment Corp.

Thanks to Elantec, video design engineers are no longer worried about going in the red.




With its true color accuracy, Elantec has the video industry seeing red.

Bright red. Like never before possible with an IC.

Just like we're extending possibilities in a variety of applications. From disk drives and LANs, to ATE, instrumentation and more.

One of the products that makes Elantec red-hot for video equipment is our 50MHz EL2020 video amplifier. It cuts differential phase error below 0.02° . And reduces differential gain error to 0.02% or less.



That means truly superior video characteristics.

Plus you get powerful cable-driving capability. All with less cost and less space than previous broadcast-quality solutions.

For all high-performance applications, look to the full family of Elantec high-speed analog products. Including everything from amplifiers and buffers, to pin drivers, comparators and transistor arrays. Each backed by the industry's only two-for-one guarantee. Elantec, analog that's ahead of the times.

Free Selection Guide. For a copy of Elantec's Selection Guide, circle the bingo number or write Elantec.

Make it a red letter day for your designs.



élantec
HIGH PERFORMANCE ANALOG INTEGRATED CIRCUITS

Elantec: 1996 Tarob Court, Milpitas, CA 95035. Telephone: (408) 945-1323. Fax: (408) 945-9305 © 1989 Elantec
European Sales: 87 Jermyn Street, London, SW1Y6JD, England. Tel: 44-1-839-3841, Telex: 917835, Fax: 44-1-930-0751

SIGNALS & NOISE

Error magnifies the ENIAC

The article "The microprocessor's first two decades: The way it was" by James F Donohue, which appeared in EDN's Special Microprocessor Issue (October 27, 1988, pg 18), requires a correction to set the record straight. Way back when, someone made an error in dimensions that has been promulgated by numerous uninformed writers, including James Donohue. He states that "the first electronic computer, the fabled ENIAC, . . . filled 3000 cubic feet."

The statement contains not one but two major errors. Normally, the error appears as "3000 square feet"; however, your article errs in the magnitude as well as the units. The statement should read "1500 square feet." To clarify the issue properly, the computer system was in a room containing approximately 1800 square feet; the computer itself occupied 1500 square feet. The ENIAC was, of course, at the BRL (Ballistic Research Laboratory), where this computer-generated letter is being prepared. In fact, my office is in the very spot where the 1800 square feet is (I've personally measured it at least once).


I would very much appreciate seeing a correction published in EDN so the proper figures will be seen by all, once and for all! One doesn't need an ENIAC or a Cray (we have the latter now as well as a small portion of the former) to get the numbers correct.

Michael B Danish

*Ballistic Research Laboratory
Aberdeen Proving Ground, MD*

Setting the record straight on CP/M

I enjoyed your Special Microprocessor Issue (October 27, 1988). The issue brought back memories of the "early days," but it also included an error that I have seen repeated



in numerous books, magazines, and even a computer trivia game. In the article "The microprocessor's first two decades: The way it was" (pg 18), James Donohue states on pg 25 that Gary Kildall wrote a disk-based operating system and called it CP/M (Control Program/Microcomputers). The "M" did not stand for "Microcomputers," it stood for "Monitor." And "Monitor" didn't mean a CRT or "the tube."

Recall that in the early days, one had to be wealthy (or a fanatic) to own a floppy-disk drive, more than 8k bytes of RAM, or a CRT. The pioneers instead used old teletype equipment for data entry and display, and paper tape or cassette recorders for mass storage. Kildall included a program with his system that used very little memory, yet allowed the user to perform very elementary functions (clear memory, load paper tape, etc), because most users did not have floppy-disk-based systems. This program was called the "monitor."

For the sake of technical and historical accuracy, let's set the record straight: The "M" in CP/M means "Monitor."

*Jerome Johnston
Applications Engineer
Crystal Semiconductor
Austin, TX*

Starts with D

The article "The microprocessor's first two decades: The way it was" (EDN's Special Microprocessor Issue, October 27, 1988, pg 18) erroneously stated that Digital Equipment Corp had teamed with Motorola to develop a 100-MIPS ECL version of the 88000 RISC processor. In fact, it's Data General that has joined with Motorola to create the processor. Data General has agreed with Motorola to build a family of products using the CMOS 88000 RISC processor, and the two companies will jointly develop the high-end ECL version, which they expect to have by 1991. Data General will design the ECL chip; Motorola will manufacture and market it. The ECL chip will be fully compatible with the CMOS 88000 chip.

Design Idea correction

If some EDN readers found my Design Idea "Single MACD performs IIR filtering" (EDN, October 13, 1988, pg 248) a bit confusing, they have my sympathy. The second page of Listing 3, starting with line 0056, was printed at the bottom of Listing 2. The text contains numerous references to FBVEC, but there's no such symbol in any of the listings!

For the benefit of anyone who hasn't by now either figured this all out from the comments in the listings, or dismissed it as a Halloween trick, an excerpt or two from my original manuscript would be in order. Most of the gremlins got into the second paragraph. I present here the original:

"To use a single MACD loop, the feedback value must be the filter output. The two delay vectors may be concatenated in either order; the coefficients are stored in reverse order of the corresponding vector elements, since the vector is addressed in reverse order because of the DMOV operation in the MACD.

SIGNALS & NOISE

With INPVEC first as shown, the first word in FBKVEC gets overwritten by the DMOV of the last word of INPVEC and gets rewritten after the MACD loop. Likewise the word at the beginning of INPVEC, which is overwritten by the last execution of the MACD, gets rewritten next call with the new input sample."

The first paragraph on pg 252 should describe a constraint on the feedback coefficient scaling, not the feedback vector (FBKVEC) scaling. The original reads:

"There is no inherent need to scale FBKVEC and INPVEC identically. Only the feedback coefficients are constrained to scale factors which can be shifted with available P modes and output shifts to keep the total shift from FBKVEC back to itself zero."

Two other, less confusing, errors also appeared. The word "bit" was

added after "ARP" in the first paragraph. The ARP (Auxiliary Register Pointer) has three bits. Finally, the last paragraph contains a sentence that begins: "Note also that the routine executes the low-order filter section in reverse order" The word "section" should be plural; that is, the last filter section is executed first.

*Richard H Neubert
Miltope North
Springfield, VT*

Wish granted

In response to David Cockerell's "μP/memory wish list" in the Signals & Noise column of EDN's October 13, 1988, issue (pg 33), David need only look to National Semiconductor's Series 32000 family of 32-bit microprocessors. Both the NS32532 and the NS32332 microprocessors feature dynamic bus siz-

ing, which lets the CPU accommodate 8-, 16-, or 32-bit-wide buses.

The company also offers a trio of dynamic-RAM (DRAM) controllers, the DP8420A/21A/22A, that make interfacing to DRAM as easy as interfacing to static RAM. These devices are software programmable to work with all popular microprocessor families.

*Jeffrey Goldberg
Series 32000 Applications Engineer
National Semiconductor
Santa Clara, CA*

WRITE IN

Send your letters to the Signals and Noise Editor, 275 Washington St, Newton, MA 02158. We welcome all comments, pro or con. All letters must be signed, but we will withhold your name upon request. We reserve the right to edit letters for space and clarity.

A Surface Mount Breakthrough!

First True Surface Mount Wirewounds.


Low aspect ratio for easy handling and stable mounting. No tipping or rolling. Field proven for high speed automatic placement.

Wraparound Terminals. Hot solder dipped copper provides maximum solder bond area, promotes efficient heat transfer and eliminates need for machine orientation.

Precision in Minimum Space. Reliable wirewound element in molded housing. Occupies up to 30% less space than comparable axial lead resistor.

Dale WSC Wirewound Resistors

Now you can have all the advantages of wirewound resistance in a space-saving package. Dale's WSC is totally compatible with standard surface mounting techniques. It eliminates the slowdowns and compromises of products merely adapted for surface mounting. You get a true SMD — designed from the board up to combine fast, economical assembly with low values, low TC's, close tolerances and high power-to-size ratios. It's the breakthrough you expect from the industry leader in resistance technology. Call your Dale Representative or Dale Electronics, Inc., 1122 23rd Street, Columbus, NE 68601. Phone (402) 564-3131.



SPECIFICATIONS

WSC-1 = 1-watt, 0.1Ω — 2.38KΩ
WSC-2 = 2-watts, .005Ω — 10.4KΩ
Tolerances: ± .05% to ± 5%
TC/R: ± 20, 50, 90 PPM/°C

Dimensions:
WSC-1 = .250L x .150W x .110H and
WSC-2 = .445L x .275W x .162H.


Tape and Reel Packaging:
WSC-1 = 16mm and WSC-2 = 24mm
NOTE: WSC-1 = .112 x .337
(std. chip) footprint.



Dale Makes Your Basics Better

PERFORMANCE

means 15ns wide word SCRAMs



15ns

SCRAMs are Static CMOS Random Access Memories from Performance Semiconductor. At 15ns address access time these 64K's and 16K's are the world's fastest. SCRAMs are manufactured in Performance's six inch class 1 fabrication facility using PACE II 0.7 micron gate length technology which has set the standard for memory speed.

There is immediate availability of 15ns 64K and 16K bit SCRAMs compatible with JEDEC standard pinouts. Also available from stock are 17, 20 and 25ns speed versions.

15NS SCRAM PRODUCT GUIDE

PART	CONFIG.	SPEED	AVAIL.
P4C164	8K x 8	15ns	NOW
P4C188	16K x 4	15ns	NOW
P4C198	16K x 4	15ns	NOW
P4C198A	16K x 4	15ns	NOW
P4C1982	16K x 4	15ns	NOW
P4C1981	16K x 4	15ns	NOW
P4C168	4K x 4	15ns	NOW
P4C169	4K x 4	15ns	NOW
P4C170	4K x 4	15ns	NOW
P4C1682	4K x 4	15ns	NOW
P4C1681	4K x 4	15ns	NOW
P4C116	2K x 8	15ns	NOW

FAST, COOL, & AFFORDABLE

For further information or to order 15ns SCRAMs call or write:

Performance Semiconductor
610 E. Weddell Drive,
Sunnyvale, CA 94089
Telephone: 408 734-9000

CIRCLE NO 49

PERFORMANCE
SEMICONDUCTOR CORPORATION

DAS 9200

Why one hour here saves a week anywhere else.

6 μ P's AT ONCE

You may not need this kind of integration capacity today. But you can evolve into it, looking at the interactions of all hardware and software components at

NOW WITH FASTER μ P SUPPORT.

The DAS 9200 Digital Analysis System: Why poke around for the problem when you can attack it on all sides at once, with the world's most powerful accumulation of digital troubleshooting tools? Now we've boosted DAS 9200 capabilities even further with Release 2 hardware and software...

128K PER CHANNEL

With the 92A90D acquisition module, you get about 128 times the memory depth of most analyzers. All DAS acquisition cards feature comprehensive triggering, plus selective data suppression, conditional branching, performance analysis, and much more.


540 CHANNELS

The DAS 9200's tightly-coupled architecture allows you to "weld" cards together to act as a single, wider card, or as individual clusters of modules that can trigger and arm each other, then display information as from a single unit. Maximum configuration: 540 acquisition channels or 1008 stimulus channels.


including a new high-speed microprocessor interface that pushes the edge of both RISC and CISC micro

support.

We now offer 33 MHz support for the 68030; 33 MHz for the 68020; 25 MHz for the 88100; and 25 MHz for the 80386—with the capacity for even greater speeds built-in.



Split screen display of data acquired simultaneously from two microprocessors. The cursors can be locked to scroll in parallel, highlighting data nearest to the same point in time.



Version 2


once, with true time-correlation of all data.

Monitor the integration of dedicated I/O processors relative to the Main CPU. Test communications links

between processors. Display disassembly activity together with high-resolution timing information to relate logic problems relative to specific events.

2 GHz


For applications requiring nanosecond edge resolution, the 92HS8 High-Speed Timing Module gives you 2 GHz bandwidth and a 500 ps sample interval, supported by a <1 pf input capacitance probe that eliminates common-mode noise and circuit loading. The 92HS8 also welds together to serve wide, parallel applications with no width/speed tradeoffs.



One new asked-for option is the 92LAN card, allowing the DAS to act a network node for efficient file transfer.


Add in its new 8 MB memory for fast response, new 40 MB hard disk, standard, and an assortment of software enhancements, and you see that the DAS not only started in a league by itself. It's staying there.

To find out more about the DAS 9200, contact your Tek representative, or call 1-800-245-2036. In Oregon, 231-1220.



(Above) A/D data captured and displayed using Graph Format.

(Left) Software Performance Analysis display shows the distribution of execution times.



MORE TO COME


Tektronix
COMMITTED TO EXCELLENCE

Oki helps you achieve faster, easier DSP application development with a complete portfolio of support tools.

Oki Semiconductor meets your DSP needs by bringing you the best price/performance available, with our MSM6992 and MSM699210 DSP devices. We also offer powerful hardware and software support tools at various price points to speed and simplify your DSP application development.

A full set of powerful DSP support tools

- ▶ *Software Simulator*—the SIM92 simulates all internal operations of the MSM6992/10 devices, allowing you to test routines without hardware. It utilizes the emulator command set and offers advanced options such as a dump-restart facility, efficiency parameters, and histograms.
- ▶ *High-Level Language*—the OSL92 programs as a subset of C and speeds DSP software development, with one line of OSL92 code equivalent to six lines of assembly code. Specifically tailored for the 6992 architecture, it exhibits remarkable performance when compared to hand-assembled code, with efficiencies of up to 95%.
- ▶ *Emulators*—Oki offers a choice of stand-alone in-circuit emulators for real-time emulation, with the EMU92 and EMU92L.
- ▶ *Software Libraries of User Routines*—these libraries contain many of the most commonly used routines in DSP programming.
- ▶ *Development System*—the PSP92 permits real-time processing of analog signals through separate “digital” and “analog” PC-AT cards. It also allows for sophisticated 16-color EGA-compatible graphics.



The best DSP choice

Oki's full complement of DSP support tools have the power to help you get your product to market faster. And Oki makes them easy to use. They are all PC-based, fully documented and use the same debugger language. So if you are evaluating DSPs for a new design, make the smart choice. Oki gives you the devices *and* the support to streamline your DSP application development.

Streamline DSP with Oki

EDN041389

- Please send me your new brochure *Keys to faster, easier DSP application development* containing detailed technical data/specs on Oki's MSM6992/10 DSP devices and complete portfolio of DSP support tools.
- Please call, we have immediate needs.

Name ()
Business Phone

Title

Company

Street Address

City State Zip Code

Mail coupon to:
Marketing Communications, Oki Semiconductor, 785 N. Mary Avenue, Sunnyvale, CA 94086. Or call (408) 720-1900.

OKI
SEMICONDUCTOR

IF YOU WRITE IN C, THEN YOU SHOULD DEBUG IN C

The ultimate in time savings is obtained when you debug your code in the same language it was written. Code development is accelerated as constant program printouts are no longer necessary. All displays of your program, including the real-time trace buffer, are in the form you specify, with options for Source only, Source and assembly or assembly only. Use your favorite C or PL/M compiler with our emulation system and SourceGate™ to enhance productivity of your engineering department. If you are working with different microprocessors, SourceGate provides the same interface for each, so learning curves are almost nonexistent when switching between projects or processors.

HMI enhances this software capability with the most advanced line of in-circuit emulators on the market today. SourceGate runs on all IBM PC family computers, Sun Workstations and many Unix systems.



Supported Processors:

8051 Family	
68HC11	64180/Z180
Z80	68000 Family
6809	8085

Now supporting the 68020 and the 8096/196 family and offering Software Performance Analysis for all units!

Sun Workstations is reg. TM, Sun Microsystems, Inc. IBM is reg. TM, International Business Machines, Inc. Unix is reg. TM, Bell Laboratories, Inc.



For complete details, contact:
Huntsville Microsystems, Inc.
 P.O. Box 12415, 4040 South Memorial Parkway, Huntsville, AL 35802
 (205) 881-6005 TWX: 510-600-8258 FAX: 205-882-6701

CIRCLE NO 2

DID YOU KNOW?

EDN serves electronic engineers and engineering managers in more than 100 countries worldwide.



CALENDAR

Modern Electronic Packaging (seminar), Baltimore, MD. Technology Seminars Inc, Box 487, Lutherville, MD 21093. (301) 269-4102. April 18 to 20.

12th Annual IEEE Design for Testability Workshop, Vail, CO. T W Williams, IEEE Subcommittee on DFT, IBM Corp, Box 1900, Boulder, CO 80302. April 18 to 21.

DOD-STD-2167A/2168 (seminar), Orlando, FL. David Maibor Associates, Box 846, Needham Heights, MA 02194. (617) 449-6554. April 24 to 25.

American Power Conference, Chicago, IL. Robert W Porter, Illinois Institute of Technology, Chicago, IL 60616. (312) 567-3202. April 24 to 26.


The Computer-Aided Software Engineering Symposium (CASES), Boston, MA. Elizabeth C Barnaby, Digital Consulting Inc, 6 Windsor St, Andover, MA 01810. (508) 475-6990. April 24 to 26.

Advanced Microprocessor Troubleshooting Techniques (seminar), Dayton, OH. Micro Systems Institute, 73 Institute Rd, Garnett, KS 66032. (913) 898-4695. April 25 to 27.

Local Area Networks: Implementation and Configuration (short course), College Park, MD. University of Maryland University College Center for Professional Development, University Blvd at Adelphi Rd, College Park, MD 20742. (301) 985-7122. May 2 to 4.

Improved Reliability Through Environmental Stress Screening (seminar), Milwaukee, WI. John T Snedeker, Center for Continuing Engineering Education, University of Wisconsin-Milwaukee, 929 N Sixth St, Milwaukee, WI 53203. (414) 227-3120. May 3 to 5.

Believe it. This 68000 SBC Runs on Only 70mA!



Yes, you read it right: a single five volt power supply and only 70mA is all that's needed to power this 3U Eurocard Single Board Computer. And no, we didn't compromise features to get there. See for yourself: 16/32-bit 68HC000 processor at 8 or 10 MHz, two RS-232 serial ports, 20 parallel I/O lines, two 16-bit timers, a clock/calendar, and even a 4 channel 8-bit Analog to Digital converter. Need more I/O? The board's standard G-64 bus interface makes it fully expandable to one of the largest selections of I/O modules in the industry.

What's more, the board comes with the highest level of software support: Real-time multi-tasking operating system, driver library for all the resources on board, and a selection of inexpensive PC hosted cross development systems. With those kind of tools and six JEDEC sockets for up to 512K of EPROM

and 256K of RAM, you are now only limited by your imagination.

The truth is, no other single board computer is easier to integrate into remote data acquisition systems, portable instruments, and other solar, battery or even hamster powered applications. Extended temperature range is a standard option.



"You'll love the price too"

So don't wait. Give GESPAC a call to receive your free data sheet and our free catalog with over 200 microsystem components & software.

**Call Toll Free
1-800-4-GESPAC
or call (602) 962-5559.**


USA - CANADA
50 West Hoover Ave.
Mesa, Arizona 85210
Tel. (602) 962-5559
Fax. (602) 962-5750

FRANCE
Z.I. des Playes
83500 La Seyne
Tel. 94 30 34 34
Fax. 94 06 30 56

INTERNATIONAL
3, Chemin des Aulx
CH-1228 Geneva
Tel. (022) 713 400
Fax. (022) 713 834

Team player

Make Mizar's dual-ported 68030 CPU
your multiprocessing MVP.



You're sure to score with Mizar's MZ 7130, the VME microcomputer with major league features. Combining 68030 power and true dual-ported memory, the MZ 7130 wins the multiprocessing pennant. All for a price that won't send you into the dugout.

Rely on the MZ 7130 for functionality: a 68030 MPU at up to 25 MHz, four MB of dual-ported DRAM with parity, 16K cache, up to one MB of EPROM, two RS-232 serial ports, SCSI, mailbox interrupts, and time-of-day clock.

Draft from options such as a 68882 FPP, up to one MB of SRAM, a VSB interface, and Ethernet™.

Build your real-time application around Mizar's team player, the MZ 7130. Call today. **1-800-635-0200.**

Mizar. The shortest distance between concept and reality.

MIZAR

1419 Dunn Drive • Carrollton, TX 75006 • (214) 446-2664

Ethernet is a trademark of Xerox Corp.

©1989, Mizar, Inc.

CIRCLE NO 3

DID YOU KNOW?

Half of all EDN's
articles are staff-written.

EDN

CALENDAR

Fiber Optics in Local Communications (seminar), Cincinnati, OH. Raycom Systems Inc, 6395 Gunpark Dr, Boulder, CO 80301. (800) 288-1620. May 9.

Modern Electronic Packaging (seminar), Chicago, IL. Technology Seminars Inc, Box 487, Lutherville, MD 21093. (301) 269-4102. May 10 to 12.

International Symposium on Measurement Technology and Intelligent Instruments, Wuhan, Hubei Province, People's Republic of China. Dr. Shawn Buckley, Cochlea Corp, 985 Timothy Dr, San Jose, CA 95133. (408) 920-2650. May 15 to 17.

Custom Integrated Circuits Conference, San Diego, CA. Marc Hartranft, Cypress Semiconductor, 3901 N First St, San Jose, CA 95134. (408) 943-2681. May 15 to 18.

Hands-On Unix for Programmers (short course), Seattle, WA. Specialized Systems Consultants Inc, Box 55549, Seattle, WA 98155. (206) 527-3385. May 17 to 19.

CASE Benchmarks: A Seminar Comparing Leading CASE Tools, Toronto, Ontario, Canada. Digital Consulting Inc, 6 Windsor St, Andover, MA 01810. (508) 470-3880. June 5 to 7.

Troubleshooting Microprocessor-Based Equipment and Digital Devices (seminar), Portland, OR. Micro Systems Institute, 73 Institute Rd, Garnett, KS 66032. (913) 898-4695. June 13 to 16.



ATE & Instrumentation Conference East, Boston, MA. MG Expositions Group, 1050 Commonwealth Ave, Boston, MA 02215. (800) 223-7126; in MA, (617) 232-3976. June 19 to 22.

0 to 60 in 5 seconds




with new UniLab 8620 analyzer-emulator.

- 64Kbytes from hard disk in 5 seconds. That's moving. But today you've got to be fast just to stay in the race for better micro-processor designs.
- The secret is a new, high-speed parallel interface: the Orion bus. Which zips data between your PC/AT and the 8620 analyzer-emulator, breaking the RS-232 bottleneck.
- The 8620 with O-bus gives you complete program diagnosis — and solutions — in real time. For more than 150 different micro-processors. Using **the same command set** environment.
- A generous 2730 trace-cycle buffer with selective filtering lets you cut through the clutter and display just the traces you wish. And you get 1μsec resolution in program time measurement. Plus continuous InSight monitoring of your program's key functions as they are performed.



InSight Display. InSight blends analyzer-emulator techniques to give you continuous, real time monitoring of key processor functions. And still services user interrupts. It displays changing register contents, I/O lines, ports, user-defined memory windows. With your own labels.

- On top of that, you get UniLab's trademark ability to debug by symptom, not just by breakpoint and single step. And, to help you complete the job on time, on the spot, a stimulus generator and EPROM programmer are included.
- Ease of use, another Orion trademark, is also built in. So you have all the familiar features and formats you're used to working with. It doesn't matter if your project is a single chip controller or complex 16-bit



Analyzer Triggers. Commonly used triggers can be selected quickly from a list of standard and user-defined triggers.

microprocessor, the 8620 is the top price/performance analyzer-emulator that does it all. At just \$4380. With processor Personality Paks typically \$550 each.

- UniLab 8620. Fast-lane debugging that gets you to market quicker.

Call toll-free: 800/245-8500.
In CA: 415/361-8883

ORION
INSTRUMENTS

702 Marshall St., Redwood City, CA 94063
TLX 530942 FAX 415/361-8970

Computer Integrated Instrumentation

YOU THOUGHT YOU'D HAVE IT MADE IN THE



Get the performance you need from the Harris 80C286.

With Harris, you get what you expect from the 80C286: speed, low power, reliable operation and fast delivery. Our 80C286 provides the extra performance you need (details are in our Application Note 111). For example, at 16MHz, our 80C286 can outperform the 80386SX by up to 25% when executing 8086 and 80286 code — the industry's largest base of installed software. At 20MHz, there's no comparison — there is no 20MHz 80386SX.

And that's another key to processor selection — a growth path for the future. Our 80C286 offers

SHADE BY DESIGNING AROUND THE 386SX™

YOU EXPECTED MORE.

you a wide performance range — from 12.5MHz to 16MHz through 20MHz and on to 25MHz — so you can migrate simply and smoothly when you want additional throughput. And it's available today, not in six or twelve months.

Another measure of performance is durability — running faster longer. The low-power CMOS design of the 80C286 does just that. No overheating. No reduced ambient temperature specification. No fans or heat sinks. Just reliable, long-term, high-performance operation.

So hang on to your hardware and software investment. Send for our technical information outlining all the 80C286's performance advantages.

For top performance and reduced system cost, move to the fastest 286 yet — the Harris 80C286.

Call 1-800-4-HARRIS,
Ext. 1290. In Canada: 1-800-344-
2444, Ext. 1290.



HARRIS
SEMICONDUCTOR

HARRIS · RCA · GE · INTERSIL

Make a quick killing in real estate.

Introducing our new high density, *highest performance* Multichip Modules.

Available now in a variety of SRAM configurations. Or choose *custom*. We'll work with you on defining mechanical and electrical requirements, as well as solve design, test and assembly issues.

Either way, we deliver fast, *tested* CMOS SRAM modules that can save you a fortune in real estate, design, and manufacturing, while speeding up system performance.

Our new, Cypress data book has one of the world's fastest multiple listings. Call today. It's free.


Multichip Hotline:
1-800-952-6300*
Ask for Dept. C47




CYPRESS
SEMICONDUCTOR




70ns
CYM1461, 512K x 8
SRAM Module



25ns
CYM1821, 16K x 32
SRAM Module




25ns
CYM1611,
16K x 16
SRAM Module




**WILL
BUILD
TO SUIT**

25ns
CYM1621, 64K x 16
SRAM Module



25ns
CYM1610, 16K x 16
SRAM Module



*1-800-387-7599 In Canada. (32)2-672-2220 In Europe. © 1989 Cypress Semiconductor, 3901 North First Street, San Jose, CA 95134. Phone: (408) 943-2666, Telex 821032 CYPRESS SNJUD, TWX 910-997-0753.

EDITORIAL

Free the Mario Brothers



Suppose for a minute that an electronics company sets out to capture a large share of the small-computer market. To do so, it designs and builds a computer that is superior to anything else available. The company's share of the market grows, but software suppliers find that the computer's architecture prevents them from independently developing programs for the computer.

In order to sell their programs, the software suppliers must first submit the programs to the computer manufacturer, which accepts them or rejects them. If the manufacturer accepts a program, it extracts an exclusive license from the software developer, manufactures the program itself, and finally sells it back to the developer. Only then can the software developer put the program on the market.

If the situation above seems implausible to you, you haven't kept up with the new video games. Nintendo of America, a manufacturer of popular video games such as *Contra* and the *Super Mario Brothers*, has been using just such a strategy to lock up about 80% of the video-game market in the US. Until recently, Nintendo has controlled 100% of the add-in market for compatible game cartridges. Nintendo exerts control by incorporating a proprietary lock-out chip that prevents the use of "unauthorized computer software" in the game unit.

By applying reverse-engineering techniques, Atari Games Corp and Tengen Inc recently came up with a method that obviates the Nintendo security chip, and they began to market games for the Nintendo system without first obtaining Nintendo's approval. Atari Games also filed an antitrust suit against Nintendo. Instead of meeting the competition head-on, Nintendo countersued, claiming, among other things, that a patent covers the lock-out chip.

Nintendo also claims that the lock-out chip promotes quality software—which only Nintendo may judge—while simultaneously preventing an over-supply of game cartridges, which Nintendo also controls. Keep in mind that in Japan, Nintendo's games don't require a lock-out chip, because, according to Tengen, Nintendo already claims 90% of the Japanese video-game market. Why spend money on an extra chip when you own the market?

Clearly, Nintendo's efforts seem to be aimed at securing control of the US video-game market. Despite the institution of the patent—which was intended to protect inventors' rights, not to confer a monopoly on any one company—the use of technology to protect markets and establish a monopoly hurts suppliers, hurts customers, and hurts the electronics industry. Years ago, the courts told large computer companies that they couldn't force buyers to purchase bundled hardware and software from one source. Likewise, copier companies were told that they couldn't force customers to buy supplies from only one source. Nintendo should take a close look at those lessons, and use technology to compete, not to monopolize.



Jesse H Neal
Editorial Achievement Awards
1987, 1981 (2), 1978 (2),
1977, 1976, 1975
American Society of
Business Press Editors Award
1988, 1983, 1981

A handwritten signature in cursive script that reads "Jon Titus".

Jon Titus
Editor

Hitachi's HMCS400 Series of CMOS Microcontrollers

The intelligent answer for small system control problems

The raccoon has a remarkable ability to thrive in any type of environment. His sheer intelligence and ingenuity let him adapt to whatever circumstances he may find, and prosper with only minimal resources at hand.

Resourcefulness also characterizes Hitachi's HMCS400 series of CMOS microcontrollers. These sophisticated devices are optimized for real-time control tasks and include a great number of peripheral functions on-chip.

This new generation of 4-bit micros is a far cry from the old 4- or 8-bit designs you're used to. They execute efficient 10-bit instructions in as little as $0.89\mu\text{s}$, and include powerful on-chip peripherals such as large EPROMs, LCD and vacuum fluorescent drives, and multiple serial interfaces.

For example, our new HD4074408 has an 8K one-time-programmable EPROM, a 512×4 bit RAM, 58 I/O lines, comparator inputs, PWM timer outputs and serial interfaces—all in a plastic package. Future devices will include A/D converters, phase locked-loop circuitry, DTMF generators, and much more.

Most importantly, Hitachi's ZTAT™ technology gives you Zero Turn-Around Time. The on-board one-time user-programmable EPROM eliminates the need to wait three or four months for mask ROM devices. The very *day* you finish development, ZTAT gets you into production. And, you can implement software changes immediately, to stay one step ahead of everyone else.

Put all of Hitachi's HMCS400 series resources to work for you: Ceramic windowed devices for deve-



Resourceful

lopment, ZTAT devices for pilot and small-scale production, and mask ROM devices for large-scale production. And, a full complement of development support tools is available for use with IBM-PC*, DEC VAX*, and Hitachi systems.

Plus, when you consider all the on-chip integration, you also get the lowest-cost solution for your design. The packaging is one of the reasons why ZTAT only costs slightly more than mask ROM microcontrollers, and is a lot cheaper than ceramic reprogrammable devices.

Clearly, Hitachi's HMCS400 series is right for a broad range of today's small systems applications in automotive, consumer, handheld instrumentation, telecom, and industrial products.

There's no need to wait. Hitachi is delivering the 4-bit all-CMOS HMCS400 series right now—

including EPROM-on-chip ZTAT devices. For more information, call your local Hitachi Sales Representative or Distributor Sales Office today.

Literature Fast Action: For product literature only, CALL TOLL FREE, 1-800-842-9000, Ext. 6809. Ask for literature number #SB-106.

*IBM-PC and DEC VAX are trademarks of International Business Machines Corporation and Digital Equipment Corporation, respectively.

Hitachi America, Ltd.

Semiconductor & I.C. Division

Hitachi Plaza

2000 Sierra Point Parkway, Brisbane, CA 94005

Telephone 415/589-8300



HITACHI®

We make things possible



Is this the way your 16-bit
controller company does business?



Call National.

THE HPC FAMILY. NOTHING ELSE GIVES YOU THE SAME DEGREE OF FLEXIBILITY AND CHOICE.

If you've been confronted with a "take it or leave it—that's all you need" attitude on the part of your 16-bit controller vendor, we suggest you take a new look at National's HPC™ family. Because for today's complex designs in information control, including printers, faxes, scanners, data storage and communications, you need a choice of optimized solutions that fulfill all your requirements.

Specifically, you probably need more in the way of intelligence, connectivity, interface and data handling. And much less in overall system costs. The HPC family more than measures up to these considerations. Let's look at just how well.

MAKE THE INTELLIGENT CHOICE.

Multiple functions mean multiple benefits. Including much faster context switching and interrupt response, due to our compact 54-instruction set. And higher system performance, because of our fast 30MHz clock rate, 67-ns instruction cycle, and 16-bit memory mapped architecture. And our ANSI-standard C compiler is just one way the HPC family can lower engineering costs, and speed your time to market.

© 1989 National Semiconductor Corporation

HPC is a trademark and TapePak is a registered trademark of National Semiconductor Corporation.

HPC PRODUCT FAMILY SUMMARY						
Part #	16-bit Timers	UPI	Memory		Features	
			I/O	ROM RAM		
HPC16003*	8	Yes	32	0	256	4 ICRs
HPC16004	8	Yes	32	0	512	4 ICRs
HPC16064	8	Yes	52	16K	512	4 ICRs
HPC16083*	8	Yes	52	8K	256	4 ICRs
HPC16104	8	Yes	32	0	512	8 CH A/D
HPC16164	8	Yes	52	16K	512	8 CH A/D
HPC16400	4	No	52	0	256	2 HDLC & 4 DMA
HPC16083MH	8	Yes	52	8K UV	256	UV Emulator

Standard features: Watchdog, Synchronous Serial Peripheral Interface, Uniform Memory Address Space, UART, 32X16-bit divide, 16X16-bit multiply, and available as standard cell.

DEVELOPMENT TOOLS:
PC-based development system
Relocatable C compiler, linker and symbolic debugger

ICRs = Input Capture Registers
HDLC = High-Level Data Link Control
*MIL-STD 883C

Another is packaging, and specifically, our unique feature called TapePak.® As the latest generation in VLSI packaging, TapePak gives you a wide variety of industry-standard, high-density, high-leadcount options. When you put it all together, then throw in eight timers and up to 11 addressing modes, you can easily see why members of the HPC family are considered smart cookies indeed.

OPT FOR INTERFACE AND CONNECTIVITY.

The HPC family has more on-chip integration, and increased I/O. And that can mean a lot more capacity to manage system functions. It can also mean a lot less, when it comes to reducing board space and chip count. In addition, our Universal Peripheral Interface (UPI) allows you to partition your system, by using the HPC as a peripheral to a host processor for high-end applications.

PUT THROUGHPUT AT THE TOP OF THE LIST.

Thanks to our on-and-off chip uniform memory mapped peripherals, all data manipulation can be accomplished on any memory location, regardless of whether it's part of an external device, or on the HPC itself. Which can be very important in ISDN, SCSI and LAN applications.

ASK ABOUT OUR NEW COMMUNICATIONS CONTROLLER.


For data communications, and especially for those applications requiring protocol conversion, we offer the newest member of our HPC family: the HPC16400. It's a complete solution, supported by a full library of application-specific software. With two full-duplex HDLC channels, driven by 4-channel DMA, plus one full-duplex programmable UART channel for rate adaption, the HPC16400 is completely optimized for TE, TA, and line-card applications.

CALL AND FIND OUT MORE.


To get a free brochure on our full HPC family, call us today at 800-825-5805, ext. 100. Once you discover how we do business, you'll agree that when it comes to 16-bit controllers, there's only one company of choice: National.

 **National
Semiconductor**


Grayhill Statistical Process Control makes DIP switch quality a reality, not a slogan



Is your DIP switch supplier being measured by SPC?



Grayhill DIP Switches are tested every step of the way in the manufacturing process. If initial contact resistance varies from control limits, the problem is immediately diagnosed and cured.



This machine automatically tests every DIP switch for actuation force. We get reliable ppm data and you get reliable DIP Switches.


The industry's reliance on Grayhill leadership has received another boost with the implementation of SPC manufacturing techniques to our DIP switch lines. (Note: SPC data not yet available for all configurations.)

In-line measurements are control-charted. Variations are identified to maintain processes within controlled limits. Only acceptable product comes off the Grayhill line and onto yours!

If your DIP switch supplier can't give you parts per million data, you should be talking to Grayhill. We offer you the widest choice of DIP switch actuators, stations, and circuitries, including MIDIP™ machine-insertable switches. Prices are competitive, but we offer features as standard that are extras elsewhere.

Grayhill DIP switches, as well as rotary and pushbutton switches, keyboards, solid state relays and I/O modules, are available from authorized distributors world-wide and are described in detail in *EEM*.

Ask us for your FREE copy of Engineering Catalog #1 with detailed DIP switch specifications... and call now for full details on SPC DIP switches.



Variable data is entered electronically at production sites and transmitted to the Grayhill mainframe to track performance and compile reports.

Grayhill
INC.

561 Hillgrove Avenue, P.O. Box 10373
LaGrange, Illinois 60525-0373 USA
Phone: (312) 354-1040 FAX: (312) 354-2820
TLX or TWX: 190254 GRAYHILL LAGE

CIRCLE NO 51

TECHNOLOGY UPDATE

GRAPHING-SOFTWARE PACKAGES

Draw your graphs on printers and plotters



Your computer can plot anything you can plot by hand—usually much better and faster.

*Jon Titus,
Editor*

Throw away your graph paper, pens, and press-on letters. Today's small computers, when combined with a pen plotter, an ink-jet printer, or even a dot-matrix printer, let you plot almost any numerical information. Whether you plot simple 2-D x-y information or require sophisticated surface plots with hidden lines, there are software packages that can do the job for you. In fact, you can choose from two main types of graphing software—stand-alone packages and add-in graphing routines. The stand-alone packages let you plot graphs from data that you've collected and saved on paper or on a disk. The add-in routines come in handy when you're developing a computer program that requires graphing capabilities.


The selection of available graphing software reflects the popularity of their respective host computers. It's no surprise that the IBM PC family and its compatible clones lead the pack for general-purpose engineering work. Thus, all but one of the stand-alone graphing packages run on IBM PC family or compatible computers. Several of the stand-alone packages also run on Apple Computer's line of Macintosh computers or on popular workstations.

In general, all the

stand-alone graphing-software packages work the same way; they let you take information from a source—usually a disk file—and then plot the data as a graph. You can display the information on your computer's monitor, or you can create a hard copy on a dot-matrix or laser printer. The packages also control a variety of plotters (Table 1). The graphing-software packages control too many types of printers and plotters to list in a table. Peruse each supplier's data sheets to find out what devices each software package controls.

Put graphs in reports

Most of the stand-alone packages also let you store a graphic image of your plot on disk. By storing an image, rather



A typical 3-D color graph shows how communication satellites cover various portions of the Earth's surface. It takes time and effort to learn how to create complex graphs such as this. (Courtesy 3-D Visions)

TECHNOLOGY UPDATE

Graphing-software packages

than numerical data, you can incorporate your graph directly into a manual or a document when you're working with a word processor. You don't need to get a hard copy of your graph and then paste it into the final version of the text. Check your word processor's manual to determine which graphics-file formats it accepts.

Obviously, your graphs require information—the results of your experiments, tests, etc. The packages obtain data from several different sources. All of the stand-alone programs let your computer read data from external files that arise from data-acquisition programs, spreadsheets, or even other computer programs. All the programs also let you enter data from your keyboard.

You'll find that each of the programs provides an internal data edi-

tor, which lets you examine your information in traditional columnar form. If you're already familiar with spreadsheet programs, you'll quickly navigate your way through such editor programs. In most cases, the editors aren't fancy, but they do let you remove useless data, add new data, modify values, and so on.

An editor also comes in handy when you need to graph a few values that you've jotted on scrap paper. You start the program, type in the information, and create a graph. The editor lets you put your typed-in data into a disk file for later use.

Dump useless data

A good data editor also lets you remove large blocks of information from your data file. For example,

if you're acquiring a transient signal by using an A/D-converter board, much of what's in your file may be useless baseline-voltage values. The ability to plot the acquired signal quickly lets you locate the transient among all the baseline data. You can then use the editor to remove the baseline information so the resulting graph shows the transient without the extraneous points. (If this application is typical of what you'll be doing, you may want the ability to quickly plot every second, fifth, or tenth data point so you can see what you have in your file.)

Data editors run the gamut from simple to complex. The basic editors in PCPlot and Graphstar require about five pages of instructions to explain how they work. At the complex end of the spectrum

TABLE 1—STAND-ALONE GRAPHING-SOFTWARE PACKAGES

COMPANY	PRODUCT	PRICE	HOST COMPUTER	MAXIMUM DATA SET	DATA EXPORT FORMATS
BINARY ENGINEERING	TECH*GRAPH*PAD (3.1)	\$395	IBM PC, APOLLO 3000/4000, DEC VAXSTATION	32,000 DATA PAIRS	ASCII, PIC
BV ENGINEERING	PCPLOT (3.25)	\$125	IBM PC, MACINTOSH	1000 POINTS/FILE	ASCII
EDMOND SOFTWARE	SEGS (2.0)	\$195	IBM PC FAMILY	11 COLUMNSx 7500 POINTS	ASCII
GOLDEN SOFTWARE	GRAPHER (1.77)	\$199	IBM PC FAMILY	32,000 POINTS	NONE
	SURFER ¹ (4.01)	\$499	IBM PC FAMILY	16,000 POINTS	(SEE NOTES)
MIHALISIN	TEMPLEGRAPH ² (3.2)	\$395	IBM PC-AT OR 80386 COMPATIBLES (SEE TEXT)	2048 POINTS (SEE NOTES)	ASCII
REBUS DEVELOPMENT	PARAMETER-MANAGER PLUS (3.0)	\$595	MACINTOSH FAMILY	32,767 POINTS/ VARIABLE	ASCII
SCIENTIFIC SOFTWARE SOLUTION	GRAPHSTAR (2.0)	\$99	IBM PC FAMILY	2100 POINTS	ASCII
SYSTAT	SYGRAPH (1.0)	FROM \$495	IBM PC FAMILY MACINTOSH FAMILY (SEE TEXT)	2000 POINTS	WKS, DBF, DIF, ASCII
3-D VISIONS	GRAFTOOL (2.0)	\$495	IBM PC FAMILY	14,400 POINTS (SEE TEXT)	DIF, ASCII

KEY:

ASCII = STANDARD NUMERIC FORMAT IN ASCII CHARACTER SET
 CGM = COMPUTER GRAPHICS METAFILE FORMAT
 DBF = DBASE DATABASE FILE FORMAT
 DIF = DATA INTERCHANGE FORMAT
 DMPL = HOUSTON INSTRUMENTS COMMAND-SET FILE
 DXF = AUTOCAD DATA FILE FORMAT
 EPS = ENCAPSULATED POSTSCRIPT FILE FORMAT
 GEM = DIGITAL RESEARCH GRAPHICS FILE FORMAT
 GKS = GRAPHIC KERNEL SYSTEM
 HPGL = HEWLETT-PACKARD GRAPHICS-LANGUAGE FILE FORMAT

PCX = PC-PAINTBRUSH BIT-MAPPED FILE FORMAT
 PIC = LOTUS GRAPHING FILE FORMAT
 TKF = TEKTRONIX GRAPHICS FILE FORMAT
 WKS = STANDARD LOTUS 1-2-3 (1A) FILE FORMAT
 WK1 = STANDARD LOTUS 1-2-3 (2.0) FILE FORMAT

AS = AUTOMATIC SCALING
 MS = MANUAL SCALING
 R = ROTATE
 Z = ZOOM

TECHNOLOGY UPDATE

lies the editor in Sygraph; it comes with a 114-page manual.

As you review the specifications for the stand-alone packages, you should also pay attention to how many values the editor can handle. For example, the Graphstar editor lets you work on a maximum of 200 values at a time. Sygraph's editor, on the other hand, can handle as many as 256 *variables* simultaneously. If the editors that you evaluate don't suit your needs, keep in mind that most programs let you exchange information with popular spreadsheet programs.

Programs offer variety

Like their editors, the stand-alone graphing packages cover the spectrum from simple to complex. If you need only a few x-y or logarithmic (log-log and semilog) graphs

or if you routinely plot the same types of simple graphs, the packages priced below \$200 will meet your needs. Thus, graphs and plots for your notebook or for internal engineering reports will be easy to produce with either PCPlot or Graphstar.

The PCPlot package provides a simple data editor and produces plots with as many as 1000 points. Unlike the other stand-alone graphing programs, PCPlot needs your computer's internal screen-print or screen-dump utility program to produce graphs on your printer. BV Engineering can supply such a utility. BV Engineering also offers PDP, a PCPlot-like program that puts graphic information on plotters. The company supplies drivers for many plotters. Unfortunately, BV Engineering's programs don't

let you store graphic images in files for later use.

If you need to plot more than 1000 points, consider Graphstar, which plots as many as 2100 points. However, remember that its editor has an upper boundary of 200 data points. Don't try to edit a longer file; Graphstar truncates your data to the first 200 values. That may be a difficult limit to adapt to if you're doing complex engineering work. Unlike PCPlot, Graphstar controls dot-matrix printers as well as plotters that accept HPGL commands. However, when plotting on a dot-matrix printer, Graphstar has a painfully long printing time.

Editors, printing speeds, and file limits are important specifications to consider when you evaluate graphing software. There's another factor you should watch out for, too: missing values. First, though, you have to know what a missing value is. Assume that you're measuring current through a circuit as you apply voltages in 0.1V steps. If you take 55 readings from 0.1 to 5.5V and graph them, any graphing package can handle the job. If you can't take a reading at one or more of the voltage steps and those voltages are still listed in your table or spreadsheet, you have what are called missing values:

3.3V	1.67A
3.4V	1.69A
3.5V	
3.6V	1.78A
3.7V	

Typically, a business-type spreadsheet program plots missing values as zeros. For the data above, the current plot goes from 1.69 to 0V and back up to 1.78V. Such a graph is useless.

Graphing programs should automatically treat missing values as though they don't exist. Thus, for the data above, the graphing pro-


GRAPHIC EXPORT FORMATS	GRAPH TYPES	GRAPH MANIPULATIONS
HPGL, PIC	2-D, POLAR, LOG	AS, MS
NONE	2-D, BAR, LOG, ERROR BAR	AS, MS
HPGL, PIC	2-D, BAR, LOG	AS, MS, R
PIC, DXF, POSTSCRIPT	2-D, LOG	AS, MS
HPGL, PIC, DXF, POSTSCRIPT ³	2-D, 3-D, BAR, SURFACE, CONTOUR	AS, MS, R, Z
CGM, HPGL	2-D, POLAR, BAR, LOG	AS, MS, R, Z
PIC	2-D, LOG	AS, MS, Z
NONE	2-D, LOG	AS, MS
CGM	2-D, 3-D, POLAR, BAR, LOG, SURFACE, CONTOUR	AS, MS, R, Z
HPGL	2-D, 3-D, POLAR, BAR, LOG, SURFACE, SPHERICAL, SMITH, CONTOUR	AS, MS, R, Z

NOTES:

1. SURFER CAN PUT EXTERNAL ARRAYS IN THE USER'S PROGRAMS.
2. TEMPLEGRAPH EDITOR HANDLES AS MANY AS 10 GRAPHS AND AS MANY AS 2048 POINTS PER GRAPH.
3. POSTSCRIPT IS A STANDARD FORMAT FOR LASER PRINTER FILES.

TECHNOLOGY UPDATE

Graphing-software packages



Combining a 3-D surface plot and a 2-D contour map lets you show the same information two ways. Most of the sophisticated stand-alone graphing packages let you produce this type of effect. You can also overlay two graphs to produce a similar combination of 2- and 3-D effects. (Courtesy Systat)

gram should ignore the 3.5 and 3.7V points. Unfortunately, both PCPlot and Graphstar treat missing values as zeros. If a program can't ignore missing values, you'll have to use the editor to remove them. That's an annoyance you may wish to live without.

Add more capabilities

Edmond's Scientific & Engineering Graphic System (SEGS) and Golden Software's Grapher form the next tier of graphing packages. Both furnish standard x-y and log graphs and support many printers and plotters. The packages give you a large choice of line widths and a variety of letter and number sizes for legends.

If your information requires a bit of preprocessing before you can plot it, consider the SEGS program. This program includes 19 mathematical operations that let you scale, offset, or otherwise manipulate your file prior to plotting. Keep in mind, however, that the spread-

sheet accepts only numerical data. It's up to you to keep track of the headings for the various columns of figures you're working on. The program *does* keep track of axis information and labels for you. (Edmond expects to announce an enhanced version of SEGS around the time this article appears.)

Sometimes, a nice neat plot of your data may not be enough to tell you what you're looking at. So, both SEGS and Grapher let you fit your data to a curve. If a linear fit is all you need, SEGS plots the best straight-line fit through your data. When you need a closer approximation, Grapher lets you choose from six types of curve-fitting operations: linear, log, power, exponential, cubic-spline, and polynomial. Grapher also gives you the coefficients for the curve-fitting equation.

These days, engineers don't live by IBM PCs alone. If you're a Macintosh user, Rebus Development's Parameter Manager Plus

software may meet your plotting needs. However, paying \$595 for a program that draws only x-y and log graphs may be difficult to justify unless you also use the software's statistical, data-management, and other sophisticated capabilities. Among the extra features is the ability to handle complex numbers.

Parameter Manager Plus handles missing data in two ways. The first option lets the program skip over the missing values and continue plotting the next set of complete data values. If you choose the second option instead, the software makes a linear approximation of the missing data and inserts it in the graph.

Also, unlike most other graphing software, Parameter Manager Plus lets you scroll through large graphs and strip charts (charts that continue from one piece of paper to another). In fact, you can plot a graph that is 400x400 in.—slightly over 10M on a side.

If you need more than standard

Foreign exchange.

It started as a simple purchase of a box lunch on a Shibuya side street. And ended by yielding some expert travel advice from an unexpected source.

That's Tokyo. By way of United.

United can get you to Tokyo from all across this country. With friendly skies service that provides the best in international travel: fine food, fine wine, and attention to the fine details.

Because we know, like you, that the little joys along the side streets can make the fast track a lot easier.

United. Rededicated to giving you the service you deserve.

Come fly the friendly skies.




UNITED

A I R L I N E S

TOKYO • OSAKA • HONG KONG • SEOUL • TAIPEI • SYDNEY • MELBOURNE • BEIJING • SHANGHAI • AUCKLAND • SINGAPORE • MANILA • BANGKOK

TECHNOLOGY UPDATE

Graphing-software packages



A laserprinter produces high-quality graphs that are ready for you to use in reports and manuals. Many graphing packages let you transfer such images directly to your word processor. (Courtesy Binary Engineering)

x-y and log graphs, the five high-end graphing packages in **Table 1**—those costing over \$200—may suit your application. In this group, you'll find packages that produce polar plots as well as surface and 3-D plots. Two packages, Tech*Graph*Pad and Templegraph, add polar plotting to the usual repertoire of x-y and logarithmic capabilities, and Surfer lets you plot 3-D surfaces. The remaining two high-end packages, Sygraph and Graftool, have both polar and 3-D capabilities.

When you investigate these five high-end packages, you move beyond the realm of the slim user's manual into the world of slip-case binders. That jump usually signifies

a change from simple to complex software, too.

However, you're in for a surprise: Binary Engineering's Tech*Graph*Pad isn't complex at all. In fact, using it is almost intuitive. Kevin Shea, Binary Engineering's president, expects that most people won't read the manual—at least not at first. Even so, you should have the program running and plotting graphs in half an hour.

Tech*Graph*Pad's menus let you maneuver from setting to setting with ease; you hardly use the function keys at all. You simply select the options and functions you want and type in legends, disk-file names, and other information. If you're looking for software that can

complement the suite of software tools running on your workstation, take heart. Tech*Graph*Pad runs on several types of Sun Microsystems and Digital Equipment Corporation (DEC) workstations. The workstation-based programs require an MS-DOS-emulation package.

It's academic

Templegraph—a program that arose from work at Temple University in Philadelphia, PA—also runs on Sun Microsystems and Hewlett-Packard workstations. Although the first sheet in the Templegraph instruction notebook says, "Don't let the size of this manual fool you..." it can be intimidating, nevertheless. Fortunately, the program incorporates a clear tree-like structure of menus that let you select options and operations by pressing the function keys on your PC's keyboard.

The only drawback to the function-key selection technique is that the keys take on new meanings as you switch from menu to menu. If you plan to plot many graphs, day after day, Templegraph can do the job. You'll need time, however, to become familiar with the menus and their actions. On the positive side, each time you select an operation, Templegraph lets you see what it does to your graph.

The two remaining graphing packages, Sygraph and Graftool, provide the widest variety of graphing features. Both packages handle standard x-y, log, 3-D, polar, and surface plots. In addition, Graftool lets you create spherical-coordinate graphs and plot complex values on a Smith chart. The program doesn't accept the values in the form $3 + i5$. You must supply the complex values in pairs: a real part (3) and an imaginary part (5), which the program plots as $3 + i5$.

Although the Sygraph software

Perfectly Balanced CMOS A/D Converters

In the eternal balancing act between speed, accuracy and cost-effectiveness, nothing comes closer to perfection than the Siemens family of A/D converters.

With speeds as fast as 13 μ s, and a total unadjusted error of only ± 0.5 LSB over the entire temperature range, they're at the top of their class in performance. And when it comes to balancing costs, their flexibility and up-gradability put them in a class by themselves.

Take our 12-bit SDA 0812. It's self-calibrating, so you can eliminate those time-consuming, labor-hungry trimming parts. It's fast (17 μ s). It also has a four-channel input multiplexer and 12-bit data output in a 2-byte format. Put it

upgrade from 8- to 10-bit resolution by simply changing parts and adding a few lines of source code.

Find out more by calling 408-980-4500, ext. 4577. Or write Siemens Components, Inc., Consumer ICs, 2191 Laurelwood Road, Santa Clara, CA 95054-1514.

Let us help you get your A/D design back in balance.



Siemens... Practical Solutions By Design.

Distributors: Advent Electronics, Inc., Almo Electronics, Hall-Mark, Insight Electronics, Marshall, Summit, Western Microtechnology.


© 1989 Siemens Components, Inc. M15A002

TYPE	BITS	SPEED	ACCURACY*	TEMP RANGE	FEATURES
SDA 0812	12	17 μ s	± 0.5 LSB	-40°C/+85°C	Self-calibrating
SDA 0810	10	15 μ s	± 0.5 LSB	-40°C/+125°C	Software-upgrade of 8-bit to 10-bit systems
SDA 0808	8	13 μ s	± 0.5 LSB	-40°C/+125°C	Faster and more accurate than the industry standard

*Total Unadjusted Error (TUE) over entire temperature range

all together and it's a perfectly balanced choice for your high-performance applications.

For an ideal balance between low and medium resolution requirements, our SDA 0808 and SDA 0810 both feature an 8-channel input multiplexer and are 100% pin-compatible with the ADC 0808 converters. In fact, you can even



TECHNOLOGY UPDATE

Graphing-software packages

seems to offer the largest variety of graphs, it requires the most documentation. The main technical manual consists of more than 900 pages. The three other manuals, which cover the command references, the program installation, and the editor, contain 250 pages in all. Sygraph is a lot like a graph-programming language. You type in command lines to open files, plot information, change legends, and perform other operations. Instead of typing in one command at a time, you can put a string of commands into a submit file that Sygraph runs in sequence to create graphs.

Besides running on IBM PCs and compatible computers, the Sygraph program runs on DEC VAX/VMS computers and on computers from Data General and NCR. You can use the program on Macintosh computers, but to do so, you must buy the Systat statistics program,

which includes Sygraph and costs \$595.

If you need a variety of graphs and you'd rather keep an eye on your graphs than on your programming syntax, Graftool may be for you. Like many of the other packages, Graftool uses a series of menus that let you select operations and graphing procedures. Menus appear on the left side of your display screen; the graphs take up the remaining area. Before you can get Graftool up and running, you'll need a copy of MS-DOS V3.0 or higher. The other MS-DOS-based programs covered so far can operate on V2.0 or V2.1.

Zoom in to see new data

When running Graftool, you can conveniently zoom and pan—operations that require a bit of explanation. Panning lets you move around on a graph so you can locate points

of interest that are off the display area, move them into the viewing area, and examine them. Essentially, you move a small viewing window—your display screen—across the graph. Once you have a portion of the graph in view, you can zoom in on it, magnifying it. Because Graftool stores all values to 64-bit accuracy, it can zoom by as many as 15 orders of magnitude (1×10^{15}).

In addition to moving around on a graph, you can view many graphs simultaneously. Obviously, there is a limit to what you'll be able to see if you try to fit 16 graphs on your display. No matter how many graphs you have on the screen, though, Graftool lets you handle as many as 4096×4096 data points in each graph. However, you'll run out of memory at about 14,400 data points.

Most of the graphing packages

TABLE 2—ADD-IN GRAPHING-SOFTWARE PACKAGES

COMPANY	PRODUCT	PRICE	HOST COMPUTER	LANGUAGES	COMPLEX VALUES	IMPORT FROM EXTERNAL FILES	DATA EXPORT FORMATS
CHIRP TECHNICAL SERVICES	VID & DIG (2.0)	\$140	IBM PC FAMILY	BASIC, PASCAL, C, FORTRAN	YES	NO	NONE
CRESCENT SOFTWARE	GRAPHPAK PROFESSIONAL (2.04)	\$149	IBM PC FAMILY	QUICK BASIC TURBO BASIC	NO	YES	PCX
HEARTLAND SOFTWARE	HGRAPH (4.2)	\$119	IBM PC FAMILY, VAX, SUN WORKSTATIONS	BASIC, PASCAL, C, FORTRAN, MODULA-2	YES	NO	NONE
MICROCOMPATIBLES	GRAFMATIC	\$135	IBM PC FAMILY	FORTAN (SEE TEXT)	NO	NO	NONE
MICROPLOT SYSTEMS	MICRO-10 (1.2)	\$129	IBM PC FAMILY	BASIC, FORTRAN, C	YES	YES	ASCII
NUMERICAL ALGORITHMS GROUP	PC GRAPHICS LIBRARY (MARK-2)	\$595	(SEE TEXT)	FORTAN	YES	YES	ASCII
PLOTWORKS	PLOT88 (18)	\$299	IBM PC FAMILY	PASCAL, FORTRAN, C	NO	YES	NONE
QUINN-CURTIS	SCIENCE & ENGINEERING TOOLS (6.1)	\$79.95	IBM PC FAMILY	PASCAL, C	YES	NO	NONE
SCIENTIFIC ENDEAVORS	GRAPHIC (4.1)	\$395	IBM PC FAMILY	C	NO	NO	NONE

TECHNOLOGY UPDATE

presented in **Table 1** also provide mathematical operations. The inexpensive packages let you do a few operations such as curve fitting, and the more complex and expensive programs provide for Fourier transforms, statistical functions, filtering, and other data-manipulation operations. In the future, you'll see companies integrate more and more mathematical operations into graphing-software packages. Likewise, companies that supply mathematical- and analysis-software packages will add more graphing capabilities. Eventually, it will be difficult to distinguish between the two packages.

There is already a top-down movement underway to integrate graphing software into many applications packages. Many data-acquisition software packages now include sophisticated graphing software—probably under license from

one or more of the vendors listed in **Table 1**. Today, Binary Engineering is working with National Instruments (Austin, TX) to incorporate Tech*Graph*Pad in National's data-acquisition software. Because graphing is a part of the data-acquisition, -analysis, and -presentation chain, the days of stand-alone graphing-software packages may be numbered. (Very specialized graphing packages will always be available, but they'll fit into narrow markets.)

Many vendors are taking a bottom-up approach to adding graphing capabilities to software. Many companies are offering ready-made libraries and collections of add-in routines that perform primitive as well as sophisticated graphing tasks. Right now, you can add graphing routines to your Fortran, Pascal, Basic, C, and Modula-2 programs. A representative sample of

nine suppliers' products appears in **Table 2**.

Unlike the stand-alone graphing-software packages that perform within a rigid set of graphing specifications, the add-in routines give you a great deal of flexibility in displaying graphical data. These routines have their own limitations, but you can combine the routines to do many things that the stand-alone packages can't. For example, if you need to place a special legend or logo on top of your graph, you'll probably find a routine that can add it for you. If such a routine doesn't exist, you may be able to combine several routines to produce the desired result.

Likewise, if you need a special data-processing routine such as a deconvolution, you can work on that algorithm and then call your add-in plotting routine to show the results. Other add-in routines add axes, legends, and tick marks. You concentrate on what you want the program to do with the data, and the prewritten graphing routines display the data for you.

Don't let the packages' graphing-routine label mislead you. Many of the packages not only draw complex and sophisticated graphs, but also offer numerical-analysis routines. Heartland's Hgraph and Microcompatibles' Grafmatic let you perform a cubic-spline fit of your data. At the other extreme, Quinn-Curtis' Science and Engineering Tools for Pascal supplies almost as many advanced mathematics routines as it does graphing routines. If you're working on a math-intensive program, the Quinn-Curtis package could save you from having to buy a math-function library.

Produce graphic files

In general, these add-in routines get data from arrays that you've set up in your program and produce the

GRAPHIC EXPORT FORMATS	GRAPH TYPES	GRAPH MANIPULATIONS	DATA PROCESSING	LICENSING REQUIREMENTS
HPGL	2-D, 3-D, POLAR, BAR, LOG, SURFACE, SPHERICAL, SMITH, CONTOUR	AS, MS, R, Z	NO	NONE
PCX	2-D, 3-D, BAR, LOG, SURFACE	AS, MS	NO	NONE
CGM, EPS, HPGL	2-D, 3-D, POLAR, BAR, LOG, SURFACE, CONTOUR	MS, R	YES	NONE
PACKED FILE	2-D, 3-D, BAR, LOG, SURFACE, WATERFALL	AS, MS, R	YES	PERMISSION
TEKTRONIX	2-D, BAR, SURFACE, LOG	AS, MS, R	NO	NONE
EPS, HPGL, GKS	BAR, SURFACE, SPHERICAL, LOG, CONTOUR	AS, MS	YES	REQUIRED
HPGL, DMPL	2-D, 3-D, SURFACE, LOG, CONTOUR	AS, MS	YES	PERMISSION
HPGL	2-D, 3-D, BAR, LOG, CONTOUR	AS, MS, Z	YES	NONE
HPGL, TKF, PIC, GEM, POSTSCRIPT	2-D, 3-D, POLAR, BAR, LOG, SURFACE, CONTOUR, SMITH	AS, MS, R, Z	YES	REQUIRED

TECHNOLOGY UPDATE


Graphing-software packages

results on a plotter or printer. Several of the programs have the ability to obtain data from bit-mapped graphics files and spreadsheet files. Some can also put the results into files for later use. All of the routines produce some form of graphic-output file that you can use to control a printer or plotter when you need a hard copy of your information.

Before you select a group of additional routines, do your homework. Typically, you need to know if the routines do what you want them to. That statement sounds obvious, but it means that you have to know exactly what your program is supposed to accomplish. You also need to know how the routines work, how you go about using them, and what you need to get them up and running.

First, always ask for a *complete* list of the routines that are available. Some suppliers send a *representative* list of routines and several complex graphs that illustrate the power of the software. There may be no relationship between the graphs and the list of routines, so you don't know whether the supplier used one routine or 50-plus routines to draw such plots.

Second, examine the manuals that come with the software to determine how the individual routines work. Beware of manuals that are devoid of examples and sample programs. Several manuals that accompany the routines listed in **Table 2** are good examples of what you should look for. The manual for the Microcompatibles Grafmatic library, for example, supplies details of each routine and information about the routine's restrictions. Each description also includes a realistic example of how to use the routine and a detailed explanation of the routine's effects or results. In addition, the manual contains a 50-page section of sample programs



A graph from a dot-matrix printer is sufficient for many needs. In this example, the Graphstar software automatically scaled the axes to accommodate the data—a noisy sine wave with an increasing bias.

that use the routines.

The manual for Heartland's Hgraph software is also easy to follow. The manual's first part shows you how to set up the programs and how to start producing graphs. The authors use a sample Pascal program to illustrate each new concept. Don't worry if you're not a Pascal programmer; the logic in each program is clear and evident. Also, Heartland supplies routine packages for many popular languages that you can run on several different computer systems. If graphing routines are new to you, the Hgraph package might be a good place to start your education.

Microcompatibles and Heartland aren't alone in offering helpful documentation. Scientific Endeavors, Plotworks, and Quinn-Curtis also


offer good materials. The Scientific Endeavors manual for the Graphic set of routines stands out because it contains an index of topics and a separate index of functions.

Make a shopping list

After you purchase a library of graphing procedures and subroutines, you may need to purchase several other items. For example, if you're going to use the Plot88 add-in routines, a math coprocessor chip is mandatory. If your particular compiler can take advantage of a math chip, adding one to your computer can be a good investment. Scientific Endeavors reports a nine-fold improvement in processing speed when a math chip handles a typical routine that makes 600 trig-function calls.

MICRO-LOGIC II.™

The CAE tool with a 10,000-gate digital simulator for your PC.



Spectrum Software's MICRO-LOGIC II® puts you on top of the most complex logic design problems. With a powerful total capacity of 10,000 gates, MICRO-LOGIC II helps engineers tackle tough design and simulation problems right at their PCs.

MICRO-LOGIC II, which is based on our original MICRO-LOGIC software, is a field-proven, second-generation program. It has a high-speed event-driven simulator which is significantly faster than the earlier version.




Shape Editor


A 200-type library of standard parts is at your fingertips. And for a new high in flexibility, a built-in shape editor lets you create unique or custom shapes.

MICRO-LOGIC II is available for the IBM® PC. It is CGA, EGA, and Hercules® compatible and costs only \$895 complete. An evaluation version is available for \$100. Call or write today for our free brochure and demo disk. We'd like to put you in touch with a top digital solution.

- Built-in shape editor
- Multiple delay models
- Printer and plotter hard copy



Schematic Editor



Timing Simulator

The program provides you with a top-notch interactive drawing and analysis environment. You can create logic diagrams of up to 64 pages with ease. The software features a sophisticated schematic editor with pan and zoom capabilities.

- Total capacity of 10,000 gates
- Integrated schematic editor
- Fast assembly language routines
- Standard parts library of 200 types
- Event-driven timing simulator



1021 S. Wolfe Road, Dept. E
Sunnyvale, CA 94087
(408) 738-4387

MICRO-LOGIC II is a registered trademark of Spectrum Software.

Hercules is a registered trademark of Hercules Computer Technology


IBM is a registered trademark of International Business Machines, Inc.

TECHNOLOGY UPDATE

Graphing-software packages

Of course, you need a compiler, too. Whether you use a QuickBasic, TurboPascal, or Lattice-C compiler, you can't use the routines without the basic language package you use to program your computer system. Also on the software side, if you purchase Chirp's VID & DIG library, you need Microsoft's Fortran library. Even if you program in QuickBasic, the Fortran library is a must. Chirp wrote many of its routines in Fortran, and many of those routines must link with the Fortran library's programs.

While you're making out your shopping list, you may need to add an assembler that's compatible with your host computer. If you plan to use the Graphic routines from Sci-



Legends and formulas spruce up a graph, and most of the graphing packages and routines let you position them as you like. However, not all graphing software lets you produce symbols such as the integral sign. (Courtesy Scientific Endeavors)

For more information . . .

To obtain more detailed information on the stand-alone and add-in graphing-software packages described in this article, contact the following manufacturers directly, circle the appropriate number on the Information Retrieval Service card, or use EDN's Express Request service.

Binary Engineering Inc
400 Fifth Ave
Waltham, MA 02154
(617) 290-5900
FAX 617-890-1340
Circle No 700

BV Engineering
2023 Chicago Ave, Suite B-13
Riverside, CA 92507
(714) 781-0252
TWX 650-308-9864
Circle No 701

Chirp Technical Services
Box 551
Del Mar, CA 92014
(619) 632-9510
Circle No 702

Crescent Software Inc
11 Grandview Ave
Stamford, CT 06905
(203) 846-2500
Circle No 703

Edmond Software Inc
United Founders Tower
5900 Mosteller Dr, Suite 1124
Oklahoma City, OK 73112
(405) 842-0558
Circle No 704

Golden Software Inc
Box 281
807 Fourteenth St
Golden, CO 80401
(303) 279-1021
(800) 333-1021
FAX 303-279-0909
Circle No 705

Heartland Software Inc
234 S Franklin
Ames, IA 50010
(515) 292-8216
Circle No 706

Microcompatibles Inc
301 Prelude Dr
Silver Spring, MD 20901
(301) 593-0683
Circle No 707

Mihalisin Associates
600 Honey Run Rd
Ambler, PA 19002
(215) 646-3814
Circle No 708

Numerical Algorithms Group
1101 31st St, Suite 100
Downers Grove, IL 60515
(312) 971-2337
FAX 312-971-2706
Circle No 709

Plotworks Inc
16440 Eagles Crest Rd
Ramona, CA 92065
(619) 457-5090
FAX 619-457-0946
Circle No 710

Quinn-Curtis
1191 Chestnut St, Unit 2-5
Newton, MA 02164
(617) 965-5660
FAX 617-965-7117
Circle No 711

Rebus Development Corp
2330 B Walsh Ave
Santa Clara, CA 95051
(408) 727-0110
(800) 247-4994 (CA)
(800) 654-5157
Circle No 712


Scientific Endeavors Corp
508 N Kentucky St
Kingston, TN 37763
(615) 376-4146
Circle No 713

Scientific Software Solutions
Box 956
Valley Forge, PA 19482
(215) 269-0198
Circle No 714

Systat Inc
1800 Sherman Ave
Evanston, IL 60201
(312) 864-5670
FAX 312-492-3567
Circle No 715

3-D Visions Inc
1520 23rd St
Manhattan Beach, CA 90266
(213) 831-4671
Circle No 716

Turn Your Cache Into Big Savings



The Intel Recommended Cache Design In 5 Chips

Now you can replace 27 ICs with only 5 chips using our new CacheRAM™, the IDT 71586. You can save two-thirds of your board space and reduce power consumption by a third. The IDT 71586 makes the ideal 2-set associative, 32 K byte cache. Optimized for Intel's 82385 cache controller, the IDT 71586 matches 25 MHz Intel80386™ designs with its 35ns access time.

Big Savings In Board Space

With on-board address latches and byte enables, the IDT 71586 eliminates extra transceivers and latches in your design. Each CacheRAM's 8K byte capacity replaces four 2K byte SRAMs and lets you save at least 4 square inches of critical board space. All

386™/82385 CLOCK FREQ.	IDT 71586 SPEED
16 MHz	55ns
20 MHz	45ns
25 MHz	35ns
—	25ns

because it's designed specifically for high-speed 386™/82385 caches. Fewer chips also means lower power requirements — typically less than 1.5 watts for 32K bytes of data storage.

Speed Upgrades For 33 MHz Processors

Forget about cache redesigns when CPU clocks speed up to 33MHz. The IDT 71586

has been designed to provide a clean upgrade path to higher speed microprocessors. Just plug in the 25ns version of the IDT 71586 and take advantage of the 30 percent added performance.

You Can Count On Us

Discover how our CacheRAM can give your system a performance edge. Call your IDT distributor for immediate delivery. For more information, including pricing, call our toll-free hotline: **800-544-SRAM.**

Ask for your free copy of our 1989 IDT Data Book Supplement that's loaded with up-to-date information on all our high performance CMOS products. It has the information you need about SRAMs; FIFOs; Dual-Ports; RISC Processors; BiCMOS ECL-I/O RAMs; CMOS FCT/FCTA Logic; Modules and more.

When cost-effective performance counts



Integrated Device Technology


3236 Scott Blvd.
P.O. Box 58015
Santa Clara, CA 95052-8015
Tel. (408) 492-8225

NEW! SWITCHMODE POWER SUPPLIES FROM STOCK

- 2 to 48 VDC Outputs
- Automatic Current Sharing On All Outputs
- N+1 Capabilities



MULTIPLE OUTPUT



- 350 to 1500 Watts
- 3 to 15 Outputs

SINGLE OUTPUT



- 400 to 3000 Watts in 5" x 8" Standard Package
- 155,000 Hrs. Demonstrated MTBF

Hot Plug-In FAULT TOLERANT (N+1) POWER SYSTEMS



- Two to Six Supplies
- Expandable, 300 to 1800 Watts
- Internal Isolation Diodes (Option)

POWERTEC

The Power in Power Supplies

20550 Nordhoff Street Chatsworth, CA 91311
(818) 882-0004 • FAX (818) 998-4225

CIRCLE NO 4

TECHNOLOGY UPDATE

Graphing-software packages

entific Endeavors, an assembler is mandatory.

To get paper copies of the information you print on your computer's display with Graphmatic, you also need Plotmatic and Printmatic, which cost \$135 each. Both libraries supply graphing and controlling software for a suite of graphics printers and plotters that operate with HPGL files. If you plan to sell a program that incorporates the graphing routines, Numerical Algorithms Group and Scientific Endeavors require licenses. Depending on your application, you may have to pay a license fee or a royalty.

Beware of errors

While you're shopping for your software library, be sure to ask how the programs handle errors. Because you're the one doing the programming, you must pay careful attention to how the add-in routines catch and signal error conditions—if they do. Software bugs in your own software are tough enough to track down, but when they occur because of a problem in someone else's software, they can be nightmarish.

The graphing routines should come to you free of problems. However, errors can occur, particularly if you send a routine information it can't handle or understand. The routine should catch such errors that occur during run time and report them in an orderly fashion. Unfortunately, all of the graphing-routine libraries in **Table 2** give such errors only passing mention—if they mention them at all.

The Plot88 manual illustrates the problem of error detection. Although the manual provides a 3-page list of error codes and messages, you can't tell in which routines the errors occur. Even if you

can locate a corresponding routine, the directions for the routine don't give a clue about where an error message or code appears.

The Graphic routines suffer from a similar problem. The manual tells you only that there are three levels of error trapping and that error messages are put in a file, GRAPHIC.ERR. It would be helpful to know what the messages are, what they mean, and where they appear in the program. It seems to be your responsibility to check the error file each time you run the program to be sure that it is free of errors.

The Quinn-Curtis routines for Turbo Pascal 4.0 and 5.0 provide some error-detecting operations. For example, the asynchronous-communication routines furnish the error codes that the manual describes. However, you have to look through the manual procedure by procedure to determine which routines supply any error-detecting steps. Few of the add-in routines in any of the libraries we examined do any internal error checking.

EDN

Article Interest Quotient
(Circle One)

High 518 Medium 519 Low 520

S A M S U N G

NOW

Number 2



Introducing
The Fastest
FIFOS
in the World.

*Samsung launches the leaders in a hot performance area.
Plus speed demon SRAMs and peripherals and our
BLOW-THE-DOORS-OFF SYSTEM ACCELERATOR.*



At Samsung, we are committed to surface mount technology.

Surface mount offers notable economies and even performance benefits. Because these advantages are becoming more and more critical, it's more and more important to deal with suppliers who have surface mount packaging available consistently. At Samsung, we have it. Our FIFOs, SRAMs, Advanced CMOS Logic Family, EEPROMs, microprocessor peripherals, DRAM Controller, linear devices, DRAMs, and transistors are all widely available in surface mount. We are committed to offering a total semiconductor solution. And part of that is offering the packaging that today's designs need.

FIFOS

THE Fantastic FIFOs™ FROM Samsung.

*Parallel processing? Large networks?
At 25 ns, we've got all the speed you could wish for.*

Leadership technology. That's what Samsung is known for as one of the manufacturing giants of the world. And it is what we are known for as, increasingly, we deliver the next generation in electronics performance enhancements.

New fast static RAMs in 256K at the highest speeds available. A new DRAM Controller that improves the performance of even RISC systems. 1-meg DRAMs at 70 ns. A brand-new microprocessor peripheral family that is the fastest made.

And above all, our new x9 CMOS FIFOs.

We call these blazingly speedy performers The Fantastic


FIFOs, because at 25 ns they are simply the fastest made by anyone.

And they're going to make FIFOs a reality in new applications.

They'll do this not just because they are so fast, but because they're very readily available and cost-effective even for high-volume applications.

In areas like networks with a great many nodes, and even in mini-supercomputers with a great many processors, FIFOs are a cost-sensitive area because of the number of them required.

Our new products will not only let you use FIFOs in these areas. They'll give you the speed that's mandatory. Speed no one else can offer.



Samsung's Fantastic FIFOs are performers that will permanently change the way FIFOs are used. Request a data sheet and pricing information today and start taking advantage of the fastest parts made.



THE FASTEST FIFOs MADE.

Part Type	Org.	Speeds	Packages	Available
KM75C01A	512x9	25, 35, 50, 65, 80 ns	28-pin DIP 32-pin PLCC	Now
KM75C02A	1Kx9	25, 35, 50, 65, 80 ns	28-pin DIP 32-pin PLCC	Now

Samsung's 1- and 4-meg DRAM Controller is a performance-boosting monster. We call it the System Accelerator because that's just what it does.

If you're attracted to speed, you're going to want to design it in.

The System Accelerator interfaces to all major microprocessors—including RISC processors, 286/386, and 68020/30.

The System Accelerator supports the fastest access modes of the newest DRAMs. And it radically reduces parts count and engineering effort compared to PAL-based designs.

But above all, it effectively increases the speed of your memory array—giving you performance exceeding 50 ns from 80 ns DRAMs*. And making for similar gains in DRAMs of other speeds.


*System dependent.



DRAM CONTROLLER

Our 1- and 4-meg DRAM Controller is a System Accelerator™ that gives you

50 ns
PERFORMANCE FROM
80 ns DRAMs.



Samsung's System Accelerator enhances performance dramatically with DRAMs of all speeds.

As well as boosting the performance you can get from the DRAMs you're already using, the System Accelerator can save you money by letting you use slower DRAMs—and getting the speed from them that you're currently using faster ones to achieve.

The System Accelerator is available in two versions. One has an externally programmable register and is

used for prototyping and moderate-volume applications. The other version is the only DRAM controller available anywhere with

a mask-programmed register. It eliminates still more components.

The register is used to accommodate system variables such as pre-charge times and refresh timing.


We offer quick turn-around on the masked version of the System Accelerator, and we have the externally programmable version available in quantity now.

Request data sheets, application notes, and information on ordering our DRAM Controller Design Kit *today*. Then get started designing-in speed.




SAMSUNG'S DRAM CONTROLLER.

Part	RAMs Supported	Package
KS84C21-25CL	256K, 1 MB	68-pin PLCC
KS84C22-25CL	256K, 1 MB, 4 MB	84-pin PLCC



Even with the most powerful CPUs, Samsung's DRAM Controller significantly improves performance. No processor, even RISC processors, can access main memory faster than the speeds of our DRAM Controller.

As a result, market acceptance has been rapid—with designs in process at a number



DESIGNING-IN
*the System Accelerator is easy when
 you use our*

68020/30
AND
286/386

SYSTEM DESIGN GUIDES.

of major computer manufacturers in the first two months of introduction.

Another reason for this is ease of design. If you have our 68020/30 and 286/386 design guides, you'll see that we've already done most of the work for you.

Interleaving is the key.

Among the features that help the DRAM Controller boost performance is *interleaving*, illustrated in the diagram below.



Interleaving with two DRAM banks.

The part's interleaving features cut cycle time in *half*, by allowing your processor to access exclusively DRAM banks that can go immediately to work—because they aren't in precharge. Whenever a bank starts to precharge, another bank


is accessed instead—all with total transparency to the user.

Interleaving alone creates significant performance improvements.

Boosting 286/386 performance and cutting parts count.

The DRAM Controller directly interfaces with 286/386 processors, either with or without cache memory.

In either case, designers are typically able both to improve performance and cut costs.



One customer eliminated each of the shaded components from his 386 motherboard by using the Samsung DRAM controller.

One 386-based design, with cache, has resulted in a 35% improvement in memory performance. And at the same time, has cut costs substantially by permitting removal of 35 PC motherboard components.

Speeding up 68020/30 systems.

The speedy 68020 and 68030 processors have large appetites for fast DRAMs—100 ns and faster.

The DRAM Controller's interleaving features, which cut access cycle time in half, make it considerably easier to satisfy the requirements of these speed-hungry processors.



Complete Design Guides.

The System Accelerator is an easy part to design-in—particularly if you have our System Design Guides. These describe actual systems based on the 68020 and the 286. And they provide detail on numerous features not discussed here, which simplify and reduce the design cycle.

Request yours today!

MICROPROCESSOR PERIPHERALS

Samsung introduces a broad CMOS family.

THE INDUSTRY'S FASTEST

Microprocessor Peripherals.

Which means fast 8086/286/386 CPUs no longer have to be chained down by peripherals that are slow.



Samsung's extensive new line of microprocessor peripherals is the highest-performance industry-standard family made by anyone.

We offer these CMOS parts with top speeds of 10 Mhz, 12 Mhz, and even 16 Mhz.

Which means that, finally, there's a place where you can get peripherals that won't slow down your fast CPU like some giant weight attached at the ankles. But will, instead, let it run the way it was meant to—fast.

What makes this all the more important is that you can get as many of these high-performance parts as you want because we're a high-volume supplier, and we have these parts ready for immediate delivery in quantity.

CMOS MICROPROCESSOR PERIPHERALS FROM SAMSUNG

Part	Speed	Available
KS53C80 SCSI Interface	1, 3 Mbyte/ sec.	Now
KS82C37A DMA Controller	5, 8, 10 Mhz	Now
KS82C50A UART	8, 10 Mhz	Now
KS82C52 Serial Controller Interface	8, 10 Mhz	Now
KS82C54A Interval Timer	8, 10 Mhz	Now
KS82C55A Programmable Peripheral Interface	8, 10 Mhz	Now
KS82C59A Interrupt Controller	8, 10 Mhz	Now
KS82C84A Clock Generator	8, 10 Mhz	Now
KS82C88 Bus Controller	8, 10 Mhz	Now
KS82C284 80286 Clock Generator	10, 12, 16 Mhz	Now
KS82C288 80286 Bus Controller	10, 12, 16 Mhz	Now
KS82C289 80286 Bus Arbiter	10, 12, 16 Mhz	Now
KS68C455 CRT Controller	4, 6 Mhz	Now
KS84C21/22 DRAM Controller	25 Mhz	Now
KS85C30 SCC	6, 8, 10 Mhz	May

Besides being fast, our peripherals are in CMOS, which means they're low in power dissipation and will keep your designs cool. And unlike most peripherals, they're available through the entire line in PLCC surface mount packaging, in addition to DIP.

Of particular note is our 82C37 DMA Controller, which at 10 Mhz is the fastest made. Also: our 53C80 SCSI Interface, and our blow-the-doors-off, performance-boosting 1- and 4-Mb DRAM Controller, discussed elsewhere in this issue and affectionately known as the System Accelerator.

Microprocessor peripherals from Samsung. Designed not to slow your CPU down—but to let it run at the speeds it was meant to.

Request a data book and application notes now.





At Samsung, we operate advanced facilities in both the United States and Korea.

Samsung Semiconductor's U.S. R&D and wafer-fabrication facilities are extensive. They represent a firm commitment to providing optimum service, timely delivery, and excellent channels of communication for our U.S. customers. Among the product lines we now produce in U.S. facilities are CMOS Programmable Logic, FIFOs, and fast SRAMs. Worldwide, we run a total of eight R&D and manufacturing facilities. Among them, one particular showpiece is our Class 1, 6" wafer facility in Kiheung, Korea, dedicated to DRAM technology. With fully automated manufacturing, it is among the largest semiconductor plants ever built.

CMOS PROGRAMMABLE LOGIC

In programmable logic, Samsung's volume production brings

Low Power WELL Within Reach.

And there's every reason for you to design it in.

Designing-in Samsung's CMOS Programmable Logic family, CPL™, is a decision that makes supremely good sense.


Not just because CPL reduces power dissipation 70% compared to bipolar PALs.®

But because CPL is the first *viable* low-power alternative to them.

CPL is viable both because we're offering it in volume. And because we're making it affordable—comparable in cost to bipolar parts.

What we're doing, in other words, is taking CMOS Programmable Logic, once and for all, out of its high-priced niche. To make low power a reality. And make compact systems more feasible than ever.

CPL reduces power dissipation up to 70% compared to bipolar PALs.



Key:

— 8 Outputs switching, each output loaded with 50pF
--- 8 Outputs switching, no load

Besides giving you a head start on reducing power consumption in new designs, Samsung CPL will let you cut your power consumption up to 70% in your existing

designs, by directly replacing your bipolar PALs. With no new development tools. And with no redesign.


And there's another critical advantage. Unlike bipolar PALs, Samsung's CPL devices are UV-erasable. Which is how we give you parts 100% tested to programming, AC, and DC parameters before shipping— for 100% programming yields and greater reliability.

CPL—low in power, 100% tested, and produced in volume by a manufacturing giant— is here to stay. Request a data book and information on our CPL Starter Kit (described on the facing page) now. And get started with this winning technology right away.

THE CPL PARTS

CPL 20	CPL 24	Flexible Output Macrocell
CPL16L8	CPL20L10	CPL22V10 ¹
CPL16R4	CPL20L8	CPL16V8 ²
CPL16R6	CPL20R4	CPL20V8 ²
CPL16R8	CPL20R6	
	CPL20R8	

Speed options: 20 ns, 25 ns, 35 ns
Power options (I_{cc} max): 35mA, 70mA



You can develop a CPL design with existing PAL development tools. Or you can do it with the convenient new Samsung CPL Starter Kit.

The Starter Kit includes a newly updated software package based on the industry-standard CUPL™, the most powerful high-level language for designing programmable logic. And it includes CPL20,

CPL24, and our new CPL22V10, CPL16V8, and CPL20V8 samples—all of which are supported by the software.

Since CPL devices are reprogrammable, this means the Starter Kit includes everything you'll need to prototype and debug your design.


You'll be doing that in short order. The CUPL software, developed by Logical Devices, Inc., includes comprehensive documentation. It runs on any IBM PC/XT/AT or compatible system. And it lets you choose from a variety of options for entering your design—including truth tables, state diagrams and ASM flow charts (for describing sequential designs), and high-level equations.



The complete Starter Kit contents:

- CPL20, CPL24, CPL22V10, CPL16V8, and CPL20V8 samples.
- A CPL data book.
- A manual for the CUPL software.
- A Programmable Logic User Guide (PLUG) diskette, which lets you browse interactively through the workings of programmable logic.
- "My First PAL Design," a booklet that leads you step by step through programmable logic design.


At just \$150, Samsung's CPL Starter Kit is a bargain. Request ordering information today and get started designing-in low power.



EEPROMS

THE MOST RELIABLE Battery-Backed SRAMs AREN'T SRAMs at All.

They're Samsung's remarkable
line of CMOS EEPROMs.



SAMSUNG CMOS AND NMOS EEPROMs.

Part Type	Org.	Speeds	Features	Technology	Pinout	Availability
KM28C64	8Kx8	200,250ns	Data Polling, 32-byte Page Mode, Low Power, 5 ms (max) write time	CMOS	28-pin DIP 32-pin PLCC	From stock
KM28C65	8Kx8	200,250ns	Same as above with ready/busy on Pin 1	CMOS	28-pin DIP 32-pin PLCC	From stock
KM28C16	2Kx8	150,200, 250ns	32-byte Page Mode, Low Power, 2 ms (max) write time	CMOS	24-pin DIP 32-pin PLCC	From stock
KM28C17	2Kx8	150,200, 250ns	Same as above	CMOS	28-pin DIP 32-pin PLCC	From stock
KM2816A	2Kx8	250,300, 350ns	10 ms (max) write time	NMOS	24-pin	From stock
KM2817A	2Kx8	250,300, 350ns	Ready/Busy, 10 ms (max) write time	NMOS	28-pin	From stock
KM93C06/7	16x16	250KHz	Serial I/O with self-timed clock option	CMOS	8-pin DIP 8-pin 50 SOIC	Now
KM93C46	64x16	250KHz	Serial I/O with timer	CMOS	8-pin DIP 8-pin 50 SOIC	Now

It goes without saying that EEPROMs are going to be more reliable than devices such as SRAMs, which use batteries to retain data during power loss.

For the simple reason that EEPROMs don't require these batteries.

What doesn't go without saying, though, is that this makes EEPROMs a better choice than battery-backed SRAMs in many applications.

Because of the relative costs, designers haven't used EEPROMs where conventional thinking calls for SRAMs—*despite* reliability improvements.

But those relative costs are changing.

Today, SRAMs cost more than they once did. And Samsung's EEPROMs, in fact, now compare favorably in price.

Even in CMOS. And even though their reliability is far greater than requirements call for.

All of which means that if reliability is what you want, there's every reason to start using these parts—and making your next battery-backed SRAMs, Samsung EEPROMs.

Robotics, industrial control, instrumentation, and communications are additional applications we excel at.



We offer an unusually fast 32-byte page mode, with write times down to 5 ms/page in the 64K chip, and 2 ms/page in the 16K chip.

Most important of all, they're available in quantity *from stock*, so you avoid escalating lead times as well as high prices.

EEPROM performance, reliability, and availability. To learn more about them, contact us now.

FAST SRAMS

INTRODUCING 256K Fast SRAMs.

*At 25 ns, they are in fact as fast
as you can get.*



SAMSUNG'S SPEEDY 256K STATICS

Part Type	Organization	Packaging	Available
KM64257	64Kx4	DIP, SOJ	Now
KM61257	256Kx1	DIP, SOJ	June
KM68257	32Kx8	DIP	3Q'89




Samsung's expertise with double-layer metal technology lets us become masters of one of the toughest areas of all.

Fabulously speedy static RAMs.

Right now we're introducing fast statics in the exciting new 256K density at 25 ns speeds.

Speeds as fast as you can find anywhere. Available in all three organizations.



We produce them in all industry standard packages, and they're manufactured in 1.2 micron CMOS technology.

Along with our Fantastic FIFOs™, our performance boosting DRAM Controller, and our 70 ns DRAMs, these static RAMs will help take you to the frontiers of performance.

Request data sheets today.

At Samsung,
we are experts in process technology.

For some years, Samsung Semiconductor has been among the world's leaders in manufacturing products that use high-speed CMOS processes. Today, we are also among the first in the world to prototype 4-meg DRAMs. These 4-meg chips are based on Samsung's proprietary CMOS technology and on 0.8 micron line widths. Like our static RAMs, these and many of our other DRAM products start with our advanced 6" wafer fabrication capabilities. At Samsung, we want to be absolutely certain of remaining at the forefront of new technologies. To this end, we have, all told, invested more than \$700 million in new-product development.

DRAMS

SAMSUNG DRAMs

Now scorch at 70 nanoseconds.

Extending our memory leadership, Samsung now offers new, lightning-quick 70 ns 1-meg DRAMs.

And good news: they are easier to get your hands on than you may think.



Samsung now offers 1-meg DRAMs in 70 ns, 80 ns, and 100 ns speeds.

Like the rest of our DRAMs, our 1-meg parts are available in all popular plastic

package formats. They are exceptionally low in power consumption, thanks to our internally developed CMOS technology. And they have been proven extremely reliable—as our

reports show. Please contact us today for information and data sheets.

THE SAMSUNG DRAMs

Part Type	Organ.	Features	Speeds	Packages	Available
KM41C1000	1Mx1	Fast Page mode	70, 80, 100, 120	DIP, ZIP, ¹ SOJ ²	Now
KM41C1001	1Mx1	Nibble mode	70, 80, 100, 120	DIP, ZIP, ¹ SOJ ²	2Q'89
KM41C1002	1Mx1	Static Column mode	70, 80, 100, 120	DIP, ZIP, ¹ SOJ ²	Now
KM44C256	256Kx4	Fast Page mode	80, 100, 120	DIP, ZIP, ¹ SOJ ²	Now
KM44C258	256Kx4	Static Column mode	80, 100, 120	DIP, ZIP, ¹ SOJ ²	2Q'89
KM41256	256Kx1	Page mode	100, 120, 150	DIP, ZIP, PLCC	Now
KM41257	256Kx1	Nibble mode	100, 120, 150	DIP, ZIP, PLCC	Now
KM41464	64Kx4	Page mode	100, 120, 150	DIP, ZIP, PLCC	Now
KM4164	64Kx1	Page mode	100, 120, 150	DIP, ZIP, PLCC	Now

¹Available mid-year.
²Tape and reel mid-year.

To receive free data and other literature

on Samsung products, simply check the items you want and return to Product Marketing Dept., Samsung Semiconductor Inc., 3725 No. First St., San Jose, CA 95134-1708. Or call this number:

1-800-669-5400

Or 408-434-5400

FIFOs M4

- Data sheet
- Pricing

DRAM Controller P1

- Data book
- Information on the DRAM Controller Design Kit
- 68020/30 System Design Guide
- 286/386 System Design Guide

Microprocessor

- Peripherals P3
- Data book

CMOS Programmable

- Logic L1
- Data book
- Information on the CPL Starter Kit

EEPROMs M2

- Reliability report
- Data book

Fast SRAMs K1

- Data sheets

DRAMs M1

- Data sheets

Name _____

Title _____

Company _____

Address _____

City _____

State _____

Zip _____

Telephone _____



CPL, Fantastic FIFOs, and System Accelerator are trademarks of Samsung Semiconductor, Inc. PAL is a registered trademark of Monolithic Memories, Inc. CUPL is a trademark of Logical Devices, Inc.

1989 ELECTRONICS & COMPUTER TECHNOLOGY TOURS

SUMMER FAR EAST COMPUTER TOUR

June 1-10, 1989

Visit:
SEOUL and TAIPEI

- Featuring:
- KOREA ELECTRONICS PARTS & EQUIPMENT SHOW
 - TAIWAN COMPUTER SHOW

SOUTH AMERICA ELECTRONICS/COMPUTER TOUR

September 23 to October 3, 1989

Visit:
BRAZIL and ARGENTINA

- Featuring:
- BRAZIL COMPUTER SHOW
 - BUSINESS MEETING IN ARGENTINA

OCTOBER FAR EAST ELECTRONICS/COMPUTER TOUR

October 8-21, 1989

Visit:
SEOUL, TAIPEI, HONG KONG, OSAKA

Optional: Bangkok, Singapore, China

- Featuring:
- KOREA ELECTRONICS SHOW
 - TAIPEI INTERNATIONAL ELECTRONICS SHOW
 - HONG KONG ELECTRONICS FAIR
 - JAPAN ELECTRONICS SHOW

CALL, WRITE OR FAX FOR MORE INFORMATION I am interested in: Summer Computer Tour South America Electronics Tour October Far East Electronics Tour EDN041389


COMMERCE TOURS INTERNATIONAL, INC.
870 Market Street, Suite 920
San Francisco, CA 94102
Tel: (415) 433-3072
Tlx: 278124 CTI UR
Fax: (415) 433-2820

Name _____
Company _____
Title _____
Address _____
City _____ State _____ Zip _____
TEL: _____ TLX: _____ FAX: _____

OPEN SYSTEMS::OPEN TOOLS™

MAXIMUM POWER FOR REAL-TIME DEVELOPMENT

Whether over the backplane or network, Heurikon has your VME and Multibus targets. VxWorks • VADSWorks • OS-9 • VRTX • Ada • Unix V.3 • Network solutions • Just a few of the Open Tools™ Heurikon has to speed your application to market. Call now for real-time response.



1-800-356-9602

HEURIKON
CORP
MICROCOMPUTERS FOR INDUSTRY

VxWorks is a trademark of Wind River Systems, Inc. VADSWorks is a trademark of Wind River Systems, Inc. and Veridy Corporation. VRTX is a trademark of Ready Systems, Inc. OS-9 is a trademark of Microware Systems, Inc. Unix is a trademark of AT&T Bell Laboratories, Inc. Multibus is a trademark of Intel Corporation. Open Systems™ Open Tools is a trademark of Heurikon Corporation. Open Tools is a trademark of Heurikon Corporation.

CIRCLE NO 104

Graphic proof of high-tech leadership.



The Casio fx-7000G \$89.95. It's the world's first programmable scientific calculator with a graphic display. It can give form to your figures, instantly drawing graphs that depict your formulas and calculations.

With a screen measuring 16 characters by 8 lines, the fx-7000G can display enough information for some of your biggest ideas. And you can store graphs and formulas, then bring them back for an instant replay.



With its 422 step memory and 193 functions—including linear regression, standard deviation and computer math—the fx-7000G lets you perform computer functions, without acquiring computer knowledge or incurring computer costs.

For additional capabilities, there's the fx-7500G (\$109.95). It has a larger memory capacity, with 195 functions, 4,006 memory steps, instant graph enlargement or reduction feature, plus a convenient horizontal folding format.

If you need even more power, our fx-8000G (\$119.95) techs you even higher, with 1,446 memory steps and 225 functions. And when hooked up with our optional FA-80 interface, it works with most parallel dot matrix printers or plotters including Casio's own models.

If you have any doubts as to who's the leader in high-tech calculators, just pick up an fx-7000G, fx-7500G or fx-8000G and draw your own conclusions.


CASIO®
Where miracles never cease

CIRCLE NO 105

Casio, Inc. Consumer Products Division: 570 Mt. Pleasant Avenue, Dover, NJ 07801
Casio Canada Ltd., 2100 Ellesmere Road, Suite 240, Scarborough, Ontario M1H3B7

SRAMs

Our New SRAMs Haul Access.




At 15 nsec, Our SRAMs Really Tear Up The Track.

If you've been wondering where to find fast SRAMs lately, we have good news for you. Now you can look to Logic Devices—the logical choice.

Our new family of CMOS SRAMs gives you more options for high-end applications, where you have to match fast CPU speeds. They're available in speed categories from 15 to 45 nsec. So even your high-performance RISC and 32-bit micro designs can forget about wait states.

Because these parts just plain haul access. But without making



you pay a power penalty. Their advanced CMOS technology runs as low as 340 mW in active mode, and 25 mW in standby. Plus they

feature proprietary Auto Powerdown™ circuitry and 2 volt data retention, making them ideal for battery backup operation. And since these

parts are plug-compatible with industry-standard SRAMs, you have a clear upgrade path to higher performance. We've reved up production for delivery today, on all popular organizations, including 64K x 1, 16K x 4 and 8K x 8—in a variety of package types.

For full details, call us today toll free at (800) 851-0767; in California, (800) 233-2518.

ORGAN.	SPECIAL FEATURES	MAX t _{AA} , ns
16K x 1*	SEP I/O	12
4K x 4*	COM I/O	15
4K x 4*	COM I/O W/OE	15
4K x 4*	SEP I/O TRANSP/WRITE	15
4K x 4*	SEP I/O HI IMP/WRITE	15
2K x 8*	COM I/O W/OE	20
64K x 1	SEP I/O	15
16K x 4	COM I/O 1 CHIP ENABLE	20
16K x 4	COM I/O 2 CHIP ENABLES + OE	20
16K x 4	COM I/O 1 CHIP ENABLE + OE	20
16K x 4	SEP I/O TRANSP/WRITE	20
16K x 4	SEP I/O HI IMP/WRITE	20
8K x 8	COM I/O 2 CHIP ENABLES + OE	25


* PRELIMINARY

Or write: Logic Devices, Inc., 628 East Evelyn Avenue, Sunnyvale, CA 94086; Telex 172387.

LOGIC
DEVICES INCORPORATED

DUAL-PORT STATIC RAMs

Specialized memories ease communications



The popularity of dual-port static RAMs is on the rise. These devices greatly simplify shared-memory implementations.

*Dave Pryce,
Associate Editor*


Although they make up only a small fraction of the hundreds of millions of RAMs produced each year, dual-port static RAMs (SRAMs) are becoming increasingly important for solving difficult interface problems. Compared with the ubiquitous single-port dynamic RAMs (DRAMs) used in conventional memory applications and the dual-port dynamic RAMs (VRAMs) used in video graphics applications, dual-port static RAMs are less familiar to designers. They're a valuable addition to your computer-equipment design arsenal, however, because they provide a simple way to untangle such snags as arbitration problems in shared-memory systems.

Unlike dual-port dynamic RAMs (VRAMs), which are serial on one side and parallel on the other, dual-port SRAMs have parallel ports on both sides. These parallel ports let you use dual-port SRAMs for local memory that is shared between two systems, such as two CPUs, or for communications and real-time DSP applications that require asynchronous communication between two devices at the same time.


Fig 1 illustrates a

typical application in which three dual-port SRAMs interface a host CPU to another CPU, a DSP, and an I/O controller. Because of the unique capabilities of dual-port chips, you can use the same memory for both working storage and communication between two devices, thus avoiding the need for special data-communication hardware.

Dual-port SRAMs provide a faster and less complex alternative to conventional single-port RAMs, which have inherent speed limitations because of their



This 2k x 8-bit dual-port static-RAM chip from Cypress Semiconductor is available in a 48-pin plastic DIP, ceramic DIP, or leadless chip carrier (LCC).



MICREL DELIVERS SMART POWER TO RUN THE WORLD.

With the new high voltage MPD8020 CMOS/DMOS/Bipolar semi-custom array.

Now you can use Micrel's MPD8020 to manage and deliver controlled smart power anywhere for real world work.

Run and control motors, switch regulators, drive lamps, power displays, control relays and solenoid drivers, run printers and so much more where you're putting big electrical energy to work running the world.

This extraordinary array, which can be tailored to your exact needs in just 45 to 60 working days, combines CMOS analog circuits, TTL/CMOS compatible high speed CMOS logic, and high voltage DMOS power drive circuits in one monolithic IC.



For Switched Mode Power Supplies.

25 to 100 Volts. Small size, up to 1MHz switching. Full and half H-bridge configurations. DMOS FETS source/sink. "Bulletproof circuits" provide overcurrent, overvoltage and over-temperature protection.



For Military Avionics.

80 Volts peak, 28 Volts operating (more than 50% derated), capable of meeting MIL SPEC 704. Use for mil spec displays, pin diode drivers, lamp drivers, compact actuator controls, relay drivers, fly-by-wire controls. Wide environmental tolerance. High MTBF. Lightweight, and small size.



For Telecommunications.

48 Volts for the central office. VLSI to reduce circuit board real estate. A perfect choice for card cages and subscriber sets. Shrink the size, increase features and reliability.



For Computer Peripherals, Office Equipment, and Industrial Controls.

24 Volts operating, 100 Volt peak allows >50% derating for ruggedness. From FAX to friction. 16 solenoid drivers on a single chip. High efficiency and low development cost. 5V to 15V controls high current and or high voltage. Customize your I/O. High side driver improves safety. Half, full or 3-phase H-bridge configurations are great for HVAC control, machine driver control, and robotics.



For Medical Equipment.

80 to 100 Volts. High voltage for feedback and physiological needs. Semi-custom array cuts costs, lowers size, reduces parts count, increases features, and improves reliability.

Sixteen Page Data Sheet Yours For the Asking.

For your copy and other information, please address Micrel Semiconductor, 560 Oakmead Parkway, Sunnyvale, CA 94086. Phone (408) 245-2500. FAX (408) 245-4175.

MICREL

SEMICONDUCTOR
THE INTELLIGENT POWER COMPANY™

TECHNOLOGY UPDATE

Dual-port static RAMs

need for multiplexed read/write (R/W) access. Dual-port SRAMs allow two independent devices to have simultaneous R/W access to the same memory. The devices communicate with each other by passing data through the common memory.

Although the market for dual-port SRAMs is growing at a rate of over 30% a year, its total dollar value is small. The market for these chips is estimated to be only \$15 million in 1989 and \$20 million in 1990. Consequently, only a handful of vendors currently serve this niche market. Integrated Device Technology (IDT) is probably the leading supplier, with at least eight different products. Other major players include Cypress Semiconductor, Fujitsu Microelectronics, Sharp Microelectronics, Vitelic Corp, and VLSI Technology.

Dual-port SRAMs are available in speed ratings from 35 to 120 nsec. At least one supplier (Cypress Semiconductor) expects to announce 25-nsec versions by mid-year. The densities of currently available chips range from 8k to 128k bits. Chip organizations range from 1k×8 to 16k×8 bits and 2k×16 to 8k×16 bits. By mid-1989,




Fig 1—Because dual-port SRAMs provide a shared memory, you can use them as a communications interface between a host CPU and other processors and controllers.

Integrated Device Technology expects to introduce 1k×8-bit and 2k×8-bit 4-port SRAMs, which are even more versatile than their dual-port siblings.

In a unique departure from the typical architecture, VLSI Technology has created a dual-port SRAM that is organized as 1k×16 and 2k×8 bits. According to VLSI

Technology, its VT16DP8 chip is the industry's first single-chip solution to the problem of transferring data between systems having dissimilar word sizes. The chip allows simultaneous reads and/or writes from either the 16-bit or the 8-bit port. The 16-bit port has the ability to read or write in either word or byte mode.




Fig 2—Typical of a dual-port SRAM's architecture, this block diagram of a chip from Integrated Device Technology shows two sets of address, data, and read/write control signals, each of which accesses the same set of memory cells.

TECHNOLOGY UPDATE

Dual-port static RAMs




Fig 3—Both the L and the R select lines of this dual-port RAM cell can independently and simultaneously select the cell for readout. Moreover, either side can write data into the cell. Arbitration logic resolves any conflict that occurs when both sides try to write data to the same cell at the same time.

As you would expect, prices for dual-port SRAMs vary widely, depending on density, speed, packaging, and grade (commercial or military). Some typical prices (in quantities of 100) for commercial-grade parts in the fastest available speed rating (usually 35 nsec) are: 1k×8 bits, \$28; 2k×8 bits, \$46; 4k×8 bits, \$60; and 2k×16 bits, \$103.

The previously mentioned VT16DP8 from VLSI Technology is a 70-nsec device that sells for \$52.50 (1000). At the low end of the price range, Fujitsu has a relatively slow (90-nsec) 2k×8-bit device that sells for \$12 (1000).

The basic architecture of a dual-port SRAM includes two sets of address, data, and control lines (Fig 2). Each set of lines (left and right) can independently and simultaneously access any word in the memory, even when both sides are accessing the same memory location at the same time.

Built-in arbitration (in the form of interrupt logic and busy logic) resolves any conflict in memory access when both the left and the right sides try to read or write to the

same memory location simultaneously. Some dual-port chips include semaphore logic, which aids in software-oriented arbitration.

The memory cell for a dual-port SRAM is a true dual-access cell. This cell has two independent and separate address-select lines and

data-bit lines that have access to the RAM cell latch (Fig 3). The L and R select lines can independently and simultaneously select the cell for readout. Moreover, either side can write data into the cell. Arbitration logic (not shown in Fig 3) resolves any conflict that occurs when both sides try to write data into the cell at the same time.

Arbitration logic is the key

As mentioned, dual-port SRAMs use one or more types of arbitration logic—interrupt, busy, and semaphore logic—to resolve conflicts. Some chips provide all three forms of logic.

Interrupt logic provides signaling between two processors that share a common memory. A common form of signaling is for one processor to cause an interrupt on the other processor. In this way, the receiving processor is informed of a communication without having to check for it continually.

Busy logic resolves any conflict that occurs when both ports of the dual-port chip attempt to access the

TABLE 1—REPRESENTATIVE DUAL-PORT SRAMs

MANUFACTURER	SIZE (BITS)	ARBITRATION LOGIC			SPEED RANGE (NSEC)
		INTERRUPT	BUSY	SEMAPHORE	
CYPRESS SEMICONDUCTOR	1k×8	•	•		35 TO 55
	2k×8	•	•		35 TO 55
INTEGRATED DEVICE TECHNOLOGY	1×8	•	•		35 TO 100
	2k×8	•	•	•	35 TO 100
	4k×8			•	35 TO 70
	8k×8	•	•	•	35 TO 70
	16k×8	•	•	•	35 TO 70
	2k×16		•		45 TO 90
	4k×16	•	•	•	30 TO 70
FUJITSU MICROELECTRONICS	8k×16	•	•	•	30 TO 70
	2k×8	•	•		90 TO 120
SHARP MICROELECTRONICS	2k×8	•	•		35 TO 55
	4k×8	•	•		35 TO 55
VITELIC CORP	2k×8		•		55 TO 90
VLSI TECHNOLOGY	2k×8 AND	•	•		70
	1k×16				
	2k×8	•	•		30 TO 45

ANOTHER GREAT OFFER FROM
THE EMPLOYEE-OWNERS* OF AVIS, INC.

The employee-owners of Avis, Inc. want you to experience the elegance of a Cadillac Sedan de Ville or similar luxury-group car at a very economical rate. With SuperValue Rates and fast service, we're trying harder than ever to give you what you want in a rental car.

Drive An Elegant Bargain.

\$49 a day. Cadillac Sedan de Ville. 100 miles/day included. 30¢/mile thereafter. Optional Collision Damage Waiver \$9/day in Cal., \$10.95-\$12.95/day elsewhere. Rate not available in metro N.Y., N.Y. state, and Illinois.

To get this low rate, here are some things you should know. The rate is available at select U.S. corporate and participating licensee locations.

It is nondiscountable and may change without notice. These cars are subject to availability. Blackout periods and additional seasonal charges may apply. There is no refueling charge if you return your tank full. There's a \$5-\$10/rental charge for additional drivers (no extra charge in Cal.). Renters under 25 pay \$5-\$10 extra/day where applicable. Cars must be returned to renting location. Local taxes and Personal Accident Insurance, Personal Effects Protection and Additional Liability Insurance are extra.

To drive this elegant bargain, call Avis at **1-800-331-1212** or your travel consultant.



We're trying harder than ever.SM



*Employees at all corporate locations. © 1989 Wizard Co., Inc.

EDN April 13, 1989

CIRCLE NO 108

Avis features GM cars. Cadillac Sedan de Ville.

87

TECHNOLOGY UPDATE

Dual-port static RAMs

same address at the same time. Such a situation can arise when one port is trying to read the same data that the other port is writing, or when both ports attempt to write to the same word at the same time.

Semaphore logic provides a set of token-passing flags that supports the block allocation of memory. Although block allocation of memory is a software technique, it can benefit from this hardware support. The semaphore logic connects to external pins, and the internal flags indicate which CPU has permission to use a block of memory.

Many applications for dual-port SRAMs require greater memory depth and/or width than a single chip can provide. In these cases, using two or more chips is the only answer.

You can expand the depth of dual-port SRAMs with little trouble. For example, four $2k \times 8$ -bit chips make an $8k \times 8$ -bit memory. You can also expand the width of dual-port SRAMs, but you must be careful how you do it. Although, for example, two $2k \times 8$ -bit chips make a $2k \times 16$ -bit memory, you can't simply connect the chips to each other.

Because several hardware arbi-




Fig 4—One solution to the system-deadlock problem that occurs when you expand dual-port SRAMs in width is to use master/slave chip combinations. If the master chip activates the Busy function, the slave chip internally disables the write signal of the losing side, thus making only one side accessible.

trators are active at the same time, expanding the memory width can create a problem. Although you can provide selective arbitration by adding external logic to the chip-enable pins of additional dual-port

chips, a better solution is to use master/slave chips in combination.

In master/slave combinations, the master chip has complete control over the slave chip and decides which side has complete access to a particular memory location at a given time (Fig 4). Unlike a master dual-port chip, a slave chip uses its Busy pin as an input rather than an output. Thus, if the master chip activates the Busy function, the slave chip internally disables the write signal of the losing side, making only one side accessible.

When expanding dual-port SRAMs in width, you must make the slave chips wait to write until after the Busy input at the slave has settled. Otherwise, the slave chips may begin writing while the busy signal is settling. This condition is true for systems using conventional dual-port chips with external slave logic as well as for sys-




Fig 5—When expanding dual-port SRAMs in width, you must make the slave chip wait to write until after the busy input at the slave has settled. This write delay is required only in width-expanded systems that use slave chips, not in single-chip or depth-expanded systems where only one chip is active at a time.

TECHNOLOGY UPDATE

tems using slave chips.

Fig 5 shows how to accomplish the needed delay in the slave chip's writing: You delay the write enable to the slave by the arbitration time of the master chip. This write delay is only needed in width-expanded systems that use slave chips, not in single-chip systems or depth-expanded systems where only one chip is active at a time.

For a clear and detailed explanation of SRAM timing requirements, as well as arbitration schemes, expansion methods, and other information on the workings of SRAMs, you can consult two excellent application notes from IDT (**Refs 1 and 2**). Much of the technical content of this overview of dual-port SRAMs is based on information contained in these notes. Complete technical information on SRAMs is somewhat scarce because of the relatively small number of SRAM manufacturers, so these two notes are especially valuable sources of information.

The availability of true dual-port memory chips lets you implement high-speed communication between

components of computer-based systems while avoiding many of the problems associated with earlier systems that provide direct memory access.

Because of the speed and versatility of dual-port SRAMs, you can expect these chips to appear as standard components in a variety of applications, from computers, disk controllers, and modems to copiers, printers, and mobile telephones. **EDN**

References

1. Miller, Michael J, *Dual-Port RAMs With Semaphore Arbitration*, Application Note AN-14, Integrated Device Technology Inc, Santa Clara, CA, 1987.
2. Wyland, David C, *Dual-Port RAMs Simplify Communication in Computer Systems*, Application Note AN-02, Integrated Device Technology Inc, Santa Clara, CA, 1987.

Article Interest Quotient
(Circle One)

High 509 Medium 510 Low 511

For more information . . .

For more information on the dual-port SRAMs discussed in this article, contact the following manufacturers directly, circle the appropriate numbers on the Information Retrieval Service card, or use EDN's Express Request service.

Cypress Semiconductor
3901 North First St
San Jose, CA 95134
(408) 943-2600
Circle No 717

Sharp Microelectronics
Sharp Plaza
Mahwah, NJ 07430
(201) 529-8757
Circle No 720

Fujitsu Microelectronics
3545 North First St
San Jose, CA 95134
(408) 432-9044
Circle No 718


Vitellic Corp
3910 North First St
San Jose, CA 95134
(408) 433-6000
Circle No 721

Integrated Device Technology
Box 58015
Santa Clara, CA 95052
(408) 727-6116
Circle No 719

VLSI Technology
1109 McKay Dr
San Jose, CA 95131
(408) 942-1810
Circle No 722

What's Missing on this LCD?

(answers below)



If you peeked at the answers, then you know it's Motion. In the actual LCD every one of the windows is in motion. Think for a minute how you would make six or seven unique motions *simultaneously* with the low level LCD controllers that you have seen. No way! Now think what your instrument or new systems could do with dynamic text and graphics. Tests show that programmers can achieve animated presentations in only hours using the CY325.


The CY325 LCD Windows Controller Chip



lets you: specify any of 250 built-in windows, or create your own with a single command; manage text and graphics with automatic cursor control; wrap or scroll text with window relative pixel plotting and clipping; read an A/D and write the waveform into the window; drive up to 6 I/O pins with logic waves, or use the 'soft-key' feature of the CY325 for menu management. Only \$75 each (\$20/1000)

Answer:

Motion is missing in each of the windows. Text actually scrolls up in the top left window above, and . . .




The next move is yours . . .

Call today for information on the CY325 LCD Windows Controller Chip or Fax your address to (415) 726-3003.



Cybernetic Micro Systems
Box 3000 • San Gregorio, CA 94074
(415) 726-3000 • Telex: 910-350-5842

CIRCLE NO 5



Some designers already take enclosures very seriously.

If you don't, maybe you should look at the enclosure system that can add superior quality and protection to your ideas.

For example, are you insisting on the right solutions from your "packaging" supplier concerning: unique aesthetics, unlimited flexibility, perfect (100%) cost efficiency at the highest quality levels?


Do you get engineered solutions for thermal dynamic conditions, EMI/RFI shielding or any national or international approval?

You will get it all from RITTAL.

If you aren't already familiar with RITTAL, take just a minute and give us a call at 1-800-637-4425. We'll send you our full-line handbook of enclosure systems and intelligent components. It's free, but the information could change your mind about the importance of enclosures... forever.

Take your design all the way to perfection... switch to RITTAL.

1-800-637-4425




RITTAL Corporation
P.O. Box 1284
3100 Upper Valley Pike
Springfield, OH 45504
Phone: (513) 399-0500
Fax: (513) 390-5599

CIRCLE NO 109



Our new 256Kx1 and 64Kx4 Mighty Memory CMOS SRAMs are ready to take on your heavy-weight advanced architecture design projects.

Perfect for high performance applications



EDI's fast new 256K CMOS Static RAMs, available now in 256Kx1 and 64Kx4 with JEDEC standard pinouts, DIP and LCC.

such as Military 1750, DSP, ALU, and other 32 bit micro designs,

our Mighty Memories are available now in DIP and LCC. Both devices feature speeds to 35ns in standard and low power versions, MIL-STD-883 Class B screened.

EDI is also listed as an approved source on 256Kx1 and 64Kx4 DESC-SMD drawings.


High density. High speed. Low power. The new Mighty Memory 256K Static RAMs from EDI, the high performance military Static RAM leader.

CIRCLE NO 114

EDI
The future...today.

“BoardMaker’s fast turnaround makes us very competitive.”

Frank Miller, President,
Sescom, Inc.



“Half our business is rush. This week, every week. We never know what we’re going to design or modify. So fast reaction time is critical for us.

“That’s where the BoardMaker comes in. It lets us react with finished circuit board designs in hours instead of days. And that makes us very competitive.

“The ability to make more changes in a given time frame.

If you send out for etched boards, there is a tendency to make do with what you thought you needed. But with the BoardMaker, you are spurred to make boards perfect—make little fixes here and there—because you can do it without waiting.

“A short cycle from brain to hardware.

With this machine, you get the finished prototype in front of you while the design is still fresh in your brain. Then you can polish the design—before your idea has turned to tapioca.

“Runs seven hours a day, five days a week.


The BoardMaker is also a good small lot production tool. We run it all week long, making boards from a half-inch square up to six inches by eleven. Most are single-sided.

“Changes during production runs? No problem.

Sometimes we have to substitute components. Or make short run specials for customers. With the BoardMaker, we just make the change and keep going.

“An affordable system.

The cost is very affordable. And we’re very happy avoiding the astronomical costs involved when we sent things out on a rush basis (and still forgot about half of what we were going to do).”



Three BoardMaker models make single- and double-sided boards for prototyping or small production runs. Cost is much less than first-generation machines; milling speed is faster. For information, call 415 883-1717 or mail the reader card. Or send \$12.95 for an all-features demo on VHS cassette.
Instant Board Circuits
20A Pamaron Way
Novato, CA 94949

See Us at Electro New York Booth #2848

ibo

Instant Board Circuits



THE SIMPSON 560 MENU DRIVEN MULTIMETER. SOMETHING NEW ON THE MENU.

From microvolt transducer measurements to high voltage work, Simpson's new *Professional Series Model 560 Digital Multimeter* is designed to quickly give the answers you need—without elaborate signal conditioning.

Diagnostic functions such as MIN/MAX Hold and Peak Hold let you find and display transient amplitudes, while the bar graph continues to monitor the incoming signal. Programmable data logging on any range or function and a built-in 500 KHz frequency



counter, further expand the acquisition capabilities of the Simpson 560.

What's more, it's now possible to speed up routine tests—saving only the measurements of interest—because the 560 offers real-

time comparison to stored test limits. Permanent records of the captured data can be generated by computers or printers connected to the optional interfaces (Centronics, RS-232 or IEEE-488). Displayed menus make it quick and easy to set the measurement parameters. And ultra-fast autoranging inputs instantly calculate the proper scale.

Order from our menu. The Simpson 560 Menu Driven DMM. You'll agree that it's done quite tastefully.

Simpson Professional Series products are made in USA.

SIMPSON

Simpson Electric Company 853 Dundee Ave., Elgin, Illinois 60120-3090 312/697-2260 FAX: 312/697-2272



CIRCLE NO 73

p, hop, hop, hop, hop

chirp, chirp, chirp



jitter, jitter, jitter

...like you've never seen them before.





hop

...a time-domain view of a frequency-agile signal (left) reveals little useful information. The new modulation-domain view on the right clearly shows the hopping sequence, settling times, and channel frequencies.



chirp

...no quantitative data is available from the time-domain view of a radar chirp on the left. However, the frequency vs time display of this single-shot event clearly shows chirp linearity and frequency.



jitter

...a time-domain view of jitter shows only that the jittered data's edge is constantly changing with respect to the clock. In the modulation domain, the jitter magnitude and periodic content are clear.

HP introduces the modulation domain.


Totally new measurement concepts are rare. The oscilloscope was one. It brought the time domain to voltage measurements. Spectrum analysis, which added the frequency domain, was another. Now, there's a breakthrough that puts you in the modulation domain. Dynamic frequency and time interval analysis.

The new HP 5371A Frequency and Time Interval Analyzer gives you entirely new ways to view dynamic signals. Views that simplify and speed analysis of transient signals, modulation, and frequency stability. As well as time transients, jitter, and timing relationships between signals. If you're designing equipment for communications, radar, mass storage, data processing, and ATE, the HP 5371A gives you new insights for faster troubleshooting and characterization.

hop ... agile radio measurements that were impossible until now.

Say goodbye to static back-to-back and "golden unit" testing that's been costing you time and money without delivering the quantitative measurements you need.

Complete characterization of hopping radio transmitters is easy for the HP 5371A. Its dynamic single-shot capability captures hopping sequence, carrier frequencies, and modulation. Then it displays signals in a frequency vs time plot for quantitative measurements of overshoot and settling time (valuable for VCO signals too). You can also examine FM details. And, histogram displays give a clear picture of channel usage.



chirp

... radar signal characterization in a snap.

Because the HP 5371A captures single-shot events and performs fast statistical computations, you can simply and inexpensively characterize pulse parameters that affect target resolution, range, and accuracy.

There's no easier way to analyze chirp linearity or phase coding than the direct measurements of frequency vs time in the modulation domain. And histogram plots of pulsewidth jitter and pulse repetition frequency give you quantitative and reliable measures of system performance. Expensive and cumbersome delay line discriminators are eliminated... forever.



jitter

... finally,

precise quantification for performance prediction.

The HP 5371A's statistical analysis and histogram capability, combined with time-variation plots, give you a valuable new tool for quantifying the affects of jitter and wander in digital communications, data storage, and computer systems.

Histogram displays and statistics of frequency or time interval show you quickly whether jitter effects are Gaussian or systematic. These results reveal valuable information leading to the prediction of bit error rate. And modulation domain displays give you a useful view of jitter periodicity. An FFT of this data gives you a jitter spectrum. With the HP 5371A, you can troubleshoot faster and get better characterization of timing jitter than ever before.

See the back page for more information.

Call 1-800-752-0900, Ext. 215U, or mail the reply card for additional product information and a FREE videotape.

 **HEWLETT
PACKARD**

The HP 5371A...your window to the modulation domain.

As significant a development as the scope or spectrum analyzer, the new HP 5371A Frequency and Time Interval Analyzer is the first commercially available instrument to make continuous frequency measurements and display frequency vs time directly. It's sure to become a basic tool in every R&D lab.

Performance to match your measurement needs.

- dc to 500 MHz (500 MHz bandwidth at microwave frequencies)
- 2 GHz to 18 GHz capability available with the HP 5364A
- up to 10 million measurements per second
- 1 ns minimum pulsewidth
- 150 ps single-shot resolution, 1 ps repetitive resolution
- 2 mV trigger level resolution

Powerful arming and triggering for measurement control.

- Holdoff by time, events or signal edge
- Sample by time, events or edge
- Arm on any of three input channels: External, A, or B

A choice of measurement modes and analyses.

- Frequency, period, phase and time interval
- Positive or negative pulsewidth, duty cycle
- Rise time, fall time
- Time variation, event timing, histograms, statistics, limit test


Plus accessories and HP-IB compatibility

Of course you can combine the HP 5371A with other test instruments and computers via the HP-IB for enhanced capability. It will also drive HP printers and plotters directly for hard-copy records. And a variety of accessories and options are available to match your specific application.

Get there faster in the modulation domain

Like its predecessors — scopes and spectrum analyzers — the frequency and time interval analyzer is sure to give designers greater insight into system problems, and provide dramatic savings in product development and manufacturing. That's the best reason yet to explore the modulation domain. So mail the attached reply card today. Or, better yet, call 1-800-752-0900, Ext. 215U. Now, it's up to you.

you never stop asking
"What if..."





Macro performance in a micro size



**Signetics 83/87C751
microcontroller—the performance
of an 80C51 packed into a 24-pin
skinny DIP or SMD 28-pin PLCC.**

Designed around the 80C51 architecture, our new 83/87C751s let you use your existing instruction set and code to gain the enormous benefits of a smaller package at a smaller price.

A lot of guts in a little package. Its 16 MHz operation means you don't have to sacrifice performance. You'll appreciate the convenience of EPROMs in UV or OTP. Coupled with the flexibility of an I²C serial bus port. And the efficiency of an 8-bit architecture backed by a complete Signetics development system.

Think of it. Increase the power of your 4-bit applications. Or replace your logic blocks. Or lighten your handheld designs. All while decreasing system costs.

Call us for a free '751 Microcontroller Information Packet at (800) 227-1817, ext. 991D. For surface mount requirements and military product availability, contact your local Signetics sales office.

One standard.  defects.

Signetics

a division of North American Philips Corporation



THE POWER SUPPLY



REDEFINED

THE WESTCOR STAKPAK™. NEW GENERATION 250 TO 1200 WATT SINGLE OR MULTIPLE OUTPUT OFF-LINE SWITCHER. 3.2 X 5.5 X 11.4 INCH CASE. FAN-COOLED.

Stack the odds in your favor by designing-in Westcor's 6 watt/cubic inch high power megahertz switcher. Capitalizing on patented and proven megahertz module technology and innovative thermal management techniques, the StakPak provides up to 1200 watts of power at 50°C with 1 to 8 isolated and fully regulated outputs.

For existing designs the StakPak's small size and low profile allow system enhancement without mechanical redesign. Simply replace your open frame switcher with up to 1200 watts of StakPak power or replace your "box switcher" with 2 StakPaks and realize up to twice the power without losing additional space. StakPak power factor correction provides 850 watts of output power from a standard 115 VAC wall outlet. In new designs, more space can be devoted to functionality or the system can be downsized.

The StakPak's 8 module output section can be factory configured in virtually an infinite number of voltage, current and power combinations. Special models providing between 250 to 1200 watts and outputs from 2 to 95 VDC are available.

Other features include outstanding electrical performance; UL, CSA, VDE safety agency approval (in process); variable speed fan option for low ambient noise environments and 3 phase or DC input options. Indeed, with unprecedented power density, versatility and new features, the StakPak redefines power packaging. Please contact Westcor for a data sheet, pricing and additional information.



STANDARD 1200 WATT STAKPAK MODELS (110/220 VAC input)

Model	Output Voltage (VDC) and Maximum Current (amperes) per Channel				
	#1	#2	#3	#4	#5
Single Output					
SP1-1801	2 @ 240				
SP1-1802	5 @ 240				
SP1-1803	12 @ 100				
SP1-1804	15 @ 80				
SP1-1805	24 @ 50				
SP1-1806	28 @ 42				
SP1-1807	48 @ 25				
Dual Output					
SP2-1801	2 @ 120	5 @ 120			
SP2-1802	5 @ 120	5 @ 120			
SP2-1803	5 @ 120	12 @ 66			
SP2-1804	12 @ 66	12 @ 66			
SP2-1805	15 @ 53	15 @ 53			
Triple Output					
SP3-1801	5 @ 180	12 @ 16	12 @ 16		
SP3-1802	5 @ 150	12 @ 33	12 @ 16		
SP3-1803	5 @ 180	15 @ 13	15 @ 13		
SP3-1804	5 @ 150	15 @ 26	15 @ 13		
Quad Output					
SP4-1801	5 @ 150	12 @ 16	12 @ 16	5 @ 30	
SP4-1802	5 @ 150	15 @ 13	15 @ 13	5 @ 30	
SP4-1803	5 @ 150	12 @ 16	12 @ 16	24 @ 8	
SP4-1804	5 @ 150	15 @ 13	15 @ 13	24 @ 8	
Five Output					
SP5-1801	5 @ 120	12 @ 16	12 @ 16	5 @ 30	24 @ 8
SP5-1802	5 @ 120	15 @ 13	15 @ 13	5 @ 30	24 @ 8

Total output power may not exceed 1200 watts for any model, single or multiple output. Lower power StakPak models are available. Please contact the factory.



WESTCOR CORPORATION • 485-100 Alberto Way • Los Gatos, CA 95032 • (408) 395-7050 • FAX (408) 395-1518

Westcor is a subsidiary of  VICOR CORPORATION

Design choices let you optimize Nubus access



You can design a reliable Nubus interface as long as you observe good design practices and keep some caveats in mind.

*J D Mosley,
Regional Editor*

To take full advantage of the Nubus's features—which include a 32-bit backplane with multiprocessing capability, multiplexed address and data lines, and a 10-MHz clock—you can either design your own boards, adapt existing boards to the Nubus backplane, or purchase one of the many Nubus-compatible boards currently available. If you choose to modify existing boards or design new boards and integrate them into a Nubus system such as the Macintosh II, you must adhere to specific design practices. You can detour the pitfalls of interface design by heeding some specific tips from the design veterans of the Nu-Group—the Nubus Manufacturers and Users Group. By avoiding any tempting design shortcuts, you'll supply end users with a Nubus interface that is free of potential problems and, ultimately, extend your system's life in the market.


The major attraction of the Nubus design is its simplicity: It can identify expansion boards (also called modules) as soon as they are plugged into the bus. End users don't need to set DIP switches or use jumpers when adding boards or reconfiguring the computer system.

The Nubus uses a geo-

graphical addressing scheme to identify boards connected to the bus and provide automatic system configuration. Each of the 16 available slots in the Nubus backplane has a unique identity and a specific 16M-byte address space, which is referred to as a *slot space*.



The board determines its slot location by sampling the four bus signals that provide the code. A configuration ROM located on each board lets the computer's initialization software dynamically detect each board's resources when you power up your system.

According to the preliminary IEEE-1196 specification, the Nubus's fair-arbitration technique ensures that all



Many manufacturers now offer Nubus computers. The Explorer II, for example, is a Texas Instruments Nubus-based machine that uses triple-size (11.024 × 14.437-in.²) Nubus expansion boards rather than the PC-size (4.0 × 12.875-in.²) boards used in the Macintosh II.


The Portable Digital Audio DAC



Our new PCM60P lets designers improve the performance of low-power, portable digital audio systems without spending a lot of money. It's a complete 16-bit CMOS D/A converter in a small package for a small price. It takes serial BTC inputs and provides single- or dual-channel outputs.

Cheap Trills!

PCM60P's dynamic performance is better than many DACs costing three or four times as much. Total Harmonic Distortion + Noise is 100% tested and guaranteed. Consider these features:



- THD+N, -86dB max
- Dynamic range, 96dB
- 4X oversampling capability
- Compact 24-lead plastic SOIC package
- 0/+70°C specified temp range
- \$14*

Dual Glitch-Free Outputs

Choose one- or two-channel output modes with no external deglitching required. PCM60P has its own internal reference, too. The output range is $\pm 2.8V_{p-p}$. Channel-to-channel mismatch is less than 1%, and idle channel signal-to-noise is 88dB (20-20kHz).

Single +5V Supply

PCM60P needs only a +5V supply, ideal for battery-operated and other low power applications. Power dissipation is a cool 50mW max.



Ask your sales rep for details and samples, or call 1-800-548-6132 toll-free for more information. Burr-Brown Corp., P.O. Box 11400, Tucson, AZ 85734.

*U.S. prices only, 500-999 quantities.

BURR-BROWN®
BB

TECHNOLOGY UPDATE

Nubus interface options


boards have equal access to the bus. The Nubus uses an algorithm to eliminate the possibility that a low-priority board might never obtain access to the bus. According to the fair-arbitration scheme, boards plugged into slots with high identification numbers are given priority in the arbitration contest. The bus uses four dedicated arbitration lines and distributed arbitration logic. Two cycles after the start of an arbitration contest between boards, the arbitration lines transfer access to the next bus owner. In contrast to the priority-ranking arbitration scheme used in the Micro Channel, this equal-access scheme can't be overridden.

In addition to noting the Nubus's simplicity, the P-1196 specification states that the Nubus is optimized for 32-bit transfers and multiprocessor operation. The bus can address as much as 4G bytes of memory and can perform 32-bit data transfers at 20M bytes/sec and block transfers at 37½M bytes/sec. Its minimum transaction time is 200 nsec. Data transfers can include 32-bit words, 16-bit half words, byte transfers, and block transfers of as many as 16 words.

Beware of design errors

To ensure that your interface will perform in accordance with the outlined specifications, you must approach the design task with caution. First on the list of pitfalls that you must watch out for is failing to verify that the board can decode attention cycles. The P-1196 spec describes four types of attention cycles: attention-null; attention-resource-lock; and two currently undefined, reserved attention cycles.


The attention-null cycle initiates a new arbitration cycle and indicates the end of a locked-resource transfer sequence. The attention-resource-lock cycle blocks a local



Sporting sockets for three daughter boards, the MacAdios II lets you convert your Macintosh II to a laboratory computer system; this board records 25,000 samples/sec on one channel while sending the plot to the Macintosh's screen.

μ P's access to the slave modules' data resources, thereby preventing a local μ P and the bus master from modifying data simultaneously. If you neglect to ensure that a module can decode attention cycles, either the board won't be capable of locking its resources or the module may incorrectly identify the attention cycle as a start cycle and misuse the address released during a lock cycle.

Problems can also occur if you



Off-the-shelf chip-set interfaces for the Nubus, such as these developed by Texas Instruments, can dramatically reduce your interface design cycle, but may diminish your application's performance.

“cheat” on the sample and assert clock edges. The Nubus's 10-MHz clock provides a 75-nsec unasserted (high signal) and a 25-nsec asserted (low signal) duty cycle. This asymmetrical duty cycle prevents bus-skew problems by providing 25 nsec between the sample and driving edges and by allowing 75 nsec for propagation and setup. The bus signals typically change on the rising edge, and the bus master samples on the falling edge. However, if you “cheat” and use the same logic circuit to decode both the sample edge and the assert edge, an error may occur and result in misread data.

You must also make sure that the bus owner always drives the acknowledge (ACK) signal high at the end of each data transfer. Because bus arbitration occurs in parallel with the Nubus's data transactions, as soon as one bus master completes its transaction, a new master immediately assumes control of the bus. This arbitration technique lets the Nubus use the bus bandwidth efficiently. If poor design techniques

TECHNOLOGY UPDATE

Nubus interface options

prevent the bus master from driving the ACK signal high at the end of the data transfer, the termination resistor will eventually make the ACK signal go high.


If the backplane is sparsely populated, you may be able to depend on the natural tendency of the ACK line to go high on its own, thereby reducing the logic requirements for the bus master. However, the greater the number of cards plugged into the backplane, the greater the contention for bus ownership and the more critical timing becomes. If the ACK line doesn't go high quickly enough, the boards accessing data on the bus may wind up reading the data twice.

When the backplane is packed with many boards, you must also consider loading violations. The specification permits a maximum of 18 pF of capacitive loading per board for backplanes containing 16 boards. Violating these loading specifications can cause a serious design problem, because the 18-pF limit includes etches and connectors. Multiple onboard drivers also add capacitance. The best way to avoid overloading the bus is to minimize the trace lengths and exercise caution in selecting drivers and receivers.

Weak drivers create havoc

A less common, but equally treacherous design error is the use of weak drivers, such as low-power Schottky (LS) diodes. Although the spec defines a 24-mA dc output drive current, which is well within the capability of an LS device, the ac drive spec is 80 mA. The circuit may operate with a backplane that has few boards, but in a fully loaded system with 16 modules, the LS drivers may not be able to drive the required 15-nsec setup time. Using advanced Schottky (AS) devices will prevent this problem.

If you're designing a Nubus inter-



The Nubus is designed to expedite parallel processing among multiple μ Ps. Levco's Trans-Link is an example of an application that taps the bus's full potential.

face for the Macintosh II, which offers only six slots for expansion boards, you may be tempted to use the LS devices because the computer can't hold a fully loaded system. However, at least one company, Second Wave, sells an expansion chassis that adds eight additional slots to the computer's standard capacity. The Expanse II is a \$2295 chassis that includes Nubus interface cards, a cable assembly, a 130W power supply, a cooling fan, and the hardware to support three internal SCSI devices. Without the interface boards, the chassis costs \$1595. For \$2295, the company offers a 4-slot, Nubus expansion chassis for the Macintosh SE/30 computer.

If you assume that your board will be used only in a 6-slot Macintosh II system, you also subject the board to the problem of incomplete address decoding. Boards designed according to the Macintosh II's parameters can decode only six 24-bit, 16M-byte slot addresses. However, when developing the Macintosh II, Apple Corp went beyond the typical P-1196 Nubus spec by including a *super-slot space*. This slot provides an additional 256M bytes per slot. In addition, although the Macintosh

II currently uses a 24-bit addressing mode, the company may upgrade the computer to a full-fledged 32-bit machine in the future. If you limit your cards to the Macintosh II's present design, rather than designing to the full parameters of the Nubus spec, you'll shorten your boards' market life.

Also note that Apple isn't the only manufacturer selling a Nubus computer. Texas Instruments markets a \$49,900 Nubus-based LISP workstation called the Explorer II and a \$39,995 multiuser, Unix-based Nubus mainframe called the System 1500. These computers use the triple-height (11.024 \times 14.437-in²) expansion boards that were originally defined in the Nubus spec. TI also sells the \$14,995 microExplorer computer, which is actually a Macintosh II with a LISP coprocessor board plugged into it.

The final design *faux pas* involves data-integrity problems. Such errors will occur if you don't include logic circuitry that will drive the Start line high after an attention cycle. Data-integrity problems also arise when the circuit fails to drive the transfer-mode (TM) lines high during block transfers.

ZAX Presents The Best Way To Develop, Program, Edit, Erase, Compile, Assemble, Debug And Compute



Along with everything else shown here, we offer emulators for the following processors: 8086/88, 186/188, 80286, 80386, 8085, 8048, V20/30, V40/50, 6301, 64180, 6809, 68000, 68020, 68030. And yes, more are on the way.

If you're dissatisfied with the formidable task of trying to assemble a suitable microprocessor development system from different vendors, take heart. Now with a simple phone call, you can receive *complete support* for all your development equipment needs from one supplier—ZAX Corporation!

WHY DOES SINGLE-VENDOR SUPPORT MAKE SENSE?

When you turn your development needs over to ZAX, you're assured that all hardware and software tools were conceived, designed and tested to work together reliably and efficiently. Both with your existing system or as a completely independent development system.

That coordination results in a complete turnkey development system instead of a collection of unmatched components. (Surprising as it seems, this modular approach to design tools still costs less than dedicated systems, yet offers more flexibility!) Also, by providing a package instead of a puzzle, you end up conserv-

ing another important resource: Time. One phone call. One purchase order. One solid commitment. No headaches.

WHAT TYPE OF HARDWARE AND SOFTWARE TOOLS ARE WE TALKING ABOUT?

ZAX offers you a choice of two different powerful emulation systems with the ICD- and ERX-series emulators. Both can be interfaced to a variety of hosts (from PC to mainframe) and both offer support for a wide variety of processors. There's also our universal interface chassis, the 300i, that's capable of linking our emulators to virtually all host computers and operating systems. And speaking of computers, ZAX can provide you with a model of its own—the BOX-ER.

ZAX can also furnish an array of useful support hardware, such as a line of PLD/EPROM programmers and erasers. Our ZP-series high-speed programmers interface to your PC for a powerful combination. And the ZE-series line of EPROM erasers include everything from an indus-

trial-class, 200-chip model to the world's fastest eraser, the 5-second Quick-E II.

Chances are a broad choice of development software is paramount to your ability to work in a familiar environment. If so, ZAX is still your best source. We offer "C," Pascal, Ada, PL/M and Fortran compilers, assemblers/loaders, symbolic debuggers, source-level debuggers, and helpful menu-driven communications programs to get you up and running, fast.

Call ZAX today and get single-vendor support working for YOU! Our toll-free number is 1-800-421-0982 (800-233-9817 in CA). ZAX Corporation. 2572 White Road, Irvine, California, 92714.

In Europe, call United Kingdom: 0628 476 741, West Germany: 02162-3798-0, France: (03) 956-8142, Italy: (02) 688-2141.

ZAX
Zax Corporation

TECHNOLOGY UPDATE

Nubus interface options


The easiest way to interface a board you've modified for the Nubus is to use a prepackaged Nubus interface chip set, such as TI's ACT2440 controller IC and BCT2420 transceiver IC. These chips contain the embedded logic necessary to implement the Nubus protocol; they replace as many as 45 discrete logic devices. As a result, they give you as much as 66% more pc-board space, which you can use to add more functions and on-

board memory to your module. The ACT2440 sells for \$24, and the BCT2420 costs \$13.33 (1000). You need two BCT2420 ICs per interface.

These off-the-shelf interface chip sets ensure conformity with the P-1196 spec and can greatly shorten your design cycle. However, many board manufacturers allege that you can't take full advantage of the Nubus's performance when you use the TI chip set because it introduces


a wait state. TI could have minimized this delay by using bipolar instead of CMOS technology. The tight 2A Nubus power constraints, however, precluded such a choice.

If your high-speed application can't tolerate the 20-nsec propagation delay introduced by the TI chip set, you can create your own discrete interface by using 7½-nsec PALs. Another alternative is to make the Nubus interface part of a kernel in an ASIC chip that also



This flowchart illustrates the signal-driving responsibilities of a bus owner. Each block represents one Nubus clock period.

NETWORK NEWS SPECIAL REPORT.



4SR-7103R3(V2)

SPRAGUE SURFACE MOUNT NETWORKS SOLVE TIME AND SPACE PROBLEMS.

The new full line of Sprague surface mount resistor, capacitor and R-C networks enables you to meet all of your design and delivery SMD requirements. For example, Series 800C SORN® Small Outline Resistor Networks reduce board space up to 75% as well as assure lower placement costs, improved reliability, and top performance. Type 806C CAPSTRATE® Small Outline Capacitor Networks are the first featuring

Sprague Multilythics® technology for integrating passive components in monolithic ceramic circuit structures. All Sprague networks are manufactured under computerized SPC control. Packaged in industry standard, small-outline, gull-wing molded cases, these networks can be supplied in anti-static plastic tubes or on embossed conductive tape and reel. In addition, Sprague offers a comprehensive custom network capability at competitive prices. For our new Thick-Film Products Catalog RN-126A, write to Technical Literature Service, Sprague Electric Company, P.O. Box 9102, Mansfield, MA 02048-9102. For applications assistance, call our Thick-Film Products Hot Line in Nashua, NH at (603) 883-9774.



CIRCLE NO 112

TECHNOLOGY UPDATE

Nubus interface options


includes a portion of the module's logic.

The TI chip set not only introduces a wait state, but also lacks direct support for Nubus master block transfers. Therefore, you must use external logic to allow your module to read and write block data.

One benefit of block mode is that it doubles the data-transfer speed. In addition, the data bursts lower the bus bandwidth consumption, resulting in less bus arbitration. However, Apple didn't design a block mode for the Macintosh II, and the external logic needed for block data transfer requires the fastest and most expensive FIFO memories available.

Nubus boards ready for action

To bypass many of the headaches associated with designing your own interface, you can choose from a variety of Nubus-compatible boards. Mercury Computer Systems, for example, offers a processor card that integrates bus-master and block-mode capabilities in one board. This single-slot processor card, which was introduced at Siggraph '88 (Atlanta, GA), features 20M-flops and 10-MIPS performance. When coupled with a module that has similar data-transfer specs, the MC3200NU can



By implementing block-mode data transfers on a bus-master board, Mercury Computer Systems' MC-3200NU coprocessor board can reach 20M flops in a Macintosh II.

transfer data at a rate of 30M bps in block mode. This transfer rate lets you perform computation-intensive vector and scalar operations, such as those used in simulating, modeling, signal processing, image processing, and Postscript manipulating. The card's nonblock transfer rate can reach 10M bps. Also, the card can transfer data to and from the Macintosh II's memory at a rate of approximately 5M bps. With 2M bytes of memory, the

MC3200NU sells for \$10,000; the Fortran and C software development package costs \$8500.

Another high-performance coprocessor board for the Macintosh II is Yarc Systems' NuSuper module. Sporting a 25-MHz Am29000 RISC μ P and offering an optional Am29027 floating-point coprocessor, the NuSuper module features a peak 25 MIPS, more than 25,000 Dhrystones, and 3M Linpack performance. The \$4000 NuSuper

Avoid Nubus design errors

According to Gerry Laws, Chairman of the NuGroup (Tustin, CA, (714) 669-1201, FAX 714-669-9105), the most common design errors made by developers of Nubus interfaces include:

- Neglecting to make sure the board can decode attention cycles,
- Cheating on the sample or assertion edges,
- Failing to ensure that the bus owner drives the acknowledge signal high at the end of a data transfer, and
- Violating loading specs.

Other potential design errors include:

- Using weak drivers,
- Designing for a 6-slot board instead of a 16-slot board,
- Failing to drive TM 0/1 high during block transfers,
- Neglecting to decode the address completely, and
- Not driving the start line high after an attention cycle.



**THE BIGGEST SOURCE
OF LCDs ISN'T
ALWAYS THE BEST.**

Versatility is essential when you need fast delivery of liquid-crystal displays that meet your exact specifications.

That's why at Philips, we developed quick reflexes along with our LCD production strength. Today, we can respond to your need for virtually any LCD cells or complete modules more efficiently than anyone else in the world.

LCDs are the fastest growing display technology for automobiles, instrumentation, computers and communications. So we offer them in

a wide selection of standard and custom designs in sizes ranging from a few to over 600 square centimeters.



As the need for LCDs to display text and graphics evolves, our engineers respond with custom patterns, 7-segment digits, dot matrices, bar graphs, pointers, symbols, fixed text, positive or negative imaging, illumination modes and other sophisticated configurations. Just call or write us for a jump on delivery and your copy of the Philips LCD brochure.

Amperex®

OPTOELECTRONIC PRODUCTS GROUP

PHILIPS

CIRCLE NO 81



Amperex Electronic Company, A Division of North American Philips Corporation
George Washington Highway, Smithfield, RI 02917 (401) 232-0500
In Canada: Philips Electronics Ltd., 601 Milner Ave., Scarborough, Ontario M1B 1MB (416) 292-5161

TECHNOLOGY UPDATE

Nubus interface options

board operates in parallel with the host μ P and offers transparent background computations. A C compiler is now available for the board, and a Fortran compiler will probably surface during the second quarter of this year.


Wire-wrap your design

Creative Solutions also offers an alternative to designing your own interface for the Nubus. The vendor's Nubus Hurdler is an interrupt-driven Nubus slave interface on a Macintosh II card with an 894-pin wire-wrap area. Selling for \$279, the Hurdler includes a slot-declaration ROM, as required by the P-1196 spec. It also comes with three 16-bit counter/timers, a software driver, and application notes. For \$199, you can purchase an interface that lets you connect the Macintosh II to a Centronics printer, or, for \$349, you can buy an interface that lets you plug the Hurdler into an IBM PC bus.

If you're interested in performing high-speed parallel processing on your Macintosh II, consider Levco's TransLink board. It lets you tap the RISC (reduced-instruction-set computer) technology of an Inmos Transputer. The starter kit, which sells for \$2597, includes a TransLink board with 1M byte of RAM, an assembler, and C. You can purchase the Occam II Transputer programming language and a Transputer development system for \$1200.

Several Nubus boards, such as National Instruments' NB-MIO-16X 16-bit A/D converter, are suitable for data-acquisition applications. The 42- μ sec version costs \$1695; the 18- μ sec board sells for \$1895 and offers a guaranteed data rate of 55 samples/sec. For \$1195, you can buy a 12-bit NB-MIO-16 multifunction board.

National Instruments also pro-



Many Nubus-board manufacturers have developed software elements that ease the development process. National Instruments' NB LabDriver, for instance, provides a graphical interface that simplifies the task of building customized data-acquisition processes.

vides software support with its \$295 NB-LabDriver software and \$1995 LabView instrumentation software package, which comes with a free library of virtual instruments that you can use with the board. LabDriver also includes a language-interface library for Lightspeed Pascal and a HyperTalk interface with Hypercard stacks. LabView provides a graphical programming platform that has analysis and graphical-presentation tools, with which you can rapidly develop programs to acquire, control, process, and display signal information.

GW Instruments offers six Macintosh II data acquisition boards, including the MacAdios II. This card simultaneously records one channel at 25,000 samples/sec and sends the plot to the Macintosh's monitor screen. Its 5- μ sec A/D converter has a throughput specification of 142,000 samples/sec. A 12-bit A/D converter, two 12-bit analog output channels, eight digital I/O channels, three counter/

timer channels, and three A/D trigger modes come with the \$1490 board.


You can plug three daughter boards into the MacAdios II to expand its capabilities with antialiasing filters, a time stamper, and as many as 96 additional analog inputs. The daughter boards range in price from \$65 for the Protoboard to \$1425 for the 1-channel, 12-bit A/D converter with an 833-kHz maximum sampling rate. For \$190 you can purchase TurboDrivers, which you can access from seven languages, including C, Pascal, Fortran, and QuickBasic.

Strawberry Tree Computers offers a line of eight Macintosh data-acquisition boards, including the 12-bit, 8-line A/D plug-in board (ACSE-12-8) for the Macintosh SE and the 16-bit, 16-line board (ACM2-16-16) for the Macintosh II. The ACSE-12-8 sells for \$595, and the ACM2-16-16 costs \$1845. The boards offer self-calibration and self-diagnostic capabilities and fea-


Cursors To Cure Measurement Curses.

Beckman Industrial Introduces The Series 9000. Speed, Accuracy, Performance And Value.

Presenting a new family of quality oscilloscopes with professional features. Choose from six models with frequency ranges of 20, 40 and 60MHz.



Model 9106,
60MHz,
3 Channel,
Dual Sweep
(A & B).



Independent cursors and on-screen readouts make waveform measurements fast and accurate.

Five of six models feature two independently-adjustable time bases. Built-in intensity modulation allows you to select a small section of a main waveform for closer examination. This feature is ideal for measuring pulse rise times or checking sync pulse amplitudes in composite video signals.

Cursors And On-Screen Readouts.

Two sets of independent cursors are featured on Models 9202 and 9204. Simply position the cursors on the waveform and you instantly have accurate on-screen numeric readouts of amplitude, time, frequency, duty cycle and phase shift. A separate frequency counter is unnecessary. Interpolation is eliminated. You save time. Improve accuracy.

Solid Design.

The Series 9000 features a low-profile cabinet, logically grouped controls, camera-mount CRT bezel and graticule illumination for waveform photography. Most models feature a three year warranty.

The Series 9000 Oscilloscope. Only from Beckman Industrial. Finally, the affordable cure for measurement curses.



Model 9204, 40MHz,
On-Screen CRT Readout.



Model 9104, 40MHz,
2 Channel, Dual Sweep (A & B).



Model 9022, 20MHz,
2 Channel.

FEATURES	9106	9104	9204	9202	9102	9022
Max Frequency	60MHz	40MHz	40MHz	20MHz	20MHz	20MHz
Input Channels	3	2	2	2	2	2
Dual Sweep (A & B)	•	•	•	•	•	
CRT Readout			•	•		
Cursor Readout			•	•		
Switchable X1/REF/X10 Probes	2	2	2	2	2	2
Warranty	3 year	3 year	3 year	3 year	3 year	1 year
Price	\$1,290	\$950	\$1,095	\$865	\$700	\$550

Beckman Industrial™

Beckman Industrial Corporation
Instrumentation Products Division
A Subsidiary of Emerson Electric Company
3883 Ruffin Road, San Diego, CA 92123-1898
(619) 495-3200 • FAX (619) 268-0172 • TLX 249031

TECHNOLOGY UPDATE

Nubus interface options

ture a data speed of 2500 to 20,000 samples/sec. The Analog Connection WorkBench application software, which costs \$495, provides an object-oriented graphical interface that lets you easily develop programs for your data-acquisition and -control applications.

If you're designing for the Macintosh II and you want to be able to plug IEEE-488 data into a Macintosh-based application such as a spreadsheet, you can use IOtech's MacII488 card and MacDriver488 driver software for Basic, Pascal, C, and other languages. Selling for \$595, the MacII488 comes with a desk-accessory program called MacDA488, which lets users plug IEEE-488 data directly into your spreadsheet. The board transfers data at speeds as fast as 600k bytes/sec.

Whether you'll use these Nubus-compatible expansion boards or design your own Nubus interface depends largely on your application and your design goals. If, for example, your work involves mainly data-acquisition applications, buying an expansion board may be the simplest solution. However, if your applications are more varied and complex, you may not be able to find a ready-to-use Nubus board that meets your needs. If the demand for Nubus computers should increase dramatically in the near future, you may have even more design and product options to choose from, which will greatly simplify your interfacing task. At present, though, it's too early to tell whether that demand will increase significantly.

EDN

References

1. *Nubus—A Simple 32-bit Backplane Bus*, P-1196 Specification, Draft 2.0, December 15, 1986.
2. Harvey, Audrey, "Simple circuitry connects plug-in cards to Nubus," *Electronic Design*, February 18, 1988, pg 97.
3. Marshall, Trevor and Jim Potter, "How the Macintosh II Nubus Works," *Byte*, Second 1988 Mac Special Edition, December 1988, pg Mac 39.


Article Interest Quotient
(Circle One)
High 515 Medium 516 Low 517

NORTHWEST

THERE'S AN ART TO ESTABLISHING BUSINESS ROOTS IN TOKYO.

To establish a strong rapport with your Tokyo contacts takes time, patience, insight and more time. A country that considers a 300 year-old bonsai tree an art form takes a little time to understand.

EXCHANGING MEISHI (business cards) is an important formality in establishing a relationship. You go first, with a bow or handshake, and then, your card, presented Japanese side up to assist with



pronunciation and cases where English capabilities are limited. Study the card you receive, repeating the surname, the first name on the card, to be sure you have the right pronunciation. Treat cards with the respect you would bestow upon their owners.

WHERE TO GET YOUR BASIC BURGERS

There's a Hard Rock Cafe in Tokyo if you have the wild craving for fries, and the



quality of the hamburgers is superb.

DO IT YOUR WAY

The nightclub can be more important than a meeting, so you'll probably be invited to one. The hottest thing is "Kara-oke." Music and images play on a video system and you sing along into a microphone. Do not decline an invitation to sing or you'll be rejecting your host. Most songs are Japanese, but don't panic—"My Way" is always available.

LOOK TO US  NORTHWEST AIRLINES

TECHNOLOGY UPDATE

For more information . . .

For more information on the Nubus products discussed in this article, contact the following manufacturers directly, circle the appropriate numbers on the Information Retrieval Service card, or use EDN's Express Request service.

Apple Computer Inc
20525 Mariani Ave
Cupertino, CA 95014
(408) 996-1010
Circle No 625

Creative Solutions Inc
4701 Randolph Rd, Suite 12
Rockville, MD 20852
(301) 984-0262
Circle No 626

GW Instruments
35 Medford St
Somerville, MA 02143
(617) 625-4096
FAX 617-625-1322
Circle No 627

IOtech
25971 Cannon Rd
Cleveland, OH 44146
(216) 439-4091
FAX 216-439-4093
Circle No 628

Levco
6181 Cornerstone Court East
Suite 101
San Diego, CA 92121
(619) 457-2011
FAX 619-457-2325
Circle No 629

Mercury Computer System
600 Suffolk St
Lowell, MA 01854
(617) 458-3100
FAX 617-458-9580
Circle No 630

National Instruments
12109 Technology Blvd
Austin, TX 78727
(512) 250-9119
FAX 512-250-0382
Circle No 631

Second Wave, Inc
9430 Research Blvd
Echelon II, Suite 260
Austin, TX 78759-6541
(512) 343-9661
FAX 512-343-0923
Circle No 632

Strawberry Tree Computers Inc
160 South Wolfe Rd
Sunnyvale, CA 94086
(408) 736-3083
TWX 650-317-2834
Circle No 633


Texas Instruments Inc
Data Systems Group
Box 181153 DSG-179
Austin, TX 78718
(800) 527-3500
Circle No 634

Yarc Systems
5655 Linero Canyon Rd, Suite 721
Westlake Village, CA 91362
(818) 889-4388
FAX 818-889-2658
Circle No 635

So before you go, dig out some of your old records and practice up.


NORTHWEST NOTES. In addition to nearly 60 flights a week to Tokyo from over 200 U.S. cities, a spacious Executive Class, a First Class with all the luxury and comfort you deserve—we give you something no other U.S. airline can offer—the knowledge, insight and information that come after 40 years of helping people do business in Asia.

NORTHWEST ASIA SERIES



U.S. RESERVATIONS 1-800-225-2525, INTERNATIONAL RESERVATIONS 1-800-447-4747
© 1989 Northwest Airlines, Inc.

WHEN THERE'S NO ROOM FOR ERROR:



INTRODUCING TEK'S 20 GHZ, MULTICHANNEL COMPREHENSIVE MEASUREMENT SYSTEM.

Imagine characterizing GaAs, ECL, or high-speed TTL circuits with 1 picosecond repeatability and .01 picosecond sample interval.

Or acquiring not one or two, but up to 68 channels of waveform data simultaneously. All under manual or program control.

Imagine reducing propagation delay measurements to the push of a button. Or performing single-ended TDR and—for the first time—true differ-

ential TDR, with unprecedented accuracy.

Nothing else lets you work at the leading edge with so much confidence.

The new Tektronix 11800 Series makes previously difficult measurements routine. Even if you use it infrequently, you'll find its operation straightforward and unforgettable.

Measurement readouts on the 11800 Series are continuous—not just misleading “snapshots.” Mean and standard deviation statistics on each measurement give you a true picture of measurement integrity.

With its maximum 136 acquisition channels, complete programmability, extensive on-board waveform processing and unparalleled accuracy, the 11800 Series is the clear choice for designers and engineers working at the leading edge of technology.

When there's no room for error, count on Tek.

For more information on these and other Tek scopes, contact your local Tek sales representative, or call 1-800-835-9433, X170.

Tektronix®
COMMITTED TO EXCELLENCE



The VME Volksclosure. \$995. Ready to Run.

Finally. The economies of mass production catch up with VME and Multibus II enclosures.

Introducing the Volksclosure, Electronic Solutions' economy model enclosure with turbo performance. All you do is add cards and peripherals for a complete, attractive desktop computer.

With the Volksclosure (also known as our Model One) everything comes standard: six VME or Multibus II slots, space for three half-height 5 1/4" disk drives, and a high-performance six-layer backplane all in a highly tooled enclosure with our handsome front panel that hides those ugly connectors and cables.



You do get a choice between two multiple-output power supplies: 190 Watts with 19A at +5V or 270 Watts with 30A at +5V. You can also choose a J2 backplane for VME extended addressing or iLBX II for a Multibus II system.

Most important, while the Volksclosure costs less, you

don't get less. It fully reflects Electronic Solutions' commitment to quality and performance. For example, it meets UL and CSA safety standards and FCC Class A EMI/RFI specs to the letter.



The New Volksclosure. How to get a lot more mileage from your packaging budget. Call right now for complete details.

We'll FAX you the facts



Want the latest data in a hurry? Nothing is faster than Electronic Solutions' new "FAX the FACTS" program. If you have a FAX machine, just call our "800" number, give us your FAX number and type of FAX machine, and the information you need from us. We'll FAX it to you immediately.



6790 Flanders Drive, San Diego, CA 92121 • (619) 452-9333 Telex II(TWX): 910-335-1169

Call Toll Free: (800)854-7086 In Calif: (800)772-7086


VXI Bus enhancement accommodates physical instruments and multiple mainframes

The MXIbus (pronounced MIX-ee-bus) is an enhancement of the VXI Bus, which is well known among system developers for its high-performance, instrument-on-a-card architecture. MXIbus lets you daisy-chain and multidrop mainframes full of card-bound instruments, and even lets you add full-size physical instruments and PCs to your VXI Bus system.

MXIbus—an acronym for Multisystem eXtension Interface bus—provides a 32-bit, multimaster, frame-to-frame interface that

lets a single VXI Bus resource manager configure your entire multi-frame system. It provides word-serial drivers and utilities that let the resource manager identify all the devices in the system, manage the system's self tests, configure the A24 and A32 address maps, establish the initial system hierarchy for multimaster arbitration, and initialize normal system operation. It also defines a method for extending TTL triggers, VME interrupts, CLK10, and SYSFAIL across multiple frames.


Incorporating a backplane-bus-on-a-cable design, the MXIbus assigns VXI Bus logical addresses to the physical devices connected to the bus. Its multidrop parallel bus architecture provides a way to couple a VXI Bus tightly to external industry-standard personal computers, such as the IBM PC/AT, PS/2, Macintosh, and EISA bus machines, and to instruments that will never physically fit on a VXI module. With the MXIbus and a PC, a VXI Bus system developer can use industry-standard software to speed



Providing an operational link among multiple VXI Bus mainframes, physical instruments, and the IBM PC/AT bus, National Instruments' MXIbus lets you control as many as 256 devices in a multidrop, parallel-bus architecture.

Data Acquisition Beyond 10 MIPS

Data Acquisition Processor™



Onboard intelligence for IBM PC/XT/AT/386

The DAP 2400™ is a complete data acquisition and control system on a single IBM PC card. The DAP 2400 features 2 processors: a 16 MHz 80C186 for control processing and a 20 MHz DSP56001 for digital signal processing.

- Sustained digital signal processing of 10 MIPS
- FFT and FIR filtering without programming
- Acquires analog and digital inputs to 235,000 samples per second
- Buffers and processes input data as required
- Updates analog or digital outputs to 250,000 values per second
- Performs 1,024 point complex FFT in under 10 milliseconds
- Executes FIR filters in less than 200 nanoseconds per tap
- More than 100 commands without programming
- Commands include: Average, Scale, Peak Detection, Range Detection, Logic, Integration, Differentiation, Thermocouple Linearization, Closed Loop Control (PID, PWM), Event Detection, Auto-Range (to 102 dB)
- Custom commands may be written in C
- Full documentation \$30
- DAP 2400 from \$2395
- Other DAP™ models from \$995

MICROSTAR
LABORATORIES™

(206) 881-4286
2863 152 Ave. N.E.
Redmond, WA 98052
Fax (206) 881-5494

PRODUCT UPDATE

development tasks.

By mapping together portions of each device's address space and interlocking the internal hardware bus cycles of the devices linked to the bus, MXIbus accommodates 8-, 16-, and 32-bit data transfers, block-mode transfer for sustained data rates approaching 20M bytes/sec, and inseparable read-modify-write operations. The 62-pin MXIbus connector encompasses 49 active signals (including 32 multiplexed address and data lines with parity), address modifiers for multiple address spaces, single-level multimaster prioritized bus arbitration, interrupt capability, bus-error handling of timeouts and deadlock conditions, and handshake lines for asynchronous operation.

Because MXIbus doesn't specify what you can attach to it, it is more of a general-purpose bus than the instrument-specific GPIB. Thus, you can tap the data flow from high-speed input devices such as optical scanners without facing the bottleneck posed by protocol-laden links.

Each MXIbus interface has address-window circuitry that monitors both the internal local address lines and the MXIbus lines. This circuitry detects the occurrence of an internal bus cycle that maps out to the MXIbus; it also detects when a MXIbus cycle's address is mapping into the internal system. The interface interlocks the local bus cycle to the MXIbus and initiates a MXIbus cycle to the specified address. Optional address-page registers permit the address windows to occupy only a small portion of the local address space. You can move the address windows to access the full MXIbus 32-bit address space by changing the page register values.

The MXIbus does not, however, accommodate system architectures in which nodes are connected in a ring. Neither does it extend the VXI Bus' Analog Summing Bus, the Local Bus, CLK100, SYNC100, ECL triggers, or Star triggers.

And, although National Instruments has distributed a proposed specification for its MXIbus among the members of the VXI Bus consortium, no formal recognition has yet occurred.

To support the proposed MXIbus standard, the company has introduced the MXI-VXI and AT-MXI interfaces. The \$1995 MXI-VXI board is a C-size VXI module with slot 0 capability. You can connect as many as 32 VXI mainframes to operate as a single VXI system with 512 slots and a common address map. A 2-meter MXIbus cable costs \$300.

The \$995 AT-MXI board links an IBM PC/AT to one or more VXI Bus mainframes via the MXIbus. The PC/AT treats each VXI Bus chassis and its internal instrument cards as though they were plugged directly into the backplane of the PC/AT. The chassis communicate via VXI protocols. The AT-MXI interface handles the bus cycle translations, performs shared-memory data transfers, and includes VXI Bus Resource Manager software and VXI word-serial device drivers. Although embedded PCs-on-a-board are currently available for the VXI Bus, you may find the combination of an AT-MXI board and your own PC to be a more cost-effective and versatile solution.

—J D Mosley

National Instruments, 12109
Technology Blvd, Austin, TX
78727-6204. Phone (512) 250-9119.
FAX (512) 250-0382. TLX 756737.

Circle No 735

Z I L O G

Z8 CMOS

Designing with 40-pin Z8 parts just got a whole lot easier.

Introducing the Z86E21,[™] Zilog's CMOS one-time programmable microcontroller for the entire Z8 family. It's the form, fit and function part you need for all Z8 designs and short production runs.

Zilog is Superintegration.[™]

As the demand for higher levels of integration grows, the need for a new approach to ASICs arises. That new approach is Superintegration from Zilog. Through Superintegration, Zilog has developed a rapidly growing family of application specific standard products (ASSPs), also known as cell-based integrated circuits (CBICs[™]), which are working cores and cells that have been combined and enhanced for specific applications.

They are not custom parts. In fact, the ASSPs and CBICs we develop use the same architecture and the same codes you're already working with.

ASSPs and CBICs mean a lot less risk than ASICs. NRE charges are eliminated. Board real estate is significantly reduced. And on-silicon coupling enhances overall performance. Think what that can mean to your design efficiency, your costs and your time-to-market.

The compatibility.

The Z8 OTP plugs right into your final production board. It fits with all 40-pin parts, whether they're NMOS or CMOS. And you can get the package you need. An 8K OTP ROM in a 40-pin DIP or 44-pin PLCC package.

The functions.

Use the Z8 OTP however it best suits your situation. It lets you write, debug or verify code. It gives you perfect fit, form and function. And it lets you avoid having to resort to a design proto-pack, with its required external EPROM, for short-run production applications.

The performance.

You get everything you'd expect from a Z8 OTP. 256 bytes of RAM, for one thing. An 8K OTP PROM, for another. Then there's the full duplex UART and the 32 I/O lines. And the ability to address 112K bytes of external memory. Plus all the overall performance advantages of CMOS and Superintegration.[™]



The reliability.

The Z8 OTP comes to you with Zilog's proven quality and reliability built in. Off the shelf. At a highly competitive price. Find out more about the Z8 OTP, or any of Zilog's growing family of Superintegration products. Contact your local Zilog sales office or your authorized distributor today. Zilog, Inc., 210 Hacienda Ave., Campbell, CA 95008, (408) 370-8000.

Right product. Right price. Right away. **Zilog**

ZILOG SALES OFFICES: CA (408) 370-8120, (714) 838-7800, (818) 707-2160, CO (303) 494-2905, FL (813) 585-2533, GA (404)923-8500, IL (312) 517-8080, MA (617) 273-4222, MN (612) 831-7641, NJ (201) 288-3737, OH (216) 447-1480, PA (215) 653-0230, TX (214) 987-9987, CANADA Toronto (416) 673-0634, ENGLAND Maidenhead (44) (628) 39200, W. GERMANY Munich (49) (89) 612-6046, JAPAN Tokyo (81) (3) 587-0528, HONG KONG Kowloon (852) (3) 723-8979, TAIWAN (886) (2) 741-3125, SINGAPORE 65-235 7155, DISTRIBUTORS: U.S. Anthem Electric, Bell Indus., Hall-Mark Elec., JAN Devices, Inc., Lionex Corp., Schweber Elec., Western Microtech. CANADA Future Elec., SEMAD, LATIN AMERICA Argentina—Tel. (1) 46-2211, Brazil—Digibyte (011) 241-3611, Mexico—Semiconductores Profesionales (5) 536-1312.

Leads could lift due to a steep bulge on the board.



Highly localized bulge in this component.

A large, flat bulge from three well defined heat sources.

Thermally induced failures?

See them easily with Holographic NDT

A powerful solution

In seconds anyone can produce an image of minute deformations and view them as they evolve. Newport's holographic systems provide the power of holographic interferometry, with push button ease.

Interpretation is easy

The crisp lines on the PC board form a topographic map of its deformations, with the elevation between successive contour lines being precisely 10 micro inches. Our system allows you to resolve tightly spaced contours even on variable contrast objects like this PC board, so you never miss a detail.

Failure identification

Failures are easily understood when you can watch the board or component deform during its power-up cycle. As the board heats up, closely spaced fringes indicate large board or component deformation, which can indicate too much heat, or perhaps excessive stress on the leads of a high reliability component.

Easy operation

Operation is simple and easy: the system is completely electronic, and it takes only 10 seconds from exposure to viewing.

Call us and we'll be happy to discuss the solution to your problem.

The HC-1034 Holographic system is a completely enclosed, self-contained, stand-alone unit. This and other systems are featured in our catalog. Call for your free copy today.



714/965-5406

Newport Corporation
18235 Mt. Baldy Circle
Fountain Valley, CA 92708
Europe: Newport GmbH, Ph. 06151-26116
U.K.: Newport Ltd., Ph. 05827-69995



Newport

32-bit Ethernet controller chip maintains layer-management statistics

Although a latecomer to the LAN-controller market, the 92C28 Ethernet controller chip promises to deliver unusually high system performance through its 32-bit interfacing capability. The \$35 (5000) device can operate as a local bus master or as a slave to a host μ P, and it maintains a full complement of network statistics as defined by the IEEE-802.3 layer-management draft specification. In addition, the company created the device using design rules that are compatible with its 1.5- μ m ASIC fabrication process and can therefore develop alternative versions of the controller for interested customers.

Internally, the 92C28 employs a 16-bit architecture, which is apparent from the device's 16-bit address and data ports. You can connect the


IC to a host μ P as a slave device, using either a memory-mapped or an I/O-mapped interface—the chip has control pins for both interface types. The I/O-mapped interface allows a low-cost, low-performance approach to LAN node design that uses the host CPU's memory for transmit and receive buffers. The memory-mapped interfacing scheme allows you to attach local memory to the LAN controller so that it can automatically manage its own buffers, thus achieving somewhat higher performance. The chip can also share its buffer memory with a μ P through a DMA request/acknowledge protocol.

Through multiplexing, you can adapt the 92C28's 16-bit data bus to a 32-bit system. You must add external latches and transceivers to

hold the incoming and outgoing 32-bit data words because the controller can only transfer 16 bits/clock cycle. However, the controller generates all necessary latch strobes and transceiver enables to ease this design approach.

This 32-bit interface not only improves the match between the LAN controller and a 32-bit μ P, but it also boosts system performance by raising the maximum data-transfer rate to 20M bytes/sec, a 50% increase over the rate obtainable with the chip's 16-bit mode. You may not need this additional bandwidth to service a 10M-bps Ethernet LAN, but the higher transfer rate can free the μ P's bus for other processing chores not related to network traffic.

The Ethernet controller's 32-bit



Although it has a 16-bit architecture internally, the 92C28 Ethernet controller can operate in both 16-bit and 32-bit systems.

DYNAMIC MEMORY TIMER

- Triggered by a Single MREQ Pulse
- Rising-edge Triggered
- TTL Interfaced
- 14 Pins DIP
- Generates All Timing Pulses for DRAM Memory Board
- Precise and Stable Timing

data delay devices, inc.

Clifton, New Jersey 07013
(201) 773-2299 • FAX (201) 773-9672

CIRCLE NO 7

“MATHCAD IS THE BEST THING TO HAPPEN TO THE ENGINEER SINCE THE POCKET PROTECTOR.”

— PC Magazine

For problems involving engineering calculations or scientific analysis, the answer is MathCAD®

MathCAD is the only PC-based software package specifically designed to give technical professionals the freedom to follow their own scientific intuition. You decide how to solve the problem – MathCAD does the “grunt work.”

- Ends tedious programming and debugging.
- Displays instant answers as you change variables.
- Generates quick plots to help you view results.

MathCAD includes such built-in features as:

- Matrix operations
- Simultaneous equation solver
- Real and complex numbers
- Dynamic error flagging
- Automatic unit conversions
- Greek character set
- Fast Fourier Transform and much more

To find out what MathCAD can do for you, call us today for a **free demo disk: 1-800-MathCAD** (in MA, 617-577-1017). Or write to MathSoft, Inc., One Kendall Square, Cambridge, Massachusetts 02139.

Requires IBM® PC or compatible, 512KB RAM, graphics card.

Math Soft
 $\Sigma + \sqrt{-} = \times \int \div \delta$
 Software Tools for Calculating Minds

CIRCLE NO 8

mode provides yet another advantage: It supports 256k bytes of buffer RAM compared with only 128k bytes for the 16-bit mode. You may need this additional storage for very active LAN devices such as file servers. For packet transmissions, the controller employs a chained, dual-buffer scheme, and for incoming packets, the chip employs a ring buffer. You program the addresses of the various buffer areas through six pointer registers in the controller.

The 92C28 maintains several network performance statistics in on-chip registers. The registered transmission statistics include the number of frames transmitted properly, the number of single- and multiple-collision frames, the number of octets transmitted properly, the number of deferred transmissions, and the number of multicast and broadcast frames transmitted properly. Registered receive statistics include the number of properly received frames and octets and the number of properly received multicast and broadcast frames. In addition, the chip records several other error statistics relating to the transmitting and receiving of packets.

Maintenance of network statistics at each LAN node can potentially help a network manager achieve maximum throughput and reliability in an Ethernet LAN, provided designers make the statistics accessible when designing node equipment. The 92C28's statistics registers implement the functions listed in the IEEE-802.3 layer-management draft specification, thus encouraging you to integrate layer-management functions in your Ethernet designs.—**Steven H Leibson**

NCR Corp, Microelectronics Div, 2001 Danfield Ct, Fort Collins, CO 80525. Phone (800) 334-5454. FAX 303-226-9556

Circle No 730

*Need interconnect samples
to complete a spec?*



Our "sudden samples" go out within 24 hours!

Our AM/PM sample service works fast! Sample requests received in the AM go out the same afternoon... requests received in the PM go out the next morning!

We know you're busy. You can't wait weeks for a sample of the socket or connector you need right now. That's why our AM/PM sample service ships your samples in **24 hours** instead of the usual **2 weeks**.

At Samtec everything you need—samples, catalogs, quotations, engineering data, shipment dates—are all handled with energy and personal interest in solving your problems. When it comes to **SUDDEN SERVICE**, Samtec really **is** a different breed of cat!

New Interconnect Guide plus Enlarged 100-page Catalog. Guide is valuable reference for latest interconnect applications. New catalog has even more Samtec interconnects and specifications for easy ordering. Get yours today!



CIRCLE NO 139


©Samtec, Inc. 1989
samtec

EUROPEAN HEADQUARTERS: SAMTEC, Ltd., 35 Deerdykes View, Westfield, Cumbernauld, Scotland G68 9HN
Phone: 02367 39292 FAX: 2367 27113 TLX: 776158

SUDDEN SERVICE


WORLDWIDE HEADQUARTERS: SAMTEC, INC., P.O. Box 1147, 810 Progress Blvd., New Albany, IN 47150 USA Phone: (812) 944-6733
TWX: 810-540-4095 TLX: 333-918 FAX: 812-948-5047

*When it comes to
SUDDEN SERVICE
Samtec really is
a different breed
of cat!*




Pin grid array sockets.

DIP sockets, capacitor sockets, adaptor plugs.



.025" sq. terminal strips, single/double row, shrouded.




Development tool simplifies the creation of user interfaces for real-time systems

The Rave (Real-time Audio/Video Environment) software-development tool simplifies the design of human interfaces for real-time applications such as those for process-control systems. The development tool is an extension of the OS-9 real-time operating system and allows you to combine audio, video, computer-generated graphics, and customizable menus in creating a user interface.

You can use Rave to create interfaces for real-time systems that nontechnical operators intuitively understand. Furthermore, you can develop a custom audio/video user interface without writing a single line of code.

Three software packages make up the Rave development tool: the Graphics File Manager, the Graphics Support Library, and the Presentation Editor. The Graphics File Manager provides the audio, video, and input drivers needed to support the run-time user interface. For example, the input drivers provide support for a standard keyboard, a keyboard customized for a specific application, and pointing devices such as a mouse, digitizing pad, or touch screen. The video driver supports a monitor and provides drawing and block copy primitives.

The Graphics Support Library builds on the Graphics File Manager and includes the menus, controls, and indicators employed in a user interface. For example, controls are objects on the display that mimic the behavior of switches or sliders. Likewise, indicators mimic the behavior of devices such as meters, LEDs, and strip-chart recorders. The Graphics Support Library includes a number of standard controls and indicators, and



A sample screen of a typical user interface demonstrates the intuitive visual effect that Rave-based applications project.

you can also build custom controls and indicators.

You use the menu-driven Presentation Editor to actually develop a user interface. The keyboard and the mouse let you interact with the Presentation Editor, thereby creating the user interface based on the controls, indicators, and menus supported by the Graphics Support Library. You can input audio to the Presentation Editor directly from a microphone or from a disk. You can use a camera to capture the video or build it from graphics primitives. A paintbrush facility allows you to modify computer-generated or real-world video images.

Currently, Rave supports a frame-grabber board, an audio I/O board, and a speech chip, but you can easily add support for any audio/visual product by developing drivers for the Graphics File Manager. You can also expect a number

of CPU-board manufacturers that currently support the OS-9 operating system to support the Rave extension as well.

The three partitions of Rave are separately priced: Graphics File Manager, \$300; Graphics Support Library, \$175; Presentation Editor, \$995. You may only need a single copy of the Presentation Editor to develop products, but you may also need to ship a copy of the run-time Graphics File Manager or the Graphics Support Library with each system you ship. All the units are scheduled for release in mid-May.

—Maury Wright

Microware Systems Corp, 1900 NW 114th St, Des Moines, IA 50322. Phone (515) 224-1929. TWX 910-520-2535. FAX 515-224-1352.

Circle No 731

This tiny vibration is about to give your customer the shakes.

Put a damper on vibration with 3M Scotchdamp™ Vibration Control Systems.

It's a fact of science. As materials become lighter, they are increasingly prone to the disruptive effects of vibration. Now there's a solution that makes life a lot easier for today's design engineers—Scotchdamp Vibration Control Systems.

Custom designed to your exact specifications, these systems combine energy dissipating polymers with other key materials to solve specific vibration problems. For example, stainless steel dampers, now being used on hard disk drive suspension assemblies, virtually eliminate vibration and thereby reduce data errors.

If you're designing electro-mechanical devices of any kind, Scotchdamp Vibration Control Systems

can help you eliminate troublesome vibrations. Team up with 3M, a world leader in vibration control materials, to increase your customers' satisfaction—and yours—through vibration-free product performance. Circle the reader service number or write: 3M Industrial Specialties Division, Building 220-7W-04, 3M Center, St. Paul, MN 55144-1000. Better yet, call (612) 733-7411 today.



3M


Software-modeling capability allows you to "emulate" your system designs

You can now simulate your system designs, using Mentor Graphic's QuickSim simulator in conjunction with SmartModel Windows, a behavioral software-modeling capability. SmartModel Windows can actually look inside the registers of the models of processors, peripherals, PLDs, and memories during simulation. This capability lets you build, simulate, emulate, and debug the system before you prototype your designs.

Emulation has always been a useful technique for evaluating your designs involving μ Ps. You could use an emulator to debug both the hardware and software of your system designs by single-stepping through the program and examining the data in registers internal to the μ P. When you finished the process, you'd just replace the emulator with the actual microprocessor. But you could only do this at the hardware level.

SmartModel Windows provides internal register visibility for some Motorola processors and peripherals, including the MC680X0 family, the MC68230, MC68440, MC68442, MC68452, MC68851, MC68881, and the MC68HC11. You can also use SmartModel Windows for PLDs from AMD/MMI, Altera, Lattice, and Texas Instruments. By July, the vendor is planning to provide SmartModel Windows for a range of Intel devices, and by the end of the year, for most devices in its SmartModel library that have internal registers.

SmartModel Windows is tightly coupled with the simulator's user interface, thereby letting you work with the SmartModel's internal registers exactly as with the external



You can single-step your hardware design through your program and examine the registers at each step. Here, SmartModel Windows models emulate a system controlled by an MC68020 μ P and containing an MC68230 parallel interfacetimer. They're shown with the Motorola chips' internal-register values that are available for examination.

nets of the design. If the simulator supports SmartModel Windows, you can single-step, set breakpoints on internal-register states, or set internal-register values. In addition to Mentor's QuickSim, the vendor is working to couple SmartModel Windows with HP's Electronic Design System.

You can get SmartModel Windows as an option to the vendor's 1-year subscription service for the SmartModel library of more than 4000 devices. Subscribers receive quarterly updates containing all new models and, if you order the SmartModel Windows option, you will receive the Windows capability for each new set of devices as they are released. The SmartModel's subscription service is \$7900 per

workstation, and the SmartModel Windows option costs an additional \$4000.—**Michael C Markowitz**

Logic Automation Inc, 19500 NW Gibbs Dr, Beaverton, OR 97075. Phone (503) 690-6900. FAX 503-690-6906.

Circle No 733

16-Bit CMOS Microcontrollers. More Functions and More Memory On-Chip. Now. From Mitsubishi.

32K bytes EPROM or ROM. 2K bytes RAM. Two UARTs, with on-board baud rate generator. 8-bit, 8-channel A-D converter. Eight multi-function 16-bit timers that operate in five modes (timer, event-counter, one-shot, pulse-period and pulse-width), and pulse-width modulation. 12-bit watchdog timer. Interrupt controller. 68 independently programmable I/O ports. All on-chip.

Plus, linear access for 16 mega-

bytes external memory. Powerful instruction set optimized for high-performance operation. High efficiency hardware multiply and divide instructions. And, configurable for 8- or 16-bit external operation. All in low power, 1.3 μm silicon-gate CMOS technology. All part of a broad 16-bit MCU product line.

IBM[®]-PC based development and software support tools. Plus, masked ROM, ROM-less and OTP ROM

versions and prototyping adapters.

All available now from Mitsubishi. Driven by your applications, we put more on-chip and give you more choices, so you can reduce system component count, save board space, lower overall design costs and get products to market fast. For more information call now. (408) 730-5900 Ext. 2106. 1050 E. Arques Avenue, Sunnyvale, CA 94086.

IBM is a registered trademark of International Business Machines Corporation.



Color LCD panel uses TFT technology to achieve high contrast and sharpness

Reproduced here, the color transparency cannot do justice to the brightness, contrast, sharpness, and vibrancy of the company's TFT (thin-film transistor), 6.3-in., 8-color LCD display. You really have to view the actual display to appreciate its visual impact.

Using amorphous silicon TFTs in an active-matrix arrangement, each pixel in the display is driven by its own transistor. Individual red, blue, and green color filters over each pixel make the 8-color operation possible. Deleting the color filters yields a high-resolution monochrome display having all the advantages of TFT technology. Both the color and monochrome displays typically employ a fluorescent backlight.

Although the interface circuitry for the TFT display is multiplexed, when examined at the individual pixel level the display actually is statically driven by the individual TFT drive circuits. This arrangement preserves the simplicity of designing in a multiplexed display and eliminates the resolution vs contrast tradeoff normally associated with other LCD technologies.

The thin-film transistors are FETs. The drain leads of the FETs are connected to form column-selecting terminals; the gate leads are connected to form row-selecting terminals. When the display selects a particular pair of row-column terminals, that individual FET turns on, activating the LCD pixel connected to that FET's source lead. Compared with previous LCD technologies, this configuration provides higher resolution, improved brightness and viewing angle, and significantly improved contrast and speed.

The extremely sharp image qual-



Active-matrix TFT technology enables this LCD panel to reproduce eight colors that have high contrast and $640 \times (200 \times 3)$ pixels of resolution.

ity of TFT technology results from the fact that when the display is passing light, the light passes straight through without any defocusing on the pixel edges. By contrast, other active displays such as CRTs and emissive flat panels appear less sharp because the emitted light travels in several directions simultaneously, resulting in an apparent defocusing of the image.

Although this LCD panel is quite expensive (\$700 in OEM quantities), it has some impressive specifications. The effective display area is 96×128 mm. The resolution is $640 \times (200 \times 3)$ pixels for color and 640×600 pixels for monochrome, totaling 384,000 pixels. The contrast ratio is very high at 40:1. The viewing angle of $\pm 45^\circ$ lets you see what's on the screen without having to look at it head on, and the dis-


play's 40-msec response time is suitable for mouse-driven applications. The LCD panel operates from 5 and 25V supplies, and power consumption is only 5W with backlight and 1.5W without backlight.

Though the display's present high cost precludes its use in most low-end applications, other applications such as medical instrumentation, avionics, and high-end portable computers would likely benefit from the use of a compact, low-power, full-color display. And, as production yields improve and costs go down, you'll likely find these displays among lower-cost consumer products.—*Dave Pryce*

Hitachi America Ltd, Electron Tube Division, 300 N Martingale Rd, Suite 600, Schaumburg, IL 60173. Phone (312) 517-1144.

Circle No 736

SIEMENS



Surface mount varistors... technology in a new dimension.

Introducing Siemens surface mount Metal Oxide Varistors... our newest generation of surface mount innovation.

Siemens pioneered surface mount technology, and we've never stopped directing its destiny. That's why our new varistors do more than provide the many advantages of surface mounting (such as reducing harmful effects of ESD) – they give you renowned Siemens quality and flexibility. For example, Siemens varistors are

symmetrical in shape – which means your production line moves faster and smoother because there's no need for orientation.

Siemens high quality surface mount varistors are available with voltage ratings from 4 to 300V AC (5.5 to 385V DC) and comply with IEC Standard 384. Each is a breakthrough of small proportions with big advantages for you.

Call 1-800-222-2203 x4546 for immediate design or delivery information. Or return the coupon for our new data sheets.



Siemens...your partner for the future in surface mount varistors.


Siemens Components, Inc., Box 1000, Iselin, NJ 08830
 Please send me your surface mount varistor data sheet.

Name _____
Firm _____
Address _____
City _____
State _____
Zip _____


CG/2000-403 WLM 555

EDN041389

**THE BEST
INDICATOR
LIGHT DATA
BOOK THE
WORLD HAS
EVER SEEN...
FREE.**



**CALL (201) 489-8989
OR FAX (201) 489-6911
FOR YOUR FREE COPY.**



FIRST RIGHT ANGLE SURFACE MOUNT L.E.D. OFFERS SPACE ECONOMY AND EASY VISIBILITY.

Industrial Devices, Inc. (IDI) 6200 Series Right-Angle LED for surface mount assembly. Subminiature series is 6mm high and withstands temperatures of near-IR or vapor phase reflow. Available in red, green and yellow high-brightness, low (2mA) current, 5V (built-in resistor) and 5V low current models. Contact Industrial Devices, Inc., 260 Railroad Avenue, Hackensack, New Jersey 07601; (201) 489-8989, FAX (201) 489-6911.



Industrial Devices, Inc., Hackensack, NJ 07601
Telephone: (201) 489-8989

CIRCLE NO 9

Prototyping board kits include a RISC-like μ P


The two EVQT960 μ P-board kits provide designers with a low-cost way to evaluate or prototype products based on the company's 32-bit, 20-MHz 80960KB RISC-like processor. The kits include working CPU boards, schematics, programmable logic equations, and a software-debug monitor. The CPU boards include an onboard prototyping area and a connector that you can use to add more circuits off board.

The 80960KB currently tops the company's embedded-controller product line. The μ P includes an integrated floating-point unit, instruction and operand caches, and an on-chip interrupt controller. The processor also supports a burst mode for fetching instructions and data, and the boards included in the prototyping kit employ interleaved memory to support the burst mode.

You can choose from kits with slightly different 80960KB-based boards. The EVQT960F20 kit costs \$1960 and includes 128k bytes of zero-wait-state static RAM and 128k bytes of flash EPROM installed on the CPU board. The board included in the \$960 EVQT960E20 kit hosts 128k bytes of 2-wait-state static RAM and sockets for 128k bytes of EPROM. The boards include a programmable wait-state generator that allows you to model different memory-subsystem architectures.

Other board features include an RS-232C port and eight DMA channels. You power the boards with any standard IBM or compatible personal-computer power supply. The prototyping area of the boards has complete access to the CPU core-system buses and signals.

The boards come with the public-domain Nindy debug monitor stored in EPROM. Nindy provides



The 20-MHz 80960KB-based CPU boards included in the EVQT960E/F evaluation and prototyping kits allow designers to quickly develop hardware and software based on the new RISC-like embedded controller.

features such as code execution at a specific address, five instruction traces, two hardware breakpoints, display/modify registers, display/modify memory, code disassembly, and code/data download via the RS-232C port.

You can communicate with Nindy from a host computer that has a terminal-emulation program and an XModem file-transfer facility. Intel also offers the ASM-960 assembly-language software package, the iC-960 C language software package, and the ICE-960 in-circuit emulator for use with the prototyping kits.

The kits include IBM PC-compatible 1.2M-byte floppy disks that contain a schematic data base of the CPU board, PLA equations, the CPU-board parts list, and source code for the Nindy debug monitor. You also receive an EVQT960 users' manual and power-supply cables in the kit. You can expect shipments of the kits by mid-year.


—**Maury Wright**

Intel Corp, Dept 9P01, 3065 Bowers Ave, Santa Clara, CA 95052. Phone (800) 548-4725. FAX 408-765-2633.

Circle No 732

A scope so good you have to see it.

© 1989 Hewlett-Packard Co. TMC01912/EDN



A 100 MHz Digitizing Oscilloscope for \$3,465. The HP 54501A.

- 100 MHz bandwidth
- Four channels
- 8-bit vertical resolution
- Instant hardcopy output
- Full HP-IB programmability
- Automatic measurements

It's no typo! \$3,465. Call for the FREE video and see the best price/performance, portable, digitizing oscilloscope on the

market. See the power of glitch, dropout and TV triggering, measurement limit test and dual timebase windowing. The HP 54501A outperforms analog oscilloscopes and delivers extra capabilities found only in expensive digitizing oscilloscopes. See the ease and versatility of the HP 54501A on videotape.

Call HP now:
1-800-752-0900.


Ask for extension 216D for your free video, or to order.



 **HEWLETT
PACKARD**

READERS' CHOICE

Of all the new products covered in EDN's **October 13, 1988**, issue, the ones reprinted here generated the most reader requests for additional information. If you missed them the first time, find out what makes them special: Just circle the appropriate numbers on the Information Retrieval Service card, use EDN's Express Request service, or refer to the indicated pages in our **October 13, 1988**, issue.



◀ DIGITAL AUDIO ADC

The CSZ5126 is a monolithic stereo A/D converter for use in digital audio applications. The chip features 16-bit resolution and has a 92-dB dynamic range (pg 296).

Crystal Semiconductor Corp.

Circle No 601

▲ FAX SOFTWARE

CAD-Fax is a communications package that consists of menu-driven software and a half-size fax modem card that plugs into IBM PCs, PS/2s, and compatibles (pg 311).

GammaLink.

Circle No 604



▲ HANDHELD DMMs


The models 83, 85, and 87 meters are environmentally sealed, handheld units with 3³/₄-digit (4000-count) liquid-crystal displays (pg 301).

John Fluke Mfg Co Inc.

Circle No 605

Philips Test and Measurement.

Circle No 606



▲ IMAGE SCANNER

The RS320 desktop scanner is capable of scanning sheets, cards, or books at resolutions ranging from 60 to 360 dpi, and can scan a letter-size document at 18 sec/page with 300-dpi resolution (pg 266).

Ricoh Corp.

Circle No 602


KEYPAD LEGENDS

This legend label system is available for the company's Series 89 keypads. The labels are available in sheet form with numbers, letters, symbols, and standard key inscriptions (pg 281).

Grayhill Inc.

Circle No 603

***The plot that took
20 years to unfold.***



How Versatec helped change your picture of the world.

If you've got a plotting problem, chances are the company that can solve it is the one with the longest history of doing just that. That's why we'd like you to reflect on the rather long history of Versatec. Because our past might just have an impact on your future.

1969. The revolution begins.

Woodstock, miniskirts and those amazing Mets. In technology, it was a year filled with excitement. A man on the moon. The jumbo jet and Concorde. The artificial heart.

But there was another event that almost went unnoticed. One that would change forever the way engineers worked. Versatec was formed. And a little while later, we introduced the first 11-inch electrostatic plotter.

While crude by current standards, our first plotter started a revolution in engineering productivity that's still going strong today, 20 years and 50,000 systems later.

In fact, today there are more Versatec electrostatic plotters in more places throughout the world than all other brands combined.

1973. The plot widens.

Watergate hearings.
Rabies vaccine.
Supermarket scanners.

Color copiers. And a new development in engineering that would change the world—computer aided design.

Automotive, architectural, aeronautical and electrical engineers were clamoring for vastly wider plots than anything ever seen before.



Versatec responded with a whole new line of wide carriage plotters. In widths from 20 to a whopping 72 inches. Plus the ability to print on paper or vellum in clear or matte finishes. A little later we'd add 200 ppi resolution, the first RS-232 and direct CRT interfaces, first I/O multiplexer, minicomputer graphics software, universal graphics software and a few dozen other innovations.

1976. Supplies meet demand.

While R2D2, C3PO and the space shuttle were cavorting in space, Versatec announced something a little more down-to-earth. Our very own supplies research group. Dedicated to making sure that our electrographic supplies are as advanced as our plotters, these folks are now responsible for over 50 patents covering a wide range of papers, films, toners and other supplies. And our warehouses in the U.S., Canada and Europe can ship our supplies at a moment's notice.

1982. The color purple (and green and blue and yellow).


While E.T. and disk cameras were getting lots of attention, we were giving serious attention to R&D. And especially to customers who needed more dimension in their plots.

The result was the world's first electrostatic color plotter. Then we carried that technology even further with second-generation systems in 24, 36, and 44 inch formats. Followed by high resolution thermal plotters in color. And another long list of firsts, including a random element processor, plot server, color plotting software, color toners and media.

1988. Drawing some fine lines.

We shouldn't have to tell you what happened in the world last year.

But we would like to remind you of one important event in the world of plotting. We introduced the first wide format laser plotter—the Model 8836. This remarkable machine





does everything but cook your lunch. It plots at a sizzling one inch per second with 400 ppi resolution, in D and E sizes. Then it cuts, rolls and tapes each plot and drops it into a bin. The architects went nuts. And the CAD guys danced with joy.

There's no time like the present.

As you can tell by now, we've been listening and responding to customers for 20 years. And lately we've been hearing a lot about size, performance and cost.

So we went to work on something entirely new. And the results are truly amazing. It's called the 8500 series. A new generation of plotters with half the size, more performance and far less cost than any other electrostatic plotters ever made. Plus the greatest range of connectivity solutions and software compatibility available anywhere. These new machines have reduced plotting time from over an hour to under two minutes.

How to learn from history.

The important lesson from our long history is simple. Whenever you need a solution to almost any plotting problem, you can count on Versatec for the answer.

No other company has the experience,

range of products, technical resources and service and support. And no other company is as dedicated to its customers.

It's been that way for 20 years. And we're making sure it stays that way for the next 20.


So find out what Versatec can do for you. Call us at our toll-free number now: (800) 538-6477; in California, (800) 341-6060. And discover a whole new world of plotting solutions.



VERSATEC
A XEROX COMPANY
Engineering Systems Division


We deliver performance.

Versatec Inc.
2710 Walsh Avenue, Santa Clara, CA 95051
Xerox is a trademark of Xerox Corporation.
Map was produced on a Versatec electrostatic color plotter by TenTime, Denver, CO.
© 1989 Versatec Inc.



What's

No matter what frequencies you work, you want everything in your connectors that engineering can deliver.



manufacturing you need for top performance, and top productivity. That kind of engineering care is why our "old

up—consistently exhibit Mil-equivalent electrical characteristics. And you can enhance performance even further with a choice of 50 ohm or 75 ohm versions.

From AMP, that's a great deal.

standards"—from dual-crimp BNCs on

Our product offerings cover the spectrum, pushing performance on out

Our entire line delivers the advanced design and controlled, precision





your sine?

to 26 GHz. And they do it time after time, with unbeatable consistency. All the while saving *you* time—on the line or in the field—with proven crimp/seal technology.



And with AMP, you get the broadest selection available anywhere, in *every* range. From cable to bulkhead and panel, right down to the board—and now including custom and semi-custom high-speed coax and transmission cable assemblies. And our field and


production tooling is second to none in dependable, repeatable terminations.

Call 1-800-522-6752 for technical literature on AMP RF connectors, or for the name of your local AMP Distributor. AMP Incorporated, Harrisburg, PA 17105-3608.



AMP Interconnecting ideas

IEEE-488 test and



By working with instrument function panels, you can automatically generate programs for test and measurement instruments. (Photo courtesy National Instruments)

measurement software

Instrument function panels and automatic code generation are making it easy for the new or infrequent user to write IEEE-488 control programs.


Doug Conner, Regional Editor

Writing IEEE-488 control and data-acquisition programs can be slow work if you use low-level IEEE-488 commands. Most users must study the instrument operating manuals carefully and become fluent in the IEEE-488 low-level instructions for each instrument before writing even the simplest control program. But some software vendors have made life easier by providing software packages with instrument-specific function panels and automatic code generation. Many of these packages also include sophisticated analysis capabilities and graphical presentation of the results.

An instrument function panel is a menu screen that uses simple English commands to set or change instrument controls. These function panels let you program an instrument without learning new commands. If you're familiar enough with an instrument to operate it in its stand-alone mode using the front panel, you should be able to control its operation using an instrument function panel.


Program instruments in plain English

Some IEEE-488 software packages offer menu-driven control of instruments, but these menus contain IEEE-488 commands, not plain English commands. For instrument function panels, the IEEE-488 commands have been translated into language that would be obvious to an instrument user, not just an IEEE-488 programmer. For example, the function panels for a



Windowing is a common feature of many IEEE-488 software packages. PCI software from Gould lets you adjust instrument settings while you view outputs.

Instrument function panels let you control instruments as easily as you could by using the instrument's front panel.



Instrument function panels, such as this one from Hewlett-Packard's ITG, let you control instruments using IEEE-488 software as easily as you could by using the instrument's front panel. As you adjust the panel settings, the high-level source code, HP Basic in this case, is automatically generated to form your control program.

digital storage oscilloscope typically have menus for triggering, timebase, channel settings, and measurements. Within these menus you can set any function that can be set on the digital storage oscilloscope's front panel. A pop-up menu often backs each function and lets you know what your options are. Thus, you don't need to remember the exact wording used for each command.

Instrument function panels also act as checklists to help you make sure that the instrument is in the desired state. You can quickly scan the function panels to see that all settings are correct, just as you would scan the front panel on an oscilloscope to confirm proper instrument settings.

As you change instrument settings on the function panels, you can use an interactive mode for instrument control while you develop your program. As you change function-panel settings, the new settings are sent to the instrument over the IEEE-488 bus. At the same time, a program generator within the software package generates the high-level-language source code to perform these instrument control functions. This high-level-language source code, usually a version of Basic or C, is your IEEE-488 test program.


One attractive feature of function panels and automatic code generation is that you don't have to give up any flexibility in instrument control: You can still use low-level IEEE-488 commands. In most cases, you

won't need this flexibility; but it's there when you need to optimize code for speed, debug a hardware problem, or do any other fine tuning.

At least one software package, Interactive Test Generator (ITG) from Hewlett-Packard, tries to keep your automatically generated code fast. ITG uses what HP calls incremental-state programming to avoid wasting time on unnecessary instrument commands. ITG tracks the current instrument state and issues only the commands necessary to reach the next state. Incremental-state programming saves time not only by omitting the transmission of unnecessary commands but also by avoiding the time it takes the hardware to execute those commands.

Instrument function panels combined with automatic code generation can help you develop IEEE-488 control programs quickly and easily, especially if you're a novice or an infrequent user. There are, however, some catches.

You'll need a function-panel software driver for each instrument you want to program. These drivers contain instrument-specific menus and the information needed to translate the menu selections into high-level code. Every software product using function panels and automatic code generation offers a library of instrument drivers. None of these libraries is large enough to cover all the instruments you might be using, so the software vendors also provide the information you need to build your own instrument drivers.




Powerful analysis capabilities are included in many IEEE-488 software packages. By using the waveform processor of Asystant GPIB from Asyst, you can interactively view and analyze waveforms. The five windows at the top keep an ongoing record of the results.

Writing your own instrument drivers is a time-consuming task. You'll spend lots of time with the instrument's operating manual, but you'll only have to do it once. Some products, such as Wavetek's WaveTest and Gould's Personal Computer Instruments (PCI) software, include dedicated function-panel-generation software. These generators help, but building your own instrument drivers is still time consuming—otherwise software vendors would offer larger instrument libraries.


Beware of slow windows

Another potential drawback of function panels and other menu-driven methods of instrument control is that the programming speed might seem slow to the experienced user. Depending on the software and the computer used, changing function panels or windows to access different functions on an instrument can be slow. When it takes more than a few seconds to change function-panel displays, you might wish there were a way to bypass the menus.

Proponents of command-driven software claim that once you've spent some time with the software and hardware—less than you would spend to program your own instrument driver—you could be writing command-driven programs. And you'd be able to do it faster than you could by moving a mouse and waiting for windows to change. Command-driven software



Virtual instruments are created on the Apple Macintosh using LabView from National Instruments. The lower-right window shows how the blocks are connected to form the virtual instrument. The upper-left window contains the controls for adjusting the input and displays the graphic results. This setup lets you modify settings and immediately see the results.



This instrument function panel is one of several that you can use to control a digital storage oscilloscope. LabWindows from National Instruments automatically generates Basic or C code in the lower window to match your instrument-function-panel settings.

might speed up development in cases involving a large number of instruments or instruments with complex setups. But the difficulty of keeping track of all the instrument settings would probably lead you to use function panels or some manual method, if only to keep track of instrument states.

Whether instrument control is through function panels or is command driven, frequent or standard setups can often be named and saved. These setups can be recalled and used later, thus saving time and simplifying programming.

Tektronix's EZ-Test III uses another approach for controlling instruments. With EZ-Test III, you set up instrument front panels manually by using an instrument's stand-alone controls. When you have it set up correctly, EZ-Test III queries the instrument for all the settings and stores the actual setup. This method avoids instrument programming issues, at least as far as instrument control is concerned. In order to use EZ-Test III, it must be possible to query an instrument for its state. All of Tektronix's digitizing instruments and many, but not all, instruments from other vendors can be queried.

Instrument control is only one of the tasks you normally need from IEEE-488 software packages. Transferring data, analyzing it, and presenting the results is the complete job.

After you have the instruments set in the desired state, the next step in using IEEE-488 software is data transfer. Some software packages, such as Wavetest and PCI, provide a menu-driven solution with automatic code generation. Other software packages let you write the code in a high-level language to fill or dump arrays of data. Automatic code generation for this step is not critical—especially if you feel comfortable writing code—because this step entails little if any instrument-specific code.

Once you have transferred the data from the instrument into the computer, you typically have access to

in the array. Other functions, such as curve fitting and filtering, are more complex, and writing them would be a major programming exercise for most users.

Of course, you can take the data acquired by any IEEE-488 software package, write it to a file, and use another software package to perform analysis on the data. But having the analysis capability in the same package as your control and data-acquisition capabilities means one less package to learn and can also save you time.

If the software package operates as a virtual instrument, such as National Instruments' LabView, data can be taken, analyzed, and presented in one continuous process. A virtual instrument is an instrument created in software although it requires a real instrument to take the raw data. For example, the voltage-vs-time

data taken by a digital oscilloscope can be processed in software to give you the results of a virtual spectrum analyzer. If you're using separate software packages, you're usually forced to operate in a batch-process mode. In this mode, the IEEE-488 software acquires and stores the data, and then a separate analysis package processes it.

Integrated analysis is more efficient

Batch processing of data is often acceptable in standardized test applications. In these cases, you may just be recording the results of tests and, perhaps, some test statistics. However, in any type of testing or design where the action you perform next depends on the results of the previous tests, you'll often save time by using an IEEE-488 software package with integrated analysis functions.

For example, in a design situation, you may need to design a filter circuit to remove some uncharacterized noise from a waveform. Digitizing the waveform, examining the power spectrum of the noise, and developing a suitable filter in software before designing the filter circuit might help you design the right circuit without trial and error. Performing all these functions with one software package will save you time.

Don't forget about presentation of results

A well-integrated software package doesn't stop at analysis; it also provides for the flexible presentation of the results. You'll find lots of variation in the data-presentation capabilities of software packages. Some packages have virtually no such capabilities and assume that you'll be using another software package. Packages that do provide plotting vary in their sophistication. Some provide autoscaling, labels, and logarithmic plots with user variables such as color, data-point identifiers, and line type. Others are more limited.

IEEE-488 software packages also differ in their software-debugging capabilities; it's important to consider your needs for the type of software you're using. If you're programming primarily or exclusively in a high-level language, there are lots of opportunities for programming errors to creep in. In this case, it's a good idea to have plenty of debugging capabilities in the software.

If you're using menus and automatically generated code, you're less likely to need sophisticated debugging capabilities. But unless your programs are short and simple, it's helpful to have some way to set break-

	COMPUTERS SUPPORTED	PRICE	NOTES
	IBM PC/XT/AT, IBM PS/2	\$2095	
	IBM PC/XT/AT, IBM PS/2	\$695	
	IBM PC/XT/AT, DEC, HP, SUN, MASSCOMP	\$795-\$4995	
	IBM PC/XT/AT	\$5395-\$9595	\$9595 INCLUDES ALL OPTIONS
	HP 9000 SERIES 200/300, HP VECTRA, IBM PC/AT	\$1490	WORKSTATION IS REQUIRED FOR FUNCTION PANELS
	IBM PC/XT/AT, APPLE MAC	\$995	
	IBM PC/XT/AT	\$495	
	APPLE MACINTOSH	\$1995	
	IBM PC/XT/AT	\$495	REQUIRES LOTUS 1-2-3 OR LOTUS SYMPHONY
	IBM PC/XT/AT	\$1515	
	IBM PC/AT	\$3300	
	IBM PC/AT	\$1795	
	IBM PC/XT/AT	\$495	
	IBM PC/AT	\$3990	

As you adjust instrument-function-panel settings, the software automatically generates high-level source code to form your control program.

points, single step, or perform source-code tracing. With these capabilities, you can make sure that the program is doing what you want it to.

Some of the IEEE-488 software packages include features not mentioned in **Table 1**. For example, WaveTest lets you write programs using either function blocks in what Wavetek calls the icon window or flow charts in the flow-chart window. You can develop your program using either method, and the software will automatically generate your program using the other method. The software also keeps both programs up to date as you make changes and automatically generates the test program in Basic.

One benefit of this method is that your program is automatically documented with a flow chart that stays current as you make program changes. By using WaveTest's menus, you can completely develop a Basic test program without writing one line of Basic code. But if the need arises, you can write part or all of the test program directly in Basic.


WaveTest has no analysis capabilities other than the math functions available in Basic. If you need more advanced analytical capabilities or graphics output, you'll need to pass the data files to other software packages.

PCI also offers complete function panels or menus and automatic code generation in Basic for all phases of program development. You can perform instrument control, data acquisition, analysis, and graphical presentation. An optional analysis package integrates cleanly into the basic package. Although it's not the most complete analysis package available, it's adequate for many applications.

A software package with excellent analytical capabilities is Asyst 3.0 from Asyst Technologies. This software product offers integrated data acquisition, analysis, and graphical presentation. Asyst 3.0 is command driven rather than menu driven, and you can use it to build custom commands, menus, and application programs.

Asystant GPIB, another product from Asyst Technologies, is a menu-driven software package for IEEE-488 use. Although menu-driven, the menus are not function panels but menus of IEEE-488 commands. Asystant GPIB also has good analytical capabilities.

Another software package with excellent analytical capabilities is the DADiSP worksheet from DSP Development Corp. DADiSP is an integrated data-acquisition, analysis, and graphical-presentation software product. This command-driven software package offers



Instrument function panels, such as this one from Summation's TestWindows, let you save and recall commonly used setups.

an instrument-command library, but not in the form of function panels.


LabWindows from National Instruments offers instrument function panels and automatic code generation. Although you'll have to write some high-level-language code for your test programs, you shouldn't have to write any low-level IEEE-488 control commands. You can write code in either Microsoft QuickBasic or Microsoft C.

At \$495, LabWindows is the least expensive package offering instrument function panels, automatic code generation, some analytical capabilities, and a graphics library for screen output and plotting. Add the optional advanced analysis package at \$895, and you get powerful analysis capabilities. LabWindows also provides an excellent set of debugging tools, such as breakpoints, source-code level tracing, and variable displays that show the contents of all currently defined variables.

The LabView software package, another product from National Instruments, is based on the idea of building virtual instruments to process data. As you develop programs, you build your own library of virtual instruments that you can use for future applications. LabView uses its own programming language called "G." You can write an application program by graphically connecting virtual instruments that act on the data. This graphical representation of connected instruments also documents what the program does, at least at the top level.

Measure is yet another IEEE-488 software product from National Instruments. Measure is designed for

Our FIFOs do more than outrun the competition.



They're bidirectional.

Why are so many design engineers shifting to SGS-THOMSON FIFOs?

Our bidirectional model is one hot reason.

The MK45264/5, an SGS-THOMSON first, houses dual 64 x 5 FIFOs plus a 245-type transceiver function in one ultra-thin 300 MIL DIP.

15ns access speed.

Of course, it takes more than a single innovation to make SGS-THOMSON the FIFO performance leader.

Consider our MK4505, the first FIFO to support two independent, asynchronous free-running clock inputs. With blazing 15ns access speed and

40MHz serial I/O rate, not many FIFOs can outrun it. If any.

Our unique MK4505M/S Master/Slave concept gives you unbeatable speed, space savings, plus a full complement of status flags and easy depth/width expansion with no additional logic.

More horsepower to come.

SGS-THOMSON will soon introduce a whole new family of FIFOs in X9 architecture five densities: 512, 1K, 2K, 4K and 8K x 9. With 25ns access speed, each one has the capability to put your design on the fast track.

Outrun your own competition.

Race ahead with SGS-THOMSON. We back you

with a combination of options and features that leave the competition in the dust—surface mount packaging, CMOS RAM-based BiPORT™ architecture, military and industrial grades and more. Plus, you can get them off the shelf or from a nationwide network that includes 6 of the top ten distributors. Send for our free FIFO Application Notes and Memory Book. They'll show you how to get on the fast track quick. Contact: SGS-THOMSON Microelectronics, 1000 E. Bell Road, Phoenix, AZ 85022. 602/867-6259.

 **SGS-THOMSON**
MICROELECTRONICS

BiPORT is a trademark of SGS-THOMSON Microelectronics.
©1989 SGS-THOMSON Microelectronics, Inc.


TIMING PROBLEMS CAN KILL YOUR DESIGN ... STOP THESE CRIMES WITH OUR DESIGN DELAY DETECTIVES.

THE CRIME


Timing violations, signal transmission line losses, and clock skew in your PC board or ASIC can kill your design. They can rob your circuits' efficiency and cause product release delays, effectively stealing revenue from your company.

THE SOLUTION

Quad Design's team of products provide accurate data early in the design process. You can arrest timing problems before they cost you time and money.



TLC Wave Form Display



MOTIVE Timing Diagram

MOTIVE, the MODular Timing VERifier, analyzes circuit timing over the full range of manufacturing tolerances in minutes, without test vectors.

PDQ, the Preroute Delay Quantifier, provides interactive placement and instant timing analysis.

TLC, the Transmission Line Calculator, thoroughly analyzes physical data from your router and detects transmission delay and distortion.



"Where there's a crime there should be a MOTIVE"

QUAD DESIGN TECHNOLOGY, INC.
1385 Del Norte Rd., Camarillo, CA 93010
Tel: 805/988-8250 FAX: 805/988-8259

CIRCLE NO 10

Manufacturers of IEEE-488 software packages

For more information on IEEE-488 test and measurement software packages, such as those described in this article, contact the following manufacturers directly, circle the appropriate numbers on the Information Retrieval Service card, or use EDN's Express Request service.

Asyst Software Technologies Inc
100 Corporate Woods
Rochester, NY 14623
(716) 272-0070
FAX 716-272-0073
Circle No 650

**Philips Test and Measuring
Instruments**
Bldg HKF
5600 MD, Eindhoven
The Netherlands
Phone local office
Circle No 656

DSP Development Corp
One Kendall Square
Cambridge, MA 02139
(617) 577-1133
FAX 617-494-1394
Circle No 651

In the US:
John Fluke Mfg Co Inc
Box C9090, MS 250C
Everett, WA 98206
(800) 443-5853
TLX 185102
Circle No 657

Gould Inc, T&M
Recording Systems Div
3631 Perkins Ave
Cleveland, Ohio 44114
(216) 361-3315
FAX 216-881-4256
Circle No 652

Summation Inc
11335 NE 122nd Way
Kirkland, WA 98034
(206) 823-8688
FAX 206-823-7994
Circle No 658

Hewlett-Packard Co
Box 10301
Palo Alto, CA 94303
Phone local office
Circle No 653

Tektronix Inc
Box 1700
Beaverton, OR 97077
(503) 627-7111
TLX 151754
Circle No 659

Laboratory Technologies Corp
400 Research Dr
Wilmington, MA 01887
(508) 657-5400
FAX 508-658-9972
Circle No 654

Wavetek San Diego Inc
9045 Balboa Ave
San Diego, CA 92123
(619) 279-2200
TWX 910-335-2007
Circle No 660

National Instruments Corp
12109 Technology Blvd
Austin, TX 78727
(512) 250-9119
FAX 512-250-0382
Circle No 655

those who want to use Lotus 1-2-3 or Lotus Symphony for data analysis.

Test engineers don't often use IEEE-488 software to make sets of routine measurements when evaluating electronic designs and products. One reason is that many engineers think they would spend more time learning the software and writing the program than they would taking the data manually. Instrument function panels and automatic code generation are changing this perception. And if you need to perform additional analysis on data after acquiring it, you have even more reason to consider using IEEE-488 software to automate your work.

EDN

Article Interest Quotient (Circle One)
High 491 Medium 492 Low 493

Model
ATE 15-25MModel
ATE 6-25MModel
ATE 100-1MModel
ATE 6-100M

Kepeco unipolar linear programmable power supplies

Kepeco ATE Power Managers are unipolar linear programmable power supplies; offering full external control over both voltage and current, with automatic crossover. Panel-mounted meters monitor both channels. Front panel LEDs (and optically isolated flags accessible through the user port) show which channel is in charge. Local control is by panel-mounted 10-turn rheostats.

High Gain, Fast Programmable, Very Low Noise, Excellent Stability

INFLUENCE QUANTITY	OUTPUT EFFECTS VOLTAGE MODE		OUTPUT EFFECTS CURRENT MODE		OFFSETS ⁽⁴⁾	
	Typ.	Max.	Typ.	Max.	ΔE_{10}	ΔI_{10}
SOURCE VOLTAGE (min.-max.):	< 0.0005% E_0 max.	0.001% E_0 max.	< 0.002% I_0 max.	0.005% I_0 max.	< 1 μ V	< 1 nA
LOAD (no load-full load):	< 0.001% E_0 max.	0.002% E_0 max.	< 0.5 mA ⁽¹⁾	1 mA ⁽¹⁾	—	—
TIME (8-hour drift):	< 0.005% E_0 max.	0.01% E_0 max.	< 0.01% I_0 max.	0.02% I_0 max.	< 20 μ V	< 1 nA
TEMPERATURE, per °C:	< 0.005% E_0 max.	0.01% E_0 max.	< 0.01% I_0 max.	0.02% I_0 max.	< 20 μ V	< 2 nA
RIPPLE and NOISE ⁽²⁾ rms:	< 0.1 mV	0.3 mV	< 0.01% I_0 max.	0.03% I_0 max.	—	—
(Slow Mode) p-p: ⁽³⁾	< 1 mV	3 mV	< 0.1% I_0 max.	0.3% I_0 max.	—	—
RIPPLE and NOISE ⁽²⁾ rms:	< 1 mV	3 mV	< 0.01% I_0 max.	0.03% I_0 max.	—	—
(Fast Mode) p-p: ⁽³⁾	< 10 mV	30 mV	< 0.1% I_0 max.	0.3% I_0 max.	—	—
INPUT:	User Selectable 104, 115, 208, 250V a-c 47-65Hz single phase					

(1) For models with output current rating of 50A and higher, the load effect is 2 mA typical and 5 mA maximum. In slow mode, the leakage current through the output capacitor adds approximately 0-6 mA to the current mode load effect.

(2) One terminal must be grounded for this measurement, or connected so that common mode current does not flow through the load or, in current mode, through the current-sensing resistor.

(3) Peak-to-peak ripple is measured over a 20 Hz to 10 MHz bandwidth.

(4) Uncommitted amplifier offsets.

ATE MODELS • QUARTER • HALF • THREE-QUARTER • FULL RACK

ACCESSORY FOR RACK MOUNTING: RA 37

50 WATTS 0-55°C No Derating QUARTER RACK SIZE A	MODEL	D-C OUTPUT RANGE		OUTPUT IMPEDANCE VOLTAGE MODE			OUTPUT IMPEDANCE CURRENT MODE		
		VOLTS	AMPS	SERIES RESISTANCE	SERIES INDUCTANCE(3)		SHUNT(2) RESISTANCE	SHUNT CAPACITANCE (4)	
					SLOW	FAST		SLOW	FAST
	ATE 6-5M	0-6	0-5	24 $\mu\Omega$	0.5 μH	5 μH	12 k Ω	1,000 μF	1 μF
	ATE 15-3M	0-15	0-3	100 $\mu\Omega$	0.5 μH	5 μH	30 k Ω	450 μF	0.4 μF
	ATE 25-2M	0-25	0-2	250 $\mu\Omega$	1 μH	10 μH	50 k Ω	250 μF	0.25 μF
	ATE 36-1.5M	0-36	0-1.5	480 $\mu\Omega$	1 μH	10 μH	72 k Ω	200 μF	0.2 μF
	ATE 55-1M	0-55	0-1	1.1 m Ω	2 μH	20 μH	110 k Ω	150 μF	0.15 μF
	ATE 75-0.7M	0-75	0-0.7	2.15 m Ω	2 μH	20 μH	150 k Ω	110 μF	0.1 μF
	ATE 100-0.5M	0-100	0-0.5	4 m Ω	4 μH	40 μH	200 k Ω	50 μF	0.05 μF
	ATE 150-0.3M	0-150	0-0.3	10 m Ω	4 μH	40 μH	300 k Ω	55 μF	0.02 μF

Size: 57³²" H x 45³²" W x 17¹⁶" D (132.6mm H x 105.6mm W x 435.0mm D)⁽¹⁾ Net Weight: 14 lbs. (6.4 kg.)

100 WATTS 0-55°C No Derating QUARTER RACK SIZE B	MODEL	D-C OUTPUT RANGE		OUTPUT IMPEDANCE VOLTAGE MODE			OUTPUT IMPEDANCE CURRENT MODE		
		VOLTS	AMPS	SERIES RESISTANCE	SERIES INDUCTANCE(3)		SHUNT(2) RESISTANCE	SHUNT CAPACITANCE (4)	
					SLOW	FAST		SLOW	FAST
	ATE 6-10M	0-6	0-10	12 $\mu\Omega$	0.5 μH	5 μH	12 k Ω	1,800 μF	2 μF
	ATE 15-6M	0-15	0-6	50 $\mu\Omega$	0.5 μH	5 μH	30 k Ω	1000 μF	0.8 μF
	ATE 25-4M	0-25	0-4	125 $\mu\Omega$	1 μH	10 μH	50 k Ω	500 μF	0.5 μF
	ATE 36-3M	0-36	0-3	240 $\mu\Omega$	1 μH	10 μH	72 k Ω	350 μF	0.4 μF
	ATE 55-2M	0-55	0-2	0.55 m Ω	2 μH	20 μH	110 k Ω	200 μF	0.3 μF
	ATE 75-1.5M	0-75	0-1.5	1 m Ω	2 μH	20 μH	150 k Ω	110 μF	0.2 μF
	ATE 100-1M	0-100	0-1	2 m Ω	4 μH	40 μH	200 k Ω	80 μF	0.1 μF
	ATE 150-0.7M	0-150	0-0.7	4 m Ω	4 μH	40 μH	300 k Ω	55 μF	0.04 μF

Size: 57³²" H x 45³²" W x 17¹⁶" D (132.6mm H x 105.6mm W x 435.0mm D)⁽¹⁾ Net Weight: 17 lbs. (7.7 kg.)

ACCESSORY FOR RACK MOUNTING: RA 37

250 WATTS 0-55°C No Derating HALF RACK SIZE C	MODEL	D-C OUTPUT RANGE		OUTPUT IMPEDANCE VOLTAGE MODE			OUTPUT IMPEDANCE CURRENT MODE		
		VOLTS	AMPS	SERIES RESISTANCE	SERIES INDUCTANCE(3)		SHUNT(2) RESISTANCE	SHUNT CAPACITANCE (4)	
					SLOW	FAST		SLOW	FAST
	ATE 6-25M	0-6	0-25	4.8 $\mu\Omega$	0.5 μH	5 μH	12 k Ω	11,000 μF	5 μF
	ATE 15-15M	0-15	0-15	20 $\mu\Omega$	0.5 μH	5 μH	30 k Ω	5,800 μF	2 μF
	ATE 25-10M	0-25	0-10	50 $\mu\Omega$	1 μH	10 μH	50 k Ω	2,900 μF	1.25 μF
	ATE 36-8M	0-36	0-8	90 $\mu\Omega$	1 μH	10 μH	72 k Ω	2,400 μF	1 μF
	ATE 55-5M	0-55	0-5	0.22 m Ω	2 μH	20 μH	110 k Ω	1,400 μF	0.75 μF
	ATE 75-3M	0-75	0-3	0.5 m Ω	2 μH	20 μH	150 k Ω	850 μF	0.5 μF
	ATE 100-2.5M	0-100	0-2.5	0.8 m Ω	4 μH	40 μH	200 k Ω	375 μF	0.25 μF
	ATE 150-1.5M	0-150	0-1.5	2 m Ω	4 μH	40 μH	300 k Ω	275 μF	0.1 μF
	ATE 325-0.8M	0-325	0-0.8	8.1 m Ω	100 μH	1 mH	650 k Ω	180 μF	0.01 μF

Size: 57³²" H x 81³²" W x 17⁹/₆₄" D (132.6mm H x 211.9mm W x 435.4mm D)⁽¹⁾ Net Weight: 35 lbs. (15.9 kg.)

ACCESSORY FOR RACK MOUNTING: RA 37

500 WATTS 0-55°C No Derating THREE- QUARTER RACK SIZE D	MODEL	D-C OUTPUT RANGE		OUTPUT IMPEDANCE VOLTAGE MODE			OUTPUT IMPEDANCE CURRENT MODE		
		VOLTS	AMPS	SERIES RESISTANCE	SERIES INDUCTANCE(3)		SHUNT(2) RESISTANCE	SHUNT CAPACITANCE (4)	
					SLOW	FAST		SLOW	FAST
	ATE 6-50M	0-6	0-50	2.4 $\mu\Omega$	0.5 μH	5 μH	12 k Ω	12,000 μF	10 μF
	ATE 15-25M	0-15	0-25	12 $\mu\Omega$	0.5 μH	5 μH	30 k Ω	8,000 μF	4 μF
	ATE 25-20M	0-25	0-20	25 $\mu\Omega$	1 μH	10 μH	50 k Ω	5,800 μF	2.5 μF
	ATE 36-15M	0-36	0-15	48 $\mu\Omega$	1 μH	10 μH	72 k Ω	4,900 μF	2 μF
	ATE 55-10M	0-55	0-10	0.11 m Ω	2 μH	20 μH	110 k Ω	2,900 μF	1.5 μF
	ATE 75-8M	0-75	0-8	0.19 m Ω	2 μH	20 μH	150 k Ω	1,200 μF	1 μF
	ATE 100-5M	0-100	0-5	0.4 m Ω	4 μH	40 μH	200 k Ω	600 μF	0.5 μF
	ATE 150-3.5M	0-150	0-3.5	0.86 m Ω	4 μH	40 μH	300 k Ω	440 μF	0.2 μF

Size: 57³²" H x 121⁷/₃₂" W x 17⁹/₆₄" D (132.6mm H x 318.3mm W x 435.4mm D)⁽¹⁾ Net Weight: 43 lbs. (19.5 kg.)

The full rack model is supplied with brackets for direct mounting in a standard 19-inch rack.

1000 WATTS 0-55°C No Derating FULL RACK SIZE E	MODEL	D-C OUTPUT RANGE		OUTPUT IMPEDANCE VOLTAGE MODE			OUTPUT IMPEDANCE CURRENT MODE		
		VOLTS	AMPS	SERIES RESISTANCE	SERIES INDUCTANCE(3)		SHUNT(2) RESISTANCE	SHUNT CAPACITANCE (4)	
					SLOW	FAST		SLOW	FAST
	ATE 6-100M	0-6	0-100	1.2 $\mu\Omega$	0.5 μH	5 μH	12 k Ω	22,000 μF	15 μF
	ATE 15-50M	0-15	0-50	6 $\mu\Omega$	0.5 μH	5 μH	30 k Ω	12,000 μF	6 μF
	ATE 25-40M	0-25	0-40	12.5 $\mu\Omega$	1 μH	10 μH	50 k Ω	11,000 μF	4 μF
	ATE 36-30M	0-36	0-30	24 $\mu\Omega$	1 μH	10 μH	72 k Ω	9,500 μF	3 μF
	ATE 55-20M	0-55	0-20	55 $\mu\Omega$	2 μH	20 μH	110 k Ω	5,200 μF	2.25 μF
	ATE 75-15M	0-75	0-15	0.1 m Ω	2 μH	20 μH	150 k Ω	3,400 μF	1.5 μF
	ATE 100-10M	0-100	0-10	0.2 m Ω	4 μH	40 μH	200 k Ω	1,200 μF	0.75 μF
	ATE 150-7M	0-150	0-7	0.42 m Ω	4 μH	40 μH	300 k Ω	1,050 μF	0.3 μF

Size: 63¹/₃₂" H x 16¹/₂" W x 20¹/₆₄" D (177.0mm H x 419.1mm W x 508.4mm D)⁽¹⁾ Net Weight: 87 lbs. (39.5 kg.)

⁽¹⁾Add 21¹/₂" (63.5mm) for connector protrusion. ⁽²⁾Based on 0.5 mA load effect in FAST mode.
⁽³⁾For determining dynamic impedance in voltage mode. ⁽⁴⁾For determining dynamic impedance in current mode.

Analogic Announces...

The World's Highest Performance Arbitrary Waveform Synthesizer

700 MHz output bandwidth
IEEE-488 and RS-232 interfaces
512K data points of memory
Math Co-processor
Single shot and repetitive signals
800 Megapoints per second
Well-proven Math Equation Entry

ANALOGIC
The World Resource
for Precision Signal Technology

Analogic Corporation
Data Precision Products
8 Centennial Drive
Peabody, MA 01961
CIRCLE NO 80

At 800 Megapoints per second, the new Analogic/Data Precision Models 2040 and 2045 outperform the competition, delivering 4 times the data rate of the fastest polynomial waveform synthesizers.

With the Analogic Models 2040 and 2045, you can define and create any periodic or transient waveform.

You can use Analogic's well-proven ME² Math Equation Entry approach, entering any equations in the form $Y = f(t)$ from the keyboard. Or, you can download waveforms created on computers, graphic tablets, or oscilloscopes.

And, you can capture real-world transients with the Analogic Model 6100 Universal Waveform Analyzer, transfer their waveforms to the 2040/2045, and modify as desired.

The Model 2040 offers two outputs, each 1 V p-p, in phase opposition to provide both single-ended and differential outputs at a bandwidth of greater than 700 MHz.

The Model 2045 provides one low level output (1 V p-p/50 ohms) at a full 700 MHz bandwidth and another output channel at 5 V p-p/50 ohms, 200 MHz bandwidth and 8 bits resolution over the full dynamic range.

To discover how to use the new Analogic/Data Precision 2040 and 2045 for your most complex waveform generator applications, call Analogic today at 1-800-343-8333.



We've captured the key to image capture technology
in three highly-integrated new devices.

Take a look.


Ready! Focus! Fire!

We did. And we nailed the target. Now, Brooktree is
What's Hot in Image Digitizing.

We turned our D/A expertise inside out and devel-
oped the A/D front end that just might fuel the next big
wave in PC and workstation demand. Simply put,
we make it easy, economical and smart to add
image capture capability to your system. Now.

Our focus on imaging has created a team
of highly integrated devices, here today,
awaiting your command.

Start with our **Bt208** flash 8-bit A/D converter. It pro-
vides the base technology for our two new Image Digi-



tizers—the **Bt251** single-channel device for gray scale
applications and the **Bt253** triple-channel device for color
applications.

Flexible architectures are the key. Take filtering—
your favorite subject, right? We make it easy for you to use
the right filter for your application, and place it anywhere
in the signal path. Use multiple filters or a single fil-
ter—it's up to you.

At the back end, the programmable DACs give
you complete control over your image. Video levels
not exact? Want to avoid adding a video amplifier?
The **Bt251** and **Bt253** digitize 0.7v to 1.2v video signals,
and on-chip DACs allows adjustment of the top/bottom of
the A/D reference ladder. So contrast enhancement or
adjustment for different or nonstandard video levels are
easily done under MPU control.



NOW

that

we've

CAPTURED

your

at-ten-tion

The **Bt251** is the monolithic CMOS single-channel, 8-bit device with the features you need. Four input video sources. Sync detection with TTL compatible sync output. DC restoration. Programmable gain/offset. 256x8 lookup table RAM for gamma correction removal, contrast enhancement or thresholding and a standard MPU interface. All in a 44-pin PLCC.

The **Bt253** is its color companion. It's a monolithic CMOS triple channel 8-bit device that digitizes three channels of video signals, generating up to 24 bits of color pixel information.

Use the Bt253 for 24, 15 or 8-bit color applications. It provides for extensive MPU control and supports two video sources. All in an 84-pin PLCC.

Couple the **Bt253** with our **Bt473** True Color RAMDAC to capture and display 8-bits each of RGB.


Feeling especially creative? Our 8-bit **Bt208** is ideal for unique designs. Tailored for video, it also supports DC restoration, on-chip reference, and digitizes 0.7v to 1.2v video signals.

And that's just the beginning. Look for us to expand our building block approach to image capture—color correction, genlock solutions...

Get What's Hot. Get into Image Capture. It's Breakthrough Time again at Brooktree. And you're invited. For our FutureViewer and complete product details, call 1-800-VIDEO IC.

Brooktree Corporation, 9950 Barnes Canyon Rd., San Diego, CA 92121

TLX 383 596 CIRCLE NO 128



Like
we said,
highly
integrated.

Brooktree



DECstation 3100. It's the hottest UNIX™-based RISC workstation available, and it's got the benchmarks to prove it.




Call for the latest industry standard benchmark kit.

1-800-369-8000

Digital. The leading supplier of UNIX-based computing systems for 20 years.

Digital
has
it
now.



dynamic RAMs
Part 2

Tailor memory-system architecture for your chosen DRAM

To tap the full potential of a dynamic RAM (DRAM), you must tailor your memory-system architecture for the DRAM you've chosen. This article, part 2 of a 4-part series, examines your architectural options in designing a memory system. Part 1 reviewed the fundamentals of DRAMs and how to choose them; parts 3 and 4 will focus on DRAM controllers and DRAM-board layout.

Ronald Wawrzynek, *Texas Instruments*

When you design a dynamic-RAM (DRAM) system, you must choose its architecture carefully. The architecture affects the system's memory-access speed, cost, and power consumption, and it may influence your selection of a DRAM. In creating the system, you can choose from a number of architectural options, each involving certain tradeoffs. To come up with the optimal architecture for your application, examine the options and their concomitant tradeoffs carefully before making your choice.

First, however, it's useful to know a little about how DRAM systems are organized. Because most μ Ps manipulate bytes, it's convenient to arrange a DRAM system as byte-wide blocks. You can easily accomplish this memory structure by accessing eight $N \times 1$ -bit DRAMs in parallel. Microprocessors that operate on

multiple-byte units—such as 16- and 32-bit μ Ps—access data by addressing either multiple blocks or multiple rows within a block.

Because today's μ Ps can access more than the N locations indigenous to today's $N \times 1$ DRAMs, designers typically build large memory structures in sections, or "banks." A memory bank is usually as wide as the CPU's data path and as long as the DRAM's capacity (N). For example, memory systems with 8-bit μ Ps are built with $N \times 8$ -bit banks, and systems with 32-bit μ Ps use $N \times 32$ -bit banks. However, the most convenient structure for a 16-bit μ P with an 8-bit data path, such as the 8088 CPU, is one with $N \times 8$ -bit banks.

All of the DRAMs within a bank have a common Row Address Strobe signal, which the DRAM controller supplies via the $\overline{\text{RAS}}$ line. Essentially, the DRAM controller uses the $\overline{\text{RAS}}$ line as a bank-select signal. Most DRAM controllers include four independent RAS output drivers for driving four separate memory banks.

There are occasions when the system's CPU desires access to selected bytes within a memory bank. For example, a 32-bit μ P may need 16-bit data for an internal array computation. Because the bytes may not lie on a 32-bit boundary, the CPU must be able to select each byte individually. You can configure the DRAM controller to access a byte by issuing either separate $\overline{\text{CAS}}$ or separate $\overline{\text{WRITE}}$ lines to the individual blocks within a bank (Fig 1). Whether you use a separate $\overline{\text{CAS}}$ or a separate $\overline{\text{WRITE}}$ line often depends on the access mode available for the DRAM.




Fig 1—The two most common methods for accessing data in a memory bank with multiple bytes is either to use a common CAS line and separate WRITE lines for each block (a), or to use a common WRITE line and separate CAS lines for each block (b).

DRAM architectures fall into two basic groups: the byte-oriented-CAS and the bank-oriented-CAS arrangements. **Figs 2 through 8** illustrate some of your architectural options for constructing a DRAM system with these two arrangements. (Note that the figures don't show all of the control signal lines; they show only the lines necessary to exemplify the different ways of interfacing some popular CPU families to DRAMs.)

The byte-oriented-CAS arrangement, shown in **Fig 2**, interfaces an Intel 16-bit 8086 μ P to a 512k-byte memory bank. Because the μ P has a 16-bit data path, the memory bank is organized as two 256k-byte blocks labeled "even" and "odd." The even block stores the

lower byte (D_0 to D_7) and the odd block stores the upper byte (D_8 to D_{15}) of a 16-bit data word. The DRAM controller has two independent CAS lines for accessing either the even or the odd byte. The μ P accesses the even block (or byte) on even address boundaries (1, 2, 4, . . .) and the odd block (or byte) on odd address boundaries (1, 3, 5, . . .).

The DRAM controller uses the A_0 line and the \overline{BHE} (Byte High Enable) line from the μ P to decide whether to transfer a high byte, a low byte, or the entire 16-bit word. Address lines A_1 to A_{18} provide the 18 addresses required to access the 256k-byte memory space. The controller must internally generate the separate row




Fig 2—The byte-oriented-CAS arrangement employs separate CAS lines for each byte in a memory bank and a common WRITE line. Because the 8086 μ P has a multiplexed address and data bus, an external 3-state buffer is necessary to prevent bus conflicts.

In the bank-oriented-CAS arrangement, the two blocks in a 16-bit bank have a common CAS line, but independent WRITE lines.

and column addresses for each block. Because the 8086 μP has a 16-bit multiplexed address/bus, the upper four address lines (A_{16} to A_{19}) are address-only lines and are shown separately in the diagram. The lower 16 address lines (A_0 to A_{15}) must connect to a 3-state buffer, which implements a bidirectional data bus. When the CPU is ready to read data, and valid data is available at the DRAM's Q outputs, the DRAM controller issues an enable signal ($\overline{\text{OE}}$) to the 3-state buffer.

Both blocks in the memory bank share the same RAS and WRITE lines. During a write cycle, the controller issues a RAS and a WRITE command to both blocks. However, it issues a CAS command only to the even or the odd block when writing a byte. When writing a word, it issues the CAS command to both blocks. The DRAM controller uses the μP 's A_{19} address line as a chip-select line. By connecting the inverted A_{19} address line to the chip-select pin on an identical DRAM controller that's supervising another 512k-byte bank, you can expand the memory capacity to the 1M-byte address limit of the 8086 μP .

CPU's construction affects memory design

The byte-oriented-CAS arrangement for interfacing a Motorola 16-bit 68000 μP to a 512k-byte DRAM bank would be slightly different (Fig 3). The memory bank is still grouped into two 256k-byte blocks (labeled "upper" and "lower"), because the 68000 also has a 16-bit data path. However, the 68000 doesn't have an A_0


address line for selecting the upper or lower block. Instead, the μP decodes the A_0 address internally and generates an upper data signal ($\overline{\text{UDS}}$) and a lower data signal ($\overline{\text{LDS}}$), which the DRAM controller uses for byte selection. In addition, the 68000 incorporates separate address and data lines.

In this system, as in the 8086 memory system, the DRAM controller generates separate CAS lines for each block and common RAS and WRITE lines. The DRAM controller uses address lines A_1 to A_{18} from the CPU to generate the row and column addresses for each block. Because the 68000 has a 16M-byte address limit, the design connects address lines A_{19} to A_{23} to a 1-of-32 decoder for generating 32 chip-select lines. In this manner, you can expand the memory in 512k-byte increments by duplicating the DRAM bank and controller and connecting the chip-select pin for each controller to one of the 32 decoder-output lines.

The 3-state buffer shown in the diagram is necessary only when you employ a delayed-write cycle. As Part 1 of this article (EDN, March 30, 1989, pg 155) explains, the delayed-write cycle briefly enables the DRAM's output buffers, which can cause a bus conflict unless there's an external buffer. The external buffer is not necessary when you employ an early-write cycle, so you can connect the DRAM's D and Q pins, thus effecting a bidirectional data bus.

You can also interface the system CPU to the DRAM by using a bank-oriented-CAS architecture. Fig 4 shows a 68000 CPU that communicates with two mem-

Fig 3—The byte-oriented-CAS arrangement for the 68000 CPU differs slightly from the arrangement for the 8086 μP . Because the 68000 μP has a separate address and data bus, you require an external 3-state buffer only when employing a delayed-write cycle.



A memory bank is usually as wide as the CPU's data path and as long as the DRAM's capacity.

ory banks. In this arrangement, a single DRAM controller generates separate $\overline{\text{CAS}}$ and $\overline{\text{RAS}}$ lines for each bank. Both of the control lines are common to both bytes in each bank. In the bank-oriented-CAS architecture, unlike the byte-oriented-CAS scheme, the lower bytes and the upper bytes of the two banks share respective $\overline{\text{WRITE}}$ signals.

The bank-oriented-CAS arrangement requires a bidirectional buffer that has two byte-enable control lines and resides in the data path between the CPU and the system memory. Because the CPU is capable of writing byte-wide data, the DRAM controller must separately enable each byte in the bidirectional buffer. Without separate enable lines, it is possible to incur bus conflicts when writing a byte to memory, because the output buffers for the alternate block turn on when the controller drives the common $\overline{\text{RAS}}$ and $\overline{\text{CAS}}$ lines low.

Both the byte-oriented-CAS and the bank-oriented-CAS arrangements can be employed in a variety of ways. For example, many high-speed memory systems use a bank-interleave architecture to eliminate CPU

wait states. This concept organizes successive memory locations into different memory banks. When the CPU reads data from successive locations, the controller accesses the next bank while the DRAMs in the previously accessed bank execute a precharge operation. Because this architecture effectively makes the precharge period transparent, the $t_a(\text{R})$ (the delay time after the falling edge of the $\overline{\text{RAS}}$ line and before valid data appears at the DRAM output) determines the read cycle time. However, successive reads from the same memory bank must wait for the precharge period to elapse before the controller can access the bank.

Fig 5 illustrates a bank-interleave structure that interfaces four 512k-byte memory banks to a 68000 CPU by using a bank-oriented-CAS arrangement. The controller selects one of the banks by decoding the CPU's A_1 and A_2 address lines. The CPU's address lines A_3 through A_{20} identify the individual locations within each block of memory. During a read operation, the DRAM controller keeps a record of the bank that's currently being accessed in order to compare it with




Fig 4—In the bank-oriented-CAS arrangement, each bank has a common $\overline{\text{CAS}}$ line, but a separate $\overline{\text{WRITE}}$ line for each byte within the bank. Because the arrangement must be able to access individual bytes, the DRAM controller must separately enable each byte in a bidirectional buffer.

the next bank request. If successive bank requests are the same, the DRAM controller must wait for the pre-charge period to elapse before initiating the next read cycle.

Because a μ P generally accesses successive locations in memory when executing a program, the average read-access time for a memory with a bank-interleave structure is typically $t_{a(R)}$ seconds. DRAMs' $t_{a(R)}$ specifications typically range between 100 and 250 nsec, although 80-nsec DRAMs are available.

Fig 6 shows a byte-oriented-CAS arrangement for an interleaved memory architecture. What differentiates this arrangement from the bank-oriented-CAS scheme is the way in which the $\overline{\text{CAS}}$ and $\overline{\text{WRITE}}$ lines are interconnected. In the byte-oriented-CAS arrangement, one $\overline{\text{WRITE}}$ line is common to all of the blocks. Two $\overline{\text{CAS}}$ lines enable either the lower or the upper block of memory. The interleaved memory architecture is ineffective for DRAMs with cyclic access modes such

as nibble mode, byte mode, and serial mode. Such DRAMs access sequential locations that are internal to the DRAMs, a scheme that defeats the purpose of interleaved memory banks.

Static-column-access mode is fast

The static-column-access mode not only assumes that the CPU accesses data sequentially but also that it accesses data within one row most of the time. The static-column architecture is a nonoverlapping structure in which the lower and upper boundaries of successive banks are adjacent. The memory is organized in a bank-oriented-CAS arrangement, which enables the mode to cross boundaries when accessing columns for a particular row address.

To initiate a static-column read-access cycle, the controller drives the $\overline{\text{RAS}}$ and $\overline{\text{CAS}}$ lines low. If the controller detects that the next read is from the same row, it maintains a low on the $\overline{\text{RAS}}$ and $\overline{\text{CAS}}$ lines and




Fig 5—Interleaving four memory banks in a bank-oriented-CAS arrangement requires a controller with four independent $\overline{\text{RAS}}$ and $\overline{\text{CAS}}$ lines, each driving separate banks. In addition, the controller needs two $\overline{\text{WRITE}}$ lines—one for the lower byte and one for the upper byte.

The DRAM controller uses the RAS line as a bank-select signal.

issues the next column address. This operation eliminates the delays that the CAS line and the precharge time incur. If the next memory read is not from the same row, the controller must return both the RAS line and the CAS line high before beginning a new read cycle.

Fig 7 shows a 2-bank memory system employing a static-column architecture. The DRAM controller uses the UDS and LDS signals from the 68000 μ P to select distinct bytes within a bank. In addition, address lines A_1 through A_{18} select the individual locations within the block, and address A_{19} functions as a bank-select line.

The static-column mode not only requires separate WRITE lines for each byte within a bank, but also requires that the WRITE lines for each bank be independent. The DRAM controller, shown in Fig 7, directs the two WRITE lines to either Bank 0 or Bank 1 by

using the bank-enable lines (BANK0 or BANK1) to control an external multiplexer.

When the CPU is crossing bank boundaries to access data, it's possible for the CAS lines for both banks to remain low during static-column access. In this case, the DRAM output drivers for each bank are continuously enabled, so external 3-state buffers are necessary. To prevent bus crashes, the controller enables only the external buffer for the currently accessed bank by using the BANK0 and BANK1 lines.

Page-mode access is similar to static-column-mode access except that the controller returns the CAS line high after each data transfer. Therefore, you can incorporate the bank-oriented-CAS architecture shown in Fig 7 in a page-mode design without the output 3-state buffers.

In sum, you must decide early in the design cycle whether to use a byte-oriented-CAS or a bank-





Fig 6—An interleaved memory connected in a byte-oriented-CAS arrangement requires a RAS line for each bank in the memory system. The controller accesses the lower and upper bytes with separate CAS lines, but uses a common WRITE line.

Run the new InterTools™ compiler. It's like winning the hundred yard dash by ten yards.



The 10% edge that makes a huge difference.

If you're in the race to develop software for embedded systems, lots of little advantages can make a big difference.

With InterTools, that's exactly what you get. Take our new InterTools C Cross Compiler for the 68000. It gives you 10% to 20% more compact code. So your application runs faster—up to 27% faster—than code from the most popular compiler!*

Work in the fast lane.

And that's just for starters. Because InterTools is a full set of software tools designed to help you win in every phase of embedded microprocessor development. From compiling and assembling, to source-

level debugging. On every popular host. And for every popular target, from the 8086 to the AM29000—and most in between.†

Get complete support.

Best of all, InterTools is from Intermetrics, the only major company that designs and builds every one of its toolkit components to work together as a fully integrated system. InterTools is a total solution, from a team of experts committed to supporting you every step of the way.

Put us to the test!

Just call 1-800-356-3594‡ right now. We'll send you a free InterTools demo kit—and help you get your next C cross development project running ahead of the pack.

The big difference in embedded systems development.

*And we have the benchmarks and data on file to prove it!

†• 68000/008/010/020/030; 68HC11/00/05/09; Z80/64180

• 8086/186/286; 8051; V20/25/30/33/40/50

• AM29000; V60/70; VAX; PDP-11; and many more.

‡In MA (617) 661-0072.

© 1989 Intermetrics, Inc. All rights reserved.
InterTools is a trademark of Intermetrics, Inc.

Intermetrics

733 Concord Avenue, Cambridge, MA 02138

FAX (617) 868-2843

In the byte-oriented-CAS arrangement, the two blocks in a 16-bit bank have a common WRITE line but independent CAS lines.

oriented-CAS arrangement. Your decision will be influenced by the type of DRAM the design employs as well as by the complexity of the DRAM-support circuitry.


The byte-oriented-CAS arrangement is perhaps the most popular, because it generally requires less support circuitry, such as external 3-state buffers. In addition, the arrangement lets you easily implement RAS-only refresh, the most common refresh method. However, the byte-oriented-CAS defers to the bank-oriented-CAS arrangement for systems that use other refresh methods or advanced access modes such as static-column-mode access. Static-column-mode DRAMs virtually require a bank-oriented-CAS arrangement. To take advantage of these DRAMs' fast access times, you must have the entire memory bank turned on and waiting for the next column address.

Generally, your choice of whether to use a byte-oriented-CAS scheme or a bank-oriented-CAS arrangement will happen by default; it'll follow naturally from your choice of a refresh method and an access mode

for your system. Once you've made those choices, the orientation you'll prefer for the CAS line will usually be obvious. **EDN**

Author's biography

Ronald Wawrzynek is a project engineer for a DRAM-controller ASIC design at Texas Instruments' Information Systems and Services Div (Richardson, TX). He has been at TI for three years, and he previously held a co-op position at IBM (Boca Raton, FL). Ron obtained a BS in electrical and computer engineering from Clarkson University, and is a member of the IEEE. He enjoys golf, cycling, and skiing in his spare time.



Article Interest Quotient (Circle One)
High 485 Medium 486 Low 487




Fig 7—To use static-column-access mode, you must put each bank in the memory system into a bank-oriented-CAS configuration. However, you must multiplex the WRITE lines between the memory banks by using bank-select lines (BANK0 and BANK1).

Remember
the first Fluke
multimeter
you ever
used?

That was then.



The Fluke 8000A Multimeter. An instant winner with engineers all over the world, this was the first voltmeter to combine high quality performance with a low price. It featured Fluke's first LED display, as well as our first large-scale custom integrated circuit. Within one year, it outsold all other voltmeters in the world.

FLUKE



PHILIPS

This is now.

Today, Fluke continues to lead the world in multimeter technology, with an impressive selection of world-class meters. Choose from over 42 different models—in handheld, benchtop, and system configurations, with multiple features and functions, 3½ to 7½ digits of resolution, and basic dc accuracies to 0.001%.



Fluke 83



Fluke 87



Fluke 85

Fluke's newest meters, the 80 Series, add the features of many dedicated instruments to leading edge DMM design, bringing new meaning to the term multimeter. These 3¾-digit, 4000 count meters offer 11 functions, 40 ranges, and basic dc accuracy to 0.1%. Unique features include Input Alert™, Min Max Average recording, Min Max Alert™ and protective holster with Flex-Stand™.



(Left to Right) Fluke 77 Low-cost DMM. Fluke 23 Industrial DMM. PM2718 true-rms DMM. Fluke 27 Ruggedized DMM. Fluke 8060A true-rms Precision DMM.




8920A 3½ digit Wideband True RMS AC Multimeter with autoranging, dB and rear panel linear analog output.



8050A 4½ digit Bench/Portable Multimeter with 0.03% basic dc accuracy, true rms ac, dB and relative.



37 3½ digit Bench/Portable Multimeter with 0.1% basic dc accuracy, Touch Hold™, Min/Max recording and relative.



PM2525 5½ digit Bench/System Multimeter with 0.02% basic dc accuracy, frequency, time, temperature dB and recording.



8840 Series 5½ digit Bench/System Multimeters with 0.003% basic dc accuracy, ohms accuracy to 0.008%.



PM2535 6½ digit System Multimeter with 0.0025% basic dc accuracy, up to 100 readings per second, IEEE-488.



8506A 7½ digit Thermal RMS System Multimeter with 0.001% basic dc accuracy, 500 readings per second.



8520A 5½ digit Bench/System Multimeter with 0.005% basic dc accuracy, burst memory and math capabilities.

Now Fluke has 29 And one challenge for e



5700A Multi-function Calibrator



PM 3655 100 MHz Logic Analyzer (up to 96 channels)



1900A Multifunction Counter



PM 8238 Multi-point Data Recorder



Application Software Packages



77 3 1/2 - Digit Handheld DMM




23 3 1/2 - Digit Handheld DMM



7261A Universal Counter/Timer



5220A Transconductance Amplifier



5440B Direct Volts Calibrator



1050 Series Color Touch Control Screen



PM 8155 Multicolor Digital PenPlotter




2393A "Tem Pak" Temperature Logging System



5440B Direct Volts Calibrator



7457A Automated Calibration System



PM 8272 XY and Strip Chart Recorder



1752A Data Acquisition System



9100A Series Digital Test System



2280B Data Logger



System 21 Modular GPIB Switching System



PM 3350 High-Speed Digital plus Analog Oscilloscope



742A-10K Resistance Standard



Helios-1 Computer Front End



8520A 5 1/2 Digit DMM



9 products. Engineers like you.



PM 6666 Programmable
Timer/Counter

PM 5193 Programmable Synthesizer/Function Generator

732A dV Reference
Standard

Recorder

6062A 2 GHz Synthesized RF Signal Generator

2176A Benchtop 10-Input Digital
Thermometer

570 400 MHz Logic Analyzer (115 channel)

PM 2525 5½ - Digit Δ
Multifunction Multimeter

80K-40
High Voltage
Probe

80i-KW
Current/
Power
Probe

87 3¼ digit
Handheld DMM

52 Handheld Dual-Input Thermometer Δ

PM 6303 Automatic LCR Meter

3340 2 GHz Real-Time Digitizing Oscilloscope

8506A 6½ - Digit Precision Thermal RMS Multimeter

Δ 8060A
Precision
4½ -
Digit
DMM

342A 5½ - Digit Bench/System Multimeter

PM 6654C Programmable System Timer/Counter

90 Series
μP Board
Tester
▷

◁ PM 3296A
400 MHz
Real-Time
Oscilloscope

Δ PM 5786 2 nS Pulse Generator

5½ - Digit DC AC Volts System Digital Meter

9000A Series Micro-System Troubleshooter Δ 8920A True RMS Digital Voltmeter

PM 3070 100 MHz Oscilloscope

PM 3320A 200 MHz and 250m SIS Digital Storage Oscilloscope

The Fluke and Philips product line includes 299 instruments and hardware products, 36 software packages and 319 accessories. We also have a challenge for you. See if you can pass this test:

1. I would evaluate test and measurement equipment from a new supplier that offered better performance and value.

True False

2. I am aware that Fluke now sells, services and supports Philips test and measurement equipment in North America.

True False

3. I don't buy out of habit, or because the salesman bought me a terrific lunch.

True False

If you answered true to these three questions, you're ready for our challenge: Try something new. Take a look at the Fluke and Philips products you may not have considered before. You'll find them in the new Fluke catalog, along with all the technical data you'll need to make an intelligent comparison, *before* you buy. Call your local Fluke sales office, or **1-800-44-FLUKE** for your free catalog, today.

Go ahead. We can meet the challenge. Can you?



FREE Fluke and Philips Catalog

Oscilloscopes Multimeters
Signal Generators Logic Analyzers
Counters/Timers Calibrators/Standards
Board Testers Data Acquisition
Thermometers Operator Interfaces
Plotters Systems

CIRCLE NO 163

FLUKE

John Fluke Mfg. Co., Inc., P.O. Box C9090, M/S 250C
Everett, WA 98206
U.S.: 206-356-5400 Canada: 416-890-7600
Other Countries: 206 356-5500

© Copyright 1988 John Fluke Mfg. Co., Inc. All rights reserved. Ad no. 1081-CORP.

It's a trap.

Trap tricky hardware and software bugs, precisely.

Powerful debug commands aren't worth much if they're too difficult to use. We've designed the SA98 to trap bugs based on simple, well defined, and detailed commands.

Quick Change Artistry

No more running up and down command trees to change or modify an emulator condition. Change commands without stopping the emulator. Define in-depth breakpoints. Call up help menus and files as you need them. And you can go from 8- to 32-bit microprocessors quickly.

You Set the Rules

Define your own soft keys and macro commands. With the PC/AT

or XT function keys configured for emulation functions, you can type in and modify commands directly.

Powerful Commands

The SA98 command structure is so powerful and precise, comparing it to other systems is tough on them. Let the power of the SA98 trap your toughest problems and break out of conventional traps.

More Than Expected

Call for a demonstration, and see how good a trap it really is. You'll see fast, well defined solutions.

Call Toll-Free Today

1-800-824-9294 (U.S.)

1-800-824-6706 (CA)

**Sophia
systems.**

Dedicated to MDS/ICE Support

Available for Rent through
U.S. Instrument Rentals, Inc.
1-800-874-7123

U.S. & European Headquarters:

Sophia Systems
3337 Kifer Road
Santa Clara, CA 95051 (408) 733-1571

Corporate Headquarters:

Sophia Systems Co., Ltd.
NS Bldg. 8F
2-4-1 Nishishinjuku, Shinjuku-ku
Tokyo 160 03-348-7000

©1988 Sophia Systems


Sophia Systems is a registered trademark of Sophia Systems Co., Ltd.

ICE is a registered trademark of Intel Corporation.

MDS is a registered trademark of Mohawk Data Science Corporation.

IBM PC/AT and XT are registered trademarks of International Business Machines Corporation.

CIRCLE NO 130



Following simple rules lets embedded systems work with μ P emulators

You can get a lot of mileage from a μ P emulator, but finding that your system crashes when you connect the emulator is frustrating. Observing some simple rules at the outset of a new design can forestall crashes, speed debugging, and let you use emulators in test and service.

Arnold S Berger, Hewlett-Packard Co

Microprocessor emulators are invaluable tools in the design, production, and maintenance of systems that contain embedded processors. Emulators are potentially useful not only in software design—where an emulator can run “out of circuit” by using its internal emulation memory—but also in software/hardware integration and even in test and maintenance. However, many engineers find that, despite their promise of improved productivity, emulators work well only in highly specialized tasks.

One reason for this state of affairs is that designers of μ P-based systems often create products without giving any special consideration to the needs of emulation. The designers of μ P emulators try to make their products affect the operation of the system under test as little as possible, both mechanically and electrically. But there are many things that digital design engineers can, and in some cases must, do to make their designs

“friendlier” to emulators.

Almost every advertisement for emulators and development systems shows a single printed-circuit card on an immaculately clean bench top. The emulator or emulator pod sits conveniently next to the pc card with its 8- to 10-in.-long cable neatly plugged into a socket on the pc card or the target system.

In the real world of embedded-systems design, the μ Ps are truly “embedded.” Actually, “buried” is a more accurate description. Typically, the processor is located in a random location on the pc card and in a random orientation. The word “random” is actually misleading because laying out a dense pc card is hardly a random process. Nevertheless, when placing and orienting the embedded processor, the person responsible for the layout probably gives little or no thought to the mechanical design of the in-circuit emulator that the electrical designer will use for debugging. A simple example illustrates this point.

Fig 1 is a schematic representation of a fairly typical electronic system. The pc cards are contained in an equipment rack; they communicate with each other over a passive mother board or backplane. Designs that permit the use of extender cards greatly improve access to the processors. However, even if the circuits operate reliably on extender cards, the orientation of the processor with respect to the target-system interface cable can still prevent you from plugging in the emulator.

For example, the 68000 μ P is usually packaged in a DIP. Many emulator manufacturers use a flat insulation-displacement cable to connect the emulator to the

Too often, designers of μP -based systems create products without giving special consideration to the needs of emulation.

target-system plug. The width of this cable is usually the same as the length of the DIP plug—about 3 in. Unless you can align the emulator almost perfectly with the plug and the target system, you will lose a significant portion of the useful length of the cable because it will have to make several 90-degree bends. In some cases, the cable won't be long enough to reach the plug, and you'll be out of luck.

In the 64700A series of emulators, Hewlett-Packard chose to make the cable very narrow—less than 1-in. wide on most emulators in the product family. The cable enters the 64-pin DIP plug at the end between pins 32 and 33. The designers chose this location because market research showed that in many applications ICs are positioned on a pc board with their longer side along the axis between the front and back of the card. However, if pin 1 faces back toward the emulator rather than toward the mother board, the cable will have to make a 180-degree turn to plug in properly. Even with the extended probe length of the 64700A family, going "around the bend" can use up a lot of cable length.

Many circuits will not work properly if the circuit cards are extended from the mother board. Sadly, this situation is becoming more commonplace as processor

clock rates extend past 20 MHz and burst modes lead to one data cycle per clock cycle. In these cases, if you locate the processor near the outside edge of the pc card, you may still be able to plug in the emulation probe.

Sometimes there are mechanical quirks that can aid in emulation. The 80186/80188 processor family is available in both leadless-chip-carrier (LCC) and pin-grid-array (PGA) packages. You can buy sockets of both types that have exactly the same pin configuration and that use the same amount of pc-board space. The processor itself is less expensive in the LCC version, but LCC sockets are both more expensive and—in applications like emulation that involve large numbers of insertion/withdrawal cycles—less reliable than are PGA sockets. Using a PGA socket allows a more reliable and less expensive emulation connection. Once the emulation phase is complete, you no longer have to frequently mate and unmate ICs and plugs from the socket. If you selected the correct sockets, you can then produce the board with an LCC socket and an IC—a combination whose cost is less than that of a PGA socket and a μP (Fig 2).

As mentioned before, the coming generations of processors have clock speeds greater than 20 MHz,




Fig 1—An emulation nightmare: The target processor is deep on daughter board 2. Another circuit board, $\frac{1}{4}$ -in. above board 2, forces you to access the μP from the open board end. Unbuffered, high-speed signals traveling between boards via the backplane rule out the use of a card extender. To make matters worse, the target processor socket orientation makes connecting the emulator cable next to impossible.

with 30 MHz becoming commonplace. Their data rates are approaching 240M bytes/sec. The emulation of such processors demands the use of active-probe technology, and the use of active probes places new demands on the emulator designer and the embedded-processor-system designer.

For example, when using an active-probe plug that occupies an area of roughly 6 to 9 in.², it's critical that you allow enough room to properly seat the probe in your board. Components near the processor may prevent the processor from plugging into the socket. With slower processors, you could always plug in extender sockets to permit the plug to clear the board. However, at 30 MHz you must consider the inductance and distributed capacitance of the connections between the μ P and the rest of the system. (Yes, these are analog effects.) Stacked sockets simply don't provide the correct characteristic impedance for signal transmission or a low enough impedance for good ground return paths.

You may have to probe other parts of the circuit in addition to the processor. If the circuit packaging is quite dense and you have failed to provide adequate test points, you may be unable to make certain types of critical measurements.

Surface mounting poses more problems

Boards built with surface-mounted components often present probing problems. For example, consider a board containing a digital-signal-processor (DSP) chip that operates as a slave and a general-purpose processor that acts as a master. The two chips operate in a tightly coupled mode, sharing a common bus and mem-

ory. Data moves in blocks from one chip to the other via coordinated DMA transactions.

Suppose that data at the end of the blocks is becoming corrupted; you suspect a timing glitch or a metastable state in your sequencing gate array. The HP 64700A family lets you connect an optional, 16-channel state/timing analyzer to other circuit nodes in the target system by using conventional logic-analyzer probes. This external analyzer is actually an extension of the HP 64700A's internal bus analyzer. You can completely couple the external analyzer to the internal μ P instruction sequence that leads to and brackets the event under scrutiny. Thus, when the DMA handshake sequence begins, the internal bus analyzer arms the external timing analyzer, and the external analyzer records the external events. However, you can't make this straightforward and powerful measurement if you haven't provided the test points for the critical nodes.

These mechanical considerations suggest electrical problems that you must keep in mind when you design a pc board. For example, although designers of emulators try to bring a high degree of transparency to their products, they still have to depend on the target-system designer's adhering to the timing rules for the target processor. Most ICs will work beyond their published timing limits, at least at room temperature. However, the emulator designer needs every available nanosecond to perform design tricks. Therefore, design to your μ P's published specs. If you don't, you're courting disaster on two fronts: Under some environmental conditions, the μ P may not operate reliably, and your emulator is even less likely to operate reliably.

Sometimes, the emulator steals several nanoseconds




Fig 2—The 80186 LCC package (a) and the 80186 PGA package are quite different. However, you can buy LCC sockets and PGA sockets with identical pin configurations. The diagram in b is a view of the component-insertion side of the LCC socket; c is a view of the side of either socket that mates with the pc board. You can easily use the PGA socket during emulation and convert to the LCC socket in production.

Typically, the processor is located in a random location on the pc card and in a random orientation.

from, for example, a memory-access cycle. Usually, the emulator needs this time to send a signal up and down the cable and to pass signals through the buffer, the cable drivers, and the receivers. If you understand the performance of your emulator in detail, you can sometimes circumvent problems that result from the emulator's internal delays by simply replacing the standard memory chips in the target-system prototype with faster parts. Such a substitution can make the difference between a reliable design/emulation system and one that "goes into the weeds" at the most unexpected times.

Another famous "gotcha" is the wire-wrapped prototype. These units are often 3-D designs with nonexistent power and ground management. Wire-wrapped boards may actually work with a processor chip in place but "die" when you plug in the emulator. Again, the explanation is the failure to consider the emulator and the target system together as a larger system.

To preserve the edge speeds on the signals it supplies to the target system, the emulator uses heavy-duty, line-driving buffers to drive its cable. If the power and ground systems have excessive inductance, there is no low-impedance path for current returning from the target system to the emulator. As a result, voltage pulses appear in various signal lines at odd times—a phenomenon often called "ground bounce." Some of these pulses exceed the switching threshold of parts on the target system or the emulator itself. Fig 3 shows a schematic representation of the emula-




Fig 3—Poor control of the ground return currents leads to distorted and spurious signals at the emulation-probe/target-system interface. The high current capability of the emulation probe's drive circuits exacerbates the problem.

tion-probe/target-system interface; Fig 4 shows an actual ground-bounce waveform. Ref 1 discusses this phenomenon in greater detail.

Simple damper improves reliability

Emulator designers would love to demand that every target system use a 4-layer pc board with power and ground planes, but target-system designers just won't comply. Economic considerations often dictate that in the finished product you use a 2-layer, or even a single-sided, board design with marginal power and ground traces. In digital-system prototyping, wire wrapping and its variations are a way of life. Fig 5 shows a solution to the problems caused by such construction—a simple "damper" socket for a Z80-based system. You place the damping resistors in the critical signal lines; they serve to damp out the fast edges of the signals traversing the cable. Typical resistor values are between 10 and 100 Ω ; higher resistances provide more damping. A good starting value is 22 Ω . This simple circuit modification produces dramatic improvements in target-system reliability.

Some of the newer processor chips provide built-in




Fig 4—Referenced to emulator-probe ground, "ground bounce" caused by poor ground management can be large enough to cross the threshold of a TTL device. The fast 2V edge, **a**, causes a pulse nearly 1V in amplitude from a 0.4V baseline, **b**, on the target-system ground.

emulation help. For example, Advanced Micro Devices' 29000 RISC processor incorporates features that ease emulation. If emulator designers could count on the use of such features by all target systems, they would be able to achieve many emulator-performance improvements. However, target-system designers usually ignore such processor features or view them as imposing unrealistic restrictions. Today, you often hear about "design for testability." "Design for emulation" is the same idea.

Part of the process of selling an emulator is the ritual Plug-in Demonstration. The poor salesperson goes to a customer site and hears, "I'll buy your emulator if it works in my target system." The salesperson then plugs the emulator in and hopes for the best. Such an exercise does relatively little to demonstrate the emulator; what it demonstrates is a limited viewpoint on the part of the prospective purchaser. Obviously, the emulator should work in a target system, but there are many other tools that contribute to the overall usefulness of a μ P development system. The emulator is just a part of the design chain. It's false economy to make a development-system purchase decision solely on the basis of the emulator's performance on a board you have already designed.

Here is an alternate scenario. As part of the overall strategy for designing a new product, you choose a development system and support software. Your

choices include an integrated set of compilers, debuggers, assembler/linkers, user interfaces, emulators, and support and verification tools. The hardware designers or the hardware/software-integration-team members study the features of the emulator and note possible performance limitations. They propose workarounds as part of an overall purchase decision. For example, suppose that the target system contains a watchdog-timer circuit that generates an interrupt at regular intervals. Emulators often fail in such situations because certain modes of operation prevent them from handling interrupts correctly. Designers who understand this mode conflict can make a straightforward addition to the design to permit disabling the watchdog timer during emulation.

Again, designing for emulation in the early stages of a project keeps you from finding yourself in a corner in the later stages.

When making your software compatible with emulators, remember this prime commandment: Modularize, modularize, modularize! Modern programming languages are wonderful for writing compact, testable, and maintainable code. The compact modules of code they produce are an excellent match for the feature sets provided by the emulation memory in most modern emulators. These emulators let you map or overlay blocks of emulator memory onto actual areas of the target system's memory space. An obvious use of this




Fig 5—A homemade damper circuit is an effective means of slowing down fast edges from emulator probe cables. Typically, you will need to damp the address, data, strobe, and clock lines.

Unless you can align the emulator almost perfectly with the plug and the target system, you will lose a significant portion of the useful length of the cable.

feature is in eliminating the need for ROM in the system under development. But unless the code modules lend themselves to the overlay process, you won't realize much of the emulation memory's value.

Consider the situation in which an emulator manufacturer supplies emulation memory in 128k-byte increments and the anticipated size of the final code is about 512k bytes—a value typical of laser printers. One solution to this seeming lack of emulation memory is the purchase of enough emulation memory to cover the entire application space. The idea is wonderful if the cost of high-speed static memory is not a problem. In fact, emulator vendors would love to sell billions and billions of bits of static RAM. However, in most cases large amounts of emulation memory are an unnecessary luxury. By keeping code modules small and self-contained, you can easily develop the entire product in—pardon the pun—byte-size chunks. (Obviously, the chunks are somewhat larger than one byte.)

Another example of the advantage of modular code is the HP 64700A family of emulation products, which provides coverage analysis of emulation memory. This verification tool is a simple but useful one for software designers. The coverage memory records every read or write access to a block of emulation memory. Thus, it can tell you if you're exercising all of the code. If the code modules can stand on their own, with well-defined boundaries between the modules, you can test a block of code with full confidence that you have examined all possible methods of accessing the block. In fact, emulator manufacturers use this feature for the final software qualification of their emulation products. Even if a particular product contains several million bytes of code, the vendor can "walk" the tests through the emulator's entire memory space by keeping the modules and their associated libraries within the bounds of the available emulation memory.

You need emulation, so design for it

Unlike most embedded-system designers, analog designers have long recognized the need to consider the design constraints imposed by test and measurement equipment. These engineers routinely pair signal and ground test points to ensure good fidelity in rise- and fall-time measurements. Taken in that spirit, these suggestions should aid embedded-system designers. For example, if you can locate the processor chip in a mechanically convenient location, do so *before* you do your pc-board layout. Otherwise, you can end up locked into a situation you can't live with. If you don't consider

the emulator's requirements early in the design of your product, you'll need to make the length, size, and flexibility of an emulator's cable part of your emulator purchase criteria.

Looking into the future, the trend toward increased modularity in software design bodes well for the future of emulation. On the hardware side, though, the picture is not as rosy. Faster, higher-performance processors impose increasingly stringent requirements on both emulator hardware and target-system pc-board layouts. By listening carefully to designers of embedded systems and engaging in a continuing dialogue with designers of IC components, emulator designers are doing their part to create instruments that can handle these tougher requirements. Now it's the embedded-system designers' turn. Unless they listen to emulator designers and heed the concepts of design for emulation, there's a good chance that they will deny themselves the benefits of μ P emulation in the development, manufacture, and support of future generations of μ P-based systems. **EDN**

Reference


1. Peurifoy, Steven W and Arnold S Berger, "Cabling technology vital to high-end emulator performance," *Personal Engineering and Instrumentation News*, November 1988, pg 47.

Acknowledgment

The author is grateful to Steve Peurifoy for the use of the results from his emulation-cable-technology study.

Author's biography

Arnie Berger is a project manager responsible for Hewlett-Packard's 64700 series of emulation products at the company's Logic Systems Div in Colorado Springs, CO. He has been at HP for 10 years; previously, he worked at Ford Motor Co and Argonne National Laboratory. Both his BS and PhD degrees are in materials science from Cornell University. Arnie is a member of the American Physics Society and has published or presented over 30 papers. His leisure activities include bicycling, running, and woodworking.



Article Interest Quotient (Circle One)
High 494 Medium 495 Low 496

Not only does Signetics offer 3 more I/O ports than the 80C51, we also do windows.

At first glance, it's easy to see why our new SC87C451 offers you a rare window of opportunity.

It's called EPROM flexibility.

And it comes in both UV and OTP EPROM versions that cut costs and save time in system development. Especially when you consider that it's fully supported by the Signetics development system.


The 87C451 gives you seven I/O ports for advanced applications. You'll find up to 60 I/O lines—28 more than on the standard 80C51.

Other 87C451 features include a "mailbox" interface for parallel communications, which gives you the ability to use port #6 for handshake data transfers. For added flexibility, the 87C451 also comes in ROM and ROMless versions, as well as in 12- and 16-MHz frequencies, and commercial and extended temperature ranges.

The 87C451 is just one part of our large and growing family of 80C51 derivatives. We also offer a 24-pin 80C51 microcontroller in ROM, UV or OTP EPROM. As well as parts with on-chip A/D that are available now. Each one is fully compatible with the 80C51 instruction set.

We're Signetics. We've got the guts—those essential microcontrollers to improve system performance. For a free '451 Microcontroller Information Packet, call us at (800) 227-1817, ext. 993D.

For surface mount requirements and military product availability, contact your local Signetics sales office. Learn the advantages of window-shopping at Signetics.



One standard.  defects.
Signetics

a division of North American Philips Corporation




CIRCLE NO 127

© Copyright 1989 North American Philips Corporation

PHILIPS

Now you have design an emb



The usual way.


The kind of real-time system you design depends a lot on your real-time development tools. If they're simple, complete and elegant, your solution will be too. And that's why nobody can help you create more elegant embedded systems than Ready.

Our real-time development system is already responsible for helping to generate over fifty million lines of real-time code. And it's the only

one based on our CARD (Computer-aided Real-time Design) technology, which was created specifically for the world of real-time. With a unique understanding of the target-host relationship built right in.

We start at the same place you do—with your requirements. And we don't care what you're building, which embedded microprocessor you use, or whether you're working in complex

Two ways to get the job done.



Our way.

environments like multiprocessing or networking. We have the tools for every piece of your project.

Tools like VRTX[®], the real-time operating systems standard. Real-time implementations of C and Ada. Automated analysis tools for verifying system performance. And our CARDtools[™] product with specifically tailored design aids to manage your software organization and data flow. We'll even pull

out documentation—automatically—that'll satisfy the DoD's stringent 2167 specs. And the most demanding commercial customers.

So why go nuts with your next real-time project? Call us, toll free, at (800) 228-1249.

That way you'll have a fair crack at getting the kind of real-time system you really want.

**READY
SYSTEMS**

DEPEND ON THE NAME BEHIND THE WORLD'S FIRST STANDARD-SIZE 9-VOLT LITHIUM BATTERY:



Kodak

**Kodak is the name in high-performance batteries
that designers and end users trust.**


The Kodak Ultralife® lithium power cell is the 9-volt to specify for maximum long-life performance. With *twice* the service life of conventional alkaline 9-volts, it reduces battery changes and equipment downtime. Its innovative design is right for *your* most innovative designs. Flat-folded ribbon electrodes utilize the full interior of the cell.

The 9-volt Kodak Ultralife lithium power cell is your choice for longer life expectancy and consistent discharge characteristics—as well as superior low-

temperature performance. What's more, you can also choose the new 3-volt Kodak Ultralife lithium battery. This 3.6 ampere hour Ultralife

battery delivers high capacity at 3 volts. It makes an excellent backup power source for a wide range of applications, especially in computers and memory systems.

And where alkaline battery performance must be specified, depend on the full line of Kodak Supralife® alkaline batteries...just like millions of your end users do!



**KODAK BATTERIES
DEPEND ON US.**



Eastman Kodak Company, c/o Ultra Technologies Inc.
P.O. Box 267, Newark, NY 14513
1 800 242-2424, 315 332-7230

© Eastman Kodak Company, 1989

Stimulus-response tests are easy with an 8-bit μ P

Despite its association with large and costly test systems, stimulus-response testing is actually simple and straightforward. You can build a low-cost stimulus-response tester around an 8-bit μ P and easily adapt it to a remarkably wide variety of tasks.

Paul D Gracie, *Microdoctors Inc*

Stimulus-response (SR) testing is a well-known technique frequently used in large, high-speed automatic-test systems. In an SR test's simplest form, the controlling CPU reads a test-stimulus value from its memory and sends it to the device under test. After waiting for the system to respond, the processor reads the response and stores the value in a new group (block) of memory locations. When the test is completed, the processor compares the results with a known-good response pattern to detect errors.

You can apply this general method to many other types of tests, such as a stimulus-comparison (SC) test. The minimum equipment you need for SR testing is neither unusually complex nor particularly expensive; you can program a small microcomputer to do simple SR tests. Moreover, you can easily adapt the concept to almost any microcomputer system.

The hardware used for the sample tests is a single-board, 8085-based microcomputer system called the TC-100 (Fig 1). It has 8k bytes of PROM, 2k bytes of RAM, an RS-232C serial port, and an 8255-based parallel port. SR testing uses the three 8-bit parallel ports as follows:

Port A: Response Input
Port B: Stimulus Output
Port C: Control Output.

The Port C output sets the static control values and contains one bit that acts as a data strobe for the stimulus output.

The basic operating system is a control monitor called Swan, which, along with the usual memory and I/O control routines, has a number of modules written




Fig 1—The test-computer block diagram illustrates the parallel I/O port used for SR tests.

Routines optimized for speed can operate at rates in excess of 100,000 operations per second.

for electronic testing. The monitor also has many features that simplify program setup and operation—for example, memory-reference labels, automatic block sizing, automatic pattern generation, and a single-step mode.

The monitor contains three commands for SR testing:

SR <BLOCK><ADDRESS>[<DELAY>] <cr>,
 SC <BLOCK><ADDRESS>[<DELAY>] <cr>,
 and SL <BLOCK>[<DELAY>] <cr>,

where “<cr>” denotes a carriage return. The SR command outputs data from <BLOCK>, waits a <DELAY> (whose optional nature is denoted by brackets), and writes the result to a block beginning at <ADDRESS>. The SC command outputs data from <BLOCK>, waits an optional <DELAY>, and then compares the result with the data stored in the block beginning at <ADDRESS>. If the result of the comparison is true, the program continues to the next address. If the result is false, the program dumps the output, comparison, and input values to the terminal and then continues. The SL (stimulus-loop) command outputs the contents of <BLOCK> into a loop with an optional <DELAY>. The SL command thus generates digital waveforms.

The command syntax is straightforward

Using the facilities of the monitor, most commands take the form SR R T <cr>. That is, the commands output a 256-byte stimulus word contained in the block of memory that begins at R (2000 hex) and write the result to block T (beginning at 2400 hex). Once you set the stimulus pattern, operation of the program is very simple.

The routines do I/O transfers at a rate of approximately 10,000 operations per second. Routines optimized for speed can operate at rates in excess of 100,000 operations per second. For greater speed, you can build a high-speed interface.

Interfaces to units under test are simple

To use the SR function, you can build an interface between the test computer and the device under test, develop a test pattern, and enter the pattern along with the proper command. All of the following applications use a simple, 256-byte pattern that increments from 0 to FF hex. In addition to counting, this pattern produces square waves.

You can develop more complex patterns and use the monitor to write the patterns to the μ P’s memory, or you can burn them into a PROM for a permanent record. For SC tests that require comparison patterns, you can write the pattern to RAM using the monitor, or you can use the SR command and a known-good device to generate the pattern.

The tester checks cable continuity

The interface shown in Fig 2 tests and maps cables that have as many as 16 conductors. In operation, the




Fig 2—In the cable-test interface, IC₁ drives the cable with one logic-0 level at a time while IC₂ scans the cable for connections.

74159, IC₁, drives one of 16 outputs low; the 74150, IC₂, scans all 16 inputs and saves the result in memory. When the 16-step scan is completed, IC₁ drives the next output low, causing IC₂ to repeat the scan. At the end of all 256 steps, the memory contains a map of all of the cable's end-to-end connections. Note that this test won't detect connections between pins of the same connector unless the connections exist within the cable. The response provides a distinctive pattern of 00 for no connection and 11 for a connection. If you use the monitor's hex-memory-dump command, the screen shows a 16 × 16-point map of all end-to-end cable connections.

Using the SC command, you can quickly test a large group of cables. After you set up the system, attach the interface to a known-good cable. Run the SR command to put a known-good map into memory. Then attach the interface to a cable that you want to test and run an SC command. If the cable is good, the system returns the prompt. If the cable is defective, the system prints an error message in the form NM XX YY: N is the output pin number, M is the input number, and XX YY indicates the type of defect. The pattern 11 00, for example, indicates a missing connection, and 00 11 denotes a shorted connection.

You can read most types of PROMs by building an interface consisting of only a socket for the PROM. The interface shown in Fig 3 works with 27xxx PROMs. Again, the stimulus pattern increments from

00 to FFh. This pattern provides the lower address bits, A₀ through A₇. The port C outputs supply the upper address bits, A₈ through A_x. The μP reads data from the PROM as a response pattern to the address stimulus and stores the data in the response RAM. You can then view the data by using the monitor's display-memory command. You can read any 256-byte page of the PROM by setting the proper page number onto the Port C output.

Measure relays' maximum operating speed

You can use this system to test electromechanical relays for both function and speed. The interface required varies with the type of relay tested, but in most cases, it is as simple as the one shown in Fig 4. The interface consists of a transistor driver for the relay coil, a socket for the relay under test, an interface to the computer, and a power supply. The stimulus pattern, which is the same incrementing pattern discussed previously, is used as a square-wave source to drive the relay coil. For a 256-byte pattern, the system drives the relay through 128 on/off cycles and records the contact condition for each half cycle. The response memory pattern is a 22 11 22 11 . . . series for a good relay; the 2 signifies an open contact, and the 1 denotes a closed contact. A 3 in the pattern means that a completely open (floating) contact is present, and a 12 or 21 shows that a shorted contact exists.

Because electromechanical relays don't cycle at a




Fig 3—To read 27xxx PROMs, you can use an interface that consists of just a socket connected to the ports.

To use the SR function, build an interface between the test computer and the device under test, develop a pattern, and enter the pattern along with the proper command.

rate of 5,000 operations per second, you must specify a delay when entering the SR command. The following procedure lets you determine the proper value of the delay setting for a particular type of relay. The test computer generates a base delay of 196 μ sec and an incremental delay of 16 μ sec per step. For preliminary testing, specify the delay with the command SR R T FFF. With this delay, the relay operates at 65.7 msec per cycle—a speed low enough to guarantee that most relays will operate reliably. This SR test produces a known-good response pattern and loads it into the response RAM. You can then use this pattern for a speed test. Your attempt to find the maximum reliable operating speed of the relay might produce results like these:

- #SC R T 900 ; RELAY ALWAYS PASSES AT 37.04 mSEC/CYCLE
- #SC R T 800 ; CONTACT SET A FAILS AT 32.94 mSEC/CYCLE
- #SC R T 700 ; BOTH CONTACTS FAIL AT 28.85 mSEC/CYCLE

When you run the test at various speeds, the system returns the prompt if the relay passes, and it prints the errors if the relay fails. You can also run this test using a variable power supply to determine the pickup

and dropout voltages of a relay under various drive conditions.

With a minimum delay of 196 μ sec, the test computer is not fast enough to test high-speed logic at full speed. To overcome this limitation, you can build a simple, high-speed interface, which is shown in Fig 5. This interface consists of a one-shot ripple counter that is triggered by the stimulus data strobe. The interface shortens the SR test time by compressing the SR cycle. Operation of the interface is as follows:

Setup: At power on, a short low pulse (*POC) clears the shift register, IC₆, and sets IC₈, pin 9 high, enabling the clock. Because all outputs of the shift register are low, IC₅'s output is high, and successive clock pulses shift the high state to the outputs Q_A through Q_G. When outputs Q_A through Q_G are high, IC₅, pin 8 becomes low. This low output, inverted by IC₃, triggers a short pulse on IC₈, pin 5, which disables the clock by setting IC₈, pin 9 low. The circuit is now ready to operate: Q_A through Q_G are high; the data, IC₆, pin 1, is low; and the clock is off.

Operation: After setting the stimulus data on port B, the computer generates a low strobe on port C—bit 8. The rising edge of the strobe sets IC₈, pin 9 high

Text continued on pg 188




Fig 4—The relay-test interface uses a transistor to drive the relay coil.




Fig 5—The high-speed interface (a) is a one-shot ripple counter that uses a shift register to move a pulse (b) to the stimulus and response registers at high speed.

Stimulus-response software can be straightforward

It's relatively simple to create software suited to stimulus-response (SR) testing for most microcomputers. In general, the software must maintain two pointers—one for the stimulus address and one for the response address. These pointers direct data to and from memory for the test. After each SR cycle, the processor increments the pointers and compares the stimulus pointer to an end value. The program then loops for the next cycle or exits for termination. The program follows the form

```
SR : INIT           ;INITIALIZE POINTERS
    MOV A, (SMEM)  ;GET FIRST STIMULUS
LOOP: OUT STIMPORT ;OUTPUT STIMULUS
      (DELAY)      ;DELAY ADDED HERE
    IN  RESPPORT  ;INPUT RESPONSE
    MOV (RMEM), A ;SAVE RESPONSE
    INC (SPNTR)   ;INCREMENT STIM ADDRESS
    INC (RPNTR)   ;INCREMENT RESP ADDRESS
    TEST END      ;TEST END ADDRESS
    RET DONE      ;RETURN IF DONE
    MOV A, (SMEM) ;ELSE GET NEXT STIM
    JMP LOOP      ;AND LOOP FOR NEXT
```

The program must first initialize the pointer registers with the start addresses of the stimulus and response blocks. To simplify the setup procedure, the program can use fixed address values and read the stimulus data set from a PROM. Using this method, you can make a "pushbutton" SR test. The first stimulus data value moves from memory to the accumulator and then out the stimulus port. At this point in the program, you can add a delay to provide time for slow devices under test to respond to the stimulus. After the delay, the program reads the data on the response port, saves it in the response memory, increments both pointers, and compares the stimulus pointer with the end value, which equals the last stimulus-block address plus one. If the result of the comparison is false, the program loads the next stimulus value into the accumulator and loops until it receives the next stimulus output. If the result is true, the SR operation is complete and the program returns to the calling routine.

You can calculate response time

The microprocessor clock speed and the number of clock cycles required to complete one turn of the program loop determine the timing of the SR operation. Two timing values are important: the stimulus-

to-response delay and the response-to-next-stimulus dwell. The minimum time required to increment and test the pointers plus the loop-close time establish the dwell time. You can determine the dwell time from

$$DWELL = (\#CC \times CP) - DELAY,$$

where DWELL is the dwell time, #CC is the number of clock cycles in the loop, CP is the clock period, and DELAY is the stimulus-to-response delay.

For 80-series processors, the stimulus-to-response delay equals one-half the sum of the output and the input cycle times; for other microprocessors, the delay can vary. For an 80-series processor, the minimum delay is 10 clock cycles; for an 8085 running at 3 MHz, the delay equals 3.333 μ sec. To obtain the minimum delay, the input instruction must immediately follow the output instruction. For devices under test that require more time to respond to the stimulus, you must add a delay between the output and the input instructions. For very short delays, you can insert one or more dummy instructions between the output and input. For example,

```
LOOP: OUT STIMPORT ;OUTPUT STIMULUS
      NOP          ;DUMMY FOR TIMING
      NOP          ;DUMMY FOR TIMING
    IN  RESPPORT  ;INPUT RESPONSE
      MOV etc. . .
```

In this routine, two no-ops, which contain four cycles each, increase the delay time to 18 cycles (6.0 μ sec at 3 MHz). You can implement longer delays by inserting a timeout loop between the output and input instructions. For example,

```
LOOP: OUT STIMPORT ;OUTPUT STIMULUS
      MVI A, DELVAL ;GET DELAY VALUE
DLY: DEC A          ;DECREMENT DELAY
      JNZ DLY       ;LOOP NOT DONE
    IN  RESPPORT  ;INPUT RESPONSE
      MOV etc. . .
```

The program moves a value, DELVAL, to the accumulator, decrements the accumulator to zero, and reads and saves the response. You can calculate the timing by

$$DELAY = (10 + 7 + ((4 + 10) \times DELVAL) - 3) \times CP,$$

where

- 10 = the minimum number of cycles,
- 7 = the number of cycles in MVI,
- 4 = the number of cycles in DEC,
- 10 = the number of cycles in JNZ for jump, and
- 3 = the number of cycles JNZ is short for no jump.

The equation is shortened to

$$\text{DELAY} = (14 + (14 \times \text{DELVAL})) \times \text{CP}.$$

Assuming you use a DELVAL of 100 decimal and a 3-MHz clock, the total delay time is $14 + (14 \times 100) = 1414$ cycles $\times 333$ nsec = 471.333 μ sec. The maximum delay possible with this routine— $14 + (14 \times 256) = 3598$ cycles $\times 333$ nsec = 1.199333 msec—occurs when DELVAL = 0 because the first DEC rolls the value over to FFh. You can obtain longer delays by inserting multiple loops or 16-bit loops in place of the simple loop shown.

You can simplify SR routines if you place some constraints on the form of the tests. For example, a program can easily calculate the incremental stimulus pattern used in some tests and thus avoid a sequence of memory-read operations. A routine that performs such a test can take the form

```
SI: LXI  H, 2000    ;LOAD RESP BLK ADDR
      MVI  A, 0     ;LOAD FIRST STIM VALUE
LOOP: OUT  STIMPORT ;OUTPUT STIMULUS
      IN   RESPOR   ;INPUT RESPONSE
      MOV  M, A     ;SAVE RESPONSE
      INC  L        ;INCREMENT ADDRESS AND STIM
      RZ         ;EXIT IF DONE
      MOV  A, L     ;ELSE GET NEXT STIM
      JMP  LOOP    ;AND LOOP.
```

This routine uses a fixed response-block start address of 2000 hex and requires 256 bytes of response RAM. Because the last two digits of the address start at 00 and increment in the same manner as the stimulus value, the same register that counts the address can also generate the stimulus. Because the program has to increment only one register, the start—at address XX00—and the 256-step cycle also simplify testing for the end of the routine. After the last test, the counter “rolls over” from XXFF to

XX00, thereby setting the zero flag. Timing for this routine is

TOTAL LOOP = 51 CYCLES = 17 μ SEC;
SR DELAY = 10 CYCLES = 3.333 μ SEC
R/S DWELL = 41 CYCLES = 13.666 μ SEC
SR TIME = 256 \times 51 CYCLES = 4.352 mSEC,

where SR TIME is the total time for 256 SR cycles.

By following the general form of the examples given, you can write many other forms of SR test programs, which include

Stimulus-comparison: These routines compare the response to a known-good pattern and take action if the response doesn't equal the known-good pattern. When the test detects an error, the program can report the error and continue, or it can pause and leave the failing stimulus data in place to allow the operator to probe for the cause of the failure.

Triggered-response: These programs monitor a trigger port after the stimulus output and record the response only after they detect a specific trigger pattern. The programs can periodically increment a timer register to determine the time to trigger. They can store this value along with the response.

Timed-response: This type of routine applies a single stimulus and records a series of responses at fixed intervals over a fixed period. This test is useful for detecting differing response times of individual bits of the response word.

Selected-stimulus: On the basis of the last response, these routines select the next stimulus value from a list. They are similar to certain types of state machines. You can use these routines to simulate a state machine and to test the devices that the state machine controls.

Single-step and manual-stimulus: Programs that include these facilities are useful for static testing and for debugging failed devices. In particular, the single-step function is useful for tracing failures detected by a stimulus-comparison test.

To overcome speed limitations, you can build a simple high-speed interface that includes a one-shot ripple counter triggered by the stimulus data strobe.

and enables the clock. The first clock pulse shifts a low state on Q_A . This low state on Q_A sets the data, IC_6 , pin 1, high and loads the stimulus data into register IC_1 , which feeds it to the device under test. The second clock pulse to the shift register moves the low state one place to the right—to Q_B . If the multiplexer, IC_4 , has selected Q_B , the pulse then loads the response data into the response register, IC_2 . The response register holds the data until the computer reads it. The low pulse continues down the outputs until it reaches Q_H . At that point, IC_5 , pin 8 returns low, thereby shutting off the clock. The circuit is then ready for the next strobe pulse to start the process again.

The SR transfer delay for this circuit depends on the clock period of Y_1 and the propagation delays of IC_3 and IC_4 . You can calculate the delay from

$$t_{td} = t_p + (t_{dr} - t_{ds}),$$

where t_{td} = SR transfer delay, t_p = clock period, t_{dr} = response clock delay, and t_{ds} = stimulus clock delay. The SR clock delays are the propagation delays of IC_3 and IC_4 . When using a 20-MHz clock for Y_1 , typical delays for the circuit shown are

$$t_{td} = 50 + (13 - 10) = 53 \text{ nsec.}$$

Note that if t_{dr} and t_{ds} are equal, the transfer delay is equal to the clock period, and if t_{ds} is greater than t_{dr} , the delay is less than the clock period. For example, if you replace IC_4 with a wire and add a second inverter from IC_3 , pin 2 to IC_1 , pin 11, the transfer delay is

$$t_{td} = 50 + (0 - (10 + 10)) = 30 \text{ nsec.}$$

You can achieve very short SR transfer delays by selecting the proper stimulus clock delay.

You can use this interface to test multiple-rank devices, such as flip-flops and registers, because it generates seven pulses on Q_A through Q_G . For example, to test a flip-flop, attach the data and control inputs of the device under test (DUT) to the stimulus register (IC_1), attach the DUT's outputs to the response register (IC_2), and attach the DUT's clock input to signal P_1 (also called Q_B). When you run the SR test with Q_C selected to load the response register, Q_A sets the flip-flop's inputs, Q_B clocks the flip-flop, and Q_C records the result. This method allows you to test devices as deep as six ranks.

The interface shown in Fig 6 is a step-and-record

TABLE 1—PORT C BIT ASSIGNMENT

PC0 AUTO MODE HIGH TO ENABLE AUTOMATIC STEPPING
 PC1 *RUN/STOP LOW TO RUN CPU, HIGH TO STOP
 PC2 *FULL/HALF LOW FOR 32 STEPS/CYCLE, HIGH FOR 16
 PC3 NOT USED
 PC4 RESET RESETS THE CPU WHEN LOW
 PC5 STEP STEPS THE CPU ONE MEMORY CYCLE WHEN HIGH
 PC6, 7 NOT USED

TABLE 2—INTERPRETATION OF MONITOR DISPLAY

XXXX AH AL DD SS CC II 00 00
 WHERE
 XXXX IS THE RESPONSE RAM ADDRESS,
 AH IS THE CPU HIGH ADDRESS BYTE,
 AL IS THE CPU LOW ADDRESS BYTE,
 DD IS THE CPU DATA BYTE,
 SS IS THE CPU STATUS,
 CC IS THE CPU CONTROL STATE, AND
 II IS THE CPU INTERRUPT STATE.

“front panel” for an 8085 CPU. Using the processor's wait line, the interface single-steps the system through 16 or 32 instructions and records the condition of the data, address, and control lines at each step. You can then display the resulting data and trace the program flow. The drivers and registers, IC_1 through IC_6 , interface and multiplex the CPU signals on P_{101} to the response port of the test computer. The remaining ICs, IC_7 through IC_{12} , control the interface and the CPU. Port C of the test computer controls operation of the interface. **Table 1** shows the assignment of the port C bits.

To operate the interface, send a value of 03 for 32 steps per test or 07 for 16 steps per test to Port C and run an SR test using the incremental data set. In the test, the interface scans the processor signals and stores the result in the response RAM. Then the CPU steps once, and the test repeats. When the test is completed, you can use the monitor to dump the response data to the screen. The resulting data are shown in **Table 2**.

Because the monitor prints 16 RAM data values per line and the test reports eight bits per step, the second half of the line includes all zeros for a 16-step test. For a 32-step test, the second half of the line contains the next step's data set. After you evaluate the data, run the SR command again for the next 16 or 32 steps. You can repeat this process as many times as required.

Note that the interface inserts long wait states into




Fig 6—The CPU front panel consists of a data multiplexer (a), a wait-state generator (b), and control logic.

ELECTRICAL CONDUCTIVE ADHESIVES.

Designed To Your Specifications

MASTER BOND EP76M EPOXY

- High conductivity
- Thermal shock resistant
- Durable, high strength bonds
- Water and chemical resistant
- Repairability
- Long storage stability without refrigeration
- Convenient packaging



For information, call or write:
Master Bond Inc., 154
Hobart St. Hackensack,
NJ 07601. 201-343-8983

Master Bond Inc.
Adhesives, Sealants & Coatings

CIRCLE NO 43

The Best Programming Site money can buy.

- Model 135 is a *GANG & SET (E)EPROM* Programmer.
- Programs virtually all (E)EPROMs including 32-pin Megabit Devices.
- Optional Universal device support including 40-pin EPROMs, PROMs, 40-pin Micros, Programmable Logic Devices.
- **New GANG Option for 40-pin MICROS!**
- DATA I/O* Protocol Compatible.
- Stand-alone or Computer Remote Operation.
- 18 Month WARRANTY & 12 Month FREE factory Device Upgrades.

Prices from
\$995.00 (US)
100% USA Made

1-800-523-1565
In Florida: (407) 994-3520



BYTEK

BYTEK Corporation • 508 N.W. 77th Street, Boca Raton, FL 33487
FAX: (407) 994-3615 • TELEX: 4998369 BYTEK

* DATA I/O is a registered trademark of DATA I/O Corporation.

CIRCLE NO 44


the program execution and therefore extends the program timing significantly. In addition, many systems that use dynamic RAM won't allow extended wait states without a loss of data. For a small system using static RAM, however, this interface is ideal for tracing the program flow. You can easily design an interface for almost any type of processor because you only need to change the wait generator and the interconnect wiring in the design shown in Fig 6.

As the preceding examples illustrate, you can use a small microcomputer as an SR system to run many useful tests. In addition to the units described, you can construct interfaces for many other functions. For example, if you add an analog-to-digital converter to the input of an interface and a digital-to-analog converter to the output, you can create a waveform recorder/generator. Because the monitor—including the SR command routines—requires only 2k bytes of memory, the system can also include many other test functions. Using the interfaces described in the various examples and the appropriate routines, you can test serial and parallel interfaces, convert serial signals to parallel signals and vice versa, generate square waves and digital patterns, scan lines that carry digital signals and print their logic states, and operate several other interfaces.

EDN

Author's biography

Paul Gracie is President of Microdoctors Inc of Palo Alto, CA; he founded the company 11 years ago. You can reach him there at (415) 324-1460. As a small-company president, his duties are related to every aspect of the business, including design and development. Besides operating a business there, Paul also resides in Palo Alto. In what little spare time he has, he studies art and history.



Article Interest Quotient (Circle One)
High 488 Medium 489 Low 490

Seagate's 3.5" drives Now with AT interface

Seagate's field proven ST157 product line now features embedded controllers with an AT® interface. These reliable to-the-bus solutions offer improved cost/performance over non-integrated solutions.


The ST125A, ST138A and ST157A provide 21, 32 and 43 megabytes of formatted capacity respectively, and feature 28 or 40 msec typical access times, with an impressive 50,000 hour MTBF. All

models support the standard 16-bit AT task file interface, 1:1 interleave capability, an internal data rate of 75 megabits/second, and up to 4 megabytes/second at the interface.

For more information on the drives that offer a lower cost of connection and higher system performance for OEMs and systems integrators, call your nearest Seagate sales office, or call Seagate directly at 800 468-DISC or (408) 438-6550.

 **Seagate**
The first name in disc drives





Portable Problem Solvers

Carry the performance today's technology requires. Not the bulk.

These are the hand-held, ultra-compact digital storage oscilloscope/digital multimeters that fit in small tool kits or attaches. And they're both battery and ac-powered.

Multi-function 3MS/s DSO.

Flip a switch to SCOPE. Capture and analyze single-shot and very slow phenomena. Store from three to six waveforms, plus auto-ranging time base setting, pre-trigger roll mode, and on-screen readout of setting conditions. Low power indicator on screen, plus separate memory back-up, built-in.

Full-function, 3 1/2-digit DMM.

Flip back to DMM for precise ac/dc voltage, current and resistance measure-

ments. Large, high-contrast easy to read display. Automatic range selection.

Leader gives you choices.

Single-Channel LCD-100 Unique combination of features and abilities provides ideal service anywhere.
Model 100P, with built-in printer inter-

face, comes with thermal printer.
Two-Channel Model 200 Even more features and memory range: X-Y capability, auto-ranging for vertical and horizontal, and up to 6 waveforms in memory with push-button throughout. Accepts optional **Model 710 Thermal Printer**, for hard-copy documentation.

CIRCLE NO 97

Call toll-free
1 800 645-5104

In NY State
516 231-6900

Leader Instruments Corporation
 380 Oser Avenue, Hauppauge, New York 11788
 Regional Offices:
 Chicago, Dallas, Los Angeles, Boston, Atlanta
 In Canada call Omnitronix Ltd. 416 828-6221

LEADER
 FOR PROFESSIONALS WHO KNOW
 THE DIFFERENCE



Use a logic analyzer to debug real-time software

Cleaning up real-time operating bugs requires real-time monitoring and analysis, for which the best tool is still the logic analyzer. However, to use a logic analyzer effectively, you need to understand the special triggering requirements that multiprocessing presents.

Ken Marti, *Tektronix Inc*

The logic analyzer is a valuable tool not only for debugging hardware, but also for monitoring and debugging real-time software that runs on microprocessor-based systems. Although you can perform the initial stages of the debugging process by running software debuggers on the development system, certain problems remain hidden until you test the software in real time on the target system. A logic analyzer provides the best method of monitoring this complex stage of the debugging process. By examining the nature of the real-time operating problems, you can determine which capabilities to look for in a logic analyzer.

It's relatively easy to use a logic analyzer to debug small, ROM-based systems because the code is always resident in memory at fixed addresses. Large systems that use multiprocessing, time-sharing methods, on the

other hand, are more challenging to debug. Typical multitasking systems run the operating-system kernel (or supervisor) and the user processes. The kernel is located in a fixed area of memory and is therefore easy to monitor with a logic analyzer. The user processes, however, aren't permanently resident in memory and don't always occupy the same area of memory when they are active. The multitasking computer loads and runs user processes dynamically; that is, it loads the code into whatever areas of memory are currently available. You don't have to abandon your monitoring procedures just because user processes are transient; a logic analyzer can help you overcome the process-identification problem by detecting complex triggering conditions.

To understand how you can apply a logic analyzer to real-time software debugging, consider the life of a user process. **Fig 1** shows the sequence of events of a typical user process, Process A.




Fig 1—The operating system kernel controls the order in which user processes run, and assigns time slices and resources to each process.

To debug a multiprocessing system, you must be able to monitor and analyze data flow and control events in real time. A logic analyzer gives you that ability.

- The occurrence of some event requires the execution of Process A.
- The kernel fetches Process A into memory from disk storage.
- The kernel causes Process A to begin executing.
- Process A runs until it completes its task and exits, or until the kernel suspends the process. The kernel may suspend Process A for several reasons. For example, if the process uses all of its time slice without completing its task, the kernel gives another user process a chance to run. Or, if Process A requires a system resource that is temporarily unavailable, the kernel notes the request and suspends the process until the resource becomes available.
- Eventually, the kernel reactivates Process A, which runs until it either exits or is suspended again by the kernel.

The multiple user processes run in discrete time-slice assignments, which the kernel assigns. The kernel runs in the intervals between each user time slice and, during these periods, allocates any system resources that the user processes need.

In systems that don't have a memory management unit (MMU) or in systems that have an MMU that is outside of the CPU chip, all user processes usually start at the same logical address (often address 0). Before executing a user process, the kernel must set up the MMU (or some other address-conversion device) so the process will address the appropriate area of physical memory (Fig 2).

Because all user processes start at the same logical address, you can't use addresses to distinguish among user processes. If, for example, you set up the logic analyzer to trigger on address 7000 in the user-program space, the logic analyzer triggers on *any* user process that accesses address 7000. To identify the user processes, you need a way of telling the logic analyzer how to recognize when Process A is running and when it isn't running. Your logic analyzer must be able to examine only Process A and ignore activities that take place when Process A is not running.

If you know how to tell when Process A is running, you can set up a logic analyzer to trigger on an event rather than on an address. The state diagram in Fig 3 is a simple example of this triggering concept.

In the setup shown in Fig 3, the logic analyzer's control logic stays in State 1 and looks only for the event (in the kernel) that indicates that Process A is about to run. When the logic analyzer recognizes such an event, the control logic advances to State 2. In State 2, the control logic looks for Event 1, and, if the event occurs, it triggers the logic analyzer. The control logic remains in State 2 until an event (again, in the kernel) indicates that Process A is being suspended or is exiting. The control logic then returns to State 1.

In a more realistic case, you may want to trigger on a sequence of events occurring in Process A. For example, you can trigger on the completion of the sequence "Event 1, followed by Event 2, followed by Event 3." You may be tempted to use a simple approach such as the one illustrated in Fig 4; however,




Fig 2—To monitor a memory-managed, μ P-based system, a logic analyzer needs access to the logical address at the CPU pins and access to the data pins.




Fig 3—This state diagram of a logic-analyzer program shows the conditions for triggering the analyzer on EVENT 1 in Process A and for ignoring all other processes.

such a state machine won't work in this application. Any suspension of the process after Event 1 but before Event 3 returns the state machine to State 1; the state machine doesn't recognize the sequence unless all three events occur within a single time slice.

To detect a sequence of events in Process A when suspensions may occur, you need a state machine with the following capabilities:

- Each state must recognize when Process A is suspended.
- In case the kernel suspends Process A during the event sequence, each state must always remember the occurrence of the event with which it is currently associated. When the kernel reactivates Process A, control can then return to the correct state.

The state diagram in Fig 5 shows you how to add these capabilities to your state machine. The modified state machine detects the sequence "Event 1, Event 2, and Event 3"—even if the process is suspended between individual events in the sequence. The state machine triggers the logic analyzer only when the event sequence is completed.

To apply the complex triggering functions shown in Fig 5, you need a logic analyzer with more capabilities than the basic feature set. First, you need a logic analyzer with a trigger mechanism that is implemented as a state machine. The more states an analyzer can store, the larger the sequence of events it can recog-

nize. Second, the trigger mechanism must be able to detect the occurrence of each independent event within each state. Finally, the trigger mechanism must have several word recognizers and a way to record its progress through the sequence of events. In Fig 5, for example, the flags track the trigger mechanism's progress.

Using a logic analyzer that has these capabilities, you can easily create a multievent triggering program. The sample program in Table 1 is one specific example, which causes triggering on the sequence "Event 1, Event 2, Event 3." It is designed for use on a Tektronix DAS 9200 logic-analyzer system that includes a 92A60




Fig 4—You can set up complex, multievent triggering by recognizing the sequence EVENT 1, EVENT 2, EVENT 3, in Process A. However, this particular approach does not recognize the temporary suspension of Process A during the sequence.

Because all processes start at the same address (unless the CPU has a built-in MMU), you can't distinguish between processes on the basis of address alone.




Fig 5—An effective multievent triggering method stores the occurrence of each event in the triggering sequence. It also recognizes suspension of Process A at any time in the event sequence and returns to the correct state when the kernel reactivates Process A.

acquisition module. The target system is a Motorola 68010-based system that runs under a proprietary implementation of the Unix operating system. However, you can modify the program for any general-purpose, multitasking operating system.

A sample trigger program

Table 1 shows a slightly modified version of what you see on the analyzer screen during the setup process. The analyzer lets you move the cursor to various highlighted fields to define states. For some fields, such as the word number, a pop-up menu lets you select "=" or "!=". You then enter symbols or hexadecimal numbers to define the Address, Data, and Control values.

The DAS 92A60 trigger program consists of four states: Wait_Proc_A, Wait_Event_1,


TABLE 1—SAMPLE ANALYZER PROGRAM FOR 3-EVENT SEQUENCE

STATE WAIT_PROC_A	IF WORD #1= ADDRESS: CURRENT PROCESS DATA: PROCESS A CONTROL: SUPER_DATA
	THEN GOTO STATE WAIT_EVENT_1
STATE WAIT_EVENT_1	IF WORD #2= ADDRESS: CURRENT PROCESS DATA: DON'T CARE CONTROL: SUPER_DATA
	AND WORD #3 != ADDRESS: DON'T CARE DATA: PROCESS A CONTROL: DON'T CARE
	THEN GOTO STATE WAIT_PROC_A
	OR IF WORD #4= ADDRESS: EVENT 1 DATA: DON'T CARE CONTROL: USER_PROG
	THEN SET FLAG #1
	OR IF FLAG #1 IS SET THEN GOTO STATE WAIT_EVENT_2
STATE WAIT_EVENT_2	IF WORD #2= ADDRESS: CURRENT PROCESS DATA: DON'T CARE CONTROL: SUPER_DATA
	AND WORD #3 != ADDRESS: DON'T CARE DATA: PROCESS A CONTROL: DON'T CARE
	THEN GOTO STATE WAIT_PROC_A
	OR IF WORD #5= ADDRESS: EVENT 2 DATA: DON'T CARE CONTROL: USER_PROG
	THEN SET FLAG #2
	OR IF FLAG #2 IS SET THEN GOTO STATE WAIT_EVENT_3
STATE WAIT_EVENT_3	IF WORD #2= ADDRESS: CURRENT PROCESS DATA: DON'T CARE CONTROL: SUPER_DATA
	AND WORD #3 != ADDRESS: DON'T CARE DATA: PROCESS A CONTROL: DON'T CARE
	THEN GOTO STATE WAIT_PROC_A
	OR IF WORD #6= ADDRESS: EVENT 3 DATA: DON'T CARE CONTROL: USER_PROG
	THEN TRIGGER

Wait_Event_2, and Wait_Event_3. Only one of these states is active at a given time. Each state contains a variable number of clauses in the form "IF event(s) . . . THEN action(s)." When a state becomes active, the control logic evaluates each clause in that state and executes the actions associated with any events that are true. A 'Go To State' action sets the state machine to a different state.

The sample program breaks each word into three groups. The Address group always specifies the memory address currently being accessed. The Data group

Real Time Hit Man



Multibus II 80386 SBC

Central Data's new Multibus* II 80386 SBC delivers deterministic performance in real time.

When you step up to 32-bit processing, you need a single board computer with memory performance to match.

That's why we built our new Intel-compatible CD22/1386 SBC with fast-page RAM—up to 16 megabytes** on board—in 4 interleaved banks. The result is a higher effective hit rate providing zero wait-state operation at 20MHz in most applications—significantly better than Intel's cache-based 386/120 in virtually every application.

Caching works great in some cases. But in real time applications, when cache hit rates can be low due to flushing and non-repetitive accesses, the memory architecture of the CD22/1386 outperforms caching—yielding consistently higher effective hit rates and reducing interrupt latencies.

And you get the full range of extra board options for which Central Data is famous. Such as

two 8- or 16-bit double-wide SBX interfaces, a defined P2 interface allowing memory and/or I/O expansion for your custom applications, plus a socket that supports either an 80387 numeric data processor or a Weitek 3167 co-processor—separately or simultaneously.

Power. It makes the CD22/1386 the real time hit man your application deserves. And it's proof of Central Data's commitment to leadership in the Multibus II market. For more information and our Multibus II catalog, just call.

Central Data

1602 Newton Drive, Champaign, IL 61821-1098
Toll free 1-800-482-0315
FAX 217-359-6904
U.K. Office 0734-313877

*Multibus is a trademark of Intel Corporation.
**When 4-megabyte chips become available.

You have to trigger the analyzer on a sequence of events in a specific user process.

specifies the data being written to the address. The Control group specifies whether the kernel (SUPER_DATA) or a user program (USER_PROG) is performing the read or write.

To specify the values that the state machine must recognize, the program uses symbolic names rather than binary or hexadecimal numbers. Table 2 shows the format of the corresponding symbol tables. The Address and Data groups contain only the items that you define in your program and their hexadecimal equivalents. The Control group shows the names and the binary equivalents of all types of bus operations that the control logic can recognize for the microprocessor. The highlighted areas indicate the three items that are relevant to the sample program.

When you start the logic analyzer, or when the kernel reactivates Process A after a suspension, State 1 (Wait_Proc_A) becomes active. Wait_Proc_A contains only one clause, which waits for an event to indi-

cate that Process A is about to be executed. In the sample program, for example, the clause waits for the kernel to write Process A's identifier (ID), PROCESS A, into CURRENT PROCESS, which is a memory location in the kernel's data space. CURRENT PROCESS always contains the ID of the current user process. State 2 (Wait_Event_1) then becomes the active state.

State 2 (Wait_Event_1) contains three clauses. The first clause watches for an event that indicates the temporary suspension of PROCESS A. The clause in the sample program recognizes the suspension when the kernel writes a process ID other than PROCESS A to kernel address CURRENT PROCESS. When the suspension occurs, State 1 becomes the active state. The second clause watches for EVENT 1 in Process A. In this example, EVENT 1 is the execution of a routine beginning at the user address 01D5C6. If EVENT 1 occurs, the control logic sets Flag #1, which,

TABLE 2—LOGIC ANALYZER SYMBOL TABLES

ADDRESS GROUP		DATA GROUP		CONTROL GROUP	
CURRENT PROCESS	040E3E	PROCESS A	003C	SYSTEM_RESET	XX XXXX 00XX XXXX
EVENT 1	01D5C6	DON'T CARE	XXXX	PREFETCH?	00 1X10 XXXX X111
EVENT 2	01CFDE			AUTOVECTOR	XX 1111 XXXX XX0X
EVENT 3	01EB76			SPURIOUS_INT	XX 1111 XXXX X0XX
DON'T CARE	XXXXXX			INT_ACK	X1 1111 XXXX XXXX
				DMA_READ	XX 1XXX XXXX XXX0
				DMA_WRITE	XX 0XXX XXXX XXX0
				DMA	XX XXXX XXXX XXX0
				INVALID_DMA	11 XXXX XXXX XXX0
				RESET	XX XXXX X0XX XXXX
				HALT	XX XXXX 0XXX XXXX
				BUS_REQUEST	XX XXXX XXXX 0XXX
				BUS_GRANT	XX XXXX XXX0 XXXX
				BUS_ERROR	XX XXXX XXXX X0XX
				B_ERR_RETRY	XX XXXX 0XXX X0XX
				VMA	XX XXXX XXXX XX0X
				DATA_SPACE_RD	XX 1X01 XXXX XXX1
				DATA_SPACE_WR	XX 0X01 XXXX XXX1
				READ	00 1XXX XXXX XXXX
				READ_L	10 1XXX XXXX XXXX
				READ_U	01 1XXX XXXX XXXX
				READ_ANY	XX 1XXX XXXX XXXX
				WRITE	00 0XXX XXXX XXXX
				WRITE_L	10 0XXX XXXX XXXX
				WRITE_U	01 0XXX XXXX XXXX
				WRITE_ANY	XX 0XXX XXXX XXXX
				SUPER_DATA	XX X101 XXXX XXXX
				SUPER_PROG	XX X110 XXXX XXXX
				SUPERVISOR	XX X1XX XXXX XXXX
				USER_DATA	XX X001 XXXX XXXX
				USER_PROG	XX X010 XXXX XXXX
				USER	XX X0XX XXXX XXXX
				PROG_SPACE	XX XX10 XXXX XXXX
				DATA_SPACE	XX XX01 XXXX XXXX
				CPU_SPACE	XX X111 XXXX XXXX
				"DON'T CARE"	XX XXXX XXXX XXXX

$\pm .025$ dB Frequency Response +

Versatility + Low \$ = **VALUE**

In a Precision Function Generator



Flattest frequency response in its price range! The Model 2100A-7 sets the standard. But there's more to the Model 2100A-7 than flat response. There's frequency accuracy of 0.5ppm, amplitude accuracy of 0.05dB of setting, multiple operational modes and much more. But best of all, there is the economical price of \$4750.00 and **value** is the sum of this design equation. The fully GPIB programmable

2100A-7 stores and recalls up to 100 complete front panel set-ups in its internal memory. All front panel parameters are knob controlled or can be incremented/decremented by a user pre-defined delta, multiply, or divide constant.

Operation modes include continuous, gate, trigger burst, triggered pulse, lin/log sweep and VC. A pulse generator and a sweep ramp/marker generator are also built in.

For more information, call or write Krohn-Hite today.

- Frequency response ± 0.025 dB
- Frequency accuracy 0.5ppm (optional 0.01ppm)
- 30.0000MHz to 31.16000MHz synthesized over full range
- Output range 10 μ V to 30V p-p



KH KROHN-HITE CORPORATION

40 Years of Quality Instruments
1949 - 1989

Avon Industrial Park, Avon, Massachusetts 02322
(508) 580-1660 TWX: 710 345 0831
FAX: (508) 583-8989



We're Building On A Proven Product Line...

You know Schaevitz as the leading source for LVDTs. With more than 400 standard designs, we have the right transducer for your linear displacement applications...and we keep making them better.

Our standard LVDT line offers:

- Ranges to 20", AC/DC models
- Linearity to $\pm 0.05\%$; infinite resolution
- Operation in extreme environments
- Compatible LVDT instrumentation


... To Bring You New Technology

Recent product developments at Schaevitz include an affordable DC-operated LVDT. This new generation sensor offers improved performance at a lower price tag than previous units. We've also extended our reach into linear position sensing with technology capable of long stroke measurement to 120".

To find out more about our linear displacement sensors and other Schaevitz products, call our **Hot Line: 609/662-8008** or write Schaevitz, 7905 N. Route 130, Pennsauken, NJ 08110-1489.

Grid Scale: $\frac{3}{16}$ " x $\frac{3}{16}$ "

Solid Solutions for Linear Position Sensing



schaevitz

The Name In Sensor Technology
609/662-8008

CIRCLE NO 11

in turn, makes State 3 (Wait_Event_2) the active state in the next cycle. If Flag #1 is already set when State 2 becomes active, the third clause immediately causes State 3 (Wait_Event_2) to become the active state. The third clause is needed so that the state machine can return to the correct state in the trigger program if Process A is suspended at any time before the 3-event sequence ends.

State 3 (Wait_Event_2) is similar to State 2 (Wait_Event_1), except that it watches for the occurrence of EVENT 2 (rather than EVENT 1) in Process A. State 3 passes control to State 4. In the sample program, EVENT 2 is the execution of a routine beginning at user address 01CFDE. Again, if the kernel suspends Process A, state machine returns to State 1 (Wait_Proc_A).

State 4 (Wait_Event_3) has only two basic functions. If EVENT 3 in Process A takes place, the control logic triggers the logic analyzer. On the other hand, any suspension of Process A returns the state machine to State 1.

Clearly, this sample trigger program is designed for a very specific situation. The details of the program are markedly different for each application. However, the program does illustrate the impressive software tracking functions you can perform with a state-of-the-art logic analyzer that is suitable for software debugging.

EDN

Author's biography

Ken Marti is a senior software engineer at Tektronix Inc (Beaverton, OR), where he has spent 10 years designing and developing application software. Ken holds a BS degree in computer science from Utah State University. In his spare time, Ken enjoys soccer, racquetball, and skiing.



Article Interest Quotient (Circle One)
High 497 Medium 498 Low 499

Floating Input Extends Regulator Capabilities

Brian Huffman

Many applications require circuit performance that is unachievable with conventional regulator design. This results in added complexity to the circuit. However, some problems can easily be solved by floating the input to the regulator. A floating input can either be a battery, or a secondary winding that is galvanically isolated from all other windings. With this method high efficiency negative voltage regulation, high voltage regulation, and low saturation loss positive buck switching regulator can all be achieved easily.

Low dropout negative voltage regulators are not currently available. This would seem to preclude high efficiency negative linear regulators. Such regulation is frequently desired in

switching supply post regulators; however, if the secondary windings are isolated from one another, a low dropout positive voltage regulator can be used for negative regulation (Figure 1).

In this circuit the LT1086 servos the voltage between the output and the adjust pin to 1.25V. The positive regulation is accomplished by conventional regulator design. Negative voltage regulation is achieved by connecting the output of the positive voltage regulator to ground. The V_{IN} pin floats to 1.5V or greater, above ground. This technique can be used with any positive voltage regulator, although highest efficiency occurs with low dropout types.







Figure 1. High Efficiency Negative Voltage Regulation

VICOR





Celebrating The New Profile

Introducing the FlatPAC™ ... Vicor's Family of User Definable, Multiple Output, Switching Power Supplies

Until now, your power system decision meant choosing between costly and unpredictable custom development, or bulky and inflexible catalog supplies...or you had to design and manufacture it yourself. Taking the next step in the power-component revolution, Vicor introduces FlatPAC, the user-definable, "off-the-shelf" alternative to customs that's economical from single units to OEM quantities...and which fits in a fraction of the space required by conventional off-line supplies!

The Off-The-Shelf Alternative

FlatPAC's unique modular design allows Vicor to provide next day delivery on over 10,000 different FlatPAC configurations. You define your power requirements... Vicor does the rest — while eliminating the non-recurring costs, unpredictable lead times, risk, inflexibility, and reliability uncer-


tainties associated with conventional solutions. No other power product offers FlatPAC's combination of power density, economy, and "off-the-shelf" flexibility!

Power Cells


Sharing a distinctive, space saving flat package profile (1.37" high x 8.6" long), FlatPACs come in widths of 2.5", 4.9", and 7.4", and supply up to 200, 400, and 600 Watts of total output power...an unprecedented 7 Watts per cubic inch in an off-line switching power supply!

The three different packages provide one, two, or three user definable "Power Cells". Each Power Cell may be specified to be an independent, isolated output with a power rating of 50, 75, 100, 150, or 200 Watts, or cells may be combined to form higher power outputs...up to 600 Watts from a single output. Standard output voltages are 5, 12, 15, 24, and 48 Volts — and because all

FlatPAC outputs are field trimmable down to zero and up to 110% of nominal, a standard output can likely



FLATPAC



In Off-Line Switchers.

take care of even your most unusual voltage requirements. For special requirements, outputs as low as 2 Volts, and as high as 95 Volts can be provided.

And you don't give up features to get FlatPAC's advantages: besides being trimmable, all FlatPAC outputs have remote sensing and overvoltage and overcurrent protection. Individual FlatPAC outputs are totally isolated: there are no cross regulation issues; any output can be positive or negative; and output returns can float up to 500V, rms, apart. FlatPAC's run on either 110 or 220 Volt lines, meet "Class A" interference specs, have built in fusing, and conform to UL, CSA, and TUV safety agency requirements. Two and three cell units also provide two isolated, sequenced, logic outputs to indicate pending loss-of-line and pending loss-of-output for system housekeeping during power cycling or brownouts.

The key to FlatPAC's flexibility and power density is Vicor's VI-200 family of high density, high efficiency, UL, CSA, and TUV recognized, component level DC-DC converters. When you specify a FlatPAC, you benefit from the field reliability and predictability that's been established in an installed base approaching half a million units.

Join The Celebration Now

Call Vicor now to discuss your special needs...you'll be celebrating when you find how quickly Vicor can ship you the smallest, most efficient, most cost effective solution to your power system requirements...at prices as low as 85¢/Watt in OEM quantities.

To Receive A Complete Catalog, Including Information On Vicor Products, Applications And Accessories, Call Vicor Today At (508) 470-2900, 23 Frontage Road, Andover, MA 01810.



Component Solutions For Your Power System



Perfect protection doesn't have to be ugly.

Your design will need protection from the tough reality of the workplace. Take a look at enclosure systems from RITTAL. They are not only tough and functional, but aesthetically beautiful, too.


See for yourself with our comprehensive handbook. It's filled with the most advanced packaging solutions... a "how-to book" on protection!

Plus our warehouses throughout the country maintain an inventory of over 200,000 units for off-the-shelf just in time delivery, anywhere. Fast.

So, why put your ideas in an ugly, inadequate box that makes your sophisticated system look like everyone else's? Just give us a call at 1-800-637-4425 and we'll send you our full-line handbook. It's free, and the information may keep you from losing your head.

Take your design all the way to perfection... switch to RITTAL.

1-800-637-4425



RITTAL Corporation
P.O. Box 1284
3100 Upper Valley Pike
Springfield, OH 45504
Phone: (513) 399-0500
Fax: (513) 390-5599

CIRCLE NO 92



Get your "hands on" the world's most extensive IC and Discrete Semiconductor database... with D.A.T.A. DIGESTs and timely Updates.

Pinouts, significant specs, package styles, functions, manufacturers, discontinued devices, alternate sources and replacements. Essential selection data on more than 525,000 IC and Discrete Semiconductor devices from over 780 manufacturers.

D.A.T.A. DIGESTs and Updates for . . .

- High-Rel Components
- Digital ICs
- Linear ICs
- Microprocessors
- Memory ICs
- Diodes
- Transistors
- Thyristors
- Interface ICs
- Alternate Sources
- Power Semiconductors
- Optoelectronics
- Application Notes
- International Semiconductor Directory



Across the world's most extensive database of IC's and Discrete Semiconductors

The D.A.T.A. DIGESTS User's Guide Diskette is acceptably easy to use:

1. Turn on your personal computer.
2. Insert the User's Guide Diskette in your "A drive" (or "B drive").
3. Press on the track and press Enter on the screen.
4. The printed list of IC's will now appear on the screen.
5. Your Digest will print Enter on the screen.

The diskette will "help you through" the rest of the steps to view whatever interests you in the DIGESTS. Don't hesitate to call us toll-free if you have any questions. 1-800-447-4666.

"Test drive" our books! Call toll-free today and qualify for a FREE D.A.T.A. DIGESTs User's Guide Diskette. With this interactive demo diskette you'll see for yourself how exceptionally quick and easy semiconductor selection can be with D.A.T.A. DIGEST books . . . **and timely Updates.**

Call 1-800-447-4666 now for your free User's Guide Diskette. D.A.T.A. DIGESTs . . . where semiconductor selection begins.

8977 Activity Road • P.O. Box 26875 • San Diego, CA 92126

**D.A.T.A.[®]
BUSINESS
PUBLISHING**

A Division of
Information Handling Services

DESIGN IDEAS

EDITED BY CHARLES H SMALL

NPN replaces PNP pass transistor

Brian Huffman
Linear Technology Corp, Milpitas, CA

Classic buck switching regulators and power supplies use PMOS or PNP transistors as their series-pass switch. In general power-supply design, you should use low on-resistance switches to achieve high efficiency and minimize heat sinks. Unfortunately, low on-resistance PMOS transistors just aren't available. The lowest on-resistance PMOS devices available typically have 0.3Ω on-resistances; comparable NMOS devices have 0.028Ω on-resistances.

You can use an NMOS transistor as a series-pass switch if you drive its gate sufficiently higher in voltage than its source, thus causing the transistor to saturate. The circuit in Fig 1 bootstraps its NMOS transistor's gate off its source to achieve saturation.

In the figure, the LT1072 switching-regulator controller sinks current into its V_{SW} input, which is a common-emitter NPN driver, at a 40-kHz repetition rate. When the V_{SW} output is off, the gate of Q_2 goes high, causing it to saturate and turn Q_1 off. When Q_1 turns off, the flying capacitor, C_1 , charges up through D_1 .

When the LT1072's V_{SW} pin turns on, Q_2 turns off and Q_3 turns on. The voltage across the flying capacitor

now appears across the gate-source junction of the NMOS transistor, Q_1 , causing it to saturate.

As is usual for buck converters, while Q_1 is on, the inductor L_1 charges up. When the V_{SW} pin turns off, the inductor dumps its charge into the load with the aid of the freewheel diode, D_2 .

The remainder of the auxiliary circuitry provides normal power-supply functions. For example, capacitor C_3 slowly starts the converter, while the 20Ω resistors reduce voltage spikes that would otherwise be generated by Q_1 's fast switching. The regulator's high-impedance error-amplifier input, V_C , uses an RC damper for loop compensation.

Q_4 through Q_7 provide short-circuit protection. The LT1004 voltage reference and Q_6 and the $7.5\text{-k}\Omega$ resistor generate a 240-mA current. This current flows through R_1 and generates a threshold voltage of 240 mV for the comparator formed by Q_4 and Q_5 . When the voltage drop across the 0.018Ω sense resistor exceeds 240 mV , Q_7 turns on. The chip's V_{SW} pin goes off when Q_7 pulls the V_C pin below 0.9V . The RC network, C_2 and R_2 , suppresses line transients that might prematurely turn on Q_7 .

EDN

To Vote For This Design, Circle No 746




Fig 1—A bootstrapped, flying capacitor, C_1 , enables this switching regulator to use a low on-resistance, NMOS series-pass switch instead of a conventional PMOS or PNP device.

Variable slew-rate filter tames noise

Jonathan Audy
Precision Monolithics Inc, Santa Clara, CA

The variable slew-rate filter in **Fig 1** reduces the noise of an input signal by using a combination of linear and nonlinear filtering. Under certain input conditions, the circuit acts as a nonlinear, variable slew-rate filter. The circuit's slew rate can vary from volts per second to volts per microsecond.

To understand the difference between a linear filter and a variable slew-rate filter, consider that the corner frequency of a linear filter does not change with varying magnitudes of input-signal level and does not distort the input signal. In contrast, the corner frequency of a nonlinear filter varies inversely with the magnitude of the input signal such that the filter's bandwidth is smaller for larger input signals. As the input signal's frequency approaches the nonlinear filter's corner frequency, no phase delay or attenuation occurs at all. But past this point, the filter severely distorts the

input waveform's shape to that of a triangular waveform.

Fig 2 shows the circuit's responses to a family of step-input signals having magnitudes from 2 to 12V. The figure demonstrates how the filtering varies from purely linear to a combination of both linear and nonlinear to nonlinear (slew-limiting), depending on the input-step size.

For example, suppose you must handle the $\pm 12V$ output of a transducer with a circuit whose 90% response time needs to be no faster than 0.1 sec. The problem with using a linear, "capacitor-resistor" type filter to set the response rate of the transducer amplifier is that the rate of change of such a circuit's output increases with increasing input-step size. Therefore, a large noise pulse of short duration would affect the output of a linear filter much more than the output of a nonlinear filter. **Fig 3** shows the response of linear and nonlinear filters to a 12V, 25-msec pulse. Without slew limiting, the output reaches a peak of 8.7V; with slew limiting, the peak reaches 4.4V.

For lower-level inputs, IC_{1A} acts as a gain stage; for larger signals, it functions as a comparator driving an integrator (IC_{1B}). Here, the IC_{1A} compares the input voltage to the output voltage of the integrator and forces the integrator's output to equal the input voltage. IC_{1A} needs no feedback resistor because the OP290 op amp is perfectly stable with the feedback provided by IC_{1B} .

When the circuit is slew limiting, IC_{1A} 's output goes to one of the output rails and the diodes, D_1 and D_2 , clamp the voltage across R_3 . Thus, a constant current flows into or out of C_1 . The final result is that R_3 , C_2 , and IC_{1B} form an integrator with the output of IC_{1B} slewing at the rate of $V_{DIODE}/(R_3 \times C_2)$ V/sec. For an input voltage that slews at less than this rate, the output of IC_{1B} simply follows the input voltage and IC_{1A} operates linearly with a very high gain. The dc gain of the complete circuit is unity. For non-slewing, dc conditions, the output of IC_{1A} is at 0V.

During slew limiting, one of the diodes carries approximately V_{SUPPLY}/R_2 , and the other is reverse biased. For the given circuit, $V_{SUPPLY}/R_2 = 15V/100k\Omega = 150 \mu A$, which yields a diode voltage of 0.3V. The circuit in **Fig 1** has a slew rate of $0.3V/(470k\Omega \times 4700pF) = 0.136 V/msec$. You can vary this rate by adjusting R_3 .




Fig 1—When input signals are high in magnitude, this circuit acts as a comparator feeding an integrator to limit the slew rate of the circuit's output. For lower-level inputs, the circuit is simply a unity-gain buffer.

To Vote For This Design, Circle No 747

DESIGN IDEAS




Fig 2—The responses of the circuit in Fig 1 to a family of step-input signals having magnitudes from 2 to 12V demonstrate how the circuit's filtering varies from purely linear to nonlinear (slew-limiting), depending on the input signal's step size.




Fig 3—The slew-rate limiting filter responds much less to a 12V, 25-msec pulse than does a simple RC filter.

386SX interfaces with IBM PC/AT chip set

Al Weidner

VLSI Technology Inc, Tempe, AZ

The Intel 80386SX is a 16-bit-bus version of the 32-bit-bus 80386. You can use this μ P in an IBM PC/AT to run 386 programs if you adapt the 386SX to the PC's requirements.

The processor clock of the 386SX is 180° out of phase with the clock supplied to the 286 by the IBM PC/AT bus (Fig 1). The 74F04 inverter, IC₂, corrects this condition. The control lines needed in the PC/AT system to control the status and I/O functions differ from those supplied by the 386SX. The PAL16R6-12, IC₃, accomplishes the necessary conversion. Listing 1 gives the thoroughly tested Boolean equations for the PAL device. Each equation's comments describe the conversion that the equation implements.

Because the 386SX will be operating in its pipelined mode in order to achieve its maximum performance, its address lines will become valid sooner and remain valid for a shorter period than the IBM PC/AT specification requires. To guarantee the correct worst-case timing-specification performance of the IBM PC/AT, three 74LS373 octal latches—IC₄, IC₅, and IC₆—hold the valid address values long enough to ensure recognition by the system.

This adapter handles all available speed variations of VLSI Technology Inc's VL82CPCAT-12QC, VL82CPCAT-16QC, VL82CPCPM-16QC, and VL82CPCPM-20QC IBM PC/AT-compatible chip sets for the 386SX μ P.

EDN

To Vote For This Design, Circle No 750

LISTING 1—PAL-DEVICE EQUATIONS

CHIP	P9T0286			PAL16R6						
;PIN#	1	2	3	4	5	6	7	8	9	10
	CLK2	MIO3	WRT3	CMD3	/ADS	/RDY286	/BHE3	RST286	NC	GND
;PIN#	11	12	13	14	15	16	17	18	19	20
	/OE	/BHE2	/SFAZ1	/S0	/S1	MIO	ADS2	SYSCLK	RST386	VCC

EQUATIONS

```

/ADS2 := /(ADS*/ADS2) ;2ND PHASE OF ADS, WHETHER READY OR NOT
BHE2 = BHE3*ADS2 + BHE2*/ADS2 ;LATCHED /BHE
SFAZ1:= ADS2*RDY286 ;1ST STAT PHASE, ALWAYS FOLLOWS ADS
; WHEN READY
/SYSCLK := SYSCLK + SFAZ1 ;INTERAL SYSCLK - SYNC EACH STATUS CYC.
/RST386 = /(RST286 + RST386*RST286
+ RST386*SYSCLK) ;RESET TO TURN OFF ONLY DURING PHASE 2
/MIO := /((ADS*MIO3)+(/ADS*MIO)) ;286 MIO, LATCHED AT EACH ADS PHASE 2
S1 := ADS2*RDY286*/WRT3 ;286 S1, HELD FOR 2 PHASE STAT CYCLE
+ ADS2*RDY286*/CMD3*MIO3 ; 0 ALL OTHER TIMES
+ SFAZ1*S1
S0 := ADS2*RDY286*WRT3*MIO3 ;286 S0, HELD FOR 2 PHASE STAT CYCLE
+ ADS2*RDY286*CMD3*WRT3 ; 0 ALL OTHER TIMES
+ ADS2*RDY286*/MIO3*/CMD3*/WRT3
+ SFAZ1*S0
    
```

DESIGN IDEAS




Fig 1—With the aid of a PAL device and a few latches, you can adapt the 386SX μ P to IBM PC/AT chip sets.

C string comparer handles abbreviations

David Rankin

Prime Computer, Framingham, MA

The string-comparison routine in **Listing 1** is only slightly longer than the standard string-comparison routine "strcmp," but it identifies any abbreviation of a string as well as merely the string itself. The abbrevi-

ation need only have some of the letters of the full string in exactly the same order as they would occur in the full string to generate a "hit."

You could use this routine, for example, in an input-command processor for a program designed for both experienced and inexperienced users. Inexperienced users would enter the full name of the command; expe-

LISTING 1—ABBREVIATION-HANDLING STRING COMPARER

```
/* ===== *
* strfit
* If the two words fit, return a zero. Else return a
* non-zero.
* ===== */
int strfit ( pattern, sample )
char *pattern, *sample;
{

/* See if the first letters match. */
if (toupper( *pattern ) != toupper( *sample ))
    return(-1);

/* See if every character in sample is found in pattern. */
while ( *sample != 0 )
{

/* Look for a character in pattern that matches
* the current character in sample. */
while (toupper( *pattern ) != toupper( *sample ))
{

/* Move to the next char in pattern. */
pattern++;

/* See if we have reached end of pattern */
if ( *pattern == 0 )
    return( -1 );
}

/* Move to the next char in sample. */
sample++;
}

/* We have successfully matched every char in sample to a
* char in pattern. */
return( 0 );
}
```

tiny SPDT switches

absorptive... reflective

dc to 4.6 GHz from \$32⁹⁵ (10-24)

Tough enough to pass stringent MIL-STD-883 tests, useable from dc to 6GHz and smaller than most RF switches, Mini-Circuits' hermetically-sealed (reflective) KSW-2-46 and (absorptive) KSWA-2-46 offer a new, unexplored horizon of applications. Unlike pin diode switches that become ineffective below 1MHz, these GaAs switches can operate down to dc with control voltage as low as -5V, at a blinding 2ns switching speed.

Despite its extremely tiny size, only 0.185 by 0.185 by 0.06 in., these switches provide 50dB isolation (considerably higher than many larger units) and insertion loss of only 1dB. The absorptive model KSWA-2-46 exhibits a typical VSWR of 1.5 in its "OFF" state over the entire frequency range. These surface-mount units can be soldered to pc boards using conventional assembly techniques. The KSW-2-46, priced at only \$32.95, and the KSWA-2-46, at \$48.95, are the latest examples of components from Mini-Circuits with unbeatable price/performance.

Connector versions, packaged in a 1.25 x 1.25 x 0.75 in. metal case, contain five SMA connectors, including one at each control port to maintain 3ns switching speed.

Switch fast... to Mini-Circuits' GaAs switches.

SPECIFICATIONS

Pin Model	KSW-2-46	KSWA-2-46
Connector Version	ZFSW-2-46	ZFSWA-2-46
FREQ. RANGE	dc-4.6 GHz	dc-4.6 GHz
INSERT. LOSS (db)	typ max	typ max
dc-200MHz	0.9 1.1	0.8 1.1
200-1000MHz	1.0 1.3	0.9 1.3
1-4.6GHz	1.3 1.7	1.5 2.6
ISOLATION (dB)	typ min	typ min
dc-200MHz	60 50	60 50
200-1000MHz	45 40	50 40
1-4.6GHz	30 23	30 25
VSWR (typ)	ON 1.3:1 OFF —	1.3 1.4
SW. SPEED (nsec)		
rise or fall time	2(typ)	3(typ)
MAX RF INPUT (bBm)		
up to 500MHz	+17	+17
above 500MHz	+27	+27
CONTROL VOLT.	-8V on, OV off	-8V on, OV off
OPER/STOR TEMP.	-55° to +125°C	-55° to +125°C
PRICE (10-24)	\$32.95 \$69.95	\$48.95 \$79.95

finding new ways...
setting higher standards

Mini-Circuits

A Division of Scientific Components Corporation

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500
Fax (718) 332-4661 Domestic and International Telexes: 6852844 or 620156

C 117 REV. E

DESIGN IDEAS

rienced users would be free to abbreviate the commands as they saw fit. Thus, you can concoct long, self-documenting names without saddling users with an onerous amount of typing; and users can democratically develop a set of abbreviations, within reasonable limits, that suits their fancies.

This routine, *strfit*, is a direct replacement for *strem* because its parameter list is the same. The first argument you must supply is the pattern word, such as the name of a command. The second argument is the user's input. *Strfit*'s algorithm determines if all of the letters in the user's input appear in the pattern word in the same order. The algorithm ignores both intervening letters in the pattern word and the case of the letters. Additionally, the first letter in the user's

input and the pattern word must match.

Thus, *WordDump* and *wdmp* generate a match, and *DisassemblyMem* and *Dasm* generate a match. *WordDump* and *Dump* don't generate a match because the first letters don't match; *WordDump* and *WDpm* don't generate a match because the letters are out of order.

Obviously, you must set up your list of commands so that all possible abbreviations match only one pattern word. As an error check, the routine that calls *strfit* could notify the user if it finds two matches for a given abbreviation.

EDN

To Vote For This Design, Circle No 749

500-kHz switcher produces -5V

David Sherman

Intermec, Lynnwood, WA

The 500-kHz switching regulator in Fig 1 produces -5V at 5 to 40 mA from a 5V supply. The circuit uses only surface-mount components. The output regulation is 4 mV for a load variation of 5 to 30 mA. The circuit's efficiency is 82% for a 37-mA load.

The figure shows IC_{1A} and IC_{1B} forming a standard

2-inverter oscillator. Obviously, you can substitute an appropriate system clock for this oscillator's output. The 500-kHz clock signal goes to a current-controlled, pulse-width modulator comprising Q₁, D₁, C₂, and Schmitt trigger IC_{1C}. This modulator generates a sawtooth waveform of variable slope across C₂, which results in a variable duty-cycle pulse train at the output of IC_{1C}. Pin 9 of IC_{1C}, shown connected to 5V, could also function as a power-down input. If you bring this




Fig 1—This 500-kHz switcher produces -5V from a 5V supply and uses only surface-mount components.

At Signetics, we let our data communications line do the talking.

In this day and age of big talk and lofty promises, we prefer to let our data communications family speak for itself.

Why? Because it speaks exactly to your need for high performance. And high reliability. All in a range of technologies and packages to solve applications from peripherals and multiplexers to LANs, fiber optic networks and more.

One example is our new CMOS SCC2698B Octal UART from the serial communications family. It delivers eight full duplex channels and support circuits in a single, low-power chip.

Or, from our transmitter/receiver family, there's the new NE5211 transimpedance amplifier for applications that require high input sensitivity such as fiber optic receivers and extended communication links. And, for communication buffer management, our new N74LS429 FIFO RAM controller addresses up to 64K locations using very little board space for very large buffer implementation.

We're Signetics. We've got the guts—those essential data communications products to improve system performance. For your free information packet, call (800) 227-1817, ext. 995D. Or for military product availability, contact your local Signetics sales office. You'll learn why we speak softly—and carry a big line.

One standard.  defects.

Signetics

a division of North American Philips Corporation



DESIGN IDEAS

Design Entry Blank

\$100 Cash Award for all entries selected by editors. An additional \$100 Cash Award for the winning design of each issue, determined by vote of readers. Additional \$1500 Cash Award for annual Grand Prize Design, selected among biweekly winners by vote of editors.

To: Design Ideas Editor, EDN Magazine
Cahners Publishing Co
275 Washington St, Newton, MA 02158

I hereby submit my Design Ideas entry.

Name _____

Title _____ Phone _____

Company _____

Division (if any) _____

Street _____

City _____ State _____ Zip _____

Design Title _____

Home Address _____

Social Security Number _____

(Must accompany all Design Ideas submitted by US authors)

Entry blank must accompany all entries. Design entered must be submitted exclusively to EDN, must not be patented, and must have no patent pending. Design must be original with author(s), must not have been previously published (limited-distribution house organs excepted), and must have been constructed and tested.

Exclusive publishing rights remain with Cahners Publishing Co unless entry is returned to author or editor gives written permission for publication elsewhere.

In submitting my entry, I agree to abide by the rules of the Design Ideas Program.

Signed _____

Date _____

ISSUE WINNER

The winning Design Idea for the January 5, 1989, issue is entitled "555 timer triggers on millivolt signal," submitted by John J O'Farrell of The Tran-Trol Co (Tallahassee, FL).

Your vote determines this issue's winner. All designs published win \$100 cash. All issue winners receive an additional \$100 and become eligible for the annual \$1500 Grand Prize. **Vote now**, by circling the appropriate number on the reader inquiry card.

pin low, the regulator will safely shut down in a low-power mode.


The key to this regulator's ability to switch a bipolar transistor efficiently at such a high frequency is the drive circuit, which comprises C_3 , R_4 , and Q_3 . When the pulse-width modulator's output is low, a constant current of approximately 1.8 mA flows through Q_2 's base via Q_3 . During this on-time, C_3 charges to 4.3V. Because of the excess charge stored in its base, Q_2 would ordinarily turn off slowly, but when the pulse-width modulator's output goes high, C_3 reverse biases the base of Q_2 . C_3 then dispenses exactly enough charge to cancel out the stored charge in Q_2 and quickly stop current flowing through Q_2 . Meanwhile, Q_3 also turns off rapidly because its biasing has prevented it from saturating. At this point, the voltage across C_3 is somewhat less than 3.2V because some of the charge has been removed.

When the pulse-width modulator's output once again goes low, a narrow, high-current pulse flows through the base of Q_2 to recharge C_3 . This pulse also assures that Q_2 turns on rapidly. Then, Q_3 supplies the sustaining current described earlier.

This circuit uses a bipolar transistor for its switch instead of an FET because surface-mount FETs either require large amounts of pc-board area or have high on-resistances, which result in unacceptably low efficiencies. Furthermore, low on-resistance SOT-23 FETs are several times the price of SOT-23 bipolar transistors.

The remainder of this regulator is conventional. A small surface-mount inductor, L_1 , such as TDK's NL453232-270K, provides energy storage; a Schottky diode, D_2 , rectifies the output. IC_{3A} , which can be any single-supply op amp, serves as the error amplifier. If you need higher current, reduce the value of L_1 ; at lighter loads, increasing L_1 will boost efficiency. R_5 and R_6 set the ratio of output voltage to reference voltage. Thus, you can set the output level at any negative voltage within the breakdown limits of D_2 and Q_2 . If your input-voltage level is sufficiently accurate and you do not need a reference for other circuitry, you can double R_5 and use the 5V input as the reference. In any case, the base of Q_3 must connect to a voltage between 2 and 3V that is bypassed with a 0.1- μ F capacitor. **EDN**

To Vote For This Design, Circle No 748



Products of Your Environment.

A field-use fiber optic connector so tough, you could roll a 5 ton truck over it. A Parallel Interconnect that allows a gas-tight interface in 60 seconds flat. A cabling assembly enabling a single connector to handle electronic signals, fiber optics and power supply.

These are but a few innovations in interconnections from ITT Cannon. But we couldn't have done it without you. Because success throughout our company relies on a thorough knowledge of your company's environment.

Take strategic partnering, for example. We don't create a custom solution by shaking your hand and jotting down a few notes. When we design-in, we get *inside* your environment.

Then there's Cannon's near-zero defect rate. It got that way, and stays that way, because we test each product in a carefully simulated environment.

As for delivery, we built a dependable system by studying the needs and scheduling realities of our customers' business environments worldwide.

And Cannon stays price competitive by always asking the question, "How will this connector be used?" Considering the connector's ultimate environment has taught us that keeping quality high ends up costing our customer less.


So if you'd like a partner who will take the time to learn about your environment, take a moment to contact ITT Cannon at (714) 261-5300.

Worldwide Headquarters
1851 East Deere Avenue
Post Office Box 35000
Santa Ana, CA 92705-6500

ITT Cannon
An ITT ElectroMechanical Components Worldwide Company
Discover our strengths.

CIRCLE NO 67

Robinson Nugent "SWAT Team"* Service solves your socket problems fast, fast, fast!




What do you need right now?
Quick quotes? Fast samples?
Early delivery?
Call for "SWAT Team" Service
(812) 948-0564 today!

What do you need... 1,000 or 1,000,000 pieces? We can deliver standard or custom screw machine sockets at an affordable low price—with quick delivery. Contact the RN "SWAT Team"—an elite group of experienced service engineers whose primary job is to get you quick quotes, fast samples, early delivery. We attack your problems with **Swift Work And Tenacity**. You get fast and certain answers every time.

Our "SWAT Team" Service can solve your socketing problems now.

Just call (812) 948-0564 for fast answers.

***The "SWAT Team" attacks your problems with Swift Work And Tenacity.**



Robinson Nugent offers the greatest variety of screw machine sockets—RN has 'em all.

PGA SOCKETS

- High temperature bodies, molded standoffs.
- Custom polarized to device and board.
- 8 × 8 thru 21 × 21 grid sizes.
- Zero profile disposal carriers.
- Elevated profile for additional cooling.
- Retentive pins secure component during wave solder.
- Mating pin header for high density board stacking.
- Long lead for multilayer board applications.

DIP/SIP CONFIGURATIONS


- Open frame for component placement.
- Automatic insertion options.
- Single in-line straight and right angle mounting.
- Low Profile.
- Elevated profile stacking option.
- Solderless press fit for back planes.
- Long lead for multilayer boards.

For information on any of these sockets just

CIRCLE NO 47

Robinson Nugent

800 East Eighth Street, New Albany, IN 47150 • Phone: (812) 945-0211 FAX: (812) 945-0804
In Europe: Rue St. Georges 6, CH2800 Delmont, Switzerland • Phone: (066) 22-9822 FAX: 011-41-622-9813



What kind of socketing problems do you have? These companies got fast response, fast solutions with RN "SWAT Team" SERVICE.

Customer "X" could not get delivery of custom PGA low profile sockets. RN responded with samples in 24 hours—product in three weeks.

Customer "G" had high extraction forces with his PGA sockets. The "SWAT Team" shipped low force PGA sockets in 24 hours.

Customer "C" had melting troubles with his PGA sockets during vapor phase soldering. High temp. PGA sockets from the "SWAT Team" solved problems fast.

Customer "T" needed a DIP socket, custom elevated with long pins to improve board density without going to surface mounting. RN "SWAT Team" sent samples competition couldn't match. Delivery of production sockets in only four weeks.

Customer "I" had DIP devices that could not solder properly to a thick board, he needed a solution fast. The "SWAT Team" responded with samples of long lead sockets the same day...and production sockets in just three days.

Dependable "SWAT Team" service is as close as your phone: CALL (812) 948-0564 NOW.



"The RN "SWAT Team" has been put in place to deliver fast answers to your tough socketing problems. You talk directly to selected service engineers whose job it is to get you quick quotes, fast samples, early delivery. Try the "SWAT Team" service. I personally guarantee you'll get the answers you need—and get them fast."



R.A. Lindenmuth
R.A. Lindenmuth
President/CEO

**SEE HOW
YOUR
CONNECTOR
MEASURES UP
TO OURS.**

If your present I/O connector can completely cover the new Fujitsu Series 230 pictured on this page, you've got a large problem.

You're wasting valuable board space.

Space you could use to cram in a few extra components. Or space you could eliminate entirely to reduce manufacturing costs.

Fact is, the Series 230's remarkably compact 1.27mm (.50") pitch and remarkably efficient 4-row, zig-zag terminal layout pack provides all the pinout you're used to in 40% less real estate.

More than that, the cable mount plug and board mount socket, in 50 and 68 positions, conforms to the SCSI II and III standards adopted by ANSI.

And, every Series 230 connector also includes features like a standard "D" shape polarization header, EMI shield, plug/socket lock and minimum-pressure insertion/withdrawal fitting. All with no extra size.

So, before you run out of space on your next compact or portable system design, call us at **(408) 562-1000** or see the EEM Catalog. For a complete list of local distributors and representatives write to Fujitsu Component of America, Inc., 3330 Scott Boulevard, Santa Clara, California 95054-3197.

We'll keep you from coming up short.

CIRCLE NO 123

FUJITSU
FUJITSU
COMPONENT OF AMERICA

PHOTO SHOWN ACTUAL SIZE



**NOW SCSI II/III
STANDARD.**




NEW PRODUCTS

COMPONENTS & POWER SUPPLIES

DIGITAL PANEL METER

- Draws only 145 μ A
- Handles inputs of ± 200 mV to ± 200 V dc.


The DP-176 3½-digit LCD digital panel meter draws only 145 μ A when operating from a 5 to 15V dc primary power source. You can configure the meter to accept analog inputs ranging from ± 200 mV to ± 200 V dc. The LCD features user-selectable decimal-point placements, a Hold function, and an all-digit test pin. Features include an 86-dB CMRR, $\pm 0.1\%$ FS accuracy, automatic polarity changeover, over- and under-range indication, $10^9\Omega$ input impedance, and external reference input for ratiometric tracking. A temperature coefficient of ± 100 ppm allows the meter to



operate at maximum accuracy under broad temperature variations. Operating range spans 0 to 50°C. \$59.

Acculex, 440 Myles Standish Blvd, Taunton, MA 02780. Phone (508) 880-3660. TLX 503989.

Circle No 351



DC/DC CONVERTERS

- Design minimizes EMI/RFI
- Feature 87% efficiency

Series 2100 20W dc/dc converters are available in single-, dual-, and triple-output versions. The units offer a 13.3W/in.³ power density, an 87% efficiency, and 50-mV p-p output noise. Input-to-output isolation of 500V dc min allows the outputs to float with respect to the inputs. Continuous 6-sided shielding minimizes EMI/RFI problems. Converters are available with input ranges

of 9 to 18, 18 to 36, and 36 to 72V. Standard outputs are 5, 12, 15, ± 12 , ± 15 , $5/\pm 12$, and $5/\pm 15$ V. Line regulation equals 0.5%; load regulation measures 0.2% for single-output models and 1% for dual-output versions. Operation range spans -25 to $+71^\circ\text{C}$. From \$129.


Conversion Devices Inc, 101 Tosca Dr, Stoughton, MA 02072. Phone (617) 341-3266.

Circle No 352

TRANSMITTERS

- Designed for harsh process environments
- Offer 1500V input-to-output isolation

Units in the 500 Series of isolated 4- to 20-mA transmitters are designed for harsh process environments. All versions are housed in hermetically sealed, die-cast metal cases and are rated for operation over a -40 to $+85^\circ\text{C}$ range. The transmitters feature 1500V rms input-to-output isolation, 2-wire operation, and wide zero suppression



for turndown ratios as high as 10:1. Model 502A accommodates type J, K, T, E, R, S, or B thermocouples. Model 504 accepts low-level inputs with a 5- to 100-mV span, and Model 506 handles signals with a span of 1 to 50V. Model 505 is a 4- to 20-mA current-loop isolator. Model 508A is a companion loop-powered digital LCD indicator with zero and span adjustments for direct readout in engineering units. It features the same environmental specifications as the transmitters. \$269 and \$249 for models with temperature and voltage/current inputs, respectively.

Newport Electronics Inc, 2229 S Yale St, Santa Ana, CA 92704. Phone (714) 540-4914. TWX 910-595-1787.

Circle No 353

PANEL METER

- Meets MIL specs
- Has a self-shielding design

The Model 2150 edgewise meter is a military-type panel meter that meets the applicable requirements of MIL-M-10304 and MIL-M-16034. Accuracy for dc and ac readings are ± 2 and ± 3 , respectively, and re-


sponse time measures 2 sec. A zero-adjust control is external. The meter's permanent-magnet, moving-coil movement is self-shielding, and the sealed waterproof case is an effective shield. You can juxtapose the meters without having to worry about magnetic interaction problems. The meter is housed in a black

plated-steel case with a glass window and is available with red or white illumination. \$291.

International Instruments, Box 185, North Branford, CT 06471. Phone (203) 481-5781. FAX 203-481-8937.

Circle No 354

VME to DEC, GOULD/SEL...



Who has the right DMA interface at the right price for your VMEbus connection?

VMIC manufactures a line of parallel DMA interface controllers that allow VMEbus connection to a wide variety of host computers including DEC, Gould/SEL, Harris, IBM, Concurrent, Elxsi, Alliant, Data General, Sun Microsystems, or any other VMEbus based system.

These high-speed VME-to-VME links support 8, 16, and 32 bit data transfers ranging from 2.25 Mbytes/sec to 4.65 Mbytes/sec. The VMEnet II™ interface allows the user to link up to 31 totally independent VMEbus systems together in one high-

speed network. For more information about the RIGHT VMEbus solution call:



VME Microsystems International Corp.
12090 South Memorial Parkway
Huntsville, Alabama 35803
(205) 880-0444
Toll Free 1-800-322-3616/ext. 389
Fax (205) 882-0859

DEC is a registered trademark of Digital Equipment Corporation. VMEnet II™ is a trademark of VME Microsystems International Corporation.


INTERNATIONAL DISTRIBUTOR: Diamond Point International, Inc. • 9 Enterprise Close, Medway City Estate, Rochester-upon-Medway, Kent • (44) (0634) 722330 • FAX: (44) (0634) 722338 • CANADIAN DISTRIBUTOR: Tracan Electronics Corp. • 1200 Aerowood Dr., Unit 4, Mississauga, Ontario L4W 2S7 • (416) 625-7752.

SENSORS

- Detect any light reflection
 - Not dependent on light intensity
- MQ area reflective photosensors respond to the reflection of any light from an object over 1 in. to more than 2 ft. Because they are insensitive to the color or surface condition of the reflecting target, the sensors will detect a wide range of colors, materials, and shapes. Any contamination on the lens will not affect the reliability of operation, because the photosensors are not dependent on light intensity. Sensors are available in both visible and infrared light versions and can be ordered with either an npn- or pnp-type output.

Aromat Corp, Industrial Products Div, 629 Central Ave, New Providence, NJ 07974. Phone (201) 464-3550. FAX 201-464-8513.

Circle No 355




PROTOTYPING KIT

- Allows you to evaluate a 3-dimensional interconnect system
- Provides a fully functional microcomputer

The Chiprack Designer's Kit comprises a complete microcomputer system in a 7x4x4-cm component

Demanding Designers Need the Best

OrCAD/SDT III Schematic Design Tools for the PC



Ease-of-use + Power = Productivity

In today's tough design environment, good engineering tools aren't good enough. You need the best to get the job done.

OrCAD/SDT III offers the power

SDT III comes with the options you'd expect to pay extra for

- **Completeness:** A library of over 6100 parts that you can browse through in a breeze. Utilities to generate Bill-of-Materials, Electrical rules check, create custom library parts.
- **Compatibility:** Over thirty netlist formats, over 50 supported display adapters, over 50 printer drivers, a dozen plotter drivers. We conform to your system better than anyone.

- **Complexity:** 4000+ sheet design capacity for single designs. 200+ levels of hierarchy. Great support for small, simple designs to large, complex hierarchical systems.
- **Control:** SDT III gives you the ability to customize the work environment to make you more productive. This includes user definable macros, text/object sizes, sheet sizes, graphical object editor, even the colors on the screen.

OrCAD/SDT III makes it easy

The lightning fast operation saves time. The intuitive, pop-up menu displays your most likely next action. This means a short learning curve and immediate productivity.

Only \$
495

Get our No-risk, Demo Disk

Try before you buy. Get our free demonstration disk and see for yourself the solid performance SDT III has to offer.

Once you've given our demo disk a spin, you'll know one of the reasons why OrCAD is the world's leading supplier of PC based CAE tools.

All OrCAD products come complete with one full year of technical telephone support, free product updates and access to our 24 hour BBS.

OrCAD 
Systems Corporation

1049 S.W. Baseline Street Suite 500
Hillsboro, Oregon 97123
(503) 640-9488

If you would like more information about this or any other OrCAD product, contact your local OrCAD representative.



- | | |
|--|---|
| 1. WA, OR, MT, ID, AK
Seltech, Inc.
(206)746-7970 | 9. IN, OH, KY, WV, W. PA
Frank J. Campisano
(513)574-7111 |
| 2. N. CA, Reno NV
Elcor Associates Inc.
(408)980-8868 | 10. VA, TN, NC, SC
Tingen Technical Sales
(919)870-6670 |
| 3. So. CA
A D G
(714)897-0319 | 11. FL
High Tech Support
(813)920-7564 |
| 4. Las Vegas, UT, AZ, NM, CO
Tusar Corporation
(602)998-3688 | 12. MS, AL, GA
Electro-Cadd
(404)446-7523 |
| 5. ND, SD, MN, W. WI
Comstrand, Inc.
(612)788-9234 | 13. DE, MD, DC, E. PA, NJ, NY
Beta Lambda, Inc.
(201)446-1100 |
| 6. NE, KS, IA, MO
Walker Engineering
(913)888-0089 | 14. CT, RI, MA, VT, NH, ME
DGA Associates
(617)935-3001 |
| 7. TX, OK, AR, LA
Abcor, Inc.
(713)486-9251 | 15. BC, AB, SK, MB
Interworld Electronics, Ltd.
(604)984-4171 |
| 8. MI, E. WI, IL
MacKellar Associates
(313)335-4440 | 16. ON, PQ & Maritimes
Electralert, LTD.
(416)475-6730 |

Call today for your FREE Demo Disk!

stack and provides a practical example of the packing density attainable with the company's Chiprack 3-dimensional interconnection system. The stack contains a 68070 μ P, an RS-232C interface, an ASIC that provides a memory interface and support logic for the μ P, 64k bytes of one-time-programmable CMOS

ROM for monitor software, and 64k bytes of CMOS static RAM. You can add other Chiprack carriers to increase the memory capacity to 512k bytes. The Chiprack stack is mounted on a mother board that contains a prototyping area and address- and data-bus buffers for the μ P. Options include a PC-com-

patible interface card and a cross-assembler. Approximately £400 to £700.

Dowty Interconnect, Knaves Beech Business Centre, Loudwater, High Wycombe, Buckinghamshire HP10 9UT, UK. Phone (0628) 810810. TLX 846874. FAX 0628-810813.

Circle No 357

Dowty Interconnect, 805 E 20th St, Santa Ana, CA 92706. Phone (714) 558-1295. FAX 714-752-6082.

Circle No 358

State of the Heart

68030 & 68020 Real-Time Program Analyzer

(Also Supporting the 68010, 68000 and 68008)

VMETRO PMA-030*




VMETRO's PMA-030 is an extremely powerful and compact instrument that enables you to give your processor a thorough checkup. Operated from a remote or on-site ASCII terminal, the PMA-030 is the ultimate tool for real-time program debugging, verification and performance analysis. The compact size of the base unit, and its small detachable target processor adaptors make the PMA-030 ideal for applications where portability is crucial. The tiny, low-cost target adaptors may also be installed permanently on the processor board to provide immediate access to the target without halting processor operation. Support for the entire 68000 family is contained in firmware, allowing the user to connect to any target by merely inserting the proper probe.

The PMA-030 is flexible and convenient to use with the following advanced features: **Triggering:** Logic state analysis on 92 signals with complex user-defined trigger sequences of up to four full width events give the user complete control over the data to be analyzed. **Filtering:** Store qualifiers on any combination of all signals and events enable buffering of useful information only in 2K trace buffer. **Performance analysis:** Cache Hit Rate, Interrupt Activity and Event count histograms are based on a near 100% Capture Ratio of the data stream and not just a snapshot common in less capable and more expensive instruments.

Output: The data sampled may be presented numerically, decoded, disassembled or graphically on your ASCII terminal, printer or transferred externally to disk.

*Stethoscope not included




VMETRO

VMETRO, INC.
2500 Wilcrest, Suite 550, Houston, Texas 77042
TEL/(713) 266-6430, FAX/(713) 266-6919

To receive a free consultation on how to find the state of your heart, call VMETRO today 713-266-6430 and ask for the doctor!

VMETRO A/S
Sognsveien 75, N-0855 Oslo 8, Norway
TEL/(47-2) 39 46 90, FAX/(47-2) 18 39 38



CABLE ASSEMBLIES

- Compatible with computer I/O interface
- Save pc-board space

The Mini-Din connector provides pc-board space saving of 75% when compared with standard circular DIN connectors. It is available with three to eight contact positions, and Mini-Din plugs and sockets are compatible with the new generation IBM and Apple personal-computer I/O interfaces. Standard cable assemblies are available in 1, 2, and 3m lengths with beige or black overmold. The cable section incorporates 28 AWG stranded conductors with foil wrap/drain wire shielding and PVC jackets. The cables have a 500V ac voltage rating and a -40 to +70°C operating range. \$5.19 (OEM qty) for a 1m plug/cable assembly.

Cinch Connectors, 1501 Morse Ave, Elk Grove Village, IL 60007. Phone (312) 981-6000.

Circle No 356

Text continued on pg 230

EDN April 13, 1989



The meeting that should never have happened.

When a disk drive crashes, you're in trouble. To an irate customer, it doesn't matter that you purchased the drive from someone else. *Your* logo is on the system.

This means you need a disk drive supplier who is also a *partner*... a company who understands what it's like to compete in today's tough computer systems marketplaces. That company is Hitachi.

An intimate knowledge of the disk drive business.

When you decide to do business with Hitachi, you get more than just a high quality, incredibly reliable disk drive. You also get the support, resources, and expertise of a \$40 billion dollar company who's one of the largest OEM computer systems manufacturers in the world. We use disk drives in our own systems, and risk losing customers if drives fail. Just like you.

This means we know what it takes to make the best. We design and build our own motors, heads, microprocessors, and custom LSIs to our own stringent specs—all checked by the most stringent Quality Assurance program in the industry.

We have over 1,500 engineers who work on nothing but disk drives. They're supported by nearly two decades of

experience manufacturing disk drives, and over 16,000 employees in R&D throughout the company.

A serious commitment to the disk drive business.

Hitachi continues to advance storage technology, through the ongoing development and manufacturing of new 5.25", 8", and 8.8" Winchester, magnetic tape subsystems and ultra-high density optical disk subsystems. We plan on being in this business for a *long* time... making sure your customers call with orders, not complaints. Next time, specify Hitachi.

Fast Action: To get information or product literature immediately, CALL TOLL FREE 1-800-538-8157, Ext. 877. In California, 1-800-672-3470, Ext. 877. Ask for literature number APB-002.

Regional Sales Offices: Waltham, MA 617/890-0804, Dallas, TX 214/991-7983, Brea, CA 714/993-1610, San Bruno, CA 415/872-1902.



Hitachi offers a complete line of Winchester, magnetic tape, and optical storage products with speeds, capacities and interfaces for virtually any application.

Hitachi America, Ltd.
Computer Division
950 Elm Avenue, Suite 100
San Bruno, CA 94066



Discover the Complete Electronic Package



NATIONAL ELECTRONIC PACKAGING AND PRODUCTION CONFERENCE
NEPCON
EAST '89

4-Day Conference,
June 12-15, 1989
3-Day Exhibition,
June 13-15, 1989

Bayside Exposition Center and World Trade Center, Boston

You'll see products and technologies covering the total product development cycle from design through final production and test of electronic circuits and systems—the complete package.

Two complete exhibit sites Bayside Expo Center and World Trade Center will be filled to capacity with leading edge products and services that can help you stay competitive.

Hungry for knowledge? Over 150 of your industry colleagues are delivering up-to-the-minute technical presentations as part of the Nepcon East Conference.

DISCOVER – The East Coasts most complete SMT resource with over half of the 600 exhibitors showing products for surface mount technology.

DISCOVER – design solutions at the East Coast premier of EPCAD, the Electronic Packaging Computer Aided Design Center featuring design automation tools.

DISCOVER – practical techniques for high density packaging—TAB, fine pitch technology, multi-chip modules and more.

DISCOVER – products and strategies for assurance of high quality production: design for manufacturability, automating inspection, total process control.

DISCOVER – the future of electronics design and manufacturing at Nepcon East '89.

Mail in the coupon to receive full information and registration materials. If you pre-register before May 26 you gain free admission to exhibits and earn a discount on the conference.


Call 312 299-9311 or mail in coupon below:

CLIP AND MAIL TO: EDN041389
NEPCON East '89 Registration
Cahners Exposition Group
1350 E. Touhy Ave. P.O. Box 5060 Des Plaines, IL 60017-5060
PLEASE SEND ME PRE-REGISTRATION MATERIALS FOR NEPCON EAST '89

NAME _____
TITLE _____
COMPANY _____
ADDRESS _____
CITY _____
STATE _____ ZIP _____
 My company is interested in exhibiting at future NEPCON events.
Call me at _____

J1

Everything you need to know about Motorola One Time Programmables. Now at a one- time-only price of \$87.54 from Hall-Mark.*



Now's the time to take advantage of Motorola's new OTP Microcontroller (MCU) course. Learn the technology of tomorrow and qualify for a free kit.

One Time Programmables are natural replacements for standard logic designs. OTP designs mean higher reliability, more flexibility, off-the-shelf delivery, lower system costs and fewer chips.

If you want to learn OTP design including hardware and software operations, call Hall-Mark for the Motorola OTP kit. You'll receive a complete training package including a Microcontroller training course manual, an assembled programming/education board with a ceramic-windowed 68HC705C8S, and development software. Use your Macintosh®, IBM PC®, or PC compatible for best results. You may also transfer programs from a standard 8K × 8 EPROM into the OTP MCU. The course teaches you the process now so you can speed through designs later.

You'll profit from the information, but you can also earn back the cost of the kit by taking the optional OTP test. If you score 100%, you'll be eligible to win a Mac® II. If your score is 90% or more, you'll qualify for a free course.

Motorola and Hall-Mark want to make it easy for you to get up to speed on the technology that is changing ideas about logic. And if all you want is someone to program your OTP devices, call your nearest Hall-Mark office for all the details.

When it comes to OTP, Motorola and Hall-Mark have everything you need and need to know.



Hall-Mark Electronics Corporation • Dallas, Texas

Delivering on Motorola OTP technology.

Alabama
Huntsville (205) 837-8700

Arizona
Phoenix (602) 437-1200

California
Bay Area (408) 432-0900
Orange County (714) 727-6000
Sacramento (916) 624-9781
San Diego (619) 268-1201
San Fernando Valley (818) 773-4500

Colorado
Denver (303) 790-1662

Connecticut
Connecticut (203) 271-2844

Florida
Ft. Lauderdale (305) 971-9280
Orlando (407) 830-5855
Tampa Bay (813) 530-4543

Georgia
Atlanta (404) 447-8000

Illinois
Chicago (312) 860-3800

Indiana
Indianapolis (317) 872-8875

Kansas
Kansas City (913) 888-4747

Maryland
Baltimore (301) 988-9800

Massachusetts
Boston (617) 935-9777

Michigan
Detroit (313) 462-1205

Minnesota
Minneapolis (612) 941-2600

Missouri
St. Louis (314) 291-5350

New Jersey
Fairfield (201) 575-4415

New York
Long Island (516) 737-0600
Rochester (716) 244-9290

North Carolina
Raleigh (919) 872-0712

Ohio
Cleveland (216) 349-4632
Southern Ohio (614) 888-3313

Oklahoma
Tulsa (918) 254-6110

Pennsylvania
Philadelphia (215) 355-7300

Texas
Austin (512) 258-8848
Dallas (214) 553-4300
Houston (713) 781-6100

Utah
Salt Lake City (801) 972-1008

Washington
Seattle (206) 547-0415

Wisconsin
Milwaukee (414) 797-7844

Send to: Hall-Mark Electronics Corporation
Attn: Glenn Whitehead/11333 Pagemill Rd./MS 667/Dallas, TX 75243

Yes, I want the MCU training course and the \$80.51 discount (final price: \$87.54).

Name _____

Title _____ Phone (____) _____

Company _____

Address _____


City, State, Zip _____

This portion to be filled out by distributor only:

Distributor _____ Branch Code _____

Salesperson's Name _____ SS# _____

Invoice # _____ Audit Confirmation _____



CONNECTORS

- Fully compatible with robotics
- Have 10 to 60 positions

Edgemate connectors replace gold edges on daughter cards without requiring costly redesign. They feature recessed gold-plated fingers to prevent accidental peelback during mating. The connectors mate with any card-edge connector that has a 0.1-in. contact spacing. They are

available with 10 to 60 positions and are fully compatible with robotics. Registration features and true-position solder legs aid in pick and placement operations. Top-activated eyelets eliminate the need for any ancillary tooling. The connectors come in tube packages to provide compatibility with automatic feed stations. \$0.09 (1000). Delivery, six to 10 weeks ARO.


AMP Inc, Box 3608, Harrisburg, PA 17105. Phone (717) 564-0100. FAX 717-561-6179.

Circle No 359

VXI BUS CHASSIS

- Includes a power supply
- Designed for ATE applications

This C-size VXI Bus chassis is designed for both military and commercial ATE applications. It features an 8-output power supply and a 12-layer backplane. DIP switches



route the daisy-chained signals through the backplane, so you don't need jumpers to span empty slots in the chassis. A cable tray allows you to easily integrate VXI Bus instruments with other GPIB instrumentation. Rack cabling enters through recessed rear connectors and is cabled via the tray to the bus instruments. The tray also features a cover to minimize internal dust problems. A cooling system pulls air in through the sides of the

Every copier company talks We're doing something about


Choosing a new copier isn't easy. You look at copiers, you listen to promises. It all gets very confusing.

Now, you don't have to listen to a lot of talk about promises. You can read ours. Because we put it in writing. If you try to compare it to other copier guarantees, you'll find there's no comparison. Suddenly, a difficult decision becomes a very easy choice to make.

Look at the certificate above. Nobody offers you as good a copier guarantee as Harris/3M. So, while

copier salespeople are all giving you a lot of talk, ours will give you something great to read.

Send in the coupon. Or give us a call at 1-800-TLC-COPY. (In Canada, 1-519-668-2230.) We'll send you our 8-page *Consumer Guide to Copiers*. Then, we can talk about it.



Harris/3M copiers have features for all sizes of offices. That includes the 6070. Seventy copies a minute, guaranteed.

COMPONENTS & POWER SUPPLIES

chassis and blows it out the rear. The chassis comes with a removable, hinged front door made of transparent plastic. \$6350.

Racal-Dana Instruments Inc, 4 Goodyear St, Irvine, CA 92718. Phone (714) 859-8999. FAX 714-859-2505.

Circle No 360

PRESSURE SENSORS


- Have an extended operating range
- Feature a 100-mV output

Pix Series pressure sensors use silicon-on-insulator (SOI) technology that extends the upper end of the operating range to 250°C. The sensors have a 0- to 100-psi range (0 to 700 kPa) and come in sealed-gauge versions. The devices have a 100-mV full-scale output (FSO) and operate from a 5-mA excitation. Nonlinearity of 0.1% FSO max and

thermal errors of 3% FSO max are guaranteed over the full operating range. Stainless steel packages provide rugged housing for the chips. A thin, stainless-steel diaphragm isolates the chip from any harsh media, providing all-media compatibility. \$250. Delivery, 10 weeks ARO for evaluation units.

NovaSensor, 1055 Mission Ct, Fremont, CA 94539. Phone (415) 490-9100.

Circle No 361



BACKPLANE

- Accommodates 13 VXI Bus modules
- Conforms to revision 1.2 of the VXI Bus specification

This 13-slot VXI Bus backplane accepts A-, B-, or C-sized VXI Bus modules. It complies fully with revision 1.2 of the VXI Bus specification, and it has an active SUMbus

protection module to monitor the bus voltage and accommodate the specified variations in load characteristics. The backplane uses an 8-layer board and strip-line construction to provide exceptionally low levels of crosstalk and immunity from interference or radiation. Approximately \$1000.

Bicc-Vero Electronics Ltd, Electron Way, Chandlers Ford,

about customer satisfaction.

it.



Yes, I'd like to know more about Harris/3M copiers and the Harris/3M Copier Promise. Send to Harris/3M, P.O. Box 785, Dayton, OH 45401

NAME _____

COMPANY NAME _____

ADDRESS _____

CITY _____ STATE _____ ZIP _____

PHONE # () _____

_____ I'd also like information on your fax machines. CHN489

HARRIS/3M

Offer is valid for a limited time and other restrictions and limitations apply; see your Harris/3M sales representative for details. ©1988 Harris/3M Document Products, Inc. Harris is a trademark of the Harris Corporation. 3M is a trademark of the 3M Company.

CIRCLE NO 14

Eastleigh, Hants SO5 3ZR, UK. Phone (0703) 266300. FAX 0703-265126.

Circle No 362

Bicc-Vero Electronics Inc, 1000 Sherman Ave, Hamden, CT 06514. (203) 288-8001. FAX 203-287-0062.

Circle No 363

OPTICAL LINK

- Has a 2-km transmission distance capability
- Operates from 5V dc

Operating at 1300 nm, the EDL-1300 Series fiber-optic data link transmits serial digital TTL data over multimode optical-fiber cable at distances in excess of 2 km. The link can accommodate data rates ranging to 50M bps. Each transmitter and receiver is housed in a 16-pin DIP, which contains an integral ST-compatible connector. The transmitter and receiver module

operates over a 0-to-70°C range. The link loss-budget equals 15 dB. The module operates from a 5V dc supply and provides a direct interface with TTL circuitry. Transmitter/receiver set, \$320.

PCO Inc, 20200 Sunburst St, Chatsworth, CA 91311. Phone (818) 700-1233.

Circle No 364

CRYSTAL OSCILLATORS

- Cover frequency range 375 kHz to 30 MHz
- Are housed in surface mounting packages

QC6111 and QC6112 crystal oscillators are packaged in 40-pad, surface-mounting, ceramic leadless chip carriers. They cover frequencies from 375 kHz to 30 MHz. QC6111 devices drive two standard TTL loads or 50 pF at logic levels of 10 and 90% of their supply volt-

age, and their maximum power dissipation ranges from 55 to 90 mW. QC6112 devices drive 10 standard TTL loads at TTL-compatible logic levels, and have power dissipations from 130 to 250 mW. Both series achieve maximum rise and fall times of 10 nsec. Versions with operating temperature ranges of -40 to +85°C are available with stabilities over ±35 or ±60 ppm. Versions with operating temperature ranges of -55 to +125°C are available with stabilities over ±60 or ±100 ppm. All of the oscillators operate from a 5V ±10% supply. £40 to £50 for sample quantities.

Salford Electrical Instruments Ltd Times Mill, Heywood, Lancashire OL10 4NE, UK. Phone (0706) 67501. TLX 635106. FAX 0706-64394.

Circle No 365

A POWERFUL ARGUMENT.

OTHER POWER SUPPLIES CAN'T. CANDELA CAN.


Candela HVD power supplies offer important advantages to OEM's.

Whatever your high voltage pulse power requirement, a Candela HVD power supply will improve both performance and reliability. A full line of standard and custom products is available. For more information contact Candela, the leader in dye lasers and capacitor charging power supplies.



Candela Laser Corporation, Wayland, MA Telephone (800) 255-1287 Dept. 205 or in MA (508) 358-7637

Super-natural capacitance.



Nature endows every object with some capacitance. But to equal the 2.2F capacitance that NEC has packed into its 14cm³ Supercaps, nature would require 3,100 spheres the size of planet earth.

Creating large capacitance in small cases has been NEC's specialty

for decades. We achieve it through intensive R&D programs that begin with materials and cover every phase of design and production.

You can see the results in our Supercaps. And our chip tantalum capacitors that offer ratings up to 6.8 μ F in the industry's smallest

surface-mount cases (only 1.6 x 3.2 x 1.6mm).

When you need capacitors with exceptional capabilities, come to NEC. We think small to help you think big. For more information about our innovative capacitor lineup, call NEC today.

For fast answers, call us at:

USA Tel:1-800-632-3531. TWX:910-379-6985. W. Germany Tel:0211-650302. Telex:8589960. The Netherlands Tel: 040-445-845. Telex:51923. Sweden Tel:08-753-6020. Telex:13839. France Tel:1-3946-9617. Telex:699499. Italy Tel:02-6709108. Telex:315355. UK Tel:0908-691133. Telex:826791. Hong Kong Tel:3-755-9008. Telex:54561. Taiwan Tel:02-522-4192. Telex:22372. Singapore Tel:4819881. Telex:39726. Australia Tel:03-267-6355. Telex:38343.

**GET MORE ROOM ON
YOUR CIRCUIT BOARD**

3.5 = 7+

mm spacing

circuits-per-inch



ACTUAL SIZE

Now you can design with 7+ -circuits-per-inch density. These new BUCHANAN subminiature electronic connectors provide the 3.5mm spacing that beats the competition's 5mm spacing hands down. This increased density lets you make the most of your valuable board space. And you get the choice of horizontal or vertical wire entry within a wire range of 14-20AWG.

PLUS: ■ Only a screwdriver needed to make connections. ■ Eliminates soldering, crimping, wrapping, and lugging. ■ Connectors maintain 3.5mm spacing when mounted end-to-end. ■ Rugged nylon 6/6 polyamid housing. ■ Hot-tin-dipped brass terminal contacts. ■ 15 Amps max. rating.

Try a free sample in your application. See for yourself what this new SMB series connector can do for you. We'll be glad to put a sample in your hands. Just drop us a note on your letterhead. Or, if you can't wait to get your hands on one, give us a call at 201-992-8400

For 5mm and 10mm applications ask about the BUCHANAN SSB4/5 series in one-piece and plug-in configurations.

406A



**INDUSTRIAL ELECTRICAL
PRODUCTS**

AMERACE CORPORATION
INDUSTRIAL ELECTRICAL PRODUCTS
530 W. MT. PLEASANT AVENUE
LIVINGSTON, NJ 07039 ■ (201) 992-8400
TELEX: 13-8403 ■ FAX: 201-992-9416

BUCHANAN®

CIRCLE NO 42

DEC TU58 - VT 103

Need a replacement?



If you're struggling with a TU58 cartridge system, Walton Data Systems have an answer - the Digifiler micro disc. Based around a standard 3½ disc, the system has been designed to be plug compatible with the DEC TU58. Digifiler gives speed advantages of over 10 times, storage capacity of 4 times and at least 10 times cheaper media.




Walton Data Systems

Walton Data Systems, Aircraft Esplanade, Farnborough, Hants GU14 6TG, England. Tel. (+44) 252 549657. Fax. (+44) 252 549657. Telex: 856614.

**FREE INFORMATION
PACK**

CIRCLE NO 124

CROSS DEVELOPMENT SOFTWARE THAT'S MAKING NETWORK NEWS.



And the news is network pricing. Validate*/XEL, the cross development software with the best support in the business, has network licensing. So now you can have all the cross development power you need for all the engineers who need it. Without paying for individual licenses for each workstation.

With Validate/XEL your development team can stop playing musical chairs. And contribute more in less time for less money.

Validate/XEL is a high perfor-

mance package for your Sun, VAX or PC. It includes a source level debugger, a compiler and an assembler that work with either a simulator or emulator. And whenever you need help, our large staff of qualified field and in-house applications engineers is at your service.

When you use Validate/XEL with one of our real time, transparent emulators, you'll be even more efficient and productive. You'll have the ability to debug your code inside the target

system in real time. And with our high speed SCSI interface to your Sun or PC, you'll be able to download to your target system in record speed.

For more information or a demonstration on your network, call toll-free. In WA call (206) 882-2000. Or write Applied Microsystems Corporation, P.O. Box 97002, Redmond, Washington, USA 98073-9702.



Applied Microsystems Corporation

1-800-426-3925

In Europe contact Applied Microsystems Corporation Ltd., Chiltern Court, High Street, Wendover, Aylesbury, Bucks HP22 6EP, United Kingdom. Call 44-(0)-296-625462.
In Japan contact Applied Microsystems Japan Ltd., Nihon Seimei, Nishi-Gotanda Building, 7-24-5 Nishi-Gotanda, Shinagawa-KU, Tokyo T141, Japan. Call 03-493-0770.

**"SWITCH DC TO HUNDREDS OF MHZ
IN 8x8 to 64x8 CONFIGURATIONS"**



It's easy to switch eight DC to 500Mhz inputs to any of eight outputs with our Model 4108 wide-band coaxial relay matrix shown at the left. This miniaturized matrix is completely self-contained, requiring only TTL control signals and DC power. For larger systems, our Model 4076 can switch 64 signal sources to any of eight outputs under IEEE-488 control with a bandwidth of DC-300Mhz by packaging up to eight 4108 modules in a compact cabinet. These miniaturized extremely wide-band matrices are perfect

for Automatic Test Equipment (ATE) where fast rise time, wide bandwidth data from the unit under test must be connected to any array of test equipment, or in telecommunications where wideband data rates must be connected between modems, transceivers or satellite uplink/downlink terminals.

Experience—We Have It
No matter what kind of high frequency switching system you're buying, it pays to deal with a company who really understands the business. Matrix does. We've been designing state-of-the-art reed relay and semiconductor switching matrices for over 17 years—to the toughest electrical and packaging specs imaginable. Our customers include government agencies, defense contractors, the TV industry, ATE and telecommunications companies and more. So deal with the leader and be sure.



MATRIX
SYSTEMS CORPORATION

5177 NORTH DOUGLAS FIR ROAD
CALABASAS, CALIFORNIA 91302
(818) 992-6776 • TWX 910-494-4975


NEW PRODUCTS

COMPUTERS & PERIPHERALS

RS-232C ADAPTER

- Provides four serial ports for the IBM PC, PC/XT, and PC/AT
- Uses the Intel 82050 or the 82510 UART

The FASTCOM4 is a 4-channel RS-232C board for the IBM PC, PC/XT, PC/AT, and compatible computers. The standard configuration uses Intel's 82050 UART, which is fully compatible with the 16450 UART but draws only one-half the power. The board is optionally available with Intel's 82510 UART. The 82510 offers baud rates as high as 288k bps, a 4-byte receive and transmit buffer, control character recognition, and two independent baud-rate generators. The board comes with COMMBIOS and COMMBUFF software development tools. COMMBIOS has interfaces for Pascal, Turbo Pascal, Lattice C, Microsoft C, Compiled Basic, and Fortran. COMMBUFF is a high-speed buffer program which



allocates 4k bytes of buffer memory per channel. The board has a shared interrupt feature that allows as many as four boards (16 channels) to be installed in a computer. \$375. Optional 82510 UARTs, \$25 each.

An optional NVRAM that stores 32 bytes of nonvolatile data, \$35.

Commtech Inc., 8622 Mt Vernon Ct, Wichita, KS 67207. Phone (316) 651-0077.

Circle No 370

SPARC COPROCESSOR

- Board for the IBM PC/AT computer runs on MS-DOS
- Uses Cypress CY7C601 SPARC chip

The SP-ARC1 is a coprocessor board for the IBM PC/AT and compatible computers. It features the Cypress CY7C601 SPARC Chip, TI's TI8847 floating-point processor, and as much as 8M bytes of interleaved DRAM—all running at 20 MHz to deliver 12 MIPS performance. The board comes with C and FORTRAN compilers, which are derived from SUN's compilers for the Sun-4 workstation. The board lets you run software developed for the Sun-4 workstation in MS-DOS applications. Essentially, the board becomes the system CPU while the host's CPU acts as an I/O processor. The board uses the host CPU to access peripherals such as

graphics cards, A/D converters, disk controllers, and communication boards. A 4M-byte system, including compilers, costs \$7995. The same system with 8M bytes costs \$9995.


Definicon Systems Inc., 1100 Business Center Circle, Newbury Park, CA 91320. Phone (805) 499-0652. FAX 805-498-3559. TLX 272849.

Circle No 371

ARRAY PROCESSOR

- Accelerates image processing for the IBM PC/AT computer
- 32-bit floating-point processor that delivers 13.3M flops

The ASAP32 is an array-processor board for the IBM PC/AT and compatible computers. The board accelerates image processing using a 32-bit floating-point processor that de-



livers 13.3M flops. The board contains 2k x 32-bits of ROM and RAM space for storing programs. The ROM contains all of the basic mathematical, vector, and I/O functions. The host loads the RAM with microcode to execute the desired function. In addition, it contains two 4k x 32-bit static RAMs for transferring data between the frame buffer and the floating-point processor. Both SRAMs have dual ports permitting pipeline operation, alleviating bottlenecks on the PC bus. The board has an extensive set of software libraries, including image filtering, image geometry, and

a 2-dimensional FFT. The libraries are software compatible with Image Technology's ITEX call conventions. \$1350. Delivery, four to six weeks ARO.


Rapid Technology Corp, 54 Ballard St, Newton, MA 02159. Phone (617) 244-7928. FAX 617-527-3177.

Circle No 372

COLOR PRINTER


- Prints Adobe Postscript images at 300 dpi
- Uses thermal transfer for A or B size paper and transparencies

The 5232-Color Postscript Printer prints Adobe Postscript images and text at 300 dpi on A or B size paper and transparencies. There are three



Now CD-ROM Technology Can Increase Your Programming Efficiency.

With the Microsoft Programmer's Library and support hardware/software from Online, you can be up and running for as little as \$995.00!



Programmer's Library helps you work faster, not harder. The library, contained on a single CD, consists of 72 reference books and technical manuals plus 3000 sample programs (over 20MB of sample code).

You can browse through the library or do a complex 'and/or' search for key words on selected levels—in just a few seconds! You can also set electronic bookmarks, transfer selected sample code to your program, or zoom in and out to quickly search through different levels.

Network access with OPTI-NET®. Programmer's Library Version 1.1 is supplied with a limited 3 user version of OPTI-NET®. This software provides LAN access to the CD-ROM database, significantly reducing the cost per user.

Don't wait! Order today. You will receive a copy of Programmer's Library which includes a limited 3 user version of OPTI-NET®, a Sony CD-ROM drive, controller card, interface cable, MS-DOS extensions, and software drivers.

Additional titles available from Online include; Microsoft Bookshelf, Microsoft Stat Pack, Microsoft Small Business Consultant and the Grolier's New Electronic Encyclopedia. Versions of OPTI-NET® provide access to the CD-ROM databases for up to 100 users.

For Next Day Shipment Call (800) 922-9204
In Maryland call (301) 428-3700



Maryland residents add 5% state sales tax.

Package 1. Internal drive for the IBM-PC with Programmer's Library:	\$ 995.00
Package 2. External player for the IBM-PC with Programmer's Library:	\$1,095.00
Package 3. External player for the IBM-PS/2 with Programmer's Library:	\$1,195.00
OPTI-NET with 1 to 8 User License:*	\$ 795.00
OPTI-NET with 9 to 100 User License:*	\$1,495.00

Additional terminal licenses of Programmers Library @ \$65.00 per terminal (above the 3 included within the purchase of the CD Package)

*See Special Offer within Programmer's Library Version 1.1.



Sharing Information Through Technology™

Products Corporation

20251 Century Boulevard ■ Germantown, MD 20874 ■ FAX (301) 428-2903


OPTI-NET is a registered trademark of Online Computer Systems, Inc. Microsoft and MS-DOS are registered trademarks of Microsoft Corporation. Sony is a registered trademark of Sony Corporation. IBM is a registered trademark of International Business Machines Corporation. Grolier is a registered trademark of Grolier Electronic Publishing, Inc.

CIRCLE NO 16

ink sheets available: 4-color (yellow, magenta, cyan, black); 3-color (yellow, magenta, cyan); and monochrome (black). The print controller uses a 16-MHz 68020 µP and either 4M bytes of RAM for A size printing or 8M bytes for B size printing. It has 35 Adobe resident fonts in ROM and supports downloadable fonts. The printer interfaces with a host through an RS-232C/422/423 serial port or a Centronics parallel port. It can print a 3-color A size drawing in 90 sec; a B size drawing takes 180 sec. An internal 20M- or 80M- byte disk drive is also available. Prices range from \$16,900 to \$22,900.

Schlumberger Graphics, 385 Ravendale Dr, Box 7169, Mountain View, CA 94039. Phone (415) 964-7900. FAX 415-961-6152. TLX 491178.

Circle No 373





TAPE BACKUP

- System for the Macintosh computers stores 150M bytes
- Performs image backup on a MAC II at 6M bytes/min

The MAC Filesafe 150 is a streaming tape backup system for the Macintosh SE and Macintosh II

FOR THOSE WHO THINK MONITORS ARE NO BIG DEAL



...AND FOR THOSE WHO DO!

Talk to the Largest... Dotronix!

By offering quality products, service and support we've quietly grown to be the largest U.S. independent display-only manufacturer. As a result of this growth we now feature the broadest product offering in the industry...

No one offers as many options in display size and performance as Dotronix!

From high resolution, large screen monitors for CAD/CAM, Desktop Publishing, Computer Graphics, and Medical Imaging to banks of small monitors for financial institutions, security systems, transportation and many other applications. We even make monitors for S-VHS playback permitting high resolution television viewing. Virtually all displays are available in high resolution, color and monochrome for most applications.

It's as simple as this: No one meets your monitor needs like Dotronix.

From broad product offerings to quality, service and support, no one gives you more than Dotronix. That's why we sell more monitors than any other U.S. independent display-only manufacturer. And that's why we'll meet your needs better than anyone else.

Call us and talk to an applications specialist.

Get the straight talk on how we can meet your application needs.

Call: 612-633-1742 FAX: 612-633-7025

**DOTRONIX**

DOTRONIX, INC.

160 First Street S.E.
New Brighton, MN 55112

CIRCLE NO 78


Locations at: Boulder, CO • Eau Claire, WI (VMI) • Minneapolis, MN • Elk River, MN • Hsinchu, Taiwan

© 1988, Dotronix, Inc.

computers. It stores 150M bytes of formatted data on an industry standard DC600XTD quarter-inch cartridge using the QIC-150 format. The stand-alone system comes in a half-height, 5¼-in. form factor and uses a SCSI interface to communicate with the host. The unit can perform an image backup on the Macintosh II computer at 6M bytes/min for a total back-up time of 25 min. The unit verifies all written data and automatically skips any bad blocks. Its software features include one-step automatic installation, menu guidance, on-line help, automatic back-up, separate tape verification, restore, tape directory, and user settable defaults. \$2195.00

Mountain Computer Inc, 240 Hacienda Ave, Campbell, CA 95008. Phone (408) 379-4300. FAX 408-379-4302.

Circle No 374




CPU CARD

- *Runs a 68020 μ P at clock speeds as high as 25 MHz*
- *Includes parallel, serial, SCSI and Ethernet interfaces*

Provided with 38 fully programmable bidirectional parallel I/O lines, the SYS68K/CPU-27 CPU card for VME bus systems is suited for use in industrial control applications. The board runs a 12.5-, 16.7-, or 25-MHz 68020 μ P and a 68882 math coprocessor. It has 1M bytes of on-board static RAM, and two JEDEC compatible EPROM sockets that


can accommodate 8M-bit devices when the devices become available. The board is supplied with these sockets occupied by the company's VMEPROM real-time kernel. The board has an additional 32k bytes of static RAM with onboard battery backup. Its parallel I/O lines are controlled by two 68230 parallel interface/timer chips, and the board has three serial I/O ports, two of which are configurable for RS-232C, -422, or -485 operation, while the third supports RS-232C only. The board also has a SCSI bus interface, and an optional Ethernet interface with its own 64k-byte buffer. Software development support is available for use under the PDOS operating system. Alternatively, you can use VMEPROM's link software to link the board to Unix 5.3 or MS-DOS operating systems. From around DM 7800 to DM 11,000.



HP-20S
Scientific with program library. Algebraic. \$49.95.




HP-22S
For science students. Algebraic. \$59.95.



HP-32S
Integration, solver, programming. RPN. \$69.95.


In this ad is the answer to



HP-27S
Scientific plus business. HP Solve. Algebraic. \$110.00.



HP-10B
Business essentials. Algebraic. \$49.95.



HP-14B
Specialized business analyses. Algebraic. \$79.95.

All prices suggested retail. Sweepstakes void where prohibited by law.

©1989 Hewlett-Packard Company PG12903

Force Computers GmbH, Daimlerstrasse 9, 8012 Ottobrunn/Munich, West Germany. Phone (089) 600910. TLX 524190. FAX 089-6097793.

Circle No 375

Force Computers Inc, 3165 Winchester Blvd, Campbell, CA 95008. Phone (408) 354-3410. TLX 172465. FAX 408-395-7718.

Circle No 376

3D WORKSTATION

- Contains a 68030 μ P and 68882 coprocessor delivering 4 MIPS
- Is source- and object-code compatible with the 9000 series 300

The HP 9000 Model 340SRX 3D graphics workstation contains a 68030 μ P and a 68882 coprocessor, which deliver a 4-MIPS performance rating. The model is source- and object-code compatible with the company's 9000 series 300 comput-



ers. In addition, it contains 4M bytes of RAM expandable to 16M bytes, a 16-in. color monitor with 1280x1024-pixel resolution, and the company's SRX graphics subsystem, which can be expanded from 8 to 32 color planes. The system is compatible with a range of 3D mechanical CAE and CAD software available from McDonnell

Douglas, PDA Engineering, and Swanson Analysis. The system runs on the company's HP-UX operating system, which adheres to AT&T's UNIX System V Interface Definition Issue 2. \$14,900.

Hewlett-Packard Co, 19310 Pruneridge Ave, Cupertino, CA 95014. Phone local office.

Circle No 377

SECURITY DEVICE

- Prevents unauthorized access to modems
- Device requires a caller to have a password and a phone number

The 232MSD Modem Security Device protects computers or private bulletin boards against unauthorized access. It works with most stand-alone modems that are compatible with the Hayes AT command set. The device uses a callback method for protection. When



HP-28S
Symbolic math capabilities.
\$235.00.




HP-42S
Superior matrix functions.
RPN.
\$120.00.

all your problems.



HP-17B
Broad business solutions.
HP Solve.
Algebraic.
\$110.00.



HP Business Consultant II
The Ultimate.
HP Solve.
\$175.00.

Whether you're an up-and-coming engineer or a recent Nobel prize winner, a business student or the CEO of a Fortune 100 company, HP offers you an entirely new series of calculators designed for your specific needs.

The most advanced scientific capabilities. Everything from numeric integration to superior matrix functions and symbolic math. HP Solve which lets you create custom menus. And the widest range of built-in business functions. Easy screen guides that lead you clearly to your solutions.

Visit our proud new family of quality HP calculators at your local retailer. Ask about our exciting Celebration Sweepstakes. But hurry, the Sweepstakes end April 30th, 1989. For the HP retailer nearest you, call 1-800-752-0900, Ext. 216T.



CIRCLE NO 17

a caller reaches the modem, the device intercepts the call and asks for a password. After validating the password, it requests the caller to hang up. The device then calls a phone number, stored in memory, associated with the password. The user at that phone number is then allowed access to the computer. If



a hacker steals a user's password, the password is unusable because the thief will not be at the user's phone number. The unit features a 50-number directory of password/phone number combinations, EEPROM storage for power-failure protection, and a systems manager that can disable the call-back procedure as an alternative. \$129.95.

B&B Electronics, 4000 Baker Rd, Box 1040, Ottawa, IL 61350. Phone (815) 434-0846. FAX 815-434-7094.

Circle No 378

320C14 DIGITAL SIGNAL CONTROLLER

In-Circuit Emulator, Macro Assembler, Development Environment


\$2495

Complete PC or Macintosh hosted development package for the DSC320C14 and TMS320E14 Digital Signal Controllers.

Package includes In-Circuit Emulator, Macro assembler, and development environment.

Also Available

TMS320C25	DSP	50 MHz
TMS320C10/15	DSP	25 MHz
TMS370CXXX	MCU	20 MHz
65C02	CPU	10 MHz
HD647180X	MCU	8 MHz
68HC05	MCU	2 MHz



All units shipped with 30-day trial period and 1 year warranty. We support what we sell!

Phone (214) 242-0450
 FAX (214) 245-1005
 1301 N. Denton Drive
 Suite 204
 Carrollton, TX 75006



Developed and manufactured in the USA. Call or write for detailed product information and prices.

DISPLAY CARD

- Drives 1280 x 960 pixels for the Macintosh II computer
- Provides 256 colors from a palette of 16.7 million colors.

The nuVista HR is a plug-in display card for the Macintosh II computer that can drive a display with 1280 x 960 pixel resolution. It can simultaneously display 256 colors from a palette of 16.7 million colors. A 2M-byte version of the card provides a virtual canvas of 2k x 1k pixels, and a 4M-byte version provides a virtual canvas of 2k x 2k pixels. The card uses the TI 34010 graphics processor for graphics manipulations. It also drives non-interlaced displays, provides square pixels, and can pan the entire video memory. It works with high resolution monitors with 64 kHz horizontal and 60 Hz vertical frequencies, such as Sony's GDM-1953 or JVC's GD-H6020US. The board is fully compatible with Apple's QuickDraw software package. The card can accommodate an additional 2M, 4M, or 8M bytes of memory using an optional NuVMX memory expansion module. 2M-byte version, \$3995; 4M-byte version, \$5995.

Truevision Inc, 7351 Shadeland Station, Indianapolis, IN 46256. Phone (800) 858-8783 or (317) 841-0332. FAX 317-576-7700.

Circle No 379



One company offers 1, 2, 5, & 10MHz 12-bit sampling A/D converters. DATEL.

Superior dynamic performance brings both harmonic distortion and signal-to-noise ratios to new lows.

We're working hard at DATEL to bring you new lows - to create new highs in performance. The *lowest* harmonic distortion. The *lowest* non-linearity. The *lowest* absolute accuracy errors. The *lowest* power consumption. The *lowest* physical size. And the *lowest* price. All to produce the highest dynamic and static performance in sampling A/D converters available anywhere.


Features unavailable anywhere else in all models include an internal sample hold with full power input bandwidth higher than Nyquist frequency, together with a functionally complete architecture. DATEL has truly produced the First complete Family of 12-bit ADCs.

With DATEL, you now have four new reasons guaranteed to shorten your ADC selection cycle. Bottom-line, compare these converters with our competition and you'll see that there is no reason to look anywhere else. Call us at (508) 339-3000.



Model	Sampling Rate	Effective Bits at Nyquist Frequency	THD* at Nyquist Frequency	Power Dissipation	Package	Price (1-9)
ADS-112	1MHz	11.0	-73 dB	1.3 watts	24-pin DDIP	\$259
ADS-132	2MHz	11.0	-73 dB	2.9 watts	32-pin TDIP	\$346
ADS-131	5MHz	10.6	-69 dB	4.2 watts	40-pin TDIP	\$549
ADS-130	10MHz	10.6	-69 dB	4.5 watts	40-pin TDIP	\$775

* THD (Total Harmonic Distortion)



DATEL

INNOVATION AND EXCELLENCE IN PRECISION DATA ACQUISITION.

Datel, Inc., 11 Cabot Boulevard, Mansfield, MA 02048 (508) 339-3000

CIRCLE NO 96




NEW PRODUCTS

INTEGRATED CIRCUITS

MOTOR CONTROLLER

- For three-phase brushless motors
- Contains Hall-cell decode logic

Combining in one IC all the functions required of a three-phase brushless motor controller, the UC3625 has separate outputs to control six power switches. The IC features Hall-cell decode logic with built-in cross-conduction protection. Other features include a tachometer, soft start, under- and over-voltage protection, current-controlled braking, and selection of either two- or four-quadrant operation. The UC3625 includes hysteric comparators on all logic inputs and noise blanking at the Hall-cell inputs. The IC also includes a direction latch, absolute-value current




sensing, and a precision reference voltage. 28-pin DIP, \$5.85 (100).

Unitrode Integrated Circuits, 7

Continental Blvd, Merrimack, NH 03054. Phone (603) 424-2410.

Circle No 385



LOWPASS FILTER

- Fifth-order Butterworth type
- DC to 20 kHz cutoff frequency

The LTC1062 switched-capacitor filter is clock tunable from dc to 20 kHz with an external resistor and capacitor and features a cutoff frequency accurate to 1%. The LTC1062 functions as a fifth-order lowpass filter, and you can cascade two devices to form a tenth-order filter. The device, which also features a buffered output, is available in commercial and military temperature ranges in 8-pin DIP and 16-pin SO packages. Prices start at \$3.30 (100).

Maxim Integrated Products, 120 San Gabriel Dr, Sunnyvale, CA 94086. Phone (408) 737-7600.

Circle No 386


CMOS EPROMs

- Organized as 8k x 8 bits
- Three speed versions are available

The 27HC64 high-speed 64k-bit CMOS EPROM has a JEDEC-standard EPROM pinout. The 27HC641 offers a bipolar PROM pinout. Both parts are available in 45-, 55-, and 70-nsec versions. Because of the CMOS process, the chips consume less power than do their bipolar counterparts. Also, unlike bipolar PROMs, the 27HC64 and 27HC641 are completely tested and then erased before shipment, thus ensuring the highest possible yield on customer patterns. The 27HC64 and 27HC641 are available in standard window ceramic DIPs, plastic DIPs, and surface-mount PLCC and LCC packages. The 27HC641 is also available in a window skinny ceramic DIP and a skinny plastic DIP. From \$12.70 (1000).

Microchip Technology Inc, 2355 W Chandler Blvd, Chandler, AZ 85224. Phone (602) 963-7373. FAX 602-899-9210. TWX 910-950-1963.

Circle No 387



DRIVERS/RECEIVERS

- RS-422 compatible
- Fabricated in CMOS

Matching the speeds of bipolar devices but consuming less power, the CMOS DS34C87/DS26C31 and DS34C86/DS26C32 are quad-differential line drivers and receivers, respectively. The drivers accept TTL or CMOS input levels and translate them to RS-422 output levels. Special output circuitry enables the individual drivers to power down without loading down the bus. The DS34C87 driver has separate enable circuitry for each pair of drivers; the DS26C31 has enable and disable circuitry that is common to all four drivers. Propagation delay is 11 nsec max. The receivers have

Your Workstation.

Your Emulator.



Now you can use 68000/020/030 in-circuit emulators with your favorite tool—your workstation. Where you usually develop code. And write memos.

Atron's PROBE Series 68000/020/030 emulators support real-time emulation to 25 MHz. Remotely. So you can develop code on your favorite Sun or VAX™ running VMS™. Download it fast via Ethernet™ to the PROBE. And execute it in the target in real-time. All from your desk.


The PROBE has real-time trace, so you can view the history of your program's execution. Source

trace capability lets you examine program flow at the C, Ada®, or assembler level. And eight hardware breakpoints let you find sequence-dependent bugs.

The PROBE has pre-fetch dequeuing, too. Here, a special algorithm removes pre-fetched, unexecuted instructions from the trace sequence and then realigns operands in the order that they were executed.

Workstations. Emulators. What's the difference? Thanks to Atron, now there isn't any.

Call 1-800-283-5933 for more information on remote emulation with Atron's PROBE Series.



CADRE
ATRON DIVISION

Saratoga Office Center
12950 Saratoga Avenue
Saratoga, California 95070


an input sensitivity of 200 mV over the common-mode input range of $\pm 7V$. Input hysteresis is typically 60 mV and propagation delay is 27 nsec max. The DS34C86 has separate enable pins; the DS26C32 has a common enable and disable function. Prices start at \$2.85 (100).

National Semiconductor Corp.,
Box 58090, Santa Clara, CA 95052.
Phone (408) 721-4474. TLX 346353.
Circle No 388

IMAGE DIGITIZERS

- Digitize at 15 MSPS rate
- Monochrome and color versions

The Bt251 and Bt253 image digitizers provide the circuit designer with a means to add image-capture capability to PCs and workstations. The Bt251, which generates 8 bits of intensity information for each pixel, is a 15-MSPS single-channel device for digitizing monochrome



(gray-scale) video signals. It supports four analog video inputs and contains an 8-bit A/D converter and a 256×8 -bit lookup-table RAM. The Bt253 is a 15-MSPS device for digitizing three channels of color analog video signals (such as RGB) or a monochrome signal, using only the green channel. The Bt253,

which generates 8, 15, or 24 bits of color information for each pixel, contains three 8-bit A/D converters and supports two separate three-channel video input ports. Bt251 (44-pin PLCC), \$36; Bt253 (84-pin PLCC), \$48 (100).

Brooktree Corp., 9950 Barnes Canyon Rd, San Diego, CA 92121.
Phone (619) 535-3251. TLX 383596.
Circle No 389

HV DISPLAY DRIVERS

- Provide 50 to 100V p-p output
- Have rise times from 2.5 to 4.5 nsec

The 1902 high-voltage CRT drivers feature output drive capabilities from 50 to 100V p-p into a 10-pF load (the typical capacitance of a high-resolution CRT). Corresponding maximum rise and fall times range from 2.5 to 4.5 nsec. The devices are RS-170 and RS-343 com-

Chips to control your head.

A Three Chip Set For High-Performance Servo Electronics

Now you can cut head-positioning electronics in high-performance Winchester disk drives down to size—using Silicon Systems' new Servo Chip Set. The 32H567 Servo Demodulator, 32H568 Servo Controller, and 32H569 Servo Motor Driver provide all of the functional building blocks required in a servo channel.

At your finger tips are advanced features like PLL synchronization, offset cancellation, on-track window compar-

ators, motor protection, automatic head retract, and a microprocessor interface that puts you in control. Couple this with our Servo Lab Software and Development Platform, and you can design your servo system in less time and effort than your competition.

The Servo Chip Set breaks down the major obstacles in the development of high-performance Winchester disk drives. With its high level of integration, it provides superior performance and

design features for lower power, reduced board space, and lower cost.

Call Now!
(714) 731-7110, Ext. 3575

For more information on this exciting Servo Chip Set and other Microperipheral Products, contact Silicon Systems or your local representative or distributor today. **Silicon Systems, Inc.**, 14351 Myford Road, Tustin, CA 92680.

silicon systems[®]

INTEGRATED CIRCUITS

patible, and can be driven directly from a standard video DAC. Additional features include a 25,000V/ μ sec slew rate and a 40-dB CMRR. The line has five basic variants that define the output voltage and rise/fall times, and the devices come in hermetic, 30-pin flat paks with mounting flanges. Commercial parts, \$185; MIL-STD-883 parts, \$255 (100).

Teledyne Philbrick, 40 Allied Dr, Dedham, MA 02026. Phone (617) 329-1600.

Circle No 390

COLOR RAM-DAC


- Includes 256 \times 18-bit RAM
- Includes three 6-bit DACs

The ADV476 monolithic IC contains a 256 \times 18-bit color-palette RAM, three 6-bit DACs, a latch circuit, a pixel read-mask register, bus control, an address register, and video

RGB outputs. The RAM-DAC provides complete pixel management and output drive for VGA color-graphics displays. Using its 256 \times 18-bit color look-up table, the ADV476 can simultaneously display 256 colors from a palette of 262,144 addressable colors. By writing to the pixel mask register, the system CPU can access different sections of the color look-up table and alter the displayed colors. The video RGB outputs are RS-170 and RS-343 compatible with no need for external buffering. The CMOS device comes in a 28-pin plastic DIP, operates from a 5V supply, and dissipates a maximum of 800 mW. The ADV476 is available in clock rates of 35, 50, and 66 MHz. \$16, \$17, and \$20 (100).

Analog Devices, 804 Woburn St, Wilmington, MA 01887. Phone (617) 935-5565.

Circle No 391



ISOLATION AMP

- Provides 1500V isolation
- Operates from ± 4.5 to ± 18 V supply

Packaged in a compact 16-pin DIP, the ISO122P unity-gain amplifier has a minimum isolation-voltage rating of 1500 Vrms and a breakdown-voltage rating of 2400 Vrms. Isolation-mode rejection (IMR) is typically 140 dB at 60 Hz. Barrier leakage is only 0.5 μ A max at 240V, 60 Hz. The ISO122P has an input/output voltage range of ± 10 V. The



ALL POWER SUPPLY ROADS LEAD TO



- Engineering Excellence In Design and Manufacturing Since 1945
- Long Life — 5 Year Warranty
- 160 Standard Units: 100 W to 100,000 W
6 VDC to 1000 VDC
1 A to 3000A
- Custom Units to 150,000W/1,500 VDC

Plot your own course—request product information from your sales representative or call
1-800-631-4298



ELECTRONIC MEASUREMENTS INC.

405 ESSEX ROAD, NEPTUNE, NJ 07753
Call TOLL FREE 800-631-4298
Except in N.J., Alaska, Hawaii & Canada
Call 201-922-9300



**ELECTRONIC
MEASUREMENTS,
INC.**

The BOSS™

BIPOLAR OPERATIONAL SOURCE-SINK



- 3 power levels 100 W to 200 W to 400 W
- 4 modes of operation: (1) bipolar power supply (2) an operational power supply (3) sourcing power supply (4) sinking power supply
- DC output voltages of ± 20 V DC through ± 200 V DC
- IEEE-488 or RS232 digital control
- Regulated and metered (V and A)

**ATR LINEAR DC POWER
SUPPLIES**



- 3 100 W 1/4 rack models
- 3 250 W 1/2 rack models
- Voltages range from 0 to 32 V DC through 0 to 128 V DC
- Regulated and metered (V and A)
- Both models are fully programmable sources of constant voltage or constant current
- Output power via rear mounted terminal boards or front panel binding posts

**IEEE-488 BUS INTERFACE
DIGITAL PROGRAMMER**



EMTL-488

A dual channel, digital-to-analog, talker/listener programmer. Applications include: Automatic Test Equipment • Environmental Testing • Motor Controls • Process Controls

- Economical interface with GPIB Bus
- Catalog units to match output voltage of any E/M power supply
- Two independent channels for controlling voltage and current
- 12 bit resolution
- Bus and processor optically isolated from load
- 3 packaging concepts
- 5-year warranty

ELECTRONIC MEASUREMENTS, INC.
405 Essex Rd., Neptune, NJ 07753, Dept. EM
PHONE: 201-922-9300
TOLL FREE: 800-631-4298

CIRCLE NO 19

INTEGRATED CIRCUITS

small-signal bandwidth is 50 kHz, and the gain error is typically $1 \pm 0.05\%$ FSR. The two-chip hybrid IC's supply range of ± 4.5 to ± 18 V lets designers use the part in standard bipolar (15V) and PC-based data acquisition systems. \$9.50 (100).

Burr-Brown Corp, Box 11400, Tucson, AZ 85734. Phone (800) 548-6132.

Circle No 392

COMPARATOR

- Provides eight high-speed latched comparators
- Is suitable for 5 to 10V single- or split-supply operation

The SCC8008 octal comparator contains eight high-speed comparators with latched outputs. The comparators are divided into two groups of four; each group has its own buffered clock input. The two groups also have independent power supplies and bandgap-reference bias generators, allowing you to operate them from different supply voltages—such as in mixed TTL and ECL logic systems. You can achieve a variety of level-shifting functions by connecting the outputs of one group to the inputs of the other. In transparent mode, the comparators have a differential gain of 26 dB and a typical propagation delay for 10-mV input overdrive of 1.1 nsec. In the latching mode, the delay between the clock input and valid latched data is typically 0.8 nsec for 10-mV overdrive, and the output-to-output skew is 0.1 nsec max. The comparator's common-mode input-voltage range is 2.7V to $(V_{CC} - 0.7V)$, and the inputs have a typical input impedance of 300 k Ω . The SCC8008 is packaged in a 68-pad leadless chip carrier and has an operating temperature range of -40 to $+85^\circ\text{C}$. Approximately £20 (100).


STC Components, Semiconductor Division, Maidstone Rd, Sidecup, Kent DA14 5HT, UK. Phone 01-

300-3333. TLX 21836. FAX 01-300-9609.

Circle No 393

STC Components Inc, 636 Remington Rd, Schaumburg, IL 60173. Phone (312) 490-7150. FAX 312-490-9707.


Circle No 394



CLOCK/TIMER/RAM

- Includes clock/calendar, timer/counter, and RAM functions
- Remains operational on a supply voltage as low as 1V

The PCF8583 incorporates a 256-byte static RAM and a real-time clock/calendar, which you can reconfigure to operate as an event counter. It is available in an 8-pin DIP, small-outline surface-mounting package, or as a naked die part. The device operates from a 2.5 to 6V supply and typically draws 10 μA of supply current. In standby mode it typically draws 2 μA , and its static RAM and clock/timer remain active at supply voltages as low as 1V. The device's real-time clock/calendar operates in a 12- or 24-hour mode, and provides year (with leap-year compensation), month, day, day of week, hour, minute, second, tenths of a second, and hundredths of a second information. You can also program it to provide an alarm on specified dates, days, and times via a status bit or interrupt. The clock/calendar oper-



Now, high performance vacuum/pressure blowers that operate from 120 VAC

Compact units feature brushless dc motors with integral controller and variable speed capability

These new Windjammer® blowers combine electronics, motor, and fan system in a compact, cost-effective package that operates from a standard 120 VAC input. An exclusive Lamb Electric design, they were developed for demanding, limited space applications such as business machines, medical equipment and



materials handling applications.

Just 5.7" in diameter, the blowers have 1-, 2-, or 3-stage fans for performance from 50" H₂O vacuum at 0 CFM to 110 CFM at 0" H₂O. With one version, a 0 to

10 VDC signal from a sensor or other device will control motor speed and adjust air performance from 0 to 100%. Or, a second model provides manual speed control by means of a potentiometer located in the blower housing.

These blowers also feature low noise performance and are UL/CSA component recognized. Get complete details by contacting AMETEK, Lamb Electric Division, 627 Lake Street, Kent, OH 44240. (216) 673-3451. Telex: 433-2140. Cable: LAMETEK.

AMETEK
LAMB ELECTRIC DIVISION

Now You Can Make Important Component Selection Decisions Faster and Easier than You Ever Imagined!



INTRODUCING CAHNERS
CAPS. AN ALL-NEW,
PRODUCTIVITY-BOOSTING
ENGINEERING TOOL THAT
AUTOMATES, ACCELERATES,
AND OPTIMIZES THE
SELECTION OF INTEGRATED
CIRCUITS AND
SEMICONDUCTORS.

Imagine having up-to-date information on more than 400,000 devices from over 250 manufacturers worldwide at your fingertips.

Think about instantly accessing crisp, clear, unabridged images of manufacturers' datasheets, with the same text, tables, and graphics found in the printed versions.

Consider applying the power of menu-driven parametric searches that can identify ICs which conform to your specifications.

This is CAPS. It's new. It's different. And it gives you the information you need to make critical component selection decisions.

Available on a subscription basis so it's always up to date, CAPS comes complete with all the hardware and software you need to install CAPS on your personal computer.

Learn more about how CAPS can take the drudgery out of your component selection process. Call or write:

CAHNERS
CAPS
Computer Aided
Product Selection

Cahnert Technical Information Service
275 Washington Street
Newton, Massachusetts 02158-1630
Telephone: 617-964-3030
Telex: 940573
Facsimile: 617-964-5490
Toll Free: 1-800-245-6696

Facts about

400,000 ICs and Semiconductors at Your Fingertips

Cahners CAPS is the newest component search and selection tool for electronic design engineers:

- PC-driven, CD-ROM-based
- Includes unabridged manufacturers' datasheets
- Represents more than 250 manufacturers worldwide

Call Toll Free: 1-800-245-6696

CAH N E R S



Computer Aided
Product Selection

275 Washington Street
Newton, MA 02158-1630
Telephone: 617-964-3030
Telex: 940573

CAPS REPRESENTATIVES

NEW ENGLAND

CT, MA, ME, NH, RI, VT
Betric Associates, Inc.
617-894-8400

UPSTATE NEW YORK

Ossmann Associates, Inc.
315-437-7052

NORTHEASTERN

NJ, NYC, E. PA
S-J Associates
516-536-4242

CHESAPEAKE

DC, DE, MD, VA
Robert Electronic Sales
301-995-1900

SOUTHEAST

AL, FL, GA, MS, NC, PR, SC, TN
Technology Marketing Associates, Inc.
407-676-3776

CENTRAL - EAST

IN, KY, MI, OH, W. PA, WV
SAI Marketing Corp.
313-750-1922

CENTRAL - WEST

MN, ND, SD, W. WI
HMR Incorporated
612-888-2122

CENTRAL - NORTH

E. WI, N. IL
Technology Sales, Inc.
312-991-6600

CENTRAL - SOUTH

IA, KS, MO, NE, S. IL
Electri-Rep
913-649-2168

SOUTHWEST

AR, LA, OK, TX
Bonser-Philhower Sales
214-234-8438

ROCKY MOUNTAIN

AZ, CO, ID, MT, NM, NV, UT, WY
Zeus Electronics, Inc.
602-263-6022

SOUTHERN CALIFORNIA

Balzer-Wolf Associates, Inc.
714-261-6877

NORTHERN CALIFORNIA

Stewart Fullerton Associates, Inc.
415-934-8028

PACIFIC NORTHWEST


OR, WA
Seltech, Inc.
206-746-7970

CANADA

R.N. Longman Sales, Inc.
416-670-8100

INTERNATIONAL

Cahners CAPS
617-964-3030
FAX: 617-558-4700
Telex: 940573



If your magnetic shielding application is this demanding, you need MμShield.

Free MμShield Magnetic Shielding Catalog

For customized shielding, MμShield materials from stock, and consultation services, contact MμShield Products Division, Bomco, Inc., Route 128, Blackburn Circle, Gloucester, MA 01930. Phone 508/283-9000. Fax 508/283-2882.

bomco
Excellence In Metal Forming

CIRCLE NO 23

QUICK—Memorize this list:

175.69	18.905	1.7868	171.67	143.98
1.6523	153.47	15.097	132.69	185.36
17.546	185.98	16.264	1.3789	1.6243
154.52	19.090	15.778	197.35	16.230
188.58	129.34	174.58	19.875	1.9465
1.3876	101.09	16.790	1.9721	1.6759
1.7566	18.236	1.7805	198.67	189.20
187.43	17.647	152.78	189.36	17.654
18.347	16.154	1.5737	18.745	195.86
17.961	1.8497	15.876	191.60	17.949
16.975	186.67	175.87	15.134	145.87
1.8264	13.478	16.783	16.598	157.83
15.783	1.1654	136.56	11.387	1.6781
15.786	118.75	158.70	114.36	17.169
11.080	1.1342	178.67	10.287	1.6085
1.2136	1.8514	10.562	1.2905	191.70

The 175 Autoranging DMM can—up to a hundred readings, and it determines minimum and maximum values. Five functions and a lot more—for \$449. IEEE-488 and battery options, too.

QUICK—Call the Keithley Product Information Center: (216) 248-0400.



The Model 175
Autoranging
DMM

KEITHLEY

CIRCLE NO 160

CIRCLE NO 24

255

NEW PRODUCTS

CAE & SOFTWARE DEVELOPMENT TOOLS

LOGIC SYNTHESIZER


- Lets you correct logic errors without leaving the simulator
- Provides input-slew-rate modeling for macrocells

The Ikos Simulation System Release 3.0 incorporates several new features. The Incremental Logic Synthesis (ILS) feature allows you to modify a circuit without leaving the simulator and automatically recompile changed portions of the net list. The ILS feature also allows you to initialize a node to a known value before simulation and force a node to a specified signal value during simulation. Other features include input-slew-rate modeling, which adds a slew-rate-dependent delay to the input of every macrocell model; back-annotation of RC wiring delays derived from actual layouts; a

vector-grading feature that lets you analyze the effectiveness of test-vector sets; and spike and violation logging for generating a complete report on the activity. Complete simulation system including ILS, \$64,000.

Ikos Systems Inc, 145 N Wolfe Rd, Sunnyvale, CA 94086. Phone (408) 245-1900. FAX 408-245-6219.

Circle No 400




8051 DEBUGGER

- Provides C and assembler debugging facilities
- Executes 8051 or 8052 code on an IBM PC or compatible

The MICRO/SLD-51 symbolic debugger executes 8051 or 8052 machine code on an IBM PC or compatible development host. The built-in

8051 simulator means that you don't need any additional hardware such as the target system or an in-circuit emulator to debug your programs. You can step through a C or assembly-language program, line by line, displaying the C or assembly-language source code as well as the contents of 8051 hardware registers and data variables stored in mem-

GET ON YETI'S TRACK



The mountain man may be out of reach but we are here to serve your demands.

Yeti's printed circuit boards have taken up the challenges of this fast changing world of electronics and OEM equipment since 1984.

Accuracy is guaranteed by our fully automated program controlled production line. Strict quality controls have minimized defection rates. Continuous schooling enables Yeti employees to be up to the latest technical innovations and standards in OEM products. Our mass-production capacities are increasing.

Just snooping for reliable suppliers you should contact us. Yeti is at your disposal.

YETI ELECTRONICS CO., LTD.

106, KAI-LUNG STREET, JIA DONG TSUEN,
BA DER SHIANG, TAOYUAN TAIWAN. R.O.C.
TEL: 886-3-3333121-6 FAX: 886-3-3328362
P.O. BOX: 362, CHUNG-LI, TAIWAN. R.O.C.


CONTACT PEOPLE:

C.K. CHEN-PRESIDENT
VIVIEN FAN CHIANG-SALES ENGINEER
JACK HUANG - SUPERVISOR



New BoardSite In-Circuit Programmers

PROGRAM YOUR EPROMS ON THE BOARD!




Data I/O's in-circuit programming expertise can dramatically reduce your production programming costs. We can help you streamline your assembly process, reduce device inventory and handling, and eliminate device sockets.

Now in-circuit programming is easier than ever. BoardSite™ brings new levels of flexibility and economy to in-circuit programming. It's PC-based for versatility and low system cost. Easy, do-it-yourself configurations mean fast, in-house changes and low NRE costs. And the

multi-level, menu-driven user interface makes operation easy.

CALL TODAY for your **FREE** copy of "Introduction To In-Circuit Programming" plus more about BoardSite.



1-800-247-5700
Ext. 972

DATA I/O
Corporation

Steel, Style & Silicon.

Fluid Level Sensor

Mixed mode device interfaces with dashboard display, includes precision on-board analog to eliminate false readings from sloshing fluids.
Design Turn: 16 weeks.

Electronic Instrument Cluster

Mixed mode system-on-a-chip replaces traditional 2-to-3 chip discrete implementations. Includes a 68HC05 microprocessor core, plus memory, analog functions and digital glue logic.
Design Turn: 26 weeks.

Smart FET Driver

Uses on-board analog functions to add smart FET driving capability with open/short failure detection and includes on-chip voltage doubler.
Design Turn: 18 weeks.

Distributorless Ignition Chip

Part of integrated engine development program that helps improve engine performance up to 40%. Integrates key analog and digital functions into a single, compact, high-reliability CMOS device.
Design Turn: 26 weeks.

Keyless Entry

Chip contains EEPROM supercell that provides direct write capability for flexible security code generation. Ten years data retention and 10,000 read/write cycles for harsh automotive environment. Can be configured for dual or single supply programming.
Design Turn: 14 weeks.

Light Controller Chip

Single chip solution includes all the digital, analog and memory functions to control headlights, parking and fog lights. Provides exit delay timer and allows manual control of exterior lights from driver door.
Design Turn: 14 weeks.



ASICs have become an integral part of today's automotive products.

Improving performance.

Increasing reliability.

Enhancing driver safety and convenience in ways unimaginable just a few years ago.

In this very demanding industry, on the most unforgiving proving grounds, NCR has earned an enviable reputation for first-pass success, responsive service and high quality.

Today, we have a solid track record of successful ASIC programs with major U.S. automotive corporations spanning initial design to high volume production—including "Just In Time" delivery and dock-to-stock QA programs.

And NCR design tools are becoming the choice of fast-track ASIC designers. With NCR Design Synthesis™, Design Advisor™ expert system and DesignSim™ A&B, designers can spend more time creating, less time bogged-down in minute details.

To kick the tires on our automotive, commercial and military ASIC libraries, call today: 1-800-334-5454.

NCR Microelectronics, 1700 South Patterson Blvd., Dayton, Ohio 45479.

Creating value

CAE & SOFTWARE DEVELOPMENT TOOLS

ory. The debugger works with files created by the vendor's C compiler and assembler, or with any 8051 assembler that can generate output in Intel Hex format. \$295.

Micro Computer Control Corp., Box 275, Hopewell, NJ 08525. Phone (609) 466-1751. FAX 609-466-4116. TWX 910-240-4881.

Circle No 401

SIMULATOR OPTIONS

- Let you describe functional blocks to the PSpice simulator
- Permit PSpice to do mixed analog/digital simulations

The Analog Behavioral Modeling option allows you to describe analog components or entire functional blocks to the PSpice simulator. The description can be a formula, a look-up table, a Laplace transform, or a table of frequency response. The transfer function can have any num-

ber of controlling variables, including time, and the formula can be as simple or as complex as you wish. This option allows you to describe a functional block by its behavior without having to know how the block will be implemented; at a later stage in the design you can replace the behavioral description by the actual circuitry. The Digital Simulation option allows PSpice to perform mixed analog/digital simulations. The circuit can have any combination of digital and analog signals, and with the aid of the Probe option you can display digital and analog signals simultaneously. The Digital Simulation option includes libraries for most TTL components, and each component includes models for many logic families. The models describe not only the device's functions but also all of the propagation delays. The models are in the form of text files that you

can examine or modify. Analog Behavioral Modeling option for an IBM PC running PC-DOS, \$350; for a VAX 8800, \$4400. Digital Simulation option for an IBM PC running OS/2 or DOS, \$1950; for a VAX 8800, \$15,900.

MicroSim Corp., 20 Fairbanks, Irvine, CA 92718. Phone (714) 770-3022. TLX 265154.

Circle No 402

1750A TOOL SET

- Cross-assembler runs on IBM PCs and compatibles
- Debugger works with Ada, C, Pascal, or Fortran programs

The complete 1750A tool set consists of a macro cross-assembler, symbolic debugger, linker, and loader. The macro cross-assembler runs on IBM PCs and compatibles, and generates relocatable object code for MIL-STD-1750A proces-

This new video signal generator simplifies production line monitor testing




You maintain video design parameters on disk, make modifications on disk as needed

Optional Function Keypad gives your test personnel a simple push-button method of sequencing test images and signals. Prevents unauthorized alterations and encourages consistent test procedures. Keypad functions can be defined and changed as necessary to meet changing requirements.

sors. It can assemble 20,000 lines of source code per minute and offers conditional assembly directives. With only 256k bytes of RAM, it can handle 64 levels of nested sub-routines and as many as 16,000 6-character symbols. The linker maps out the target addressing scheme; each of 100 logical groups may link any mix or overlap of program modules. The symbolic debugger runs on the host PC and is therefore non-intrusive; it sports an embedded miniassembler for on-the-spot patches to the program under test. The loader allows the debugger to work on programs written in Ada (or other languages) that run on the target system. Complete tool set, \$6845; individual tools also available.

Sabtech Industries Inc, 3910-B Prospect Ave, Yorba Linda, CA 92686. Phone (714) 524-3299.

Circle No 403



C CROSS-ASSEMBLER

- *Runs on Macintosh Plus, SE, or II*
- *Generates code for Motorola 6800 and 6300 families of μ Ps*

Crossbow-6800 is a cross-development package that includes an assembler and a programmer's editor. It runs on a Macintosh Plus, Macintosh SE, or Macintosh II host and assembles code for Motorola 6301, 6800, 6801, and 68HC11 μ Ps at a rate of 30,000 source-code lines per minute. The built-in editor extends the standard Macintosh editing fa-

cilities by adding features such as block- and auto-indenting, independent tab settings, case translation, and comparison of versions in adjoining windows. The assembler provides multifile, conditional, macro, and sectioned-assembly directives. You can direct the assembler to generate object files in Intel Hex format, Motorola S records, or absolute binary code; it optionally creates tabulated source listings and symbol tables. If the assembler finds an error in the source code, it returns you to the editor, places the cursor after the offending word, and explains the nature of the error in a separate window. A built-in communications feature allows you to download the assembler output to a target system at standard transfer rates from 300 to 57,600 bps, using either of the host's serial ports. You can select XON/XOFF handshaking to prevent the target


Quantum Data's FOX

saves testing time and steps, adjusts to changing monitor specs

The FOX accommodates production line testing of analog or digital, monochrome or RGB video displays. Tests cover a complete spectrum of monitor adjustments including linearity, geometry, focus, color levels and more. It can be used to bring a monitor into specification as well as check overall performance. You maintain customized video images and test sequences for each of your monitors on disk as an MS-DOS file. Distribute them to your test stations as needed. When monitor changes occur each testing station can access new parameters by pressing a keypad button. No EPROM's to program when new model additions come your way! You'll find the FOX has no equal when it comes to video signal generation accuracy and repeatability. Saves time and money all the way down the production line.

Right for today . . . ready for tomorrow

The FOX's mainframe design incorporates plug-in modules that protect your investment. As your design parameters expand you'll be ready. A simple plug-in module is all it takes to put you in touch with a whole new range of video generating capabilities. Modules for 125 MHz, 250 MHz and 400 MHz operation are available now. They deliver analog, digital, monochrome and RGB video. And the FOX includes a library of over 100 test images on disk, ready to use. **CALL NOW** for your copy of our new 8700 Series FOX brochure today.



QUANTUM DATA®

2111 Big Timber Road, Elgin, IL 60123 U.S.A.

(312) 888-0450 • TELEX 206725 • FAX (312) 888-2802

International sales and service offices in the U.K., Japan, Korea and Taiwan

system's buffers from overflowing during a transfer. You can also perform file transfers under the XModem protocol. \$295.

Onset Computer Corp., 199 Main St, North Falmouth, MA 02556. Phone (508) 563-2267. FAX 508-563-9477.

Circle No 404

MOTION PROGRAMMER

- *Accepts CAD plotter commands in HPGL format*
- *Converts plotter commands to X-Y motion commands*

SMCCAD is a program that runs on IBM PC/XTs, PC/ATs, and compatibles. It accepts plotter commands in HPGL (Hewlett-Packard

Graphics Language) format and converts the commands to constant, programmable-velocity X- and Y-motion commands for the vendor's Smart Motion Control Card (SMCC). The SMCC plugs into an IBM PC expansion slot and can control dc brush, dc brushless, ac induction, and stepping motors. A dynamic buffering feature on the SMCC allows the software to convert a number of moves that are limited only by the available disk space. To run the program, you need 640k bytes of RAM; two 360k-byte floppy-disk drives (or a hard-disk drive if the input drawings are large or intricate); a CGA, EGA, or VGA adapter and color monitor; an SMCC board; and PC-DOS version 2.1 or higher. SMCCAD software, \$699; SMCC board, \$1199.

Delta Tau Systems, 21119 Osborne St, Canoga Park, CA 91304. Phone (818) 998-2095. FAX 818-998-7807.

Circle No 405

GREAT DESIGNS ARE A SNAP WITH...

HIROSE HR10 SERIES CONNECTORS.

The uncomplicated design of the HR10 Snap-Lok™ circular connectors assures rugged dependability and enables rapid, error-free mating and unmating even in the most adverse situations.

With three shell sizes (7mm, 10mm and 13mm) and insert arrangement from 4 to 20 contacts—including the newest HR10B (with 10 signal lines and 50 Ohm matched impedance coaxial)—there is no problem finding a connector to fit your needs.

The handsome high-tech design and sturdy construction of the Snap-Lok connectors will ensure engineering integrity. That's why so many leading manufacturers worldwide insist on only Hirose HR10-Series connectors.

Take a closer look. See how they work. Notice how few pieces are needed for assembly. Fewer internal parts reduce weight and lower labor costs, too. Choose solder cup or crimp terminals, gold or silver plating; it doesn't matter. You'll always be getting the best with the Hirose HR10 series.

Lock-up your new design with Hirose connectors.

Call or write for information, pricing and samples. "Your Link to the Future"

Hirose
HR10



HRS HIROSE ELECTRIC (USA) INC. 2685-C Park Center Drive
Simi Valley, CA 93065 (805) 522-7958 or FAX (805) 522-3217 ©1989 HRS

See us at Electro Show, Booth #2819

CIRCLE NO 29

COMPONENT LIBRARY

- *Includes more than 600 models of military-qualified parts*
- *Models conform to MIL-M-38510 specification*

The MIL-spec 38510 component library includes more than 600 electronic components qualified for military applications. Each model includes a commercial or ANSI graphical symbol, a precisely characterized simulation model for both functional and timing simulation, and a packaging model for pc-board layout. The library is designed for use with the vendor's line of EDA workstations and software. Five kits are available: TTL, CMOS, ECL, PLD/PLA, and memory components. From \$5000 to \$10,000, depending on the number and complexity of the parts in the kit.

Daisy Systems Corp., Box 7006, Mountain View, CA 94039. Phone (415) 960-6863.

Circle No 406

INTRODUCING DDL2000

Meta-Software and SILVACO International have JOINED FORCES by combining their device libraries to form *DDL 2000*, a new Discrete Device Library featuring over 2000 devices for PCB designers — a proven and powerful industry standard!

Leading edge PCB designers need the best discrete device models and circuit analysis tools available!

You Should Be Demanding

- **Variety** — DDL 2000 features over 2000 models for Diodes, Zener Diodes, JFETs, BJTs, Bipolars, PowerMOS, Op Amps, comparators, Timers and SCRs.
- **Models** — from actual measurements over temperature
- **Special features** — Users can modify key parameters for worst case and Monte Carlo analysis

Your Workstation Alternative

- **Compatibility** — DDL 2000/HSPICE runs on your Mentor workstation as a superior alternative to Accusim/Acculib
- **Computers** — DDL 2000/HSPICE is available on – Sun – Apollo – Vax – IBM – CRAY – PC 386
- **HSPICE Interfaces** — Analog Workbench, Cadence Design Framework, and more!

Custom Modeling

- Lab facilities with throughput to meet your needs
- 24 hour turn-around service
- Cost effective!

Meta-Software provides HSPICE, the industry's leading software for optimizing analog circuit simulation. DDL 2000 *combined* with HSPICE gives engineers a design solution of unbeatable sophistication!

SILVACO International provides UTMOST II, the most powerful device modeling and characterization software package available. UTMOST II features complete, fast and accurate solutions for model optimization, parametric testing, process control and yield analysis.

We do it *your* way,
to *your* specifications!

Compare DDL 2000
quality and prices
with the competition!

DDL 2000 prices

Individual parts \$200

PC 386 version \$4,000

Workstation version: starts at \$4,000

META-SOFTWARE



SILVACO

International



DDL2000

THE TOTAL SOLUTION

META-SOFTWARE

50 Curtner Ave., Suite 16
Campbell, CA 95008
Phone - USA: 408-371-5100
USA Toll Free: 800-346-5953
Europe: 41-22-66-27-01
Japan: 81-03-394-1431


SILVACO

International

4701 Patrick Henry Dr., #6
Santa Clara, CA 95054
Phone - USA: 408-988-2862
Japan: 81-045-681-3666
Europe: 49-089-840-2581
Taiwan: 886-02-708-6792
Korea: 82-02-782-5360

NEW PRODUCTS

TEST & MEASUREMENT INSTRUMENTS



DUAL-DISPLAY DMM

- Measures two quantities with one pair of leads
- Displays two measurements simultaneously

The model 45 is a 5-digit DMM that sports an unusual dual display. Through one pair of test leads, the meter measures two quantities in rapid succession—for example, a

power supply's dc output and rms ripple voltage—and displays both measured values simultaneously. Not only is the dual display unusual, so is the inclusion of a frequency counter, which can measure the frequency of a signal whose rms value is measured by the DMM. The unit incorporates a min/max mode, which records the highest and lowest values attained by a measured quantity. It also includes a relative-measurement mode in which you can store any measured value as a reference and display subsequent readings with respect to the reference. When measuring dc voltage, the unit can resolve 100,000 counts with 0.02%-of-reading inaccuracy at 2.5 readings/sec, 30,000 counts at 5 readings/sec and 3000 counts at 20 readings/sec. An

RS-232C port is standard. \$595.

John Fluke Mfg Co Inc, Box C9090, Everett, WA 98206. Phone (800) 443-5853, ext 33.

Circle No 410

Philips Test and Measurement, Building HKF, 5600 MD Eindhoven, The Netherlands. Phone local office.

Circle No 411

VXI BUS MODULE


- Resolves 16 bits on 8 channels
 - Makes 200k measurements/sec
- The DVX 2502 B-size VXI (VME eXtensions for Instrumentation) module contains an 8-channel data-acquisition system that includes an amplifier whose gain is software programmable and a 16-bit ADC that makes 200,000 conversions/sec.

MCM

for **CASE TECHNOLOGY** Users

NEW!

\$ 4950



Autorouter in the CASE 300%

- 100% Autorouting with Initial- and Full Routing
- 100% Optimizing routing for manufacturing needs
- 100% Integrated with your CASE-CAE system
- Ripup and Reroute Algorithm with Backtracking
- Simultaneous routing on all signal- and power layers
- User definable Routing Strategy and Routing Time
- Full support of SMD-Technology

Easy to install · Easy to learn · Easy to use

MCM GmbH, W. Germany — Exclusive distributors in U.S.
Viva & Associates
1475 Saratoga Avenue, Suite 100 • San Jose, CA 95129
Tel: 408-446-3777 • FAX 408-446-3797


CIRCLE NO 39

MCM

Your PC as **Logic Analyzer**

NEW!

\$ 2450



200 MHz 8 CHANNEL LOGIC ANALYZER PC Expansion Board

- 200 MHz Clock Rate Non-Interlaced
- 8000 Bytes Memory Depth
- Expandable to 32 Channels x 200 MHz in one PC
- Up to 128 Channels x 200 MHz in an expansion box
- 16 Timing Diagrams simultaneously
- HEX, BIN or ASCII Display
- Window Interface
- Stand-Alone Logic Analyzer in all PCs and Laptop-PCs
- Implementable with all In-Circuit Emulators and Automatic Measuring Systems

With this high speed timing analyzer MCM has developed the true alternative to the integrated state logic analyzers and stand alone solutions.


A must for every developer

MCM GmbH, W. Germany — Exclusive distributors in U.S.
Viva & Associates
1475 Saratoga Avenue, Suite 100 • San Jose, CA 95129
Tel: 408-446-3777 • FAX 408-446-3797

CIRCLE NO 131

V-Series

a victory for the user.



V-Series™ microcomputers are engineered to be winners in your systems designs. For high-performance MS-DOS-compatible devices and complete systems-on-chip, you have more choices of more dedicated parts for more dedicated applications.



Call now for more information about the full range of winning microcomputer solutions.
NEC Electronics Inc.
401 Ellis St. Mountain View, CA 94039
1-800-632-3531

© 1989 NEC Electronics Inc.


V-Series, V20, V25, V30, V33, V40, V50, V60, V70 are trademarks of NEC Electronics Inc.
MS-DOS is a trademark of Microsoft Corporation.

Win with V-Series

NEC

MAXIM IMPROVES YOUR ANALOG DEVICES APPLICATIONS

WIN WITH MAXIM



From 1 ppm references to fast 12-bit A/Ds, Maxim offers you the widest selection of *plug-in-replacements* for Analog Devices parts today. They're all available in DIP, SO, or PLCC—at very competitive prices. And, only Maxim makes pin-compatible *improved equivalent* devices like the 3 μ s MAX162 that out performs the 5 μ s AD7572 in speed and noise. Or, the MAX150 which replaces the AD7820 and an external voltage reference.

In fact, Maxim is the *first and only* alternate source for a growing number of Analog Devices parts—such as the AD7534 14-bit DAC, the AD7228 octal voltage output DAC, the AD536A RMS-to-DC converter, the AD7575 5 μ s 8-bit ADC with T/H, and more. All Maxim parts are designed to withstand 2000V of electrostatic discharge (ESD), and 50mA of electrical over-stress (EOS). And every DIP is burned-in absolutely FREE.

Choose Analog Devices replacements or Maxim improved parts.

D/A CONVERTERS

AD565A 12-Bit 250ns I-DAC w/Ref
AD566A 12-Bit 250ns I-DAC
AD7224 8-Bit V-DAC
*AD7225 8-Bit Quad V-DAC
AD7226 8-Bit Quad V-DAC
(MAX500 8-Bit Quad Serial V-DAC)
*AD7228 8-Bit Octal V-DAC
AD7520 10-Bit M-DAC
AD7521 12-Bit M-DAC
AD7523 8-Bit M-DAC
AD7524 8-Bit Latched M-DAC
*AD7528 8-Bit Dual M-DAC
(MAX7624 8-Bit Latched M-DAC)
AD7530 10-Bit M-DAC
AD7531 12-Bit M-DAC
AD7533 10-Bit M-DAC
*AD7534 14-Bit Latched M-DAC
*AD7535 14-Bit Latched M-DAC
*AD7536 14-Bit Latched M-DAC

AD7541 12-Bit M-DAC
AD7541A 12-Bit M-DAC
AD7542 12-Bit Latched M-DAC
AD7543 12-Bit Serial M-DAC
(MAX543 12-Bit Serial M-DAC)
AD7545 12-Bit Latched M-DAC
*AD7545A 12-Bit Latched M-DAC
(MAX7645 12-Bit Latched M-DAC)
AD7548 12-Bit Latched M-DAC
*AD7628 8-Bit Dual M-DAC

A/D CONVERTERS

*AD578 12-Bit 3 μ s ADC
*AD7572 12-Bit 5 μ s/12 μ s ADC
(MAX162 12-Bit 3 μ s Complete ADC)
(MAX170 12-Bit 5 μ s Serial 8-pin ADC)
(MAX172 12-Bit Low-Cost 10 μ s ADC)
AD7574 8-Bit 15 μ s ADC
(MAX160 8-Bit 4 μ s ADC)
*AD7575 8-Bit 5 μ s μ P ADC w/S/H

(MAX165 8-Bit 5 μ s μ P ADC, S/H, Ref)
(MAX166 8-Bit 5 μ s μ P ADC, S/H, Ref)
*AD7576 8-Bit 10 μ s μ P ADC
AD7581 8-Bit 8ch 67 μ s DAS
(MAX161 8-Bit 8ch 20 μ s DAS)
AD7820 8-Bit 1.3 μ s ADC
(MAX150 8-Bit 1.3 μ s ADC with Ref)
*AD7824 8-Bit 4ch 2.5 μ s ADC
(MAX154 8-Bit 4ch 2.5 μ s ADC with Ref)
*AD7828 8-Bit 8ch 2.5 μ s ADC
(MAX158 8-Bit 8ch 2.5 μ s ADC with Ref)

VOLTAGE REFERENCES

AD2700 +10V, 3ppm Ref
(MAX670 Ultra Precise +10V Ref)
AD2710 +10V, 1ppm Ref
(MAX671 Ultra Precise +10V Ref)
AD580 +2.5V Ref
AD581 +10V Ref
AD584 Programmable Ref

THERMOCOUPLE CIRCUITS

*AD594 Therm. Amps w/Comp.
*AD595 Therm. Amps w/Comp.
*AD596 Therm. Cond./Cont.
*AD597 Therm. Cond./Cont.

RMS-TO-DC CONVERTERS

*AD536A True RMS-TO-DC Converter
*AD636 Low Level RMS-TO-DC Conv.

V/F AND F/V CONVERTERS

VFC32 Prec. V/F & F/V Conv.

AMPLIFIERS

AD3554 Wideband Op Amp

MULTIPLEXERS

*AD7506 16-CH CMOS Mux
*AD7507 DIFF-CH CMOS Mux

* Second sourced only by Maxim

Send us your application and win an HP27S calculator.



Now that you know how Maxim devices replace or upgrade the Analog Devices parts in your application, send us a schematic or a block diagram detailing how they'd be used.* If, in our humble opinion, your submission is one of the ten best, we'll send you a brand new HP27S calculator! Every entrant will receive a great looking Maxim baseball hat and a 1989 Analog Applications Handbook, so don't delay.

Make a winning choice.

Send your entry today to: WIN-WITH-MAXIM, Maxim Integrated Products, 120 San Gabriel Dr., Sunnyvale, CA 94086. Or call your local Maxim representative and ask for a free sample of any Maxim improved part from the table above. They're all winners.

* Only applications used in actual prototypes, or in production are eligible. Descriptions to be written on company letterhead including name, title (or business card). Void where prohibited by law. Entries must be received by May 19, 1989 to be eligible. Maxim retains no rights to re-publish applications submitted.

MAXIM

Distributed by Anthem/Lionex, Bell/Graham, Hall-Mark, Nu Horizons, and Pioneer. Authorized Maxim Representatives: Alabama, (205) 830-4030; Arizona, (602) 730-8093; California, (408) 248-5300, (619) 278-8021; (714) 739-8891; Colorado, (303) 841-4888, Connecticut, (203) 754-2823; Florida, (407) 365-3283; Georgia, (404) 992-7240; Illinois, (312) 577-9222; Indiana, (317) 921-3450; Iowa, (319) 377-8275; Kansas, (316) 838-0884, (913) 339-6333; Massachusetts, (617) 449-7400; Michigan, (313) 968-3230; Minnesota, (612) 944-8545; Missouri, (314) 291-4777; New Hampshire, (603) 645-0209; New Jersey, (609) 933-2600; New Mexico, (505) 268-4232; New York, (516) 752-1630, (315) 437-8343; North Carolina, (919) 846-6888; Ohio, (216) 659-9224, (513) 278-0714, (614) 895-1447; Oklahoma, (214) 386-4888; E. Pennsylvania, (614) 895-1447; W. Pennsylvania, (609) 933-2600; South Carolina, (704) 365-0547; Tennessee, (404) 992-7240; Texas, (214) 238-7500, (512) 835-5822, (713) 960-9556; Utah, (801) 266-9939; Wisconsin, (414) 796-1128. Canada, (416) 238-0366, (604) 439-1373, (613) 225-5161, (514) 337-7540.

Maxim is a registered trademark of Maxim Integrated Products. © 1989 Maxim Integrated Products.

New Instruments

DC Current and Voltage Calibrator

Model CR-103/J



Model CR-103/J is comprised of two complete instruments. DC voltage section is an ultra-stable, chopper stabilized amplifier with selectable precision resistors in the feed-back loop. The temperature compensated, aged zener diode is the reference. DC current section is the same configuration plus a precision, reference resistor. HIGH STABILITY-LOW NOISE

Features Current Mode

Variable Constant: Two Ranges $\pm 10\text{nA}$ to $\pm 100\text{mAdc}$
 High Resolution: $\pm 0.0001\%$ (1 PPM)
 Minimum selectable setting 10 nAmps
 High Accuracy (1 Mode): $\pm 0.005\%$ of setting + 0.005% of range
 Compliance (Power): ± 100 volts
 Noise: 2 u Amps
 Calibration cycle: 12 months

Features Voltage Mode

Variable Constant: Three Ranges: $\pm 100\text{nV}$ to ± 10 Vdc
 High Resolution: 0.0001% (1 PPM)
 Compliance (Power): 50 mAmps
 Noise: 5 uV
 "Crowbar" (Zero) Ref.

Price: \$2,095

Engineering Contact: **Bob Ross**

Tel: (617) 268-9696 • FAX: 268-6754

CIRCLE NO 45

μ P-based Programmable E/I dc Calibrator

Model 521



The new Model is a micro-processor based, IEEE-488 (GP-IB) controlled, Voltage and Current DC Calibrator. One of its important applications is an imbedded standard as used in Data Acquisition and Process Control Systems.

An important feature of the new micro-processor that has been installed is that the programming of this instrument is transparent with respect to the programs written for the earlier 520, 520/A and even the older 501/J (GP-IB version).

The height is only 3 1/2" and features current mode outputs from 10 nanoamperes (nA) to 110 milliamperes (mA), in two ranges, with extraordinary compliance of 100 Vdc. Even with this power, ideal for transducer instrument testing (4-20 and 10-50 mA), the accuracy is $\pm 0.005\%$ of setting.

The voltage has three ranges with outputs from 100 nV to 100 Vdc and optional to 1100 Vdc. Compliance current is 100 mA. The one-year accuracy is $\pm 0.002\%$ of setting.

All ranges and both modes resolve to 1 ppm. A crowbar zero provides a reference for this essential value.

Price: \$3,150.

Engineering Contact: **Bob Ross**

Tel: (617) 268-9696 • FAX: 268-6754

ELECTRONIC DEVELOPMENT CORP.

11 Hamlin St., Boston, MA 02127


CIRCLE NO 31

INSTRUMENTS

The ADC exhibits no missing codes from 0 to 50°C and allows for internal, external, and data-dependent triggering. The differential inputs have a CMRR >100 dB at 60 Hz. The unit incorporates a 1k-word buffer for the A/D conversion results; the buffer continues to accumulate data during DMA transfers, thus avoiding gaps in the acquired data. The sequence controller, which includes a precision clock, can store such information as the correct gain and trigger mode for each channel. \$3700. Delivery, eight to 10 weeks ARO.

Analogic Corp., 8 Centennial Dr, Peabody, MA 01961. Phone (800) 343-8333; in MA, (508) 977-3000. TLX 949307.


Circle No 412



LOGIC ANALYZER

- Converts your scope into 16-channel analyzer
- Has clock with four speeds to 10 MHz

You can connect the 3.75-lb, 4 x 7 x 10-in. LA-1610 logic analyzer to an oscilloscope. When you've set the scope's sensitivity to 0.5 V/div and its sweep speed to 50 $\mu\text{sec/div}$, you've converted the scope into a 16-channel logic analyzer that can capture 256 events and display 32 of them at once on the scope's screen. You can also position a cursor and read the data on a set of six 7-segment LEDs. You can qualify the trigger conditions in several ways; for example, by setting specific values for the incoming data. You can use the unit as a timing analyzer; it has an internal clock



LOW PRICE PC ICE.

There is a low-cost 80C196 emulator that lets you debug your software *before* target hardware is available. One that supports in-target debug in real-time. Provides full symbolic support. And displays your source code during debug. All from your PC/AT host. All for \$3,500.

And best of all, it's a Genuine Intel emulator. The ICE™-196KB/PC Emulator.

Economy Without Compromise.



CIRCLE NO 32

\$3,500 Each.
Available Now.

At this price, no 80C196 programmer should be without one. To order, or for more information, call:
800-874-6835

© 1989 Intel Corp.
ICE™ is a trademark of Intel Corp.


TEK BRINGS FFT ANALYSIS OUT OF THE DARK AGES.



See the light. With the Tektronix 2630 Fourier Analyzer.

See the light with power. Used as a smart terminal, your PC can unleash the incredible power of the 2630 through high-quality graphics, full keyboard control and nearly limitless mass storage.

See the light with flexibility. Two or four channels. Variable frame size. Optional zoom. And optional arbitrary signal generation. Get all the advanced post-processing you need with seamless data transfers to PC-based



programs such as PC-Matlab, Matrix_x[™] and STARMODAL[™].

See the light with simplicity. All the controls are on one screen. Master common measurements in minutes. And when you're ready to step beyond the ordinary, the touch of a button opens up possibilities limited only by your imagination.

Step out of the Dark Ages into the light with the 2630 Fourier Analyzer. And never look back. For details, or to receive a demo disk, call 1-800-234-1256,

or write: Tektronix, 1350 Dell Ave., Suite 104, Campbell, CA 95008.

The 2630 *Personal* Fourier Analyzer

PC-Matlab is a product of the MathWorks, Inc.

Matrix_x is a trademark of Integrated Systems, Inc.

STARMODAL is a trademark of Structural Measurement Systems, Inc.

Copyright © 1988 Tektronix, Inc. All rights reserved. AJA-918


Tektronix[®]
COMMITTED TO EXCELLENCE

TEST & MEASUREMENT INSTRUMENTS

whose rate you can set to four values from 1.25 to 10 MHz. \$495.

Global Specialties, Box 1405, New Haven, CT 06405. Phone (800) 634-0762; in CT, (800) 445-6250. FAX (203) 468-0060.


Circle No 413



a scope. The isolator consists of two units—a battery-powered transmitter and a receiver. The properties of the fiber-optic cable impose the only real limit on the permissible common-mode potential between the transmitter and the receiver. Though the spec is 100 dB to 10 kHz, the CMRR at dc is essentially infinite. The isolator is dc coupled and has a -3-dB bandwidth of 15 MHz. With 1m cable, \$2495; with 50m cable, \$2795.

Nicolet Instrument Corp, Box 4288, Madison, WI 53711. Phone (800) 356-3090; in WI (608) 271-3333. TWX 910-286-2737.

Circle No 415



20-MHz GENERATOR

- Produces synthesized quadrature outputs
- Resolves frequencies to six digits

The KSG-20Q is an IEEE-488-controlled 0.1-Hz to 20-MHz frequency synthesizer and function generator. It has a pair of outputs related in phase by 90° that can deliver 20V p-p into a 50Ω load. The output amplifiers can slew at 1.5V/nsec; they follow attenuators that you can program over a 60-dB range. Six-digit resolution lets you increment the output frequency in steps of μHz at the lowest frequency and several Hz at the highest frequency. An LCD indicates the output voltage in dBV or V p-p and the frequency. The unit stores several front-panel setups. \$2245; KSG-20 (with single output), \$1845.

ET Tech Inc, 15 S Van Brunt St, Englewood, NJ 07631. Phone (201) 569-3339. TLX 642145.

Circle No 414

SCOPE ISOLATOR


- Measures at CMV limited only by fiber-optic cable
- Provides 15-MHz bandwidth (-3dB)

The Isobe 3000 is a wideband fiber-optic isolator for off-ground analog signals that you need to display on

BENCHTOP SUPPLY

- Provides two 0 to 30V and one 4 to 6V output
- Includes a tracking output facility

The TS3023S is a triple-output benchtop power supply. Two of its outputs provide as much as 2A at voltages in the range 0 to 30V, and the third output provides as much as 4A at 4 to 6V. All the unit's outputs feature remote-sensing terminals. The 2A, 0 to 30V outputs each have two 3½-digit LCDs that simultaneously display both the output current and voltage. With the corresponding output switched off, you can use these displays to preset the output voltage and the output current limit prior to connection of a load. These outputs also have coarse and fine voltage controls that allow you to set the output voltage at a resolution higher than 5 mV. Their current-limit control is logarithmic to ensure adequate control



POWER TOOL.

ICE™-196KB/HX. Intel's all-new, high-power emulator offers greatly expanded capabilities and new debugging power. Like advanced break/trace. Expanded mappable memory. Precise 12 MHz real-time debugging. And powerful Intel symbolics.

ICE-196KB/HX. It's the new Power Tool for 80C196 designers.



Power Tools for Power Users.



CIRCLE NO 33

Free Intel Language

Buy an ICE-196KB/HX Emulator now and receive your choice of one of the following Intel 80C196 languages:
ASM • PL/M • C
A \$750 value! Absolutely Free!
To order or for more information, call:
800-874-6835
Offer expires June 30, 1989.

© 1989 Intel Corp.
ICE™ is a trademark of Intel Corp.



The program in a switch.

Introducing Vivisun Series 2000, the programmable display pushbutton system that interfaces the operator with the host computer. The user friendly LED dot-matrix displays can display any graphics or alpha-numerics and are available in green, red or amber. They can efficiently guide the operator through any complex sequence, such as a checklist, with no errors and no wasted time.

They also simplify operator training as well as control panel design. Four Vivisun Series 2000

switches can replace 50 or more dedicated switches and the wiring that goes with them. In short, Vivisun Series 2000 gives you more control over everything including your costs.

Contact us today.



AEROSPACE OPTICS INC.

3201 Sandy Lane, Fort Worth, Texas 76112
(817) 451-1141 • Telex 75-8461 • Fax (817) 654-3405

SERIES
VIVISUN 2000™



Programmable display switches. Making the complex simple.

For specialty
flat glass,
call on the
Solutions People.

If your design calls for flat glass as thin as 0.003" or as thick as 2 1/4", come to the greatest name in glass.

Corning has been developing glass to meet specific needs since 1908. Today, that experience is invaluable in providing solutions for design engineers.

Why should you come to Corning?

We offer flat glass in the widest range of compositions with characteristics such as near-zero alkali content, flat smooth surfaces, and low thermal expansion coefficients. In addition, our PYREX® and VYCOR® brands are industry standards.

Corning has provided design solutions for an astonishing range of flat glass applications, such as:

- LED, LCD and CCD windows and covers
- Circuit-board substrates

- Substrates for resistor networks
- IR and UV-transmitting windows
- Thin-film interface filters
- High temperature industrial viewports
- Solar panels
- Thin-film recording heads
- Substrates for vapor deposition
- Touch screens and panels

That's why we're the world's largest manufacturer of specialty flat glass.

Circle the reader service number to receive more information about Corning's flat glass properties. Or call us.

When it comes to flat glass technology, we really shine.

Materials Business
Corning Glass Works
MP 21-3-4
Corning, NY 14831
607-974-4454



CORNING

CIRCLE NO 34

digelec PROM & Logic
Programmers

**THE LOW COST
OF HIGH PERFORMANCE...**



**MODEL 824
PORTABLE PROGRAMMER**

● PROGRAMS:

- 16K to 1024K Bit E²/EPROMs from all manufacturers (more than 220 devices)
- Intel (87xx) and Motorola (68701/68705, 28-and 40-pin) single chip micros

● FEATURES:

- 64K Byte standard RAM (expandable to 256K Byte)
- Built-in UV eraser
- Fully programmable VCC & VPP for future programming needs
- Plug-in SOFTPACK cassette for do-it-yourself software updates
- Detects Device type (signature)
- Detects misplaced device

● SUPPORTS:

- 5 different programming algorithms, including Intel Intelligent and Quick-Pulse, AMD Flashrite

● OFFERS OPTIONALLY:

- SOFTLINK remote control software for IBM PC/XT/AT
- PLCC module
- Adapter for 1 M bit EPROMs and Motorola micros

We provide on-line technical support and have a fully staffed lab on site.


digelec

USA: DIGELEC INC.,
22736 Vanowen Street
Canoga Park, CA 91307
Tel: (800) 367-8750
In CA: Tel: (818) 887-3755
Fax: (818) 887-3693

CIRCLE NO 35

269

HERMETIC-SOT JOINS THE RANKS.



Introducing the First Hermetic Surface Mount Transistor.

Amperex now offers you its custom semiconductor packaging expertise in a new form...H-SOT. The development of the ceramic H-SOT package allows you to have the transistors of your choice mounted in a leadless package that is rugged and reliable. Even for military duty.

H-SOT features:

- Hermetic seal
- Leadless design
- SOT-23 footprint
- JAN-TX screening

Enlist our services and take advantage of surface mount technology in your hi-rel and military applications. Call us at 401/762-9000 x328 to discover the broad range of hermetic surface mount transistors available to you.

Amperex[®]

HYBRID MICROELECTRONIC PRODUCTS GROUP

PHILIPS



Amperex Electronic Company, A Division of North American Philips Corporation,
Providence Pike, Slatersville, RI 02876. Phone: 401/762-9000 x328
FAX: 401/762-9000 x404.

CIRCLE NO 38

DID YOU KNOW?

EDN is distributed
at every major
electronics/computer show in the
U.S., France, and Germany.

EDN

INSTRUMENTS

at low current settings. They automatically cross over from constant voltage to constant current mode, and a display annunciator indicates when the constant current mode is active. You can switch the two 0 to 30V outputs into a tracking mode. The 4A, 4 to 6V output has a single 3½-digit LCD that displays the output voltage when the output is switched off, and the output current when the output is on. All the outputs are protected against both forward and reverse voltages. £385.

Thandar Electronics Ltd, 2 Glebe Rd, Huntingdon, Cambridgeshire PE18 7DX, UK. Phone (0480) 412451. TLX 32250. FAX 0480-411463.

Circle No 416

VLSI TESTERS

- *Burst 200M patterns/sec without multiplexing*
- *Drive and sense on 256 and 512 pins*

The LT-1001 and the LT-1101 are 256-pin and 512-pin testers, respectively, for VLSI devices. Except for pin count, the systems provide identical electrical performance. The I/O channels have a voltage range of -2.5 to +7.5V. They drive the DUT (device under test) from a 50Ω source and load the DUT with 50Ω. According to the vendor, these impedance and voltage levels, coupled with a nonmultiplexed 200M pattern/sec data rate, allow the systems to test ECL, high-speed TTL, and CMOS parts and also allow single-pass testing of BiCMOS and BiMOS devices. The systems combine shared resources with tester-per-pin architectural concepts. LT-1001, \$1,200,000; LT-1101, \$2,300,000. Delivery, 90 days ARO.

Tektronix Inc, Box 4600, MS 94-441, Beaverton, OR 97076. Phone (503) 629-1035.

Circle No 417

A.T.E.



P.D.Q.

Keithley's 556
adapts to your tests as fast as you
can change cards.

If your automated test requirements change often, you know how difficult it is to keep up. Expensive new instruments. Sensors that require special conditioning. Complex programming.

Not any more. Now the Keithley Model 556 GPIB Measurement & Control System lets you interface a full range of transducers to the IEEE-488 bus. Mix any 10 signal conditioning modules from a library of over 25 specialized functions. Thermocouples, strain gages, digital and analog I/O, power control, frequency, motion . . . more.

Simple yet powerful commands run with the language of your choice, and work with Mac, NEC, DEC, HP, or any 488 controller. On-board intelligence and memory let the 556 run as a stand-alone datalogger or process controller.

Best of all, this power and performance start around \$2500. Check it out, PDQ, with a toll-free call to the PC Team at 1-800-552-1115. Or write: Data Acquisition & Control Division, Keithley Instruments, Inc., 28775 Aurora Rd., Cleveland, OH 44139.



KEITHLEY

digelec PROM & Logic
Programmers

**1-2-3-4
AT A TIME
MAKES PROGRAMMING
AS EASY AS
1-2-3-4**



MODEL 825 SET PROGRAMMER

● PROGRAMS:

- Up to 4 devices simultaneously with the **same** or **different** data.
- 16K to 1024K Bit E²/EPROMs** from all manufacturers (more than 220 devices)
- Intel (87 xx) and Motorola (68701/68705, 28- and 40-pin) single-chip micros**

● FEATURES:

- 8, 16, 32 bit or GANG** operations
- 64K Byte standard RAM** (expandable to **256K Byte**)
- Built-in UV eraser**
- Plug-in **SOFTPACK** cassette for do-it-yourself software updates
- Programming **Verification at 3 VCCs**
- Fully **programmable VCC & VPP** for future programming needs
- Detects Device type** (signature)
- Detects misplaced device**

● SUPPORTS:


- 5 different programming algorithms, including **Intel Intelligent** and **Quick-Pulse, AMD Flashrite**

● OFFERS OPTIONALLY:

- SOFTLINK** remote control software for **IBM PC/XT/AT**
- PLCC** module
- Adapter for **1 M bit EPROMs** and **Motorola micros**

digelec

USA: DIGELEC INC.,
22736 Vanowen Street
Canoga Park, CA 91307
Tel: (800) 367-8750
In CA: Tel: (818) 887-3755
Fax: (818) 887-3693



Brochure presents network-access products

This 24-pg brochure describes the vendor's complete line of network-access and restoration products. The booklet covers digital, VF, and coaxial patching and switching equipment; interface converters; the Restorer multiline dial-backup system; NTS network management systems for data; the Artacs PBX Management system for voice; and Interview Series test instrumentation.

Atlantic Research Corp, Teleproducts Div, 7401 Boston Blvd, Springfield, VA 22153.

Circle No 420


Study reports on user ratings of equipment

The vendor's annual computer-user survey "US User Ratings of Mainframes and Minicomputers" polls more than 1100 mainframe and minicomputer users. The 40-pg study combines data about systems and usage with user ratings of equipment and manufacturer support and provides an evaluation tool for prospective users of computer systems. Current users discuss their system's hardware configuration, organization, price, and planned expansions. Additional questions cover specific reasons for customer satisfaction, such as ease of operation, system or peripheral reliability, maintenance service,

technical support, ease of programming and conversion, and overall satisfaction. \$200.

Datapro Research, 1221 Avenue of the Americas, New York, NY 10020.

INQUIRE DIRECT



Modular system for measuring pc-board copper

This 4-pg brochure introduces the MR 4000 modular-coating thickness-measuring system that helps you select the components that are most suitable for pc-board surface-copper or plated through-hole quality-control requirements. The publication provides complete component specifications and a list that explains the functions of each component. Further, it specifies two statistical packages, standard and "Stats-Plus" for customized header software.

CMI International, 2301 Arthur Ave, Elk Grove Village, IL 60007.


Circle No 421

Comprehensive listing of power supplies

The vendor's 1989 catalog lists more than 150 new power supplies and dc converters. The 200-pg publication lists products that come in commercial, industrial, and military versions. Other sections of the 9-part catalog deal with laboratory and test equipment, custom power

More quality switching components from P&B


Circuit Breakers



P&B circuit breakers provide the quality you need at a price you can afford. Both thermal and magnetic types are available, and many are UL recognized as supplementary protectors and CSA certified as appliance component protectors.

CIRCLE NO 83

General Purpose Relays



One of the broadest lines of general purpose relays in the industry is offered by P&B. Open and enclosed styles are available with various contact materials, contact arrangements, termination styles and coil voltages.

CIRCLE NO 84

Time Delay Relays



P&B time delay relays combine precision, solid state timing circuits with our proven electromechanical relays. A wide selection of timing functions, timing ranges, degrees of precision and package styles permits you to select a unit with just the features you need.

CIRCLE NO 85

Make your move to P&B for new general purpose and power P.C. board relays.



New Models Expand Offering

For applications from consumer goods to industrial controls, P&B relays have the features you need for general purpose and power switching on your printed circuit board. New series greatly expand our already broad line of P.C. board relays. Many models are available from stock, and they're all built to the same exacting standards that have made our T90 series the industry-standard 30A, P.C. board relay.

New Miniature Relays Switch 1mA to 10A

Our new T73 and T74 series miniature P.C. board relays join the T70 series as inexpensive SPDT units for general purpose applications. A variety of contact materials allow units in these series of sealed relays to switch loads from 1 mA through 10A.

Expanded Line of 4,000V Isolation Relays

Extensions to our line of RK series relays feature 8mm coil-to-contact spacing for 4,000V isolation. SPDT models switch loads to 20A, and DPDT models switch up to 5A. Both sealed and unsealed types are offered.


T90 & T91 — Our 30A Workhorses

Relays in our T90/T91 series have SPDT contacts for loads to 30A. T90 is available as a sealed or open-style relay. T91 has quick connect terminals for load connections and is offered with either a sealed or unsealed enclosure. High temperature units are available.

Find Out More

Contact us today for free information on the complete line of P&B P.C. board relays, including more new models for switching 2A and less. Potter & Brumfield, A Siemens Company, 200 S. Richland Creek Drive, Princeton, Indiana 47671-0001.

Call toll-free 1-800-255-2550 for the P&B authorized distributor, sales representative or regional sales office serving your area.



Potter & Brumfield A Siemens Company

systems, and accessories. A product selector guide, a section of mechanical drawings, and warranty and ordering information complete the catalog.

Lambda Electronics, 515 Broad Hollow Rd, Melville, NY 11747.

Circle No 422

Supplement for microwave test accessories

In this 20-pg supplement to the 1986 catalog, the vendor describes the latest coaxial and waveguide-measurement accessories. The publication features the 2.4-mm coaxial connector and products such as detectors, attenuators, and terminations. Also highlighted are mm-wave waveguide products that range from 26.5 to 110 GHz and include precision coupler/attenuators, mismatches, and terminations. The publication notes that the recent in-


roduction of new vector and scalar network analyzers has generated a need for updated calibration and verification kits to support these instruments. A current index provides a list of discontinued products.

Hewlett-Packard Co, 19310 Pruneridge Ave, Cupertino, CA 95014.

Circle No 423

Discussion of distributed control systems

A Hands-On Approach to Distributed Systems Using ARC Control discusses the design and application of ARC Control, an IBM PC or compatible bus-based intelligent I/O subsystem. The 74-page handbook provides figures, photos, and tables and concludes with four appendixes containing an acronym guide, answers to ARC-control questions, references, and a component list



that provides power-consumption requirements.

Contemporary Control Systems Inc, 2500 Wisconsin Ave, Downers Grove, IL 60515.

Circle No 424



ARIES[®]
ELECTRONICS, INC.

P.O. Box 130
Frenchtown, NJ 08825
Telephone (201) 996-6841
Telex 6974615
FAX 201-996-3891

Headers, Sockets, Jumpers, DIP Switches, .025 Sq. Stix, etc.

**LOW COST, EASY TO USE
FLEX CABLE JUMPERS
with solid
flat pins**

Solid copper flat pins are firmly crimped, through polyester insulation, into solid copper flat conductors making a series of gas-tight connections producing excellent electrical characteristics.

The thin flexible copper flat conductors are laminated between tough flame retardant polyester (qualities to Mil C-5543-A, NASA 729 and UL Style 2643), using a polyester mylar adhesive.

Flat copper solid pins make easy interconnection of flexible jumpers to p.c. board holes, or other types of interconnect hardware.

**Series 171 Flat Pin Flex Jumpers
available 2" to 24" lengths**

4, 5, 6, 7, 8, 9, 10, 12, 15 and 20
conductors on .100 centers our standard.
Consult Aries for other sizes.

See EEM Vol. C, pgs. 1185-1190

ICEolate Bugs Twice as Fast!



Softaid ICEBOX and IceAlyzer In-Circuit Emulators give you the affordable and extremely powerful microprocessor development systems you need to complete hardware/software projects on time and within budget.

- 64180, 647180X, Z80, Z280, Z180, 8085, 8088/86, 80188/186, V40/50, NSC800
- 65,536 Full speed hardware breakpoints
- Source Level debugging with windows
- Performance Analyzer isolates bottlenecks
- Real time trace buffer
- ICEBOXes priced at \$595 to \$1595
- IceAlyzers from \$3090

Call for free "Guides to Applications Development"



8930 Route 108
(800) 433-8812

Columbia, MD 21045
(301) 964-8455


EDN PRODUCT MART

This advertising is for new and current products.

Please circle Reader Service number for additional information from manufacturers.

ELMEC ULTRA HIGH-SPEED FIXED DELAY LINES

FDC TYPE
SINGLE
IN LINE



FDR TYPE
SURFACE
MOUNT

FDC and FDR types can be fully matched to high speed logical elements such as 100K, 10KH and 10K series and has an extensive range of applications including analog circuit.

Part Number	Impedance	Delay Time	Output Rise Time (20%-80%)	Pass Band
Single In Surface Mount				3dB
FDC 0505 FDR 0505	500 ± 10%	0.5ns ± 0.10ns	300ps or Less	800MHz or More
FDC 1005 FDR 1005		1.0ns ± 0.10ns	300ps or Less	800MHz or More
FDC 1505 FDR 1505		1.5ns ± 0.15ns	400ps or Less	550MHz or More
FDC 2005 FDR 2005		2.0ns ± 0.20ns	400ps or Less	550MHz or More
FDC 2505 FDR 2505		2.5ns ± 0.20ns	500ps or Less	450MHz or More
FDC 3005 FDR 3005		3.0ns ± 0.20ns	500ps or Less	450MHz or More
FDC 3505 FDR 3505		3.5ns ± 0.25ns	600ps or Less	400MHz or More
FDC 4005 FDR 4005		4.0ns ± 0.30ns	700ps or Less	350MHz or More
FDC 4505 FDR 4505		4.5ns ± 0.30ns	700ps or Less	350MHz or More
FDC 5005 FDR 5005		5.0ns ± 0.30ns	700ps or Less	350MHz or More
FDC 0510 FDR 0510	1000 ± 10%	0.5ns ± 0.10ns	300ps or Less	800MHz or More
FDC 1010 FDR 1010		1.0ns ± 0.10ns	300ps or Less	800MHz or More
FDC 1510 FDR 1510		1.5ns ± 0.15ns	400ps or Less	550MHz or More
FDC 2010 FDR 2010		2.0ns ± 0.20ns	400ps or Less	550MHz or More
FDC 2510 FDR 2510		2.5ns ± 0.20ns	500ps or Less	450MHz or More
FDC 3010 FDR 3010		3.0ns ± 0.20ns	500ps or Less	450MHz or More
FDC 3510 FDR 3510		3.5ns ± 0.25ns	600ps or Less	400MHz or More
FDC 4010 FDR 4010		4.0ns ± 0.30ns	700ps or Less	350MHz or More
FDC 4510 FDR 4510		4.5ns ± 0.30ns	700ps or Less	350MHz or More
FDC 5010 FDR 5010		5.0ns ± 0.30ns	700ps or Less	350MHz or More


ELMEC TECHNOLOGY OF AMERICA, INC. 1225 Ridgcrest St., Monterey Park, CA 91754
Phone: (213) 265-1861 FAX: (213) 265-1908

CIRCLE NO 325



"The Best 8051 Emulator"

NEW
Source Level
support for
PL/M-51
and C-51



5 ft. cable

8051

See EEM 88/89
Page D-1304

PC based emulators for the 8051 family

- (8051/51FA/52/31/32/44/152/451/452/535/552 + CMOS + more ...
- PC plug in boards or RS-232 box
- Pull-down menus combined with Command-Driven User Interface.
- Context sensitive help and On-Screen Editing of data
- 20 MHz real time emulation
- 128K emulation memory
- 48 bit wide, 16K deep trace buffer with loop counter
- Program Performance analyzer
- Powerful Macros with IF-ELSE, REPEAT-WHILE structures
- Source Level debug for PL/M-51 and C-51
- Symbolic debugging with in-line assembler and disassembler
- Execution time counter
- Trace can be viewed during emulation!

PRICES: 32K Emulator for 8031 \$1790; 4K Trace \$1495*

CALL OR WRITE FOR FREE DEMO DISK!

Ask about our demo VIDEO!

*U.S. only


NOHAU
CORPORATION

51 E. Campbell Avenue
Campbell, CA 95008
FAX (408) 378-7869
(408) 866-1820

CIRCLE NO 326

FREE CATALOG!

MULTIBUS BOARD
PRODUCTS
MULTIBUS I, II &
VME ENCLOSURES



1989 36 Page Catalog features:

- ZX-286 PC/AT CPU
- ZX-286/20 20MHz CPU
- ZX-386/16 CPU
- ZX-298 SCSI Host Adapter w/Clock
- ZX-981 Universal Enclosure


ZENDEX

6700 Sierra Lane, Dublin, CA 94568
TEL: (415) 828-3000 FAX: (415) 828-1574

CIRCLE NO 327

FREE SCHEMATIC CAPTURE DEMO DISK

SCHEMA II+:
Capture More Than Ever



Incredible speed, ease of use and power have made SCHEMA a best-selling schematic capture program for engineering professionals the world over. Now, SCHEMA II+ sells for \$495 and

supports most common IBM
PC/XT/AT/PS2 configurations.



OMATION

In Texas Call (214) 231-5167

FREE Demo Disk: 1-800-553-9119

CIRCLE NO 328

PRECISION CLIP-ON DC MILLIAMMETER



MODEL APS428C

- ENABLES CURRENT MEASUREMENTS FROM 20 µA to 2 A WITHOUT CIRCUIT INTERRUPTION
 - DC AND TRUE RMS AC MODES
 - PRECISION OFFSET CAPABILITY UP TO 2 A
 - ENABLES MEASUREMENT OF MAGNETIC FIELDS FROM 1 µG TO 2 G (WITH OPTIONAL MAGNETOMETER PROBE)
 - PROBE ISOLATION: 300V
 - COMPATIBLE WITH HEWLETT PACKARD CLIP-ON PROBES AND MAGNETOMETER PROBES
- Call us to discuss your specific application!

**A P P L I E D
P H Y S I C S
S Y S T E M S**

415-965-0500

897 Independence Ave.
Mountain View, CA 94043

CIRCLE NO 329



PLD/EPROM

#1 in
Software
#1 in Speed



- Software driven and upgradable
- Direct control by IBM PC/XT/AT/PS2 eliminates time consuming downloading
- Automatic batch/macro file support
- Virtual memory -- requires no RAM modules even for megabit devices.

SAILOR-PAL: Universal pin drivers support PALs, GALs, PLDs, EPLDs, PEELs, ECLs, EPROMs, PROMs, FPLAs, FPLSs and MICROs. Accepts JEDEC files from CUPL, AMAZE, ABEL, etc. \$1095 - \$1895

SAILOR-2,-8: 2 and 8-socket set/gang high speed EPROM programmers, to Mbit devices. \$545/\$975



ADVIN SYSTEMS INC. Sunnyvale, CA 94086
(408) 984-8600 • FAX (408) 736-2503

Please call for free demo disk.

CIRCLE NO 330

To advertise in Product Mart, call Joanne Dorian, 212/463-6415

Only a Specialized Manufacturer Could Provide
Versatile and Economic Products



With more than 11 years' experience in this field, we proudly offer you various types of conductive silicone rubber pads, rubber pads with multicolor and screen printing, silicone rubber overlay, rubber pads with screen printing on plastic keypads, O rings, washers, inner caps, tubes, etc., and screen printing flexible circuit boards. Please contact us for more information.




GENERAL SILICONES CO., USA
650 W Duarte 305, Arcadia CA 91006, U.S.A.
Tel: (818) 445-6036. Telex: 3716189 GSCUI.
Fax: 818-4456084

CIRCLE NO 331

E/EPROM & MICRO PROGRAMMER

\$895



- EP-1140 includes: software, cable, user's manual, 2 free software update coupons, toll-free technical support, one-year warranty & a unconditional 30-day money back guarantee
- Programs 24-, 28-, 32- & 40-pin E/EPROMs
- Supports 874X & 875X series microcontrollers
- Connects to a standard parallel port
- Hardware to support future parts to 8 Megabit
- Software updates on floppy disk
- 32-pin model, EP-1132, available for \$695


The Engineer's Programmer™

CALL TODAY 800-225-2102

BP MICROSYSTEMS

10681 Haddington, #190, Houston, TX 77043
713/461-9430 FAX 713/461-7413
Electro Booth #374

CIRCLE NO 332




WE'RE BENDING THE RULES FOR CIRCUIT DESIGNERS

BEND/FLEX™, the bendable board material flexible enough to bend into any multi-plane shape. Eliminates stiffeners, flex-hardboard connectors. May reduce cost of two- and three-plane interconnect systems by as much as 30%!

Rogers Corporation. One Technology Dr.,
Rogers, CT 06263. (203) 774-9605.

CIRCLE NO 333




ISDN "S" INTERFACE TRANSFORMERS

Tokin America has introduced a line of transformers designed for the Integrated Services Digital Network. These miniature units meet the requirements of CCITT 1.430 and support 2B + D channels at a total line rate of 144 kbps to 192 kbps. A number of winding ratios are available as standard. Applications include telephone, terminal, computer, or any other high speed digital transmission equipment.

Tokin America
155 Nicholson Lane, San Jose, CA 95134
408-432-8020

CIRCLE NO 334




UNIQUE NEW SAMTEC LCD CONNECTOR

New LCD connector is a hybrid, combining the advantages of pin and socket connectors and "elastomeric" connectors, without the disadvantages. One standard connector accommodates a wide variety of LCD designs. It handles LCD's up to 4" in length, any desired width. Snap-strip feature allows shorter length connectors in any multiple of .100" (2.54 mm) so that there is no wasted board space, no custom connector charges. Elastomeric provides a "cushion" for high vibration and thermal/physical shock. This new LCD Series connector features "zero insertion force" which eliminates insertion/withdrawal damage to the display and connector.

Samtec, Inc.
P.O. Box 1147, New Albany, IN 47150
Telephone 812/944-6733 Fax 812/948-5047

CIRCLE NO 335

WAVEFORM SYNTHESIZER




- For IBM-PC/XT/AT and compatibles
- Generates user-definable signal
- Up to 2000 points per envelope

QUA TECH
INCORPORATED

\$795.00

478 E. Exchange St. Akron OH 44304
(216) 434-3154 TLX: 5101012726
1-800-553-1170

CIRCLE NO 336



SOLVE MULTIBUS I SPEED PROBLEMS

New Microstrip Backplanes enhance performance of Multibus I with 80386 and other fast processors. Send for Catalog and free backplane design tutorial.


Hybricon

12 WILLOW ROAD, AYER, MA 01432
FACTORY WESTERN OPERATIONS
508-772-5422 602-921-1824

CIRCLE NO 337

25PDT SWITCH

HIGH DENSITY PC MOUNT



HDMP-25 LOW PROFILE **HDMP-25M THRU-PANEL KNOB**
GOLD PLATED STRESSED ELLIPTICAL CONTACTS

Route data - address buses - communications
Swap ICs/EPROMs In-circuit
Reconfigure hardware
Redundant designs

Upgrade firmware or run diagnostics
*without down time
*without user interruption

HDMP-25EK evaluation kit includes switch, printed circuit board and I/O connectors: \$34.95

HDMP-25 (1-9) \$17.50 (10) \$13.75 (100) \$9.95
HDMP-25M (1-9) \$18.50 (10) \$14.25 (100) \$10.35

ANNULUS **ANNULUS TECHNICAL INDUSTRIES, INC.**
1296 Osprey Drive P.O. Box 7407
Ancaster, Ontario CANADA L9G 4G4
Tel 416-648-8100 FAX 416-8102

CIRCLE NO 338

MOUSER ELECTRONICS


consider the
SOURCE
Make
MOUSER Electronics
your factory-authorized source
for over 80 quality electronic
component manufacturers like:

**AUGAT, NEC,
TECCOR, RCA, GE,
& SGS-Thomson.**

Toll-free ordering
Coast-to-coast distribution
Same day shipping
25 years of service
Call today for your free
MOUSER Electronics Catalog.
1-800-992-9943

CIRCLE NO 339

To advertise in Product Mart, call Joanne Dorian, 212/463-6415




**25MHz 48 CHANNEL
PC-BASED LOGIC ANALYZER
\$1595.00 + POD PRICE**

- 48 Channels @25MHz x 4K word deep
- 16 Trigger words/16 trigger sequence
- Automatic set-up and loading of symbol tables
- Comparison of Reference and Trace Memories
- Storage and recall of trace data to disk
- 20 Channel Waveform Display
- Disassemblers available for:
8088, 8086, 68000, Z80, 8085, 80286
6502, 6801, 6303, 8031, 6809, 6811
NCI □ 6438 UNIVERSITY DRIVE,
HUNTSVILLE, AL 35806
(205) 837-6667

CIRCLE NO 340

Redel Connectors




The Plastic Choice

- REDEL Features:
- Quick Connect-Disconnect Design
 - Autoclaveable PSU Shell Material
 - Lightweight and Compact
 - Temperature & Corrosion Resistant
 - Color Coding and Keying Exclusivity
 - Variety of Shell Styles and Configurations
 - 2-9 Solder or Printed Circuit Contacts
 - Precision Designed and Engineered
 - Cable Assemblies

Sold and distributed by
LEMO USA, INC., P.O. Box 11488, Sanata Rosa, CA 95406
Phone (707) 578-8811, FAX 707/578-0869, Telex 340-933.
Please call for the rep nearest you.

CIRCLE NO 341

**DATA ACQUISITION &
CONTROL COMPUTER**



The SBS-250 is an intelligent data acquisition and control system on a single card. Includes CAMBASIC™ language, a multitasking industrial compiler. Programs autorun on powerup. Supports bit manipulation, floating point, interrupts, strings, serial communications, realtime clock and more. Built-in EPROM and EEPROM programmers. CMOS-temperature range -20° to 65°C. 12-bit A/D converter, 32 digital I/O lines, two serial ports, keypad port, opto-module rack and relay drivers. Only 4.5" x 5". IBM PC can be used to develop programs. Try it FREE for 30 days. Call 303-430-1500 for demo information and complete catalog. Price \$395 single unit.

OCTAGON SYSTEMS CORPORATION 6510 W. 91st Ave.
Westminster, CO 80030

CIRCLE NO 342

**NEW
100% Autorouter**

HiWIRE-Plus provides the integrated schematic-capture and PCB layout versatility needed by leading-edge designers. Now it also offers an advanced 100% autorouter. Affordably! See the full-page ad (on page 25) then call Wintek at:

(800) 742-8428

CIRCLE NO 343

**EXTRUDED ALUMINUM
PANEL MOUNT ENCLOSURES**



- Depths 6" & 8"
- Any depths, 10 or more
- Satin, clear anodize finish
- Lock-in panel-mount
- Modifications and screen printing available

DIN STANDARDS


Bezel	Case
48 x 96 mm	44 x 91 mm
72 x 144 mm	67 x 136 mm
96 x 192 mm	91 x 184 mm
96 x 96 mm	91 x 91 mm
	184 x 184 mm

FREE CATALOG

Buckeye
555 Marion Road
Columbus, OH 43207
614/445-8433

CIRCLE NO 344

dress up your **PC BOARDS**



with our **PCB LED'S!**

2mm,3mm 5mm, Single, Bilevel & Multi-LED Arrays. Diffused or Clear, 2mA Low Current, Sunlight Visible, 3V & 5V Blinking, 5V & 12V Integrated Resistor, BiColors, TriColors, Cross to Dialight 550, 551, 555, 547 Etc.

LED™ Put More LIFE in Your LIGHT
LEDTRONICS, INC. TEL: 213-676-7996
FAX: 213-676-0108 TLX: 494-5454
4009 Pacific Coast Hwy., Torrance, CA 90505

CIRCLE NO 345

SCASI Analyzer Emulator

-POWERFUL
-EASY TO USE
-AFFORDABLE

Features:
32K x 7 byte Trace Memory
50 nsec Time-Stamp Resolution
Async & Sync Tracing
Single-end & Differential
Easily readable "SCSI English" display
Gives a quick, clear and precise view of SCSI protocol.

ANCOT CORPORATION (415) 363-0667
1755 E. Bayshore Road, 18A, Redwood City, CA 94063

CIRCLE NO 346

E(E)PROM, MEMORY CARD & MICRO PROGRAMMER \$345 - \$595

- All 24/28/32 pin EProms/EEProms to 4 MBit (upgr. to 32MB).
- Flash EProms; Micros: 8741,-2,-8,-8H,-9,-9H,-51,-C51,-52,-55 ...
- Memory Cards: Seiko/Epson, Mitsubishi, GI. Modular design.
- Stand-alone E(E)Prom & Memory Card Duplication / Verify.
- User friendly menu - driven driver for IBM-PC & Macintosh.
- Built-in Eraser/Timer option (\$50). Gang-Module ready.
- Full 1 year warranty. Direct technical support. Dedicated BBS.

INTELLIGENT PROM EMULATOR \$395

- 2716 thru 27512 (2k to 64k bytes). Binary/Hex/Intel/Motorola.
- Intelligent features include: Reset Output, Address Compare, Address Snapshot, Trigger Input, Program Editing capabilities.
- FAST data loading via parallel port (64k bytes in less than 10sec).

MC/VISA/AMEX Call today for datasheets!

B&C MICROSYSTEMS INC.
355 WEST OLIVE AVE. SUNNYVALE, CA 94086
TEL: (408) 730-5511 FAX: (408) 730-5521

CIRCLE NO 347

Telecom Design!

LOOP CURRENT DETECTORS

Line Sense Relays connect in series with Tip and Ring and provide a relay closure in response to loop current flow. For on-hook, off-hook monitoring, switchhook flash detection, and rotary dial pulse counting. Simple design, rugged construction.

- M-949-01 for U.S. FCC Part 68
- M-949-02 for international IEC/VDE
- M-949-03 for Canadian DOC CSA
- M-949-XX Custom modules

For more info call: **1-800-426-3926**
(In Washington State: 206-827-9626)

TEL TONE®
10801-120th Avenue NE, Kirkland, WA 98033

CIRCLE NO 348

To advertise in Product Mart, call Joanne Dorian, 212/463-6415




JE680 Universal IC Programmer

Programs PROMs, EPROMs, EEPROMs, PALs, GALs, RALs, EPLDs and PEELs

JE680 Features:

- Stand-alone or computer controlled modes w/ MS-DOS menu-driven software (included)
- Parallel and RS232C interface ports
- Auto-Sense™ of IC insertion
- Supports/translates between 18 data formats
- Full functional test on logic devices
- Over 400 IC definitions in ROM - no personality modules needed
- JEDEC standard supported, accepting input from virtually all major software packages
- One-Year Warranty

Listing of over 400 programmable devices and 74-page catalog available upon request!




JE680 Universal IC Programmer\$1799.95

Jameco Electronics • 1355 Shoreway Road, Belmont CA 94002
• Phone (415) 592-8097 • FAX (415) 592-2503

CIRCLE NO 349

REAL WORLD I/O For PC/XT/ATs




- DG24 • 24 line digital I/O; 10 MHz 8255. \$95
- AD500 • 8 channel 12-bit (plus sign) integrating A/D; prog. gains of 1, 10 & 100; 7 digital I/O lines. \$239
- AD100 • Single channel version of AD500; 10 digital I/O lines. Same programmable gains. 700 meg input Z. \$149
- AD1000 • 8 channel 12-bit A/D; 25 uS; sample & hold; 3.5 MHz timer/counters; 24 digital I/O lines. \$295
- ADA300 • 8 channel 8-bit 25 uS A/D; single D/A sample & hold; 24 digital I/O lines. \$239
- AD200 • 4 channel 12-bit 125 uS A/D; 3.5 MHz timer/counters; 24 digital I/O lines. \$239
- DA600 • Fast settling dual bipolar D/A. \$179
- PD200 • Prototype board w/ address decoder; manual \$99

All boards include BASIC, Pascal, C, and Forth drivers. 30 day return; 1 year warranty. Call for "Real World Interfacing" application notes.

Real Time Devices, Inc.

P.O. Box 906 State College, PA 16804
(814) 234-8087

CIRCLE NO 350




41 STANDARD PACKAGES FOR TEMPERATURE ASSEMBLIES.

Specify your temperature probe assembly from 41 packages, 12 lead materials, 9 thread sizes, 6 assembly materials, 11 connectors, and 58 thermistors. All standard. If these don't meet your needs, we'll make a custom probe from your drawing. Send for our catalog. Or call toll-free, 800 343-4357 (513 767-7241).

YSI Incorporated
Yellow Springs, Ohio 45387 USA



CIRCLE NO 751




MICRO/Q 2000

FOR A DECOUPLING CAPACITOR THAT SAVES SPACE, DEFEATS NOISE, IS SUITABLE FOR MILITARY APPLICATIONS AND BEATS HUMIDITY, HEAT AND COLD:

ROGERS MICRO/Q® 2000

Rogers Corp., 2400 S. Roosevelt,
Tempe, AZ 85282. 602/967-0624

CIRCLE NO 752




NETOPT / NETSIM ANALOG CIRCUIT ANALYSIS AND OPTIMIZATION SOFTWARE

NETSIM analyzes circuits in both time and frequency domains, performs Monte Carlo, tolerance/worst case analysis and extracts poles/zeros and transfer functions. • Produce yield estimates and sensitivity analysis of your analog designs • NETOPT includes all features of NETSIM and adds sophisticated optimization capabilities • Compensate for circuit/device parasitics, generate non-standard responses and center designs for maximum yields. • NETSIM is available for IBM PC® (\$850) and VMS®/UNIX® (\$1700.00)/NETOPT is \$1995.00 for the PC and \$3995.00 for the VMS/UNIX version.

RLM Research

P.O. Box 3630, Boulder, CO 80307-3630
(303) 499-7566

CIRCLE NO 753



SAVE SPACE WITH MINI/BUS® BARS

Improve power distribution
Reduce required board layers
Eliminate up to half the decoupling capacitors
Fit between or beneath IC's


Send for Rogers Mini/Bus® Bars
Application Bulletin.

Rogers Corp., 2400 S. Roosevelt St.
Tempe, AZ 85282 602/967-0624

CIRCLE NO 754

Analog Circuit Simulation

Completely Integrated CAE with ICAP/2



From Schematic
Capture through
SPICE
Simulation to
Post Processing

for Only
\$790†

†**ISPCICE \$95**, the complete SPICE program that runs on all PC's. Performs AC, DC, and Transient analyses.

ISPCICE/386 \$386, enhanced SPICE for 386 PC's.

†**SPICENET \$295**, a schematic editor for any SPICE simulator. Generates a complete SPICE netlist.


†**INTUSCOPE \$250**, a graphics post processor that performs all the functions of a digital oscilloscope.

†**PRESPICE \$200**, extensive model libraries, Monte Carlo analysis and parameters sweeping.



P.O. Box 6607 (213) 833-0710
San Pedro, CA 30 Day Money
90734-6607 Back Guarantee

CIRCLE NO 755



HARDWARE DEBUGGER

The BusBoy51 is a new in-circuit debugging tool for 8051 based boards. Useful in both prototype and production testing, it will help isolate wiring errors and component failures. The BusBoy 51 is menu driven with a serial interface to the operators terminal. It provides preprogrammed tests for 8051 memory and I/O, detecting stuck and shorted address or data bits. The BusBoy 51 is powered by the target system and autobauds. Use the BusBoy 51 to verify prototypes, test failed boards to isolate the memory or buffer chip responsible, final check production boards for proper memory and I/O operation.


BusBoy C51 \$389.00 51H \$349.00

CALL (315) 478-0722 FAX (315) 475-8460

Logical Systems Corporation

P.O. Box 6184, Syracuse NY 13217-6184 USA
TLX 6715617 LOGS

CIRCLE NO 756



HIGH SPEED PULSE GENERATORS. This free new 80 page catalog describes over 150 models of ultra high speed pulse generators, impulse generators, monocyte generators, samplers, delay generators and accessories such as transformers, power splitters and scope probes covering the PRF range of 0 to 250 MHz, rise times from 40 psec to 10 nsec, pulse widths from 130 psec to 100 usec and amplitudes from 5 to 400 volts.


AVTECH ELECTROSYSTEMS LTD.

P.O. Box 5120 Stn. F
Ottawa, Ontario, Canada K2C 3H4
(613) 226-5772, TLX: 053-4591
FAX: (613) 226-2802

CIRCLE NO 757

To advertise in Product Mart, call Joanne Dorian, 212/463-6415

RELAYS



MADE
IN
U.S.A.

Reliable general purpose, magnetic-latching, and time-delay relays. Light, medium and heavy duty power loads.

DELTROL
controls


Send for
Engineering
Manual or Call
414/671-6800

DIVISION OF DELTROL CORP.
4527

Fax: 671-6809

CIRCLE NO 758

SERIAL/PARALLEL Communications Board



- Two Parallel Printer Ports
- Two 8-Bit Digital I/O Ports
- Two Serial Ports, RS-232, RS-422 or RS-485
- Address Selectable
- Selectable & Shareable Interrupts

1-800-553-1170

QUA TECH
INCORPORATED

478 E. Exchange St., Akron, OH 44304
TEL: (216) 434-3154 FAX: (216) 434-1409
TLX: 5101012726

CIRCLE NO 759

DATA I/O MEMORY PROGRAMMER

**NOW
\$995.**



Save \$300 on the single-socket 201 EPROM Programmer, and get programming reliability for all EPROMs and EEPROMs up to 512K. Plus:


- Full editing from the front panel
- Stand-alone or computer remote control operation
- Full after-sales support from Data I/O®

1-800-247-5700
Ext. 808

DATA I/O
Corporation

CIRCLE NO 760

LOW COST INTERFACE CARDS FOR PC/XT/AT/PS2



RS-485/422 Card [PC485] \$95/125

- Serial Async. Communication up to 4,000ft; 2 or 4 wires; NS16450 UART;
- Can be configured as COM1-COM4; Maximum Baud Rate: 56KB/115KB;
- Dual drivers/receivers; Handles 64 devices; Compatible with most comm. softw.
- DB9 or phonejack. Sample communication software available - \$50/150

IEEE-488 Card [PC488A] \$145

- Includes INSTALLABLE DOS DEVICE DRIVERS and support for BASIC.
- Additional Support for ASSEMBLY, C, Pascal and FORTRAN - \$50.
- IRQ (1-6), DMA channel 1 or 2. Up to 4 boards per computer.
- Compatible with most IEEE-488 Software packages for IBM-PC (e.g. ASYSTANT-GPIB, Lotus Measure). Compatible with NI's GPIB-PC1A.

IEEE-488 Card [PC488B] With Built-In Bus Analyzer \$345

- Software Support for BASIC, QuickBASIC and GWBASIC.
- Additional libraries for C, Pascal, FORTRAN, Assembly available - \$95 (all)
- Powerful menu-driven BUS ANALYZER runs in the background while 488 programs or commands are executed; Features Program Stepping, Break points, real time bus data capture (4K buffer), instant screen toggling.
- Complete Controller / Talker / Listener capability. Based on TI's TMS-9914.
- NEC-7210 based card (compatible with Nat. Instruments PCII/PC1A) - \$445.

PS2 Ser/Par Card [PS2IOA] \$95/125


- I/O card for PS2 Models 50-80; Ser. port 1-2; Par. port 1-3; IBM registered ID.

A/D + D/A + DIO + Counter \$295-995

- 16/8 Channels; 12-14 bit Resolution; 25k-100k/sec; 16 DIO; 16 bit Counter; MC / VISA / AMEX Call today for datasheets!

B&C MICROSYSTEMS INC.
355 West Olive Ave, Sunnyvale, CA 94086
TEL: (408)730-5511 FAX: (408)730-5521

CIRCLE NO 761



SAVE SPACE WITH Q/PAC® COMPONENTS

- Provide built-in capacitance
- Eliminate decoupling capacitance
- Gain 4-layer board quietness with 2-layer economy
- Vertical or horizontal mounting

Send for Rogers Q/PAC®
Application Bulletin.

Rogers Corp., 2400 S. Roosevelt St.
Tempe, AZ 85282 602/967-0624

CIRCLE NO 762



Tango. Now More Than Ever, The Best Value in PCB Design.

Take a look at the all new Tango Series II. Our pop-up menu interface sets a new standard for ease-of-use and productivity. Lay out simple prototypes or complex, multi-layer, SMT designs with over 100 new features including user-definable tracks, pads, and grids.

For IBM-PCs and compatibles, Tango-PCB Series II, just \$595. Tango-Route Series II autorouter, just \$495. Both include one year's updates, free tech support, 30-day money-back guarantee. Call today.



FREE EVALUATION PACKAGE

800-433-7801 619-695-2000

ACCEL Technologies, 7358 Trade Street, San Diego, CA 92121

CIRCLE NO 763

IEEE 488 Solutions.

- Hardware & software interfaces for PC, AT, 386, PS/2, Macintosh, SUN, HP & DEC.
- IEEE converters to SCSI, RS-232, RS-422, modem, Centronics, digital I/O & analog I/O
- IEEE extenders, expanders & buffers
- IEEE drivers for DOS, UNIX®, Lotus 1-2-3, Symphony & Quattro.


Call or send for your
FREE Technical Guide
Demo disks and application notes available

LOtech

(216) 439-4091
Telex 6502820864 • Fax (216) 439-4093
LOtech, Inc. • 25971 Cannon Road
Cleveland, Ohio 44146

CIRCLE NO 764

\$76.50* Single Board Computer



*500 piece price, model MCL45 (shown)


6800 MPU, serial I/O, parallel I/O, RAM, EPROM,
44-pin 4.5" x 6.5" PCB

EXPANSION MODULES: RAM, EPROM, CMOS RAM/
battery, analog I/O, serial I/O, parallel I/O, counter/
timer, IEEE-488, EPROM programmer, floppy disks,
cassette, breadboard, keyboard/dsplay.

WINTek

Wintek Corp
1801 South Street
Lafayette, IN 47904
317-742-8428
(800) 742-8809

CIRCLE NO 765



Free Catalog
For
Connector
Specifiers

LEMO's Pocket Catalog permits connector specifiers to quickly determine which LEMO connectors meet their needs. Catalog includes tables that are organized around the main elements needed to specify connectors: number of contacts, working voltages, amps, collet ranges to accommodate cable OD, shell styles and insulating materials. Connector families include mixed and multi contact connectors, environmentally sealed connectors, coaxial, triaxial, high voltage and plastic.

LEMO USA, INC.

P.O. Box 11488, Santa Rosa, CA 95406
phone 707/578-8811, telex 340-933, fax 707/578-0869.

CIRCLE NO 766

To advertise in Product Mart, call Joanne Dorian, 212/463-6415

Free MSDOS & Mac Software Catalog for Electronic Engineers


AC/DC Circuit Analysis • Active and Passive Filter Design • Screen/Printer & Pen Plotter Graphics for Engineers • LaPlace Transfer Function/FFT Analysis • Logic Simulation • Root Locus Analysis • CAD/CAE • Digital and Analog Signal Processing • Curve Fitting • Statistics • Thermal Analysis • Math • Microstrip Design and Analysis • Data Acquisition • VISA & M/C Accepted

Engineering
Professional Software

2023 Chicago Ave., Suite B-13 • Riverside, CA 92507
Tel: (714) 781-0252 • U.S.A. • TELEX: 6503089864

CIRCLE NO 767

NEW LSPC SERIAL/2 HIGH SPEED DATA COMMUNICATION CONTROLLER



- Synchronous Full Duplex Serial Controller (Z82530)
- Max Data Rate of 400 Kbps Externally Clocked
- Support For Two DMA Channels
- Designed For The IBM PC/AT™ Bus

IBM PC/AT is a trademark of International Business Machines, Inc.



Computer Modules, Inc.
2348C WALSH AVENUE
SANTA CLARA, CA 95051

Tel: (408) 496-1881

CIRCLE NO 768

presenting
PADS
SUPERSTATION
for TOTAL INTEGRATION


Obtain complete cradle-to-grave performance from your personal computer CAD system when performing electronic packaging design. From schematic capture to printed circuit design, to 100% completion autorouting capabilities, it's all here. Now you have one more reason you should be using PADS: Total Integration. Call our Sales Hotline today to receive a free Integrated Evaluation Package for the PADS-SUPERSTATION.

Call Your Local Authorized Dealer

In MA: (508) 486-8929
Outside MA: (800) 255-7814

CAD
Software, Inc.
119 Russell St.
Littleton, MA 01460

CIRCLE NO 769



ANALOG CIRCUIT SIMULATION


ECA-2 is a complete Electronic Circuit Analysis package with built-in graphics and the fastest simulations.

- AC, DC, Transient
- Fourier, Temperature
- Worst-case, Monte-Carlo
- Full, nonlinear simulator
- Interactive or batch
- SPICE compatible models
- 2-100 times faster than SPICE
- Over 500 nodes
- Sine, Pulse, PWL, SFFM and Exponential generators
- Money back guarantee

ECA-2 IBM PC or Macintosh **\$675**

EC-Ace, a subset of ECA-2, \$145

Call 313-663-8810 For FREE DEMO disk



CIRCLE NO 770




IMPROVE BOARD PERFORMANCE

MICRO/Q 1000 capacitors can be retrofitted to solve noise problems on existing boards. Because MICRO/Q 1000 caps share mounting holes with existing IC pins, no board redesign is required. Effective decoupling becomes a matter of adding one insertion step.

Rogers Corp., 2400 S. Roosevelt St., Tempe, AZ 85282. 602/967-0624

CIRCLE NO 771



MULTIBUS™ AT-COMPATIBLE SBC

Multibus I is now IBM PC/AT™ compatible with MAT286™ our newest single board solution. MAT286 includes all of the functions of a 10 MHz AT motherboard, plus 2 serial ports, a parallel port, two SBX expansion-module interfaces, up to 512K EPROM/EEPROM/DRAM, and up to 4M of parity-checked, dual-ported DRAM. A piggy-back card, MATxSYSIO, adds EGA, floppy, and SCSI interfaces. Embed all the guts of an AT, two SBX modules, and more, into two Multibus slots!


Phone (408) 253-0250 or write for more information.

Single Board Solutions, Inc.

20045 Stevens Creek Blvd, Cupertino, CA 95014

Multibus is a registered trademark of Intel Corp. MAT286 and MATxSYSIO are trademarks of Single Board Solutions, Inc. IBM and PC/AT are trademarks of International Business Machines Corp.

CIRCLE NO 772



STEP MOTOR CONTROL 27K steps/sec! 16 Million steps!

New CY545. Rates up to 27K steps/sec, up to 16 million steps per single motion. Separately programmable start rate, accel/decel rate, and max rate. Pulse & direction output. External jog mode and limit switch detection. Serial or parallel interface, LED/LCD & Thumbwheel interface lines, and more. ASCII commands. Supports 64K external memory. CMOS 40-pin DIP. \$75 each (\$25/1000). Credit Cards OK.



Cybernetic Micro Systems
Box 3000, San Gregorio CA 94074
(415) 726-3000 Tx: 910-350-5842

CIRCLE NO 773

9-Track Tape Subsystem for the IBM PC/XT/AT



Now you can exchange data files between your IBM PC and any mainframe or mini-computer using IBM compatible 1600 or 6250 BPI 9-Track tape. System can also be used for disk backup. Transfer rate is up to 4 megabytes per minute on PCs and compatibles. Subsystems include 7" or 10½" streaming tape drive, tape coupler card and DOS compatible software. For more information, call us today!

QUALSTAR

9621 Irontdale Ave., Chatsworth, CA 91311
Telephone: (818) 882-5822

CIRCLE NO 774



CONVERT RGB INTO COLOR COMPOSITE VIDEO

Now you can convert RGB computer signals into NTSC composite video with the ENC series of RGB Encoders. Three different models are available for compatibility with most analog and TTL RGB computers having 15 kHz scan rates. Output of ENCs can drive VCRs, projection TVs, and monitors. Interface cables and application assistance available. Only \$395.00 each.



Communications



Specialties, Inc.

Tel: (516) 499-0907 FAX: (516) 499-0321

CIRCLE NO 775

To advertise in Product Mart, call Joanne Dorian, 212/463-6415

Born Tough.



Qualogy products are made tough enough for any game. From conception, the versatile line of Qualogy PC/AT products is designed to meet the most demanding industrial requirements. Our **passive backplane** approach provides performance, upgradability and serviceability that "mother-board" designs simply cannot match.

Rugged rackmount enclosures and systems are made of heavy gauge welded steel. A positive pressure filtered air flow cooling system

provides system components and up to 4 drives with lasting protection against harsh environments. Powered by an industrial grade supply, enclosures and systems are available in 10 and 12 slot models and a unique split 12 slot version that can support 2 complete systems.

When the name of the game is speed, Qualogy single board

computers win again. Our powerful **386** system is available in speeds from 16 MHz to a blazing **25 MHz** with up to 8 Megabytes of on board SIMM memory providing an alternative to VME based systems that can cost twice as much. The more economical Qualogy 286 single board computers sport speeds from 8 to 16 MHz with up to 4 Megabytes of on board SIMM memory.

Improve your score with Qualogy, call (408) 434-5200.



Industrial PC/AT computers and peripherals.




1751 McCarthy Blvd. Milpitas, California 95035 408-434-5200 Fax 408-434-5242 Telex 4993489

Qualogy is a trademark of Qualogy, Inc. IBM PC/AT is a registered trademark of International Business Machines, Inc. Copyright © Qualogy, Inc., 1989. All rights reserved.

CIRCLE NO 150

**Are you comparing
us to other test
equipment leasing
companies?**



It's just not possible.

Why can't you compare us? It's simple. Our inventory is made up of instruments from the most respected test equipment manufacturers. Each instrument is meticulously inspected, tested, and calibrated in our metrology labs—with quality control procedures so uncompromising they exceed the National Bureau of Standards and Military Specification requirements. And delivery takes just 24 hours, once your order is received.

Select your equipment, then choose from a wide array of financing programs, including

short-term rentals, and operating and finance leases. Each is custom-tailored to your situation. Or, talk to us about purchasing your equipment with terms that are convenient for you.

Sound like we're incomparable? We are. And we'll help you be incomparable too. Count on us.

800-553-2255

LEASAMETRIC

Instrument Rental Division

1164 Triton Drive
Foster City, CA 94404

Improving working conditions for engineers: Should the IEEE do more?

Paul Kinnucan

The free market structure that characterizes the US economy tends to create a tussle between engineers and employers over salaries, benefits, job security, discrimination, and other career-related issues. Fortunately, electrical and electronics engineers have a potentially powerful ally when confronting employers with such issues—the Institute of Electrical and Electronics Engineers (IEEE), the world's largest engineering society.

The New York City-based society, which comprises 304,000 members worldwide in 754 chapters, works to improve the professional lives of engineers.

According to Edward Bertnolli, IEEE vice-president of professional activities, the IEEE's goals range from providing members with information on salaries, pensions, and patent rights to pressing Congress for tax and pension reform legislation.

Despite these efforts, some members believe that the IEEE isn't doing enough to resolve the many problems that plague today's engineering profession. They want the society to devote more of its \$82 million annual budget and 500 full-time staff members to improving work conditions and pursuing a wider range of legal issues. In the past, the IEEE



Kevin Hawkes

Though the IEEE originally functioned as a technical society, it now works to provide its members with information on salaries, job opportunities, pensions, and legal rights.



has responded to such demands for more career-related support—though few members have rallied as vehemently as some of today's critics.

The IEEE originally functioned as a purely technical society and gradually became the career-conscious institution it is today. Formed in the 1950s by the merger of several societies, some of which date back to the late 19th century, the IEEE worked to improve and broaden the applications of what it terms "electrotechnology." To educate its members, the society created numerous technical journals (including its flagship publication, the *IEEE Spectrum*), conferences, and technical standards.

The IEEE changes direction

In the 1960s, however, the society came under increasing pressure to address the career-related concerns of its members. Such pressure became especially intense in the early 1970s when many members were put out of work because of the recession in the US aerospace industry. At that time, the US members voted to have the IEEE devote its resources to improving working conditions for electrical and electronics engineers.

The IEEE created a US Activities Board (USAB) in 1972 to direct the society's activities and provide the support its members requested. The USAB, based in Washington, DC, also oversees another IEEE initiative—developing and presenting IEEE positions on US technology policy.

Today, the USAB comprises 20 full-time staff members and commands a \$2.7 million annual budget. To help IEEE members understand and deal with the current issues in the industry, the USAB offers both professional and legal assistance.

The group gathers and publishes a range of information that can help engineers to improve salaries, benefits, and working conditions. For example, the USAB issues an annual membership salary survey and booklets on pensions, patent rights, age discrimination, and professional ethics.

Each year, the USAB sponsors workshops and conferences on the status of engineering careers. These meetings let IEEE's members and managers and employers exchange information and views on engineering career-related issues, such as pensions, patent rights, and age discrimination. In addition, the USAB maintains speakers bureaus that list members who are willing and qualified to speak on these issues.

The USAB also sponsors electronic registries of members who are actively seeking work. Potential employers may search the database to find qualified candidates. To protect the employed registrants, the companies that operate the registries never divulge registrants' names to prospective employers. Instead, registrants are notified when potential employers express an interest in them. The registrants can then contact the prospective employers. Currently, the USAB sponsors two registries, one for company-employed registrants (PEER) and one for self-employed registrants (SEER).

Justice for all members

In addition to heightening the members' awareness of career-related issues and simplifying their job search, the USAB tries to improve working conditions by providing legal guidance. The group appears before Congress regularly to support legislation that might benefit its members and to oppose

legislation that might harm members. In the late 1970s, for example, the USAB successfully lobbied in support of legislation that established Individual Retirement Accounts (IRAs). Such accounts, in effect, let employees create their own pension funds—a valuable benefit to engineers who, because of high job mobility, often don't stay long enough with an employer to benefit from company-sponsored plans.

The society's current lobbying agenda includes support for:

- Establishing portable pensions, which allow employees to transfer their pension assets from one company's plan to another when changing jobs
- Outlawing integrated pensions, whose benefits are offset by the employee's Social Security benefits
- Requiring companies to adopt defined-contribution pension plans, which protect employees' pension benefits from the ravages of inflation
- Repealing a provision (Section 1706) in the 1986 tax reform act that eliminated certain tax benefits for self-employed engineers
- Providing a cooling-off period for employees who accept early retirement in return for a compensation package (golden handshake) and
- Allowing early retirees to sue their former employers for improved compensation even if the retirement agreement includes a no-sue provision.

To magnify its influence on Congress, the USAB always tries to ally itself with other groups that have interests on similar issues, Bertnolli says. Last year, for example, the USAB appeared before Congress with the American Asso-

ciation of Engineering Societies to support legislation that would pave the way for portable pensions. Bertnolli points out that the joint lobbying effort represented nearly 1½ million engineers before Congress.

The USAB confronts other government organizations to protect the interests of its members. For example, the USAB will lobby the Defense Dept intensively this year to push for legislation that will make it illegal for defense contractors to use mandatory uncompensated overtime as a way of lowering their bids.


In addition to lobbying for new legislation, the USAB monitors the enforcement of current laws and regulations. The group tracks the performance of an agency responsible for enforcing a Federal law against age discrimination. It also monitors employment advertisements for evidence of age discrimination and advises companies that violate the law.

If IEEE members are directly affected by such legal violations, the society often takes court action. The USAB has a long-standing policy of testifying on behalf of members in age-discrimination and ethics cases as a "friend of the court." Several years ago, for example, the society took part in an ethics case involving members who worked on the design of San Francisco's Bay Area Rapid Transit (BART) system.

Too little, too late

Despite the IEEE's declared dedication to these causes, the society hasn't escaped criticism. Irwin Feerst, a member and perennial IEEE presidential candidate, questions both the scope and the vigor of the IEEE efforts. Feerst claims, for example, that the society

Critics claim that the IEEE needs to broaden its current agenda of career-related activities and pursue its lobbying efforts more vigorously.



doesn't monitor Congress closely enough and therefore misses opportunities to lobby for important engineering issues.

Feerst would like to see the IEEE expand its current legislative agenda significantly. Regarding patent rights, for example, Feerst wants the IEEE to press for legislation that would entitle engineers to 25% of the royalties gained by a company as a result of the engineer's patented work. The IEEE, however, currently supports most companies' position that the ideas and products developed by an engineer should belong to the company that currently employs the engineer.

Feerst's major criticism of the IEEE is that it doesn't strike at the root of what he believes is the cause of most of the professional problems facing US engineers—an oversupply of engineering talent. "There is a huge glut of engineers in the US today," Feerst declares.

According to Feerst, this oversupply has made it difficult for many engineers, especially older engineers who are more expensive than younger engineers to employ, to find work. Furthermore, those engineers who do find work can't always negotiate for improved salaries, benefits, and working conditions.

A question of degree

Feerst urges the IEEE to actively discourage young people from entering the engineering profession by publicizing this issue and its harmful consequences. To reduce the engineering population, he also advocates banishing anyone from the IEEE who has a bachelor of engineering technology (BET) degree. Companies are eager to hire such persons, whom Feerst terms "subprofessionals," because

they command a lower salary than individuals with an EE degree. The IEEE aids these potential competitors of EEs by conferring membership on them, Feerst claims.

In addition to suggesting that the IEEE tighten its membership requirements, Feerst advises the society to support legislation that would make it illegal for US companies to employ non-nationals as electrical engineers. Because such engineers are often willing to work for extremely low wages, they decrease the job opportunities available for engineers who are US citizens, Feerst says.



Although Feerst has advocated these measures for years, he has thus far made little headway in gaining support from the IEEE hierarchy, which selects the specific professional issues that the organization will address. Support hasn't been forthcoming, Feerst says, because these measures oppose the interests of the IEEE hierarchy, which is composed primarily of academics and corporate executives. He believes that academics have a natural interest in encouraging young people to enter the engineering profession. Similarly, he asserts corporate executives want to have

a large pool of engineering talent from which to draw.

The IEEE hierarchy, however, cites different reasons for refusing to support Feerst's proposals. It disagrees with Feerst's premise that there is an oversupply of engineers, according to USAB chairman Bertnolli. In fact, the IEEE maintains that dropping enrollment in US engineering schools could precipitate a critical shortage in engineering talent. Such a shortage could put US companies at a serious disadvantage in competing against companies based in other countries, notably Japan, that have a large engineering force. For this reason, the IEEE is increasing its efforts to encourage students to choose engineering as a profession by providing speakers and video tapes for school functions, Bertnolli says.

Finding the IEEE hierarchy unresponsive to his views on professional issues, Feerst has long sought to unseat that hierarchy through the IEEE electoral process. He hasn't been successful at attaining his desired position of authority, but Feerst has managed to circulate his views throughout the engineering industry. Although IEEE members probably won't see any drastic changes in the society's agenda in the near future, they may begin to reevaluate their satisfaction or discontent with the society's efforts to improve the professional lives of engineers. **EDN**


Author's biography

Paul Kinnucan, a Boston-based freelance writer, specializes in electronics, computer, and aerospace-related topics.

Article Interest Quotient
(Circle One)

High 512 Medium 513 Low 514

Break it before you make it.



All too unwittingly, you can create a monster. You can spend upwards of \$100,000 to get a board designed and the preproduction unit fabricated. Only to learn it doesn't work.

Or, you can stop getting eaten alive. You can deploy our Prisma software on Sun® workstations. The first "real time," *really* integrated CAE, CAD, and CAM software for printed circuit board design.

Its semantic database instantly stores all of the



changes made in design, layout, or manufacturing while notifying the other design tasks to modify their data. Making it all but impossible to design boards that cannot be manufactured.

So if you're wondering how to sell competitively in the next year or next decade, think about that \$100-grand monster we can help you avoid. Call us at (714) 863-1700. And find out how Prisma can help you blaze new trails without breaking the bank.

© 1989 Calay Systems, Inc., 16842 Von Karman Ave., Irvine, CA 92714.

The Calay logo is a registered trademark of Calay Systems, Inc. Sun is a registered trademark of Sun Microsystems Inc.



GE Medical Systems

We're Building a World Class Team at GE Medical Systems

There's never been a better time to choose GE

At GE Medical Systems, we're not satisfied being the world leader in medical diagnostics systems. We want to be even better; and with your help, we can.

If you are one of the very best, bring your vision, imagination, and drive to our CT Team. The following positions offer outstanding opportunities for technical and international career growth.

SR. SOFTWARE DESIGNER

Help us to incorporate your ideas by: developing system software specifications, defining architectures, and developing algorithms and software for diagnostic applications. Use workstations, Unix, C, and object-oriented design to accomplish your tasks.

SR. DIGITAL DESIGNER

Develop data acquisition and control specifications and designs using high speed gate array and VLSI solutions. Work with Manufacturing to resolve design quality issues.

SR. SYSTEMS ENGINEER

Function as a key lead contributor in expanding GE's technology for CT diagnostic imaging equipment by: developing operator protocols, algorithms and performance models, performing analysis for software or hardware design and conducting studies to assure system performance.

These positions require an MS or PhD (EE, CS, or Physics) with 5+ years experience in medical imaging, image processing, signal processing, or real-time data acquisition. Experience with Unix, C, and Objective-C is desirable.

GE's highly competitive salary and benefits package befits an industry leader. Please send your resume, in strictest confidence, indicating position of interest, to: **MR, GE Medical Systems, P.O. Box 414, W407, Milwaukee, WI 53201.**

An Equal Opportunity Employer



CAREER OPPORTUNITIES

1989 Editorial Calendar and Planning Guide

Issue Date	Recruitment Deadline	Editorial Emphasis	EDN News Edition
May 11	Apr. 20	Analog Technology Special Issue Computer Peripherals	Closing: Apr. 28 Mailing: May 18
May 25	May 4	Digital ICs, Computer Peripherals	Closing: May 25 Mailing: June 15
June 8	May 18	Components, Digital ICs	Closing: June 9 Mailing: June 29
June 22	June 1	Semicustom ICs, Computer Boards	Closing: June 22 Mailing: July 13
July 6	June 15	Product Showcase — Volume I, Power Supplies	Closing: July 21 Mailing: Aug. 10
July 20	June 29	Product Showcase — Volume II, Components	Closing: Aug. 4 Mailing: Aug. 24
Aug. 3	July 13	Integrated Circuits, Computer Boards	Closing: Aug. 18 Mailing: Sept. 7
Aug. 17	July 27	Military Electronics Special Issue Military Software	Closing: Aug. 30 Mailing: Sept. 21
Sept. 1	Aug. 10	Test & Measurement, Integrated Circuits	Closing: Sept. 15 Mailing: Oct. 5
Sept. 14	Aug. 24	Industrial Product Showcase, Digital ICs	Closing: Sept. 28 Mailing: Oct. 19
Sept. 28	Sept. 7	Integrated Circuits, Computer Peripherals	Closing: Oct. 27 Mailing: Nov. 16
Oct. 12	Sept. 21	DSP Chip Directory, Integrated Circuits	Closing: Nov. 9 Mailing: Nov. 30
Oct. 26	Oct. 5	Test & Measurement Special Issue Computers & Peripherals	Closing: Nov. 22 Mailing: Dec. 14
Nov. 9	Oct. 19	CAE, Integrated Circuits	Closing: Nov. 30 Mailing: Dec. 14
Nov. 23	Nov. 2	16th Annual μ P/ μ C Directory, Integrated Circuits	Closing: Dec. 21 Mailing: Dec. 14
Dec. 7	Nov. 16	Product Showcase — Volume I, Power Supplies	Closing: Dec. 21 Mailing: Dec. 14
Dec. 21	Nov. 30	Product Showcase — Volume II, Components	

Call today for information:

East Coast: Janet O. Penn (201) 228-8610

West Coast: Mary Beth West (213) 826-5818

National: Roberta Renard (201) 228-8602

Sun Microsystems invites you to take CIM to its limits. Then, go beyond them.

You might not expect a high technology company to put such an emphasis on CIM. But Sun Microsystems sees CIM as nothing less than a strategic advantage in the very competitive workstation market.

Sun already boasts shop floor control and automated handling and distribution, as well as complex board and system testing and decision-making support. Now we want to integrate our systems into one, functional architecture.

Our goal: the ultimate CIM system.

This architecture will combine the ease of our user interface, vivid graphics, and networking capabilities with object-oriented programming in UNIX™ and "C," and distributed RDBMS to create the ultimate CIM system.

Sun has the resources to make it happen as one of the fastest-growing companies in America, with over one billion dollars in sales last year. We have a remarkable number of CIM experts in-house. More important, we have the explicit commitment and support of top management to make Sun unsurpassed at CIM.

But we need more. More people skilled in CIM to help us accomplish our ambitious goals.

Here's your challenge.

Join the Sun Microsystems CIM effort, and you'll have the opportunity to work on any one of several challenges:

- Tools & Technologies Development
- Applications Software Development
- Systems Integration
- Engineering Services
- User Support Services

Experience in UNIX or "C" is essential to qualify for these positions. Candidates should also have manufacturing systems integration experience.

If you meet those spec's, apply now. Here are four of our current openings:

System Administrator

You will provide system administrative support to the UNIX end-user community. This will include installing and maintaining all file servers, timeshare machines, laser printers, and networks, while working with third-party vendor software. Requires a BSCS/Information Systems and 1+ years' UNIX systems administration experience. Strong communication skills and an excellent working knowledge of UNIX and UNIX utilities, software documentation, shell programming, and networking are also needed.

Software Development Engineers

Requires experience in CIM, systems integration and application software development for state-of-the-art software systems engineering in a UNIX environment. Additionally, you will need 3+ years' experience with UNIX and "C" as well as 3 years' CIM experience.

Engineers — Surface Mount Technology

Develop, maintain, support and improve Pick & Place, paste, printing and re-flow processes for internal surface mount production line. Requires a BSME and 2-5 years' related experience in SMT process development. Panasonic and/or Fuji experience desired.

Sr. CIM Systems Software Engineers


We have several positions available for individuals with experience in process control applications including factory automation and/or distribution, as well as statistical analysis in a manufacturing environment. Requires 3 years' experience as a group leader and experience with structured analysis and design techniques in an application design environment. Strong user interface and excellent communication skills required. Systems integration background and 3+ years' UNIX and "C" experience are preferred. For some positions, 4+ years' experience with relational database required.

To apply, please send your resume in confidence to **Professional Employment, Sun Microsystems, Inc., MS DAQ, 2550 Garcia Avenue, Mountain View, CA 94043.** Letter-quality resumes will get to our hiring managers faster, since all resumes are electronically scanned and processed by the Resumix™ system. An equal opportunity employer. Principals only, please.

UNIX is a registered trademark of AT & T. The Sun logo and Sun Microsystems are registered trademarks of Sun Microsystems, Inc. All other products or services mentioned in this document are identified by the trademarks or service marks of their respective companies or organizations.



Systems for Open Computing.™



T H E O P E N C H A L L E N G E

First, there was the vision...

History-Making Opportunities: Mars Observer, Space Station & Landsat... in Princeton, New Jersey

Space exploration began with a vision. The fire of imagination - fused with superior technical proficiency - leading the way to limitless possibilities. A special vision that creates the kind of breakthroughs that characterize GE Astro Space.

With over 150 satellites currently circling the globe, and long-term, history-making projects such as the Mars Observer, Space Station and Landsat...GE Astro Space can offer Engineers the kind of rare opportunities that few are destined to realize.

If you're the visionary Engineer we're seeking, join us in fulfilling an array of project requirements...paving the way for a new generation of emerging space technology. Our mission requires the technical proficiency of Design Engineers with applicable BSEE or BSME degrees and a minimum of 3 years experience within the following areas:

■ Electrical Engineers

Spacecraft Power Systems

Battery/Solar Array Technology

Spacecraft Power Electronics

Power Conversion Techniques, DC/DC, Analog Circuits

High Voltage Power Supply

High Reliability Traveling Wave Tube Power Supplies

■ Communication Systems Engineers

RF/Microwave

MW Amps, MIC/MMIC

Antenna Systems

Shaped/Multiple Beam Satellite Antennas

■ Mechanical Engineers

Spacecraft Structures

Honeycomb Panels, Thermal, Composite Materials

MIC/Hybrid Packaging

Metal and Ceramic Packaging with Chip and Wire Components, GaAs FETs, GaAs MMIC Chips

The Time is Now

We're a company anxious to meet Engineers who want to cross the engineering frontier. Rush your resume, in professional confidence, to: Employee Relations, Dept. EDN/4-13, GE Astro Space, P.O. Box 800, Princeton, New Jersey 08543-0800.



GE Astro Space

Cross the engineering frontier.

An equal opportunity employer

Quality in. Quality out.



At Compaq, the value of our products is simply a reflection of the personal values inherent in each Compaq professional. Attributes like teamwork, mutual respect, leadership and commitment to quality translate into some of the most advanced business PCs on the market.

Our continued success has created immediate opportunities for professionals at our Houston headquarters. Start with a BS in a related engineering field and three-plus years' experience. Add to that a strong set of personal values and the desire to do what's never been done before, and you could be part of a winning team.

Automation/Systems Engineers

Your BSEE or BSCS should be accompanied by five years' experience in PCB assembly factory automation. You'll need a strong background in hardware/software networking and expertise in PLCs and factory cell controller installation in UNIX or VMS environments. Familiarity with 'C', PASCAL, BASIC, FORTRAN and CLIPPER programming languages is necessary. Experience in JIT, SPC, MRP, CAD, CAE, AI and GenRad test data collections along with your knowledge in the design

and development of systems specifications is essential. In addition, you should be familiar with Novell, networks and D-BASE III. Strong communication skills are a must.

Sustaining Engineers

As a Compaq Sustaining Engineer, you'll have a hand in the analysis and correction of circuit and component issues in one of the following areas:

- Digital—Resolve complex technical issues in high-speed digital designs.
- Power Supply—Analyze and solve technical problems in sophisticated power supply designs.
- Peripherals—Troubleshoot and resolve OEM-related issues (drives, monitors, keyboards, displays).
- PCBs—Develop printed circuit board specifications for existing and new PC technologies.

Materials Assembly Engineers

Along with your BS or MS in Engineering, Metallurgical Science or related degree, you'll need five years' experience in surface mount technology and expertise in process development, materials analysis and metallurgical

analysis. Experience in TAB, fine pitch surface mount assembly, solder technology, adhesive technology, reliability testing and failure analysis is preferred. Strong written and verbal communication skills are essential.

Component Reliability Engineers

Help maintain one of the industry's highest user satisfaction ratings. You should be familiar with bipolar and CMOS device process reliability, and be able to determine reliability of components. You should also be familiar with Intel microprocessors and ASIC devices.

Make a quality career decision.

Compaq offers competitive salaries, comprehensive benefits and an unequalled work environment. If you're interested in one of these positions, please call us at 1-800-243-9003. Or simply submit your resume and the position for which you wish to be considered to:

**Compaq Computer Corporation,
Dept. EDN413-TH, P.O. Box 69200,
Houston, Texas 77269-2000**

© 1989 Compaq Computer Corporation
© 1989 Accent Software, Inc.

All rights reserved.

Compaq is an affirmative action employer, m/f/h/v.

COMPAQ

SOFTWARE DESIGN ENGINEERS

Data Communications...High Visibility...
Advancement Opportunities

General DataComm provides customers around the world with the most sophisticated, comprehensive selection of integrated data communications products available. As a result of our aggressive new product design schedules, we are currently seeking individuals for a variety of engineering "software/firmware design" positions.

- Network Management
- Relational Database
- UNIX™/"C"
- Real Time Firmware
- ISDN, T1, Baseband

Sr. Software Engineers / Software Engineers

Opportunities are available in our Network Management Systems Directorate, where you would be intimately involved in several generations of design for multi-user distributed Network Management Systems. For these opportunities, you should possess a BSCS/BSEE or equivalent with 3-5 years of experience in software product development and have high proficiency in "C" programming in UNIX™, DOS environments. Background in Sun Microsystems® or relational database design is helpful.

Sr. Firmware Engineers / Firmware Engineers

Other engineering positions are available in our Transmission Development Directorate. You will be involved with the design of state-of-the-art transmission products such as ISDN, T1, Baseband and Analog modem products. For these positions, you should possess a BSEE/BSCS or the equivalent with 3-5 years of experience in Assembly language programming; some higher level language background is essential. Also, experience in real time microprocessor programming is required. (Intel 8086 or Z80 or Z180).

We can offer you a highly competitive salary, healthcare and dental programs, life insurance, 100% tuition reimbursement, profit sharing, and a stock purchase plan.

For further information on these and other available positions, please telephone David G. Alley, Manager, Human Resources, at (203) 758-1811 or write in confidence to:

General DataComm, Inc.
Technology Center
Middlebury, CT 06762-1299



General DataComm, Inc.

An Equal Opportunity Employer

PUT THE POWER OF PARTNERSHIP TO WORK FOR YOU WITH EDN'S WEEKLY RECRUITMENT PACKAGE

Reach the best-qualified engineers in the electronic OEM weekly. And do it for less. Place equivalent space in both the *Career Opportunities* section of EDN's magazine edition and the *Career News* section of EDN's news edition in the same month and get a 30% discount off EDN's news edition rate.

Contact Roberta Renard,
National Recruitment
Sales Manager at
201/228-8602 for
complete details.

CRT Display Engineers

Clinton Electronics, located in Northern Illinois, is a privately-owned, no-nonsense hands-on company and an innovative world leader in CRT technology. Our management sets the tone of freedom and flexible thinking. If you have enthusiasm and are not afraid of hard work let us hear from you. Company growth and internal promotions have created opportunities in the following areas at our corporate headquarters.

- Applications Engineering
- Processing Engineering
- Manufacturing Engineering
- Screening Engineering

If you have any experience in the above areas or if you have experience in the CRT industry, send us your resume. We offer a professional environment and an excellent compensation package. Please forward your resume to: **Ken Judson, (815) 633-1444, Clinton Electronics Corporation, 6701 Clinton Road, Loves Park, IL 61111.** An Equal Opportunity Employer.



**CLINTON
ELECTRONICS
CORPORATION**

Performance Has No Limits Here.

ENGINEERS

SUNBELT

- Ada, Pascal, UNIX, C
- Networks/Communications
- X.25/SNA/SDLC
- Embedded Systems/DOD2167
- Sr. Antenna/RF Engineers
- Avionics(VHSIC/ASIC)
- Optics/IR Sensors
- RF/Analog/Monolithic
- Space Station/Shuttle
- TPS Design/ATLAS

INDEPENDENT PERSONNEL CONSULTANTS

P.O. Box 16019
Huntsville, AL 35802
Tom Thrailkill (205) 883-6511

SALES REP WANTED!

Patented three phase monitor to protect all three phase equipment from open phase, reverse phase and hi-low line voltage. For information call

Motor Check, Inc.
P.O. Box 67
Gillette, N.J. 07933
201-647-2511

Attention Computer Scientists, Software and Systems Engineers.

Computer Sciences Corporation's Defense Systems Division, headquartered in Moorestown, New Jersey with facilities nationwide, is setting the pace in an industry built on the future. We've been awarded major contracts in areas vital to our country's defense and to your career. As part of CSC, you'll explore new dimensions in computer-based military computer systems for tactical and strategic command and control defense systems.

We have a record number of challenging projects on the boards. You'll be actively involved in projects such as the AEGIS Weapons System, BSY-2 Submarine Combat System, and the Strategic Defense Initiative.

Your background should include a minimum of two years experience in real-time programming, executive and operating system development in any of the following areas:

- Real-Time Operating Systems/Executives
- Military Applications
- I/O Systems
- Inter-Computer Communications
- Ada Professionals
- 1750A Instruction Set Architecture
- 68XXX Series Architecture
- Ultra or CMS-2
- VAX VMS, MASSCOMP, AN/UYS Series

We can offer you highly competitive salaries, comprehensive benefits and the opportunity to be part of a high powered company. For immediate consideration, please send your resume with salary history to: **Paul Tootell, Computer Sciences Corporation, Defense Systems Division, Dept. EDN413, 304 West Route 38, P.O. Box N, Moorestown, NJ 08057.** An Equal Opportunity Employer.



**Computer Sciences
Corporation**

EDN Databank

Professional Profile

Announcing a new placement service for professional engineers!

To help you advance your career, Placement Services, Ltd. has formed the EDN Databank. What is the Databank? It is a computerized system of matching qualified candidates with positions that meet the applicant's professional needs and desires. What are the advantages of this new service?

- It's absolutely free. There are no fees or charges.

- The computer never forgets. When your type of job comes up, it remembers you're qualified.
- Service is nationwide. You'll be considered for openings across the U.S. by PSL and its affiliated offices.
- Your identity is protected. Your resume is carefully screened to be sure it will not be sent to your company or parent organization.

- Your background and career objectives will periodically be reviewed with you by a PSL professional placement person.

We hope you're happy in your current position. At the same time, chances are there is an ideal job you'd prefer if you knew about it.

That's why it makes sense for you to register with the EDN Databank. To do so, just mail the completed form below, along with a copy of your resume, to: Placement Services, Ltd., Inc.

IDENTITY

Name _____ Parent Company _____
Home Address: _____ Your division or subsidiary: _____
City _____ State: _____ Zip: _____ Location (City, State) _____
Home Phone (include area code): _____ Business Phone if O.K. to use: _____

PRESENT OR MOST RECENT EMPLOYER

EDUCATION

Degrees (List)	Major Field	GPA	Year Degree Earned	College or University

POSITION DESIRED

EXPERIENCE

Present or Most Recent Position _____ From: _____ To: _____ Title: _____
Duties and Accomplishments: _____ Industry of Current Employer: _____

Reason for Change: _____

PREVIOUS POSITION:

Job Title: _____
Employer: _____ From: _____ To: _____ City: _____ State: _____
Division: _____ Type of Industry: _____ Salary: _____
Duties and Accomplishments: _____

COMPENSATION/PERSONAL INFORMATION


Years Experience	Base Salary	Commission	Bonus	Total Compensation	Asking Compensation	Min. Compensation
Date Available _____	I Will Travel <input type="checkbox"/> Light <input type="checkbox"/> Moderate <input type="checkbox"/> Heavy			<input type="checkbox"/> I own my home. How long? _____	<input type="checkbox"/> I rent my home/apt. <input type="checkbox"/>	
<input type="checkbox"/> Employed	<input type="checkbox"/> Self-Employed	<input type="checkbox"/> Unemployed	<input type="checkbox"/> Married	<input type="checkbox"/> Single	Height _____ Weight _____	
Level of Security Clearance _____		<input type="checkbox"/> U.S. Citizen	<input type="checkbox"/> Non-U.S. Citizen	My identity may be released to: <input type="checkbox"/> Any employer <input type="checkbox"/> All but present employer		
<input type="checkbox"/> WILL RELOCATE		<input type="checkbox"/> WILL NOT RELOCATE		<input type="checkbox"/> OTHER _____		

EDN Databank

A DIVISION OF PLACEMENT SERVICES LTD., INC.

265 S. Main Street, Akron, OH 44308 216/762-0279

We Have Them All, Why Should We Be Biased?



VARTA offers the correct solution for each and every energy supply problem. In all sizes; in all systems. Why not make use of the VARTA consultation service. After all, it's only a manufacturer with a comprehensive programme who can give unbiased advice.

The world's largest battery only manufacturer.



VARTA

VARTA Batterie AG
Am Leineufer 51
D-3000 Hannover 21
W-Germany · Tel. (0511) 79 03-1

VARTA Batteries Inc.
300 Executive Boulevard
Elmsford · N.Y. 10523-1202
USA · Tel. (0914) 5922 500
CIRCLE NO 152

VARTA Batteries Pte. Ltd.
P.O. Box 55
Bedok North Post Office
Singapore 9146 · Tel. (0241) 2633

EDN's CHARTER

EDN is written for professionals in the worldwide electronics industry who design, or manage the design of, products ranging from circuits to systems.

EDN provides accurate, detailed, and useful information about new technologies, products, design techniques, and careers.

EDN covers new and developing technologies to inform its readers of practical design matters that will be of concern to them at once or in the near future.

EDN covers new products

- that are immediately or imminently available for purchase
- that have technical data specified in enough detail to permit practical application
- for which accurate price information is available.

EDN's Magazine Edition also provides specific "how to" design information that its readers can use immediately. From time to time, EDN's technical editors undertake special "hands on" engineering projects that demonstrate EDN's commitment to readers' needs for useful design information.

EDN's News Edition also provides comprehensive analysis and news of technology, products, careers, and distribution.

EDN

275 Washington St
Newton, MA 02158
(617) 964-3030

BUSINESS/CORPORATE STAFF

Peter D Coley
VP/Publisher
Newton, MA 02158
(617) 964-3030; Telex 940573
Ora Dunbar, Assistant/Sales Coordinator

Mark J Holdreith
Advertising Sales Director
Newton, MA 02158
(617) 964-3030
Heather McElkeny, Assistant

Deborah Virtue
Business Director
Newton, MA 02158
(617) 964-3030

NEW ENGLAND
Chris Platt, Regional Manager
199 Wells Ave
Newton, MA 02159
(617) 964-3730

STAMFORD 06904
George Isbell, Regional Manager
8 Stamford Forum, Box 10277
(203) 328-2580

NEW YORK, NY 10011
Daniel J Rowland, Regional Manager
249 West 17th St
New York, NY 10011
(212) 463-6419

PHILADELPHIA AREA
Steve Farkas, Regional Manager
487 Devon Park Dr, Suite 206
Wayne, PA 19087
(215) 293-1212

CHICAGO AREA
Clayton Ryder, Regional Manager
Greg Anastos, Regional Manager
Jack Johnson, Regional Manager
Cahners Plaza
1350 E Touhy Ave, Box 5080
Des Plaines, IL 60017
(312) 635-8800

DENVER 80206
John Huff, Regional Manager
44 Cook St
(303) 388-4511

DALLAS 75243
Don Ward, Regional Manager
9330 LBJ Freeway, Suite 1060
(214) 644-3683

SAN JOSE 95128
Walt Patstone, Regional Manager
Bill Kianke, Regional Manager
Philip J Branon, Regional Manager
James W Graham, Regional Manager
3031 Tisch Way, Suite 100
(408) 243-8838

LOS ANGELES 90064
Charles J Stillman, Jr
Regional Manager
12233 W Olympic Blvd
(213) 826-5818

ORANGE COUNTY/SAN DIEGO 92715
Jim McErlan, Regional Manager
18818 Teller Ave, Suite 170
Irvine, CA
(714) 851-9422

PORTLAND, OREGON 97221
Pat Dakin, Regional Manager
Walt Patstone, Regional Manager
1750 SW Skyline Blvd, Box 6
(503) 297-3382

UNITED KINGDOM/BENELUX
Jan Dawson, Regional Manager
27 Paul St
London EC2A 4JU UK
44 01-628 7030
Telex: 914911; FAX: 01-628 5984

SCANDINAVIA
Stuart Smith
27 Paul St
London EC2A 4JU UK
01-628 7030
Telex: 914911; FAX: 01-628 5984

FRANCE/ITALY/SPAIN
Alasdair Melville
27 Paul St
London EC2A 4JU UK
01-628 7030
Telex: 914911; FAX: 01-628 5984

WEST GERMANY/SWITZERLAND/AUSTRIA
Wolfgang Richter
Sudring 53
7240 Horb/Neckar
West Germany
49-7451-7828; Telex: 765450

EASTERN BLOC
Uwe Kretzschmar
27 Paul St
London EC2A 4JU UK
01-628 7030
Telex: 914911; FAX: 01-628 5984

FAR EAST
Ed Schrader, General Manager
18818 Teller Ave, Suite 170
Irvine, CA 92715
(714) 851-9422; Telex: 183653

HONG KONG
John Byrne & Associates Ltd
1613 Hutchison House
10 HGarcourt Road
Central Hong Kong
Tel: 5-265474
Tlx: 61708 WEDIN HX
Fax: 5-8106781

JAPAN
Kaoru Hara
Dynaco International Inc
Suite 1003, Sun-Palace Shinjuku
8-12-1 Nishishinjuku, Shinjuku-ku
Tokyo 160, Japan
Tel: (03) 366-8301
Telex: J2322609 DYNAO

KOREA
Kim Kyong-Hae, BK International
Won Chang Bldg, 3rd Floor 26-3
Yoido-dong, Youngdungpo-ku
Seoul 150, Korea
Tel: 785-6665; FAX: 784-1915
Telex: K32487 BIZKOR

**SINGAPORE/MALAYSIA/INDONESIA/THAILAND/
THE PHILIPPINES/AUSTRALIA/NEW ZEALAND**
Asia Pacific Media House PTE Ltd
Peter Cheong
100 Beach Rd
#24-03 Shaw Tower
Singapore 0718
Tel: 2915354; Telex: RS 50026 MESPLY

TAIWAN
Acteam International Marketing Corp
6F, No 43, Lane 13
Kwang Fu South Rd
Mailing Box 18-91
Taipei, Taiwan ROC
760-6209 or 760-6210
Telex: 29809; FAX: (02) 7604784

PRODUCT MART
Joanne Dorian, Manager
249 West 17th St
New York, NY 10011
(212) 463-6415

INFO CARDS
Donna Pono
Newton, MA 02158
(617) 558-4282

CAREER OPPORTUNITIES/CAREER NEWS
Roberta Renard, National Sales Manager
(201) 228-8602

Janet O Penn, Eastern Sales Manager
(201) 228-8610
103 Eisenhower Parkway
Roseland, NJ 07068

Mary Beth West, Western Sales Manager
12233 West Olympic Blvd
Los Angeles, CA 90064
(213) 826-5818

Staci Comstock, Sales Assistant
(201) 228-8608
FAX: 201-228-4622

Wendy A Casella, Advertising/Contracts Coordinator
Nan E Coulter, Advertising/Contracts Coordinator
Aileen B Turner, Advertising/Contracts Coordinator
(617) 964-3030

William Platt, Senior Vice President, Reed Publishing USA
Cahners Magazine Division
Terry McDermott, President, Cahners Publishing Co
Frank Sibley, Senior Vice President/General Manager,
Boston Division
Tom Dellamaria, VP/Production & Manufacturing

Circulation
Denver, CO: (303) 388-4511
Eric Schmierer, Group Manager

Reprints of EDN articles are available on a custom printing basis at reasonable prices in quantities of 500 or more. For an exact quote, contact Joanne R Westphal, Cahners Reprint Service, Cahners Plaza, 1350 E Touhy Ave, Box 5080, Des Plaines, IL 60018. Phone (312) 635-8800.


New switched capacitor filters push frequency limits out to 150 KHz.

There is now on the market a dual universal switched capacitor filter that is specified to operate over the ambient temperature range and supply tolerances at 150 KHz with high Q's.

It's called the ML2111. And it's made by Micro Linear.


Center-Frequency Accuracy and High Q

The ML2111 consists of two independent switched capacitor filters performing second order functions. Each independent filter has separate highpass, notch, allpass, bandpass, and lowpass outputs.




Bandpass Filter with $f_{CLK} = 7.5$ MHz

The center frequency of up to 150 KHz is tuned by an external TTL or CMOS clock. Center frequency accuracy is $\pm 0.4\%$ or $\pm 0.8\%$ maximum. Q accuracy is $\pm 3\%$ or $\pm 6\%$. This is over temperature and supply voltage tolerance. Signal to noise ratio at 150 KHz is 80 dB.



Circuit and Plot of Notch Filter with $Q=50$ and $F_0=130$ KHz



Ease of Use Means More Versatility

With all parameters specified over the entire ambient temperature range as well as supply voltage tolerances of $\pm 10\%$, the ML2111 is designed for ease of use.

Designers only need to match two resistors for setting Q. Power requirements can be $\pm 5V$, or a single 5V power supply. And Micro Linear guarantees ML2111 performance over the full temperature range as well as VCC tolerance.

Since Qs of up to 100 can easily be obtained, the ML2111 is ideal for LORAN C, aircraft navigation, Sonar, ultrasound, high speed communication links, and other applications where center-frequency accuracy and high Q are needed.

In addition to offering higher reliability, design time and part counts are reduced.

As the only integrated solution available, the ML2111 lowers overall costs substantially at these high frequencies.

The ML2111 is available in 20-Pin DIP and 20-Pin SOIC package. The price is \$6.95 in 100 unit quantities.

Call or Write for More Information

If you would like more information on the ML2111 switched capacitor filter, or on Micro Linear's complete range of linear devices, please call (408) 433-5200, extension 900, or write:

Micro Linear, Dept. F
2092 Concourse Drive
San Jose, CA 95131

ADVERTISERS INDEX

ACCEL Technologies Inc	279	Huntsville Microsystems Inc	40	Rogers Corp	276, 278, 279, 280
Advin Systems Inc	275	Hybricon Inc	276	Rohde & Schwarz**	165
Aerospace Optics Inc	268	Imprimis Technology	28-29	Samsung Semiconductor*	67-78
Amerace Corp	234	Industrial Devices Inc	132	Samtec Inc	125, 276
Ametek	252	Instant Board Circuits Corp	93	Schaevitz Engineering	200
AMP	140-141	Integrated Device Technology Inc	65	Seagate Technology	191
Amperex Electronic Corp*	109, 270	Intel Corp	265, 267	SGS-Thomson Microelectronics	149
Analogic Corp	153	Intermetrics Inc	163	Siemens Components Inc*	131
Ancot Corp	277	International Rectifier	C3	Siemens Semi*	59
Annulus Technical Ind Inc	276	Intusoft	278	Signetics Corp	99, 177, 217
Applied Microsystems Corp	235-237	IOtech Inc	279	Silicon Systems Inc	248-249
Applied Physics Systems	275	ITT Cannon	219	Siliconix Inc	4
Aries Electronics Inc	274	Jameco Electronics	278	Simpson Electric Co	94
Augat-Interconnection Systems	16-17	John Fluke Manufacturing Co Inc	6, 165-169	Single Board Solutions	280
Avantek	278	Keithley Systems	253, 255, 271	Softaid Inc	274
Avis	87	Kepeco Inc	151-152	Spectrum Technology	63
B&C Microsystems	277, 279	Krohn-Hite Corp	199	Sprague Electric Co	107
Beckman Industrial Corp	111	Leader Instruments Corp	192	Stag Microsystems Inc	2
Bomco	255	Leasametric Inc	282	Tatum Labs	280
BP Microsystems	276	Ledtronics Inc	277	Tektronix Inc	36-37, 114-117, 266
Brooktree Corp	154-155	Lemo USA Inc	277, 279	Teltone Corp	277
Buckeye Stamping Co	277	Linear Technology Corp	201-202	Teradyne Inc	30-31
Burr-Brown Corp	102	Logic Dynamics	82	Tokin America	276
BV Engineering	280	Logical Systems Corp	278	TRW LSI Products Inc	23
Bytek Corp	190	LSI Logic Corp	8	United Airlines	57
CAD Software Inc	280	3M Co	127	Varta Batteries Inc	295
Cadrel Atron	247	Macrochip	244	Versatec	137-139
Cahners CAPS	254-255	Master Bond	190	Vicor	203-205
Cahners Exposition Group	228	MathSoft Inc	124	Viva & Associates	262
Calay Systems	287	Matrix Systems	238	VME Specialists	224
Candela	232	Maxim Integrated Products	264	VMETRO Inc	226
Casio Inc	81	Mentor Graphics Corp	10-11	Walton	234
Central Data Corp	197	Meta Software Inc	261	Wavetek	3
Clairex Electronics	253	Micrel	84	Westcor	100
Commerce Tours Trade	79	Micro Linear	297	Wintek Corp	25, 277, 279
Communications Specialties Inc	280	Microstar Laboratories	120	Yeti	256
Computer Modules Inc	280	Microtek Intl Inc**	59	YSI Inc	278
Corning Electronics	269	Mini-Circuits Laboratories	26, 27, 215, 300	Zax Corp	105
Cybernetic Micro Systems	89	Mitsubishi Electronics America Inc	129	Zendex	275
Cybernetic Micro Systems Inc	280	Mizar Inc	42	Ziatech Corp	1
Cypress Semiconductor	46	Mouser Electronics	276	Zilog Inc	121
Dale Electronics Inc	34	National Semiconductor Corp	50-51		
Data Business Publishing	208	NCI	277		
Data Delay Devices	124	NCR Microelectronics Div	257		
Data I/O Corp	C4, 256, 279	NEC Corp	14-15, 233		
Datel*	245	NEC Electronics	263		
Deltrol Controls	279	Newport Corp	122		
Digelec Inc	269, 271	Nohau Corp	275		
Digital Equipment Corp*	156	Northwest Airlines	112-113		
Dotronix	241	Octagon Systems	277		
Eastman Kodak	283	OKI Semiconductor	38-39		
Elantek	32	Omaton Inc	275		
Electronic Designs Inc	92	Online Computer	240		
Electronic Development Corp	265	OrCAD Systems Corp	226		
Electronic Measurements Inc	250-251	Orion Instruments	43		
Electronic Solutions	118	PBI/Philips Int**	67A-D		
Elmec Technology of America Inc	275	Performance Semiconductor Corp	35		
Farnell International Ltd**	6	Philips T&M**	109, 131		
Fujitsu Component of America Inc*	222	Potter & Brumfield	272-273		
Fujitsu Limited**	C2	Powertec	66		
Fujitsu Microelectronics Inc*	C2	Precision Monolithics Inc	20		
General Silicones	276	Qua Tech Inc	276, 279		
Gespac Inc	41	Quad Design	150		
Grayhill Inc	52	Qualosy	281		
Hall-Mark	229	Qualstar Corp	280		
Harris Semiconductor	44-45	Quantum Data Corp	258-259		
Harris/3M	230-231	Ready Systems	178-179		
Heurikon Corp	80	Real Time Devices	278		
Hewlett-Packard Co	18-19, 95-98, 133-135, 242-243	Rittal Corp	90-91, 206-207		
Hirose Electric	260	RLM Research	278		
Hitachi America Ltd*	48-49, 227				

Recruitment Advertising 288-294

Compaq Computer Corp
Independent Personnel Consultants
Motor Check Inc

*Advertiser in US edition

**Advertiser in International edition

This index is provided as an additional service. The publisher does not assume any liability for errors or omissions.

LOOKING AHEAD

EDITED BY JULIE ANNE SCHOFIELD

Consumers are unaware of fax for personal computers

Personal-computer facsimile boards have been around since 1985, but many telecommunications and management-information-system experts are unaware of them, according to an industry report by Venture Development Corp (Natick, MA). This low level of awareness might discourage some manufacturers, but it could also help them form new marketing strategies.

These boards enable personal computers to act as facsimile transceivers, but buyers of personal-computer fax boards see them as

additions to stand-alone facsimile machines, not as replacements for them. Of the owners VDC surveyed, 58.3% said that the same individual or department purchased both stand-alone facsimile machines and personal-computer fax boards. Most of the owners usually order the stand-alone units from local dealers, but 81% of personal-computer fax-board users ordered their boards directly from the manufacturer. VDC expects this figure to decrease as more computer dealers offer these boards.

The most important factor for first-time buyers was the compati-

bility of the board with the other facsimile equipment in their office, and many buyers want to be able to test personal-computer fax boards at their site. Reliability, transmission speed, copy quality, ease of use, and price also heavily influenced buyers. The average price for a personal-computer fax board is \$500, reports VDC.

Half of the companies that have personal-computer fax boards own only one unit, 19% own two, and 31% own three or more. Nearly half of the owners surveyed by VDC plan to buy more boards over the next five years.

NASA information-systems budget to increase to \$1.3B


The market for contracted information systems and services in the National Aeronautics and Space Administration (NASA) will increase from \$910 million in 1988 to \$1.3 billion by 1993, predicts Input (Mountain View, CA). This figure represents an average annual growth rate of 8.7%.

NASA has used computers extensively for both administrative systems and mission support, and these systems have functioned in a highly decentralized mode. But NASA is now making changes that will require more information sharing than at any time in its history, reports the market research and consulting firm. In selected areas, such as procurement, software management and assurance, and the Space Station program, NASA is moving away from its decentralized approach.

Historically, NASA has not always been on the cutting edge of information systems technology. But reports from oversight agencies have prompted NASA to start a wide-ranging program to intensify


its automation of highly technical areas. This program includes establishing sophisticated local-area networks to facilitate information sharing, improving its own development of software, a significant upgrade of computer facilities at its centers, and implementing artificial intelligence to enhance decision-support activities.

Traditionally, NASA has used contractors more than most agencies in performing mission activities. According to Input, software products and hardware lead contracted information-systems expenditures at 24% and 23%, respectively.



99¢

from



dc to 2000 MHz amplifier series

SPECIFICATIONS

MODEL	FREQ. MHz	GAIN, dB			• MAX. PWR. dBm	NF dB	PRICE \$	
		100 MHz	1000 MHz	2000 MHz			Min. (note)	Ea.
MAR-1	DC-1000	18.5	15.5	—	13.0	0	5.0	0.99 (100)
MAR-2	DC-2000	13	12.5	11	8.5	+3	6.5	1.50 (25)
MAR-3	DC-2000	13	12.5	10.5	8.0	+8□	6.0	1.70 (25)
MAR-4	DC-1000	8.2	8.0	—	7.0	+11	7.0	1.90 (25)
MAR-6	DC-2000	20	16	11	9	0	2.8	1.29 (25)
MAR-7	DC-2000	13.5	12.5	10.5	8.5	+3	5.0	1.90 (25)
MAR-8	DC-1000	33	23	—	19	+10	3.5	2.20 (25)


NOTE: Minimum gain at highest frequency point and over full temperature range.

- 1dB Gain Compression
- +4dBm 1 to 2 GHz

designers amplifier kit, DAK-2

5 of each model, total 35 amplifiers

only \$59.95



finding new ways ...
setting higher standards

Mini-Circuits

Unbelievable, until now... tiny monolithic wide-band amplifiers for as low as 99 cents. These rugged 0.085 in. diam., plastic-packaged units are 50ohm* input/output impedance, unconditionally stable regardless of load*, and easily cascable. Models in the MAR-series offer up to 33 dB gain, 0 to +11 dBm output, noise figure as low as 2.8dB, and up to DC-2000MHz bandwidth.

*MAR-8, Input/Output Impedance is not 50ohms, see data sheet. Stable for source/load impedance VSWR less than 3:1

Also, for your design convenience, Mini-Circuits offers chip coupling capacitors at 12 cents each.†

Size (mils)	Tolerance	Temperature Characteristic	Value
80 x 50	5%	NPO	10, 22, 47, 68, 100, 220, 470, 680, 1000 pf
80 x 50	10%	X7R	2200, 4700, 6800, 10,000 pf
120 x 60	10%	X7R	.022, .047, .068, .1µf

† Minimum Order 50 per Value

- Designers kit, kcap-150 pieces of each capacitor value, only \$99.95

A Division of Scientific Components Corporation
P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500
Fax (718) 332-4661 Domestic and International Telexes: 6852844 or 620156

C113-Rev. D

TO-220
IRF724
IRF744
IRF520
IRF530
IRF540
IRF630
IRF640
IRF624
IRF644
IRF720
IRF730
IRF820
IRF830
IRF840
IRF924
IRF934
IRF910
IRF930
IRF940
IRF9620

IRFBG30
HEXSense®
IRCZ24
IRCZ34
IRC530
IRC540
IRC640
IRC634
IRC730
IRC830
IRC840
HEXDIP™
IRFD1Z0
IRFD014
IRFD024
IRFD110
IRFD120
IRFD220
IRFD901
IRFD9024



IRL540
FULLPAK
IRFIZ24
IRFI530
SOT-89
IRFS1Z0
D-PAK
IRFR014
IRFR024
IRFR120
IRFR220
IRFR310
IRFR320
IRFR420
IRFR9014
IRFR9024
IRFR9120
TO-18
IRFP044
IRFP054

IRFP350
IRFP360
IRFP440
IRFP448
IRFP450
IRFP460
IRFP9140
IRFP9240
IRFPC40
IRFPC50
IRFPE40
IRFPE50
IRFFP40
IRFFP50
TO-3
IRF140
IRF150
IRF240
IRF250
IRF244
IRF254


IRF460
IRF9140
IRFAC50
IRFAE50
IRFAF40
IRFAF50
IRFAG50
TO-39
IRFF024
IRFF110
IRFF120
IRFF130
IRFF420
IRFF9010
IRFF9110
TO-240AA
IRFK2H250
IRFK2H450
IRFK4H250
IRFK4H450
IRFK6H180
IRFK6H450

They can copy these numbers.

But they can't copy these.



HEXFET IRF530 under avalanche



As IR HEXFETs® hold their lead in power MOSFETs, our competitors become bolder and bolder in attempting to duplicate our success.

They're using our part numbers. And in some cases, they've even put "IR" in front of them. They've thought of everything. Except performance, ruggedness and reliability.

The numbers *in the charts* tell the story. You'll find them in our guaranteed avalanche ratings. Our quarterly reliability reports, the most comprehensive

in the industry. In AOQLs you can take right past incoming inspection to your production line.

And in our Generation III HEXFET process that's optimizing cell density and providing unparalleled performance per square inch.

The bottom line: If you're buying FETs, make sure they're IR, as in International Rectifier. Or you just might get a signed and numbered copy.



IR INTERNATIONAL RECTIFIER

WORLD HEADQUARTERS: 233 KANSAS ST., EL SEGUNDO, CA 90245, U.S.A. (213) 772-2000, TWX 910-348-6291, TELEX 472-0403
EUROPEAN HEADQUARTERS: HURST GREEN, OXTEY, SURREY RH8 9BB, ENGLAND TELEPHONE (0883) 713215, TELEX 95219

CIRCLE NO 153



When (Count < 9) & Clear then Count := Count + 1
else Count := 0;

17 MILLION PLDS A MONTH BEGIN WITH DATA I/O.

No company supports as many programmable logic devices as Data I/O®—virtually every PLD on the market. From design, to programming and test, Data I/O is the industry choice for PLD development tools.

UNIVERSAL SUPPORT FOR EVERY PLD MANUFACTURER.

We give you the freedom to choose the right PLD for your design—from any manufacturer. You can use our tools to design and program all PLD architectures, including PALs, FPLAs, PLEs and EPLDs, and all technologies from vertical-cell AIM, ECL, and CMOS to bipolar. And you can pick any package—DIP, PLCC, LCC or SOIC.

UNIVERSAL DESIGN TOOLS. ABEL™ 3.0,

Data I/O's high-level design language, lets you describe your design with any combination of equations, state diagrams, or truth tables. For multiple PLD design, use the advanced logic synthesis capabilities of GATES™. And for complete device testability,



PLDtest® is our universal tool for automatic fault grading and test vector generation.

UNIVERSAL PROGRAMMING TOOLS.

The UniSite™ 40, our most sophisticated programmer, handles all devices—memory, logic, and microcontrollers—in a single site. The modular approach to logic programming is the 29B with a

LogicPak™. Or for portable convenience, choose the 60A.

UNIVERSALLY APPROVED BY PLD MANUFACTURERS. With Data I/O, you can depend on the accuracy and reliability of your programmed PLD. We work with semiconductor manufacturers—long before devices are released—to develop, and obtain approvals for, our programming algorithms. So reliable support will always be ready when you need it.

A CLOSER LOOK AT UNIVERSAL SUPPORT.

Call us today for more information about our complete line of PLD development tools and qualify for your FREE copy of the ABEL 3.0 demonstration disk. Your PLDs will be off to a better start and a faster finish.



1-800-247-5700

Ext. 363

Data I/O Corporation 10525 Willows Road N.E. P.O. Box 97046, Redmond, WA 98073-9746 U.S.A. (206) 867-6899/Telex 15 2167
Data I/O Canada 8775 Airport Road, Suite 302, Mississauga, Ontario L4V 1V2 (416) 678-0761
Data I/O Europe World Trade Center, Stravinskylaan 833, 1077 XX Amsterdam, The Netherlands +31 (0)20 6622866/Telex 16616 DATAIO NL
Data I/O Japan Sumitomo-seimei Higashishinbashi Bldg., 8F, 2-1-7, Higashi-Shinbashi, Minato-ku, Tokyo 105, Japan
(31) 432-6991 Telex 2522685 DATAIO J

© 1988 Data I/O Corporation

CIRCLE NO 77

DATA I/O
Corporation